GENAI.WORKS OPEN AGENT HACKATHON 2026 · TRACK: THE AGENT THAT CAN EXPLAIN WHY

Why Agent

Ask why a business metric changed. Get the drivers, summing exactly to the change, and a citation on every sentence back to the exact Zetaris query and rows. C1

ENTRANT

Ben Wat (solo)

SPONSOR TECH

Zetaris + Meterless (H-MEM, Scout)

REPO

github.com/bradywatkinson/why-agent

Built without Cursor

PROBLEM & USERS

Dashboards show what changed. Analysts must prove why.

When a KPI moves, someone has to slice it by every dimension, check that the pieces add up, and defend the story.

Chat-over-data answers make this faster but harder to trust:

Numbers without provenance

No way to open the query and rows behind a sentence.

Drivers that overlap

The same trips counted twice through two dimensions.

No memory

Every question starts cold; earlier findings are never cross-checked.

WHO IT IS FOR

Business & data analysts

Get the why behind a metric move, already decomposed into drivers that reconcile to the total.

Analytics leads & decision makers

Act on an answer that states its own checks, caveats and limits.

Reviewers & auditors

Trace any number to the federated query and the rows it came from.

SOLUTION

Ask why: guard, recall, scan once, explain, cite, remember

Zetaris Meterless

01

Guard

Meterless Scout

Screen the question for injection, exfiltration and destructive intent before any query.

02

Recall

Meterless H-MEM

Hybrid recall of prior findings, schema and month coverage.

03

Discover

Zetaris catalogue

SHOW LIGHTNING TABLES / DESCRIBE map the fact table and columns.

04

Scan once

Zetaris join

One query joins yellow_taxi and taxi_zones into an evidence cube.

05

Explain

Shift-share

Split the change into mix vs within-segment; every breakdown must reconcile.

06

Answer

Cited claims

Typed claims, each citing query rows, a memory or a named reference.

07

Remember

Meterless H-MEM

Store the finding with provenance; supersede the old one; take feedback.

Deterministic planner, no LLM: every number is computed from rows Zetaris returns, and every sentence is a template filled from those rows. Each run leaves a full audit record.

A real question, answered live over 38.7M federated rows

"Why did average tips change between December 2024 and January 2025?"

$3.46 → $2.96


−$0.50 · −14.5% avg tip per trip

12 claims, every one cited

5 breakdowns reconcile exactly to −$0.50

1 federated Zetaris scan for all of it

10,982,621 vs 10,408,144 valid trips measured



Live UI: answer with [C#] citations (left), streaming audit log (right), LIVE · zetaris badge

Drivers add up exactly, and nothing is counted twice

CHANGE DECOMPOSITION (MIX VS WITHIN-SEGMENT)

payment type Q3 · mix −$0.10 · within −$0.40 · ✓ reconciles

segment	share 2024-12	share 2025-01	value 2024-12	value 2025-01	mix	within	total
Credit card	74.5%	70.3%	$4.49	$4.10	−$0.04	−$0.27	**−$0.31**
Code 0 (unlisted)	8.9%	15.6%	$1.27	$0.45	−$0.15	−$0.13	**−$0.27**
Cash	13.4%	11.2%	$0.00	$0.00	+$0.07	−$0.00	**+$0.07**
Dispute	2.4%	2.2%	$0.06	$0.05	+$0.01	−$0.00	**+$0.01**
No charge	0.8%	0.7%	$0.05	$0.02	+$0.00	−$0.00	**+$0.00**
Unknown	0.0%	0.0%	–	$0.00	−$0.00	+$0.00	**−$0.00**

rate code Q4 · mix −$0.20 · within −$0.30 · ✓ reconciles

segment	share 2024-12	share 2025-01	value 2024-12	value 2025-01	mix	within	total
Missing (null)	8.9%	15.6%	$1.27	$0.45	−$0.15	−$0.13	**−$0.27**
Standard rate	85.2%	79.3%	$3.34	$3.12	+$0.01	−$0.18	**−$0.17**

Mix vs within-segment table per breakdown, with a ✓ reconciles check

Shift-share identity is exact

Each segment's mix + within contributions sum to the headline −$0.50. A breakdown that doesn't reproduce the headline is excluded, and the answer says so.

Mostly within segments


Across rate code, mix explains only −$0.20 (39%). Manhattan trips: $3.01 → $2.58 (−$0.38). Card-paid: $4.49 → $4.10 (−$0.27).

Double count caught and merged


Missing rate code grew 8.9% → 15.6% of trips. The same 978,903 → 1,621,071 trips are payment “Code 0”, so the agent reports one driver, not two.

Descriptive decomposition, not causal; the answer says so.

Every claim opens the exact query and rows behind it



Claims, typed finding / caveat / memory, each with citation chips



Chip opens Q2 with the cited rows highlighted

Claim → query

Click [C#] or a chip: the query panel opens with the exact rows highlighted.

Roll-up → cube cells


Q2…Q7 are client-side roll-ups of one Zetaris scan (Q1). “n cell(s)” opens the raw cells summed.

Run → audit JSON

Plan, SQL, timings, rows, guard verdicts and memory reads/writes in one download.

ARCHITECTURE

A deterministic planner between guard, memory and Zetaris



TECH STACK

Tech stack: TypeScript, Zetaris, Meterless H-MEM and Scout

Runtime	TypeScript · Node 20+ (built on Node 22) · npm · tsx
Data / query	Zetaris Lightning (local Docker platform) · Spark SQL · REST run-query API · NY_TAXI CSV on public S3
Memory	Meterless H-MEM reference engine (vendored by npm run setup) · TrustLedger (append-only)
Safety	Scout-style guard (guard.ts) · scored with the official Meterless Scout eval runner
Interface	Single-page web UI over SSE (server.ts) · CLI (ask, guarded sql, audit) · downloadable audit JSON
Testing	Offline FixtureAdapter (sql.js, synthetic, labelled FIXTURE) · guard, parser, decomposition, e2e tests

Development disclosures Built without Cursor. Pre-existing: the Meterless agentathon-starter template (Apache-2.0), the H-MEM reference engine (vendored at setup, not committed), and patterns from the Zetaris getting-started helper scripts, re-implemented. No LLM in the loop.

SPONSOR TECH · ZETARIS

Zetaris federates; one scan answers every breakdown

Live REST queries

POST /api/proxy/sql-editor/sqls/run-query with an API token minted inside our own instance; key lives only in .env.

Self-discovering schema


SHOW LIGHTNING TABLES and DESCRIBE DATASOURCE TABLE map pickup time, fare, tip, payment type, with a stated reason per mapping.

Federated join in Zetaris

yellow_taxi (38,667,711 rows) ⋈ taxi_zones, both S3 CSV, cast and grouped in Spark SQL.

What's unique One query builds an evidence cube (period × validity × payment × rate code × borough × distance × time of day). The headline and every breakdown are roll-ups of it, each row linked back to the cube cells it summed.

Zetaris UI: NY_TAXI registered as a federated source (CSV in S3)




yellow_taxi (38.7M rows) ⋈ taxi_zones — queried live by the agent through the Zetaris REST API

Schema mapping and month coverage are learned once and stored in H-MEM, so later runs skip discovery and the extra coverage scan.

SPONSOR TECH · METERLESS H-MEM

H-MEM is the agent's evidence memory, not a chat log



Recall before planning, mem-7 written, TrustLedger events

`add`	Store schema mappings, month coverage and findings with provenance zetaris:<run>/<query>.
`query`	Hybrid recall before planning; reads logged to the TrustLedger.
`supersedes`	A re-run finding links to and replaces the old one for the same question.
`feedback`	👍 / 👎 in the UI adjusts the stored finding's confidence.
`ledger.history`	Drives the TrustLedger viewer: create / read / supersede / feedback.

What's unique Memory is citable evidence: a second identical run adds a claim that the result matches the finding stored in H-MEM. Live and fixture memories live in separate stores, so synthetic findings can never be recalled as evidence about real data.

A Scout guard checks the question, the SQL and the data

1 · Question


Injection, mode switching, secret exfiltration, out-of-band tools, privilege escalation, destructive intent: blocked before any query.

2 · SQL

Read-only verbs, one statement, allowed databases only, no PII columns.

3 · Returned rows

Cells with instruction-like text are redacted before they reach the answer.



Injection attempt blocked; no query was sent to Zetaris

What's unique

Meterless publishes Scout Intent as a spec without a reference implementation. guard.ts implements its guard stage for this agent and exposes Scout.decide(), so the official Meterless eval runner can score it.

Honest result Precision 1.0 / recall 1.0 on the published v1/injection set (10 examples: 7 injection, 3 clean). That set is not held out; I read it while writing the guard. Treat it as a regression check.

LIMITS & FUTURE WORK

Honest limits today, and what comes next

LIMIT TODAY	WHY	NEXT
Deterministic, rule-based planner (no LLM)	Fixed vocabulary: 7 metrics, period forms, 5 dimensions. No LLM key was available.	Optional LLM front-end that only fills the same typed plan; numbers still come only from rows.
~60–70 s per full scan	S3 CSV read dominates on a single-node local Spark driver.	Cache or materialise evidence cubes in Zetaris; columnar sources.
Guard evaluated on a non-held-out set	Pattern-based; 10-example public set read during development.	Held-out and adversarial evaluation; add Scout intent classification.
Descriptive, not causal	Explains through 5 built-in dimensions only.	Federate external drivers through Zetaris, e.g. weather_data already in the NY_TAXI catalogue.

Repo github.com/bradywatkinson/why-agent Run it `npm install · npm run setup · npm test · npm start`