Online Quiz Application - index.html

QuizMaster HTML source code

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Online Quiz Application</title>
  <link rel="stylesheet" href="style.css">
</head>
<body>
  <div class="app">
    <header><h1>QuizMaster</h1><p>Test your knowledge. Beat the clock.</p></header>

    <!-- Screen 1: category selection -->
    <section id="startScreen" class="screen active">
      <h2>Choose a Quiz Category</h2>
      <div class="categories" id="categories"></div>
    </section>

    <!-- Screen 2: quiz -->
    <section id="quizScreen" class="screen">
      <div class="top-bar">
        <span id="catName"></span>
        <span class="timer" id="timer">01:00</span>
      </div>
      <div class="progress"><div id="progressBar"></div></div>
      <p class="q-count" id="qCount"></p>
      <h2 id="question"></h2>
      <div class="options" id="options"></div>
      <button class="btn" id="nextBtn" disabled>Next</button>
    </section>

    <!-- Screen 3: result -->
    <section id="resultScreen" class="screen">
      <p class="banner" id="banner"></p>
      <h2>Quiz Result</h2>
      <div class="score-circle"><b id="percent">0%</b><span id="scoreText"></span></div>
      <p class="best" id="bestScore"></p>
      <div class="summary">
        <div><b id="sTotal">0</b><span>Total</span></div>
        <div><b id="sAttempted">0</b><span>Attempted</span></div>
        <div class="good"><b id="sCorrect">0</b><span>Correct</span></div>
        <div class="bad"><b id="sWrong">0</b><span>Incorrect</span></div>
      </div>
      <h3>Answer Review</h3>
      <div id="review"></div>
      <div class="btn-row">
        <button class="btn" id="restartBtn">Restart Quiz</button>
        <button class="btn outline" id="anotherBtn">Another Category</button>
      </div>
    </section>
  </div>
  <script src="script.js"></script>
</body>
</html>
```