

PENGAJUAN BARANG UMUM / ALKES RS PRIMA HUSADA
NOMOR : 291 / RSPHU / I - PM / PAD / X / 2025

Tanggal	15 Oktober 2025				
Pengajuan Dari Unit*	Radiologi				
Alasan Pengajuan	Untuk melindungi X Ray Mobile dari kerusakan power Suplay akibat Naik turun nya Voltase Listrik.				
I.DATA BARANG DAN SUPLIER					
1.	No	Nama Alat	Jumlah yang diajukan	Stok Alat di Unit	Ket
	1.	UPS	1 unit	0	
2.	Fungsi alat** (fungsi di isi sesuai nomor alat)	1. Untuk Stabilisasi Tegangan Voltase dari PLN / Listrik alat X Ray Mobile.			
3.	Penempatan alat**	1. Di X Ray Mobile			
4.	Merk/Tipe**	1. Ups vector Ablerex Srt8kxli / Srt8000xli 8000va 8000w 230v Sinewave 2yr			
5.	Spesifikasi**	1. Ups vector Ablerex Srt8kxli / Srt8000xli 8000va 8000w 230v Sinewave 2yr			
Yang Mengajukan	Kabid Umum dan Keuangan	Kabid Penunjang Medis	Mengetahui Kabid Yanmed	Menyetujui Direktur	
 (Suliaynto Amd TekMed)	 (Wulandari)	 (Nur Lailatul Farida,S.Kep.,NS)	15/25. /10  (Ns.Sisca Puspitasari,S.Kep)	 (Heni Indra W,S.Kep,M.Kep)	
TANGGAPAN DARI KABID RS PRIMA HUSADA SUKOREJO Stabilisator digunakan untuk X Ray Mobile terutama untuk MCU krn. tegangan listrik tidak stabil					
TANGGAPAN DARI DIREKTUR RS PRIMA HUSADA SUKOREJO					



LAMPIRAN I
DOKUMENTASI ALAT

• ablerexMSII

PARALLEL ON-LINE UPS

The Ablerex MSII Parallel On-Line UPS, is the perfect solution for mission critical users who demand high reliability, availability and performance for critical electronic equipment and computer loads.

It features double conversion True Online Technology, field-proven full Digital Signal Processor (DSP) and utilises our uniquely patented inverter control technology. The Ablerex MSII Parallel On-Line UPS is a scalable system which achieves N + 1 redundancy without any additional parts.

Simple Parallel Installation(No extra PCB require)

Install for operation in parallel to increase power capacity or make redundant system. Simply connect the parallel control lines through the RJ-45 connector on the rear panel with CAM-bus and communication is established to all units. The maximum parallel operation configuration is 4 units.

Full Digital Signal Processor (DSP) Control

Provides both pure sine waves at the output and perfect sine waves to the input current to ensure compatibility with all kinds of loads. Full DSP technology also allow :

- **Programmable Frequency Converter**

Reprogram the UPS to be a Frequency Converter for either 50Hz or 60Hz through front keypad configuration.

- **Easy-to-Set User Personalization**

Through the LCD front panel, you can easily change the built-in parameters and settings of the DSP controllers, such as UPS operation modes voltage configurations, synchronization frequency windows, bypass voltage tolerance and buzzer alarm status.

