



PENGAJUAN BARANG UMUM / ALKES RUMAH SAKIT PRIMA HUSADA
NO: 076.1/I-PNJ/PRN/I/2024

Tanggal	23 Januari 2024		
Pengajuan Dari Unit*	NICU		
Alasan Pengajuan	Perlu penambahan		
I.DATA BARANG DAN SUPLIER			
1.	No	Nama Alat	Jumlah
	1.	INKUBATOR TRANSPORT	1
	2.	MIXSAFE (NEOPUFF UPGRADE)	1
	3.	PULSE OXYMETRI BAYI	2
	4.		
2.	Fungsi alat** (fungsi di isi sesuai nomor alat)	1. - Sebagai alat transport bayi untuk merujuk - Sebagai alat transport bayi untuk bayi sakit yang memerlukan Oksigen - Sebagai alat transport bayi kecil (BBLR) dan usia kehamilan kurang karena resiko Sianosis dan Hypotermi 2. Merupakan alat bantu pernafasan dengan fungsi ganda, Dapat digunakan sebagai alat CPAP dan juga dapat berfungsi sebagai T-Piece resuscitator 3. Sebagai alat pantau gambaran proses penghantaran oksigen ke seluruh tubuh	
3.	Penempatan alat**	Ruang NICU	
4.	Merk/Tipe**	1. GEA MEDICAL type TI-2000 2. Mix-safe Forte Infant Blending Resuscitator 3. Pulse Oxymetri Oxy 9 Wave Bionet	
5.	Spesifikasi**	1. AC power requirement: AC220V-230V/50Hz or AC110-120V /50-60Hz, 400VA DC Power requirement: DC12V/10A or DC24V/6A Control Mode: Air mode and Baby mode controlled by micro-computer Air temperature control range: 25°C - 37°C (Override mode 37°C - 38°C) Baby temperature control range: 34°C - 37°C (Override mode 37-37.5°C) Skin temperature sensor accuracy: ± 0.2°C The temperature fluctuation range between incubator temperature and average incubator temperature (under stable temperature condition): ≤ 1.0°C Temperature uniformity: ≤ 1.5°C (mattress is on the horizontal position) Noise inside hood: ≤ 52 dB(A) Failure alarm: over-temperature alarm, temperature deviation alarm, sensor alarm, motor fan failed alarm, power failure alarm and so on. Battery continuous working time: 90min (Set temperature is 36°C—Ambient temperature is 15°C) 2. Dimesion221 X 200 X 170mm Oxygen / Ar Bleder System is 100% Reusale Portable Miini Compressor Input gas flow range10 L/Min flow capability Manometer Range0 - 80cm H²O Max Pressure relief 8L/Min5 - 70cm H²O Peak Inspiratory Pressure 8L/Min1 - 9cm H²O Recomended body weightUp to 10kg (22 lb) WeightApprox. 4kg Power Supplay12 VDC Operating TimeApprox, 120 - 180 minutes Charging Time3 hours (at complete discharge) Pressure Maximum25 ± 2 Psi / 2 ± 0.2 bar Advantage system is compact and easy use	



3. Low Perfusion SpO2 Measurement, SpO2, BPM, Pulse Parameter Display, Nellcor Compatibility, 3.2" Color TFT LCD for Clear View, Landscape & Portrait Views, Li-on Rechargeable Battery – Cordless Use for Up To 20 Hours				
Yang Mengajukan Karu Perin  Ns. Dhora Putri Meryda, S.Kep	Kabid Yanmed  dr. Nur Mazidah	PLT Kabid Jangmed  Putri Indah Purnamasari, AMd. Keb	Kabid Umum dan Keuangan  drg. Endy Wira Pradana, MMRS	Direktur RS  dr. Ekowati S.K.P., MMRS
TANGGAPAN DARI KABID RUMAH SAKIT PRIMA HUSADA				
TANGGAPAN DARI DIREKTUR RUMAH SAKIT PRIMA HUSADA				

*Alasan pengajuan: belum pernah tersedia/ ada tetapi rusak/ perlu penambahan/ ada tetapi hilang/ untuk back up

** Spesifikasi : Tidak di approve jika tidak di isi secara lengkap



LAMPIRAN FOTO

INKUBATOR TRANSPORT



TI-2000

TRANSPORT INCUBATOR

MIX-SAFE

MIX-SAFE
INFANT BLENDING RESUSCITATOR



SPECIFICATION





PULSE OXYMETRI BAYI

