

Lab03 – Creating a scheduled container operation

In this exercise, you will create a CronJob and render its executions.

1. Create a CronJob named `current-date` that runs every minute and executes the shell command `echo "Current date: \$(date)"`.

```
brahim@Training:~/Lab03$ kubectl create cronjob current-date --schedule="* * * * *" --image=nginx -- /bin/sh -c 'echo "Current date: $(date)"'
cronjob.batch/current-date created
brahim@Training:~/Lab03$
brahim@Training:~/Lab03$
```

2. Watch the jobs as they are being scheduled.

```
brahim@Training:~/Lab03$ kubectl get jobs --watch
NAME                                COMPLETIONS  DURATION  AGE
current-date-28171464              0/1          16s       16s
current-date-28171465              0/1          0s        0s
current-date-28171465              0/1          0s        0s
```

3. Identify one of the Pods that ran the CronJob and render the logs.

```
brahim@Training:~/Lab03$ kubectl get pods --show-labels
NAME                                READY  STATUS   RESTARTS  AGE  LABELS
current-date-28171464-nvxfw         0/1    Completed  0        2m53s  batch.kubernetes.io/controller-uid=1dbe6b6d-c8a1-4cc6-9a2c-ab169d99db38,batch.kubernetes.io/job-name=current-date-28171464,controller-uid=1dbe6b6d-c8a1-4cc6-9a2c-ab169d99db38,job-name=current-date-28171464
current-date-28171465-nt2l8         0/1    Completed  0        113s   batch.kubernetes.io/controller-uid=f5e3c6b9-1a8b-4a6a-b790-e62bd4f0463
```

4. Determine the number of successful executions the CronJob will keep in its history.

```
brahim@Training:~/Lab03$ kubectl get cronjobs current-date -o yaml | grep successfulJobsHistoryLimit:
  successfulJobsHistoryLimit: 3
brahim@Training:~/Lab03$
brahim@Training:~/Lab03$
```

5. Delete the CronJob.

```
brahim@Training:~/Lab03$ kubectl delete cronjob current-date
Error from server (NotFound): cronjobs.batch "current-date" not found
brahim@Training:~/Lab03$
brahim@Training:~/Lab03$
```