
HAFELE


PinLock Combination lock



Keypad and rotating lever



Espagnolette lock



PinLock is a solution for schools, wellness centres, sports facilities, staff rooms, etc. where secure keyless locker solutions are required.

The advantage is that there is no need to issue keys which can be lost. A continuous battery monitoring facility indicates a low battery (warning light).

The lock is locked by entering a variable four-digit PIN code and operating the rotating lever. The lock is unlocked again be re-entering the four-digit PIN code and operating the rotating lever.

A six-digit master code can be used to open the door (emergency opening) if the PIN code is forgotten.

The combination lock is blocked for 15 minutes if the wrong PIN code is entered 3 times.

Material: Housing: Plastic, deadbolt: Stainless steel

Finish: Housing: Black

Electronically secured deadbolt lock with Locking system:

apertures for 6 mm profile rods

(espagnolette lock) Dim. (W x D x H): 60 x 140 x 24 mm DIN left or DIN right Mounting: Installation: For screw fixing

Technical data

Degree of protection	IP 54
Ambient temperature (operation)	−5 °C − +55 °C
Relative humidity	20 – 80 % (not condensed)
Service life of battery	approx. 50000 locking cycles
Square spindle	7 mm
Door thicknesses	0.4 – 20 mm
Voltage supply	1.5 V Mignon AA battery (2 pieces)
Key change	10000 different key changes possible (4–digit PIN code)
Data storage in the event of a power failure	>10 years

	Backset A	Cat. No.
Keypad and rotating lever	_	225.12.300
Espagnolette lock	15 mm	225.12.310
Espagnolette lock	25 mm	225.12.320
Fixing set for metal doors 0.4 – 5 mm	_	225.12.901
Fixing set for wooden doors 10 – 14 mm	_	225.12.902
Fixing set for wooden doors 16 – 20 mm	_	225.12.900

Order reference


Accessories for espagnolette locks not supplied.

AFELE

Electronic cam lock miniLock









- Smallest electronic cam lock in the world
- Up to 10 years battery life
- Semi-flush and surface mounting options
- Easy and quick assembly
- No need to use extra handle

miniLock can be used wherever secure keyless locker solutions are required.

There is a wide range of usages like schools, hospitals, offices, shopping malls, wellness centres, sports facilities, staff rooms, post boxes etc.

miniLock is an electronic cabinet lock with 3 different password levels:

- · user password
- service password
- master password

Its unique features are small size, easy and quick installation, applicable for both wood and steel cabinets, usage for both left and right hand doors, longer battery life and high security.

Material: Housing: Plastic Finish: Housing: Black

 Functionality: 9 different programming options including single user and multi user mode

Door thickness: Maximum 20 mmMounting: DIN left or DIN right

Installation: For screw fixing with hexagon nut

Technical data

Dimensions (W x H x D)	34 x 85 x 27 mm
Weight	71 g (excluding cam and mounting)
Keypad	Silicone keypad with metal dome
Operating temperature	0°–50° C
Storage temperature	-10° / +70° C
Operating moisture	20%-80% Rh (without condensation)
Replaceable Battery	3 V Lithium CR 2450
Battery Life	10 years (10 uses per day)

Supplied with

- 1 miniLock
- 2 Cam versions
- 1 Stop cam
- Fixing material

	Cat. No.
miniLock	225.12.730

Order reference

Striking plate not supplied, please order separately.