

Course 2: Supervised Learning



IMT Atlantique
Bretagne-Pays de la Loire
École Mines-Télécom


Last session

- 1 AI definition
- 2 Applications & Open Issues
- 3 Deep learning
- 4 Foundation models


Today's session

- Learning from labeled examples
- Challenges of supervised learning

Vector space (\mathbb{R}^d)



Vector space (\mathbb{R}^d)





Notations

Vector space (\mathbb{R}^d)



What is the vector x ? (1/2)



What is the vector \mathbf{x} ? (2/2)

Traditional Machine Learning

\mathbf{x} is the data, or a small transformation of the data

Ex: images, or edges in the image

The era of Foundation models

\mathbf{x} is the projection of data in an **embedding** space

- Advantage: richer semantically than the original image
- Disadvantage: Not interpretable nor easily understandable

Vector space (\mathbb{R}^d)

Vector $\mathbf{x} (\in \mathbb{R}^d)$



What is the vector x ? (2/2)

Traditional Machine Learning

x is the data, or a small transformation of the data

Ex: images, or edges in the image

The era of Foundation models

x is the projection of data in an **embedding** space

- Advantage: richer semantically than the original image
- Disadvantage: Not interpretable nor easily understandable

Vector space (\mathbb{R}^d)

Vector $\mathbf{x} (\in \mathbb{R}^d)$



What is the vector \mathbf{x} ? (2/2)

Traditional Machine Learning

\mathbf{x} is the data, or a small transformation of the data


Ex: images, or edges in the image

The era of Foundation models

\mathbf{x} is the projection of data in an **embedding** space

- Advantage: richer semantically than the original image
- Disadvantage: Not interpretable nor easily understandable

Vector space (\mathbb{R}^d)



In this class, we will illustrate the concepts using images... **BUT in the lab, you will use embedding spaces (the future is probably there)**


Learning: Training and Test sets

The Training Set

Data used by the model to **learn** from examples.

The Test Set

A smaller, hold-out portion that the model has **never seen**. Used to **evaluate** its performance.




Learning: Training and Test sets

The Training Set

Data used by the model to **learn** from examples.

The Test Set

A smaller, hold-out portion that the model has **never seen**. Used to **evaluate** its performance.



Definition

Given a training set, composed of:

- **x**: inputs (raw signals or feature vectors (e.g. embeddings))
- **\hat{y} : labels** (annotated by humans)

Learn:

- a function $f()$ such that $\hat{y} \approx f(x)$
 $\Rightarrow f()$ is **learned** by the Machine Learning algorithm
- Ideally, $f()$ should **generalize** (\neq memorize) to unlabeled examples.

Supervised learning


Definition

Given a training set, composed of:


- \mathbf{x} : inputs (raw signals or feature vectors (e.g. embeddings))
- $\hat{\mathbf{y}}$: **labels** (annotated by humans)

Learn:


- a function $f()$ such that $\hat{\mathbf{y}} \approx f(\mathbf{x})$
 $\Rightarrow f()$ is **learned** by the Machine Learning algorithm
- Ideally, $f()$ should **generalize** (\neq memorize) to unlabeled examples.




Supervised learning: in practice



Supervised learning: in practice




Supervised learning: in practice



Loss

- Here, labels are encoded as one-hot vectors,
- We compute a **loss** $\mathcal{L}(f(\mathbf{x}), \hat{\mathbf{y}})$
- Training consist in minimizing the loss!


Supervised learning: in practice



Loss

- Here, labels are encoded as one-hot vectors,
- We compute a **loss** $\mathcal{L}(f(\mathbf{x}), \hat{\mathbf{y}})$
 - Euclidean distance: $\mathcal{L}(f(\mathbf{x}), \hat{\mathbf{y}}) = \sum_{i=1}^D (f(\mathbf{x})_i - \hat{\mathbf{y}}_i)^2$
 - Cross-entropy: $\mathcal{L}(f(\mathbf{x}), \hat{\mathbf{y}}) = - \sum_{i=1}^D \hat{\mathbf{y}}_i \log(f(\mathbf{x})_i)$
- Training consist in minimizing the loss!


Supervised learning: in practice



Loss

- Here, labels are encoded as one-hot vectors,
- We compute a **loss** $\mathcal{L}(f(\mathbf{x}), \hat{\mathbf{y}})$
 - Euclidean distance: $\mathcal{L}(f(\mathbf{x}), \hat{\mathbf{y}}) = \sum_{i=1}^D (f(\mathbf{x})_i - \hat{\mathbf{y}}_i)^2$
 - Cross-entropy: $\mathcal{L}(f(\mathbf{x}), \hat{\mathbf{y}}) = - \sum_{i=1}^D \hat{\mathbf{y}}_i \log(f(\mathbf{x})_i)$
- Training consist in minimizing the loss!
⇒ Here, one can use gradient descent (see class 1.)

Supervised learning: in practice




Loss

- Here, labels are encoded as one-hot vectors,
- We compute a **loss** $\mathcal{L}(f(\mathbf{x}), \hat{\mathbf{y}})$
 - Euclidean distance: $\mathcal{L}(f(\mathbf{x}), \hat{\mathbf{y}}) = \sum_{i=1}^D (f(\mathbf{x})_i - \hat{\mathbf{y}}_i)^2$
 - Cross-entropy: $\mathcal{L}(f(\mathbf{x}), \hat{\mathbf{y}}) = - \sum_{i=1}^D \hat{\mathbf{y}}_i \log(f(\mathbf{x})_i)$
- Training consist in minimizing the loss!
 \Rightarrow Here, one can use gradient descent (see class 1.)

Supervised learning

Examples


- **Classification** (\hat{y} is categorical)
- **Regression** (\hat{y} is scalar)
- Tons of applications:
 - Pattern recognition,
 - Prediction...



Supervised learning

Examples


- **Classification** (\hat{y} is categorical)
- **Regression** (\hat{y} is scalar)
- Tons of applications:
 - Pattern recognition,
 - Prediction...



Supervised learning

Examples


- **Classification** (\hat{y} is categorical)
- **Regression** (\hat{y} is scalar)
- Tons of applications:
 - Pattern recognition,
 - Prediction...



Challenges of supervised learning (1/6)

An ill-defined problem


- An infinity of potential solutions, one must be the “best one” but is unreachable,
- \Rightarrow requires **priors or constraints**.



Challenges of supervised learning (1/6)

An ill-defined problem


- An infinity of potential solutions, one must be the “best one” but is unreachable,
- \Rightarrow requires **priors or constraints**.



Challenges of supervised learning (1/6)

An ill-defined problem

- An infinity of potential solutions, one must be the “best one” but is unreachable,
- \Rightarrow requires **priors or constraints**.




Challenges of supervised learning (2/6)

Bias/variance trade-off

A **simple** solution that almost matches is better than a complex one that fully matches!

- Bias: Error from **erroneous assumptions in the learning algorithm**.
- Variance: Error from **sensitivity to small fluctuations** in the training set.

Polynomial regression,
 $d = 1$ (under-fit; high bias)




Challenges of supervised learning (2/6)

Bias/variance trade-off

A **simple** solution that almost matches is better than a complex one that fully matches!

- Bias: Error from **erroneous assumptions in the learning algorithm**.
- Variance: Error from **sensitivity to small fluctuations** in the training set.

Polynomial regression,
 $d = 2$




Challenges of supervised learning (2/6)

Bias/variance trade-off

A **simple** solution that almost matches is better than a complex one that fully matches!

- Bias: Error from **erroneous assumptions in the learning algorithm**.
- Variance: Error from **sensitivity to small fluctuations** in the training set.




Challenges of supervised learning (2/6)


Bias/variance trade-off

A **simple** solution that almost matches is better than a complex one that fully matches!


Polynomial regression,
 $d = 1$ (under-fit; high bias)



Polynomial regression,
 $d = 2$




Polynomial regression,
 $d = 6$ (over-fit; high variance)




Challenges of supervised learning (3/6)

Overfitting

Mimicking is not learning: **overfitting** problem.



X n_epochs
Iterate on epochs
To tune hyperparameters




To detect overfitting, you may use a validation set:

- Split the **training** dataset into two parts:
- The first part is used to train,
- The second part is used to validate (Validation Set), i.e. check for overfitting.

Challenges of supervised learning (4/6)

Curse of dimensionality

- Geometry is not intuitive in **high dimension**,
- Efficient methods in 2D are not necessarily still valid.




$$V_d^s = \frac{\pi^{d/2} R^d}{\Gamma(d/2 + 1)} \text{ versus } V_d^c = (2R)^d$$

see <https://youtu.be/dZrGXYty3qc?t=533>

Challenges of supervised learning (4/6)

Curse of dimensionality

- Geometry is not intuitive in **high dimension**,
- Efficient methods in 2D are not necessarily still valid.




$$V_d^s = \frac{\pi^{d/2} R^d}{\Gamma(d/2 + 1)} \text{ versus } V_d^c = (2R)^d$$

see <https://youtu.be/dZrGXYty3qc?t=533>

Challenges of supervised learning (5/6)

Riemannian manifolds



The natural space of data may not always be suited to represent data!
⇒ Part of the reason why embeddings are richer semantically.

Challenges of supervised learning (6/6)

Computation time

Example on ImageNet, simply going through all images:

- $n = 10.000.000$, $d \approx 1.000.000$,
- $\approx 10^{13}$ elementary operations,
- $\approx 2\text{h}45$ on a modern processor.

Scalability

- Finding the best solution to a problem would be feasible with unlimited computation time,
- But searching through the space of possible functions is often **untractable**,
- Solutions must be computationally reasonable, which is the true challenge today.

Challenges of supervised learning (6/6)

Computation time





Example on ImageNet, simply going through all images:

- $n = 10.000.000$, $d \approx 1.000.000$,
- $\approx 10^{13}$ elementary operations,
- $\approx 2\text{h}45$ on a modern processor.

Scalability

- Finding the best solution to a problem would be feasible with unlimited computation time,
- But searching through the space of possible functions is often **untractable**,
- Solutions must be computationally reasonable, which is the true challenge today.

Accuracy, Precision and Recall



https://www.researchgate.net/publication/346129022_Overview_of_Machine_Learning_Part_1/figures

A useful tool: the confusion matrix

		Ground truth		
		+	-	
Predicted	+	True positive (TP)	False positive (FP)	Precision = $TP / (TP + FP)$
	-	False negative (FN)	True negative (TN)	
		Recall = $TP / (TP + FN)$		Accuracy = $(TP + TN) / (TP + FP + TN + FN)$

https://www.researchgate.net/publication/334840641_A_cloud_detection_algorithm_for_satellite_imagery_based_on_deep_learning/figures?lo=1

Lab Session 2 and presentation in Session 3

Lab Supervised Learning

- Basics of machine learning using sklearn (including new definitions / concepts)
- Tests on the modality chosen in Lab 1 (text, vision or audio), based on the same foundation model than in Lab 1.

Project 1 (P1)

Odd binome number must choose one supervised learning method among those available (see Lab 2). You will present

- A description of the theory behind both methods,
- Basic tests on toy datasets and on your modality.

During Session 3 you will have 7 minutes to present.

Careful, **7min is very short!**

Your presentation should be **educational** and addressed to the rest of the class.

List of Supervised Learning Methods

- Adaboost
- Support Vector Machines (SVM)
- Decision Trees
- Random Forest classifiers
- Logistic Regression
- Ridge Classifier