Module 8: Context, Pipeline and Expert Parallelism

Splitting Sequence Length and Model Depth

BRAIN team

IMT Atlantique · January 2027

IMT Atlantique
Bretagne-Pays de la Loire
École Mines-Télécom

BRAIN

Lecture map

1. Context parallelism
2. Pipeline parallelism
3. Expert parallelism
4. Composing parallel dimensions

Guiding question

When width sharding is not enough, how do we divide long contexts and deep models without losing exactness or utilization?

What should be clear by the end?

1. Distinguish context parallelism from sequence parallelism.
2. Explain exact ring attention through online softmax.
3. Compute pipeline bubbles for a micro-batch schedule.
4. Map parallel dimensions to a real cluster topology.

PART 1

Context parallelism

1. Context parallelism
2. Pipeline parallelism
3. Expert parallelism
4. Composing parallel dimensions

Two techniques shard the sequence axis for different reasons

Sequence parallelism

Complements tensor parallelism by sharding token activations around norms, dropout, and elementwise operations.

Context parallelism

Splits a long context across devices so each rank stores only part of the queries and token activations.

The hard part

Attention couples every local query with keys and values that may live on every other rank.

Most layers are local after token sharding


With T split over C context ranks, each rank owns roughly T/C positions.

- tokenwise normalization and MLPs operate locally
- residual additions operate locally
- attention needs remote key-value blocks
- some losses and metrics need global reductions

Memory effect

Token activation memory falls roughly with $1/C$, while communication appears inside every attention layer.

Ring attention rotates key-value blocks



after C rounds: every Q_r has seen all KV blocks

Memory behavior

Only a few KV blocks are resident per rank; no rank gathers the full context or materializes a global $T \times T$ score matrix.

Source: Hugging Face Ultra-Scale Playbook and Ring Attention

Online softmax makes blockwise attention exact

For one query row, maintain running maximum m, normalizer ℓ, and numerator o. For a new score block with maximum m_b:

$$m' = \max(m, m_b)$$

$$\ell' = e^{m-m'}\ell + \sum_j e^{s_j - m'}$$

$$o' = e^{m-m'}o + \sum_j e^{s_j - m'} v_j$$

Final attention is o/ℓ. Rescaling preserves contributions computed under earlier maxima.

Causal attention can imbalance ring work

Early query positions have few valid keys. Late queries have many. A naive contiguous partition gives ranks unequal useful work after masking.

Symptom

Some ranks wait while others process large valid attention regions.

Mitigation


Interleave or pair early and late context blocks so valid attention work is balanced.

PART 2

Pipeline parallelism

1. Context parallelism
2. Pipeline parallelism
3. Expert parallelism
4. Composing parallel dimensions

Pipeline parallelism assigns layer ranges to stages



Why micro-batches?

Split a global batch into M micro-batches so different stages can work on different micro-batches concurrently.

Pipeline bubbles shrink as micro-batches increase

For P balanced stages, M micro-batches, and negligible communication:

$$\text{ideal utilization} \approx \frac{M}{M + P - 1}$$

Worked example

$P = 4$, $M = 16$ gives idle fraction $3/19 \approx 15.8\%$.
Below 10% requires $M > 9(P - 1)$, hence at least 28 micro-batches here.

Trade-off

More micro-batches reduce bubbles but can create smaller, less efficient kernels and more activation bookkeeping.

AFAB and 1F1B trade memory for schedule complexity

All-forward-all-backward

simple schedule
many outstanding activations
higher peak memory

One-forward-one-backward

after warmup, alternate directions
fewer stored activations
more coordination

Both still have warmup and cooldown bubbles. Interleaving virtual stages can reduce them further at added complexity.

The slowest stage sets pipeline throughput

$$t_{\text{cycle}} \approx \max_s t_s$$

- Equal layer counts need not mean equal work.
- Embeddings, output projection, and activation sizes can skew stages.
- Stage boundaries determine activation communication volume.
- Profile stage time and memory before moving boundaries.

Checkpoint: schedule arithmetic

Think, then compare

For six stages and twelve micro-batches, estimate idealized forward utilization. Name two real effects that make measured utilization lower.

PART 3

Expert parallelism

1. Context parallelism
2. Pipeline parallelism
3. Expert parallelism
4. Composing parallel dimensions

Routing tokens to distributed experts

1. A router selects top-k of E expert MLPs for each token.
2. Dispatch sends tokens to ranks hosting those experts.
3. Local experts compute and return outputs for weighted combination.

What changes?

EP distributes expert weights. Shared attention weights remain replicated over EP ranks. Uneven routing can overload one rank.

Source: Megatron Core parallel configuration: EP subdivides the data-parallel dimension

PART 4

Composing parallel dimensions

1. Context parallelism
2. Pipeline parallelism
3. Expert parallelism
4. Composing parallel dimensions

The device count factorizes across parallel groups

$$N_{\text{GPU}} = D \times T_p \times C \times P$$

Dimension	Splits	Communication pattern
data	independent micro-batches	gradient or shard collectives
tensor	hidden width and heads	frequent activation collectives
context	sequence positions	key-value exchange per layer
pipeline	layer depth	point-to-point activations

Subgroups reuse existing devices

- D counts the total data-parallel degree.
- FSDP degree F divides D: D/F groups replicate state shards.
- EP degree E_P can divide D: each expert has D/E_P replicas.
- Shared and expert parameters use different synchronization groups.

Eight-device example

$D = 4, T_p = 2, C = P = 1$. Setting $E_P = 4$ still uses eight devices.
Global tokens/update: $B_\mu\, T\, A\, D$.

Source: Teaching layout: combined EP/FSDP requires separate expert shard-group definitions

Map the chattiest group to the fastest fabric

1. Start by placing frequent TP collectives on a fast fabric.
2. Add context parallelism when token activations or attention exceed local memory.
3. Use pipeline parallelism when model depth spans nodes.
4. Replicate the resulting model group with data parallelism when batch and devices remain.

Selection rule

State the rank layout and measure exposed transfer time. Persistent state excludes activations, gathered weights, and communication buffers.

Four cases lead to different strategies

Binding constraint	First strategy to evaluate
model fits, short context, more GPUs	DDP or FSDP replicas
one wide layer does not fit	tensor parallelism
weights fit, 128k-token examples do not	context parallelism plus checkpointing
model exceeds one node	pipeline across nodes, TP within node

Checkpoint: cluster design

Think, then compare

Design a layout for 32 GPUs arranged as four 8-GPU nodes. State the memory constraint, proposed D, T_p, C, P, and which communication crosses node boundaries.

Key takeaways

1. Context parallelism shards tokens and uses exact blockwise attention with online softmax.
2. Pipeline parallelism shards depth, while micro-batches trade bubble size against memory and kernel efficiency.
3. Load balance matters across causal context blocks and pipeline stages.
4. Count independent axes once and test placement against measured memory and communication.