

Git Cheat Sheet



Git Basics

git init <directory>	Create empty Git repo in specified directory. Run with no arguments to initialize the current directory as a git repository.	
git clone <repo>	Clone repo located at <repo> onto local machine. Original repo can be located on the local filesystem or on a remote machine via HTTP or SSH.	
git config user.name <name>	Define author name to be used for all commits in current repo. Dews commonly use --global flag to set config options for current user.	+
git add <directory>	Stage all changes in <directory> for the next commit. Replace <directory> with a <file> to change a specific file.	
git commit -m "<message>"	Commit the staged snapshot, but instead of launching a text editor, use <message> as the commit message.	
git status	List which files are staged, unstaged, and untracked.	
git log	Display the entire commit history using the default format. For customization see additional options.	+
git diff	Show unstaged changes between your index and working directory	+
Undoing Changes		
git revert <commit>	Create new commit that undoes all of the changes made in <commit>, then apply it to the current branch.	
git reset <file>	Remove <file> from the staging area, but leave the working directory unchanged. This unstages a file without overwriting any changes.	+
git clean -n	Shows which files would be removed from working directory. Use the -f flag in place of the -n flag to execute the clean.	

Rewriting Git History

git commit --amend	Replace the last commit with the staged changes and last commit combined. Use with nothing staged to edit the last commit's message.	
git rebase <base>	Rebase the current branch onto <base>. <base> can be a commit ID, a branch name, a tag, or a relative reference to HEAD.	+
git reflog	Show a log of changes to the local repository's HEAD. Add --relative-date flag to show date info or --all to show all refs.	

Git Branches

git branch	List all of the branches in your repo. Add a <branch> argument to create a new branch with the name <branch>.	
git checkout -b <branch>	Create and check out a new branch named <branch>. Drop the -b flag to checkout an existing branch.	
git merge <branch>	Merge <branch> into the current branch.	

Remote Repositories

git remote add <name> <url>	Create a new connection to a remote repo. After adding a remote, you can use <name> as a shortcut for <url> in other commands.	
git fetch <remote> <branch>	Fetches a specific <branch>, from the repo. Leave off <branch> to fetch all remote refs.	
git pull <remote>	Fetch the specified remote's copy of current branch and immediately merge it into the local copy.	+
git push <remote> <branch>	Push the branch to <remote>, along with necessary commits and objects. Creates named branch in the remote repo if it doesn't exist.	+

Additional Options +



git config	
<code>git config --global user.name <name></code>	Define the author name to be used for all commits by the current user.
<code>git config --global user.email <email></code>	Define the author email to be used for all commits by the current user.
<code>git config --global alias.<alias-name> <git-command></code>	Create shortcut for a Git command. E.g. <code>alias, glog "log --graph --oneline"</code> will set "git glog" equivalent to "git log --graph --oneline"
<code>git config --system core.editor <editor></code>	Set text editor used by commands for all users on the machine. <editor> arg should be the command that launches the desired editor (e.g., vi).
<code>git config --global --edit</code>	Open the global configuration file in a text editor for manual editing.
git log	
<code>git log --limit<</code>	Limit number of commits by <limit> . E.g. "git log -5" will limit to 5 commits
<code>git log --oneline</code>	Condense each commit to a single line.
<code>git log --stat</code>	Include which files were altered and the relative number of lines that were added or deleted from each of them.
<code>git log -p</code>	Display the full diff of each commit.
<code>git log --author=<pattern>"</code>	Search for commits by a particular author.
<code>git log --grep=<pattern>"</code>	Search for commits with a commit message that matches <pattern>.
<code>git log <since>..<code><until></code></code>	Show commits that occur between <since> and <until>. Args can be a commit ID, branch name, HEAD, or any other kind of revision reference.
<code>git log -- <file></code>	Only display commits that have the specified file.
<code>git log --graph --decorate</code>	--graph flag draws a text based graph of commits on left side of commit msgs. --decorate adds names of branches or tags of commits shown.

git diff	
<code>git diff HEAD</code>	Show difference between working directory and last commit.
<code>git diff --cached</code>	Show difference between staged changes and last commit.
git reset	
<code>git reset</code>	Reset staging area to match most recent commit, but leave the working directory unchanged.
<code>git reset --hard</code>	Reset staging area and working directory to match most recent commit and overwrites all changes in the working directory.
<code>git reset --hard <commit></code>	Move the current branch tip backward to <commit>, reset the staging area to match, but leave the working directory alone.
<code>git reset --hard</code>	Same as previous, but resets both the staging area & working directory to match. Deletes uncommitted changes, and all commits after <commit>.
git rebase	
<code>git rebase -i</code>	Interactively rebase current branch onto <base>. Launches editor to enter commands for how each commit will be transferred to the new base.
git pull	
<code>git pull --rebase <remote></code>	Fetch the remote's copy of current branch and rebases it into the local copy. Uses git rebase instead of merge to integrate the branches.
git push	
<code>git push <remote> --force</code>	Forces the git push even if it results in a non-fast-forward merge. Do not use the --force flag unless you're absolutely sure you know what you're doing.
<code>git push <remote> --all</code>	Push all of your local branches to the specified remote.
<code>git push <remote> --tags</code>	Tags aren't automatically pushed when you push a branch or use the --all flag. The --tags flag sends all of your local tags to the remote repo.