

12 SEPTEMBER 2025 • MANUAL

POT JS

This is the Javascript API for the Go POT implementation that allows to write and read key-value pairs to and from the Swarm decentralized storage network.

A POT storage tree structure allows to have updateable key-value maps stored on an immutable, decentralized, content-addressable network like Swarm. It is called Proximity Order Tree (POT) after a fundamental, new storage technique that is described in a forthcoming paper.





INDEX

USE	3
QUICK START	3
<i>Example</i>	3
INTRODUCTION	4
<i>Purpose</i>	4
<i>Proximity Order Tree</i>	4
<i>Coding</i>	5
<i>Error Strategy</i>	8
<i>Crashes</i>	8
<i>Further Reading</i>	9
TUTORIAL	9
<i>Web App</i>	9
<i>Node App</i>	15
FUNCTIONS	24
EXAMPLES	26
<i>Example 1</i>	26
<i>What You Should See</i>	27
<i>Example 2: Interaction</i>	27
<i>Example 3: Initialization</i>	29
<i>Example 4: Synchronous</i>	30
<i>Example 5: Network</i>	31
<i>Example 6: Network II</i>	32
<i>Example 7: Node</i>	32
<i>What You Should See</i>	32
<i>Examples 8 and 9: Web App</i>	33
<i>What You Should See</i>	35
BUILDING	37
<i>What You Should See</i>	38
CLEAN BUILD	38
<i>What You Should See</i>	38
REQUIREMENTS	39
<i>POT JS API</i>	39
<i>GO POT</i>	40
TESTS	41
<i>What You Should See</i>	41
DEVELOPING	46
FILES	47
MAKE	48
DEVELOPER NOTES	49
<i>Notes on Debugging</i>	49
<i>Note on syscall/js</i>	49
<i>Initialization</i>	50
<i>Types</i>	51
<i>Tests</i>	52
<i>Error Handling</i>	53
<i>A JS API in implemented in Go</i>	53
ROADMAP	58

USE

QUICK START

- Drop `pot.wasm`, `potjs.js`, and `wasm\_exec.js` in a directory.
- Write some html and js using functions **new()**, **put()**, **get()**, **save()**, **restore()**.
- Check out the function reference and examples.

There is no need to *build* the project, i.e., no need to install or run Go, to *use* it.

EXAMPLE

```
<script src="wasm_exec.js"></script>
<script src="potjs.js"></script>

<script>

(async () => {

    await pot.ready()
    map = await pot.new()
    await map.put("hello", "POT!")
    value = await map.get("hello")
    console.log("key <hello> has:", value)
})();

</script>
```

Check out the function reference.



INTRODUCTION

This is an introduction to how POT JS is used. The basics are simple. You may work through the structured explanation below; or turn to the practical tutorial, to get a deeper understanding. You might decide to check out the separate function reference after a cursory look at this introduction, to beat your own path.

PURPOSE

The purpose of POT JS is to provide a simple and efficient way to store and retrieve key-value pairs to and from the immutable, decentralized storage network Swarm.

This is achieved with the main primitives being:

```
kvs = await pot.new(swarm, batch)
await kvs.put("some key", "some value")
value = await kvs.get("some key")
```

This almost constitutes a complete example program, cf. example 1 (pg. 26).

PROXIMITY ORDER TREE

POT JS allows to use proximity order trie (POT) functionality in the browser or to run it with node.js.

A proximity order tree is a data structure that allows to operate a key-value store on an immutable storage network. Concretely, it allows to use Swarm as a database; or to store a map-like structure to it, and be able to change it.

This evokes two oxymorons: an immutable storage would seem to not allow for any update of values, nor adding of additional key-value pairs. And Swarm is content-addressed: a hash of the content (not an arbitrary key) constitutes the address of the content in the network, to retrieve it by.

POT exploits a feature observed in Merkle tries when hashing its nodes: after an update, there is only one path back to the root that has to be re-hashed to arrive at a new root hash. All other hashes in



the trie remain the same, as no values that are part of their pre-images have changed. POT uses this observation to implement an update to the data stored in the trie as a change of the root hash. Because a network like Swarm functionally provides the inverse to the hashing process – it returns the pre-image to the hash, as that is the definition of content-addressing – the update process of a Merkle trie can be repurposed as the re-indexing mechanism of a tree that stores content-addressed data. A new root hash will be created on every update that serves as the new entry point to the now-valid tree of data entries. Deleted nodes are not present anymore, updated ones in their new form. Those entries still exist in-storage. But they are not part of the hash tree anymore. The nodes that held the key-value pair of an updated pair that now has a new value are simply not part of the picture anymore as their combined key and value contents has changed its hash.

The keys to values are not a native search input to Swarm, which is made for retrieving pre-images of hashes. To search for a specific key to retrieve the value that was stored under it is therefore not something Swarm's base layer can help with. To navigate this data store at a useful pace – for the system to both understand where to find the value to a key, as well as where to insert the new value associated with a new key – a proximity order trie uses the bit patterns of a key's hash to establish a logarithmic time search order. It is described in a forthcoming paper.

POT JS uses the implementation of POT in Go:

<https://github.com/ethersphere/proximity-order-trie>

CODING

INITIALIZATION

For use in the browser, to initialize, include the generic **wasm_exec.js** and **potjs.js**, then wait for the initialization to finish:

```
<script src="wasm_exec.js"></script>
<script src="potjs.js"></script>

<script>

(async () => {

    await pot.ready()

    ...
})();
...
```



DATA STORAGE

After `pot.ready()` resolves, the JS `pot` object can be used to create a new map. Use `put()` and `get()` functions on it.

This example uses an in-memory storage, the default that is useful for testing and prototyping.

```
map = await pot.new()

await pot.put("hello", "Hello, P.O.T.!")

value = await pot.get("hello")
```

See [example1.html](#).

NETWORK CONNECTION

The connection to a Swarm network needs a URL to a Swarm bee node http API and a batch id to pay for storage. The arguments are given to the `new()` function.

For example, for node.js:

```
bee = process.argv[2]
batch = process.argv[3]

map = await pot.new(bee, batch)
```

An example invocation would be

BATCH ID

A batch ID stands for 'postage stamps' that Swarm uses for incentivization, i.a. to compensate its Bee nodes to keep copies of the stored data.

The Makefile for example 9 is an example for how to start a local Swarm test network and create a batch id on it, in essence a free batch of stamps on your own local Swarm test network.

The following script extracts the new batch ID and stores it into `.batch_id`

```
@echo "⊙ starting five local swarm nodes"
fdp-play start --detach

@echo "⊙ buy stamps (free in this test setup)"
swarm-cli stamp buy --yes --verbose --depth 20 --amount 1b | tee .batch_creation
```



```
grep "Stamp ID:" .batch_creation | cut -c11-74 > .batch_id
@echo "⊙ postage batch ID: $(cat .batch_id)"

@echo "⊙ start tests (check browser)"
node test/test_node.js loc-net http://localhost:1633 $(cat .batch_id)

@echo "⊙ wait before shutdown"
sleep 120

@echo "⊙ bee node logs"
docker container logs --tail 1000 fdp-play-queen

@echo "⊙ stopping nodes"
fdp-play stop
```

EXPLICIT INITIALIZATION

You may leave out `potjs.js` to initialize with more direct control: include only the generic Go WASM wrapper `wasm_exec.js`, create a `Go` object and instantiate the POT WASM object `pot.wasm`, then run it once it is loaded. See [example3.html](#):

```
<script src="wasm_exec.js"></script>

<script>

const go = new Go()
WebAssembly.instantiateStreaming(fetch("pot.wasm"), go.importObject)
  .then((potwasm)=>{ go.run(potwasm.instance) })

...
```

Use `onWasmLoaded()` for the start of your POT JS use:

```
async function onWasmLoaded() {

  map = await pot.new()

  await map.put("hello", "POT!")

  value = await map.get("hello")

}
```



ERROR STRATEGY

The error strategy of the API is JS-Style, using JS exceptions triggered from the go wasm functions via promise mechanisms, rather than returning error codes, Go-style.

The implementation of this is in Go though (**potjs.go**), not in JS, creating JS code in Go, with full data/situational access on the Go side. A major challenge is that Javascript exceptions cannot be thrown from Go. What works is to call the reject parameter of in the executor of JS promises that are constructed in Go. Because the most relevant functions are implemented like this at any rate, this covers most cases.

Synchronous functions, however, in part return JS error objects that have to be tested for where an exception would normally be expected.

CRASHES

The Go WASM executable, **pot.wasm**, can deadlock and crash, in which case it cannot be recovered. All POT JS functions stop working and throw an error instead that reports that the Go executable is down. In this case, **pot.wasm** must be re-initialized before the POT JS functions can be used again. This affects all **pot** and **map** functions, it means that while everything else might still work, literally the methods of a **map** that on the face look like native Javascript functions, are dead.

Reasons for crashing are deadlocks and uncaught panics on the side of the Go executable. Multiple measures are in place to keep the executable alive in all scenarios, to handle panics gracefully and to not allow a deadlock to happen. To maximize robustness, one might still want to program aware of this case, which means to avoid synchronous functions in production.

The capability to deadlock is not a fault of the Go POT implementation but presumably lies in the single-thread nature of Javascript that can be programmed highly asynchronously but is not truly parallel, multi-threaded, or multi-process (except when using the duly limited Web Workers). That Javascript is designed this way provides strong safeguards against a class of difficult to track errors. But they are coming off when crossing from Javascript into Go-land *and back*: a blocking wait in Go that hands control back to the browser deadlocks its main Javascript execution thread. Javascript waits for Go to continue and Go for Javascript. This is reliably the case when Go executes a network fetch that is handed back from WASM to Javascript to execute. When using POT JS to write to and read from Swarm, almost every function contains a fetch. When programming against one of the in-memory persistence models, none does.



FURTHER READING

Refer to the examples in the `examples/` folder and or the Examples chapter to understand how POT JS might be used in the specific use case you envision.

The function reference in the `doc/` folder explains all available functions with additional example snippets.

The tutorial visits a number of relevant angles to get a fuller picture.

TUTORIAL

This is a step by step guide how to use POT JS in the browser, or with node.js.

We'll discuss the building blocks, alternative options, and aspects that deserve attention.

We will start with a minimal in-browser example, develop it into a more interactive experience that is the prototype of a web app while shifting functionality from the browser to the server-side to show both options.

If you are really fast, frankly, checking out `examples/example1.html` may be all you need to get going, then use the `function reference` document in `doc/`.

WEB APP

INSTALLATION

For our first tutorial, create a new directory, and clone POT JS into it

```
% mkdir t1 ; cd t1
% git clone https://github.com/brainiac-five/potjs
```

There is no building or installation required beyond this.



The files we need will be `potjs/lib/pot.wasm` and `potjs/lib/wasm_exec.js`. That is, the Go implementation with JS interface compiled to WASM, and Go's standard JS WASM wrapper. They are both portable across operating systems and browsers.

PHASES

In general, there are the initialization, standard operations, and error conditions to think of. We will look at the happy path first.

INITIALIZATION

POT JS uses the Go implementation of POT. The Go parts are compiled to a WASM executable, which is loaded into Javascript. The procedure is the about the same in both the browser and node.js.

For our first example, create a html file `t1.html` that has the following contents:

```
<script src="potjs/lib/wasm_exec.js"></script>
<script>
  const go = new Go()
  WebAssembly.instantiateStreaming(fetch("potjs/lib/pot.wasm"), go.importObject)
    .then((r) => { go.run(r.instance) })
  async function onWasmLoaded() {
    console.log("READY.")
  }
</script>
```

tutorial/t1-step-1.html

This is the standard for initialization that any project using POT JS needs to employ. In node.js a different function is used for streaming, and it can all be used pre-packaged, as we will show later. But the basics to get started are always this:

The first line includes Go's standard JS WASM wrapper.

The fourth line `WebAssembly.instantiateStreaming( ... )` loads the Go implementation of POT in its web assembly form, `pot.wasm`, to be used with Javascript.

Once it is loaded, it is executed by `go.run(r.instance)`, and actually does not stop. It keeps running and waiting for the next call.



But when its initializations are done – e.g., registering the Javascript function `pot.new()` etc. – it calls `onWasmLoaded()` to signal that the POT functionality is now usable.

To run the script, serve the directory with a web server, e.g. ...:

```
% npx http-server -c1 .
```

... and in a browser open:

```
http://localhost:8080/t1.html
```

The page will be blank. If you open the developer console (with Mac Chrome, option + command + J), you should see:

```
pot: » POTWASM
pot: » init done
t1.html:12 READY.
pot: » ready
```

browser console of tutorial/t1-step-1.html

In the terminal you should have log entries by `http-server`:

```
Starting up http-server, serving .

http-server version: 14.1.1

http-server settings:
CORS: disabled
Cache: 1 seconds
Connection Timeout: 120 seconds
Directory Listings: visible
AutoIndex: visible
Serve GZIP Files: false
Serve Brotli Files: false
Default File Extension: none

Available on:
  http://127.0.0.1:8080
  http://192.168.178.192:8080
Hit CTRL-C to stop the server

[2025-09-13T11:45:40.420Z] "GET /t1.html" "Mozilla/5.0 (Macintosh; Intel Mac OS X 10_15_7) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/138.0.0.0 Safari/537.36"
(node:6393) [DEP0066] DeprecationWarning: OutgoingMessage.prototype._headers is deprecated
(Use `node --trace-deprecation ...` to show where the warning was created)
[2025-09-13T11:45:40.476Z] "GET /potjs/lib/wasm_exec.js" "Mozilla/5.0 (Macintosh; Intel Mac OS X 10_15_7) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/138.0.0.0 Safari/537.36"
[2025-09-13T11:45:40.567Z] "GET /potjs/lib/pot.wasm" "Mozilla/5.0 (Macintosh; Intel Mac OS X 10_15_7) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/138.0.0.0 Safari/537.36"
```

terminal output of tutorial/t1-step-1.html



→ you successfully initialized POT.

STANDARD OPERATIONS

The main functions of POT JS are `put()` and `get()`. Maps are created with `new()`. They are saved to the network (or to in-memory POT if that is elected) using `save()` and retrieved with `newByReference()`.

We add a write and a read to our example. In `onWasmLoaded()` under `READY`. add:

```
map = await pot.new()
await map.put("hello", "POT!")
value = await map.get("hello")
console.log("key <hello> has:", value)
```

The first line creates a new key-value-store. What is special about POT is that it can be stored on an immutable storage network like Swarm. For our test though, we are using an in-memory storage for now.

The next line puts the string “POT” in the store, retrievable under the key “hello”.

The next line does exactly that: retrieve the value of key “hello”, which should be “POT”.

The last line prints the resulting `value` on the browser console, which will be “POT”.

To try it out, serve the directory, e.g., ...:

```
% npx http-server -c1 .
```

... and open the page:

```
http://localhost:8080/t1.html
```

The page will again be blank.

If you open the developer console, you should see:

```
pot:  » POTWASM
pot:  » init done
t1.html:12 READY.
pot:  » initialize new P.O.T.
pot:  » created new in-memory persister
pot:  » using in-memory persister
pot:  slot ref: 1
pot:  » ready
pot:  » put hello: POT!
```




```
if(!wasm) wasm = "pot.wasm"
WebAssembly.instantiateStreaming(fetch(wasm), go.importObject)
  .then((r) => { go.run(r.instance) ; resolve(pot) })
  .catch((e) => { reject(e) })
})

pot.ready = () => { return pot.start }
```

lib/potjs.js

It wraps the initialization steps we discussed above into a promise and allows to inquire via `pot.ready()` whether the initialization has **started**. This is not quite as precise as waiting for the call of `onWasmLoaded()` and will be improved going forward because it can be too early.

However, using `potjs.js` our tutorial code can be abbreviated to:

```
<script src="potjs/lib/wasm_exec.js"></script>
<script src="potjs/lib/potjs.js" wasm="potjs/lib/pot.wasm"></script>

<script>
  async function onWasmLoaded() {
    console.log("READY.")
    map = await pot.new()
    await map.put("hello", "POT!")
    value = await map.get("hello")
    console.log("key <hello> has:", value)
  }
</script>
```

tutorial/t1-step-3.html

This code works exactly like the version before, giving the same logs.

SUB-COMPONENT INTEGRITY

To safeguard the integrity of the included scripts – but not the WASM script – fingerprints can be hardcoded into the HTML.

The required SHA-384 hashes can be found in `potjs/lib/*.sha384`. A “sha384-” must be prepended for the integrity tag.

The first two lines become:

```
<script src="potjs/lib/wasm_exec.js" integrity="sha384-
PWCs+V4BDf9yY1yjKD/p+9xNEs4iEbuVq+HezA0JiY3XL5GI6VyJXmsvnjiwNbce"></script>
```



```
<script src="potjs/lib/potjs.js" wasm="potjs/lib/pot.wasm" integrity="sha384-woy0Fou09EcyFemKbNcnl+HI7XRxaENJQgJPdgPuBMqagXwTWzUgF+zLVIGzeQQF"></script>
```

beginning of tutorial/t1-step-4.html

This code works exactly like before, showing the same results.

ERROR CONDITIONS

The WASM executable is not a library but a Go program that runs continually, waiting for the next request. If it crashes, the functionality it extends just goes away. The main methods of JS objects that POT JS defines become unavailable.

It is relatively easy to deadlock the Go WASM by using the synchronous functions in the wrong context. Those are the POT JS functions ending on **Sync**. They are generally not safe to use when using a Swarm network as storage backend, that is, in the standard case.

In case the Go WASM program goes down, it has to be re-initialized.

NODE APP

For the next step, we will look at how POT JS works with node.js instead of the browser.

We'll create a single-script web app next that can persist data it handles server-side on Swarm. The result is going to be almost identical to example 8 (**examples/example8.js**).

Create a new folder, change into it and clone potjs into it.

```
% mkdir t2 ; cd t2
% git clone https://github.com/brainiac-five/potjs
```

INSTALLATION

For clarity, copy the two executables we need out of the repo and delete the rest.

```
% cp potjs/lib/pot.wasm .
% cp potjs/lib/wasm_exec.js .
% rm -rf potjs
```

Create a node.js/potjs test script **t2.js** and run it.



Stop the server and enhance the definition of the `page` variable to become an input form:

```
const page = `

```
<form method=post action="http://localhost:3000">
 key <input name=key>
 value <input name=value>
 <input type=submit name=button value=put>
<hr />
 key <input name=search>
 <input type=submit name=button value=get>
 value <input name=result>
</form>
</pre>`
```


```

part of `./tutorial/t2-step-3.js`

Running the server again, reloading the page `http://localhost:3000` in the browser you should see:

POT JS Example 8: Node.js Web App

| | |
|-------|------------------------------------|
| key | <input type="text"/> |
| value | <input type="text"/> |
| | <input type="button" value="put"/> |

| | |
|-------|------------------------------------|
| key | <input type="text"/> |
| | <input type="button" value="get"/> |
| value | <input type="text"/> |

screen of `./tutorial/t2-step-3.js`



INTERACTION

To interact with the form in the browser, we'll first clean up marginally. Change the WASM hook to:

```
global.onWasmLoaded = () => {  
  kvs = pot.newSync()  
}
```

part of `./tutorial/t2-step-4.js`

Replace the request handler, `server()`, with:

```
const http = require('http')  
const qs = require('querystring')  
  
const server = http.createServer(function(request, response) {  
  if (request.method == 'POST') {  
    var body = ''  
    request.on('data', function(data) {  
      body += data  
    })  
  
    request.on('end', async function() {  
      var value = "put"  
      post = qs.parse(body)  
  
      if(post.button == 'put')  
        await kvs.put(post.key, post.value)  
      else  
        value = await kvs.get(post.search)  
  
      response.writeHead(200, {'Content-Type': 'text/html'})  
      response.end(value)  
    })  
  }  
  else {  
    response.writeHead(200, {'Content-Type': 'text/html'})  
    response.end(form)  
  }  
})  
.listen(3000, '127.0.0.1')
```

The following line reads the value entered in the second form field and writes it to the POT. The first form field is used to enter the key that it is saved under.

```
await kvs.put(post.key, post.value)
```

In the browser, this looks like this: e.g., entering A for the key, and 123 for the value.



```
async function put(key, value) {
  await kvs.put(key, value)
  return `put ${key}: ${value}`
}

async function get(search) {
  value = await kvs.get(search)
  return `get ${search}: ${value}`
  <script>
    document.getElementsByName('result')[0].value = `${value}`
  </script>
}
```

part of `./tutorial/t2-step-5.js`

Then replace the request hook with calls to the `put()` and `post()` functions we just defined.

They are replacing the direct calls to `kvs.put()` and `kvs.get()`.

We are also adding a variable, `log`, to gather a minimal status report.

```
request.on('end', async function() {
  var log
  const post = qs.parse(body)
  if(post.button == 'put')
    log = await put(post.key, post.value)
  else
    log = await get(post.search)

  console.log("srv: " + log.match(/.*\/)[0])

  response.writeHead(200, {'Content-Type': 'text/html'})
  response.end(form + '<hr><br><pre>\t\t' + log)
})
```

part of `./tutorial/t2-step-5.js`

The complete code we arrived at is:

```
const page = `<pre>
  <form method=post action="http://localhost:3000">
    key   <input name=key>
    value <input name=value>
          <input type=submit name=button value=put>
  <hr />
```



```
key    <input name=search>
      <input type=submit name=button value=get>
value  <input name=result>
</form>

</pre>`

const fs = require("fs")
require("./wasm_exec") // note the ./

var go = new Go()
var kvs

WebAssembly.instantiate(fs.readFileSync("./pot.wasm"), go.importObject)
  .then((r) => { go.run(r.instance) })

global.onWasmLoaded = () => {
  kvs = pot.newSync()
}

async function put(key, value) {
  await kvs.put(key, value)
  return `put ${key}: ${value}`
}

async function get(search) {
  value = await kvs.get(search)
  return `get ${search}: ${value}`
  <script>
    document.getElementsByName('result')[0].value = `${value}`
  </script>
}

const http = require('http')
const qs = require('querystring')

const server = http.createServer(function(request, response) {
  if (request.method == 'POST') {
    var body = ''
    request.on('data', function(data) {
      body += data
    })

    request.on('end', async function() {
      var log
      const post = qs.parse(body)

      if(post.button == 'put')
        log = await put(post.key, post.value)
      else
        log = await get(post.search)

      console.log("srv: " + log.match(/.*/)[0])

      response.writeHead(200, {'Content-Type': 'text/html'})
      response.end(page + '<hr><br><pre>\t\t' + log)
    })
  }
  else {
    response.writeHead(200, {'Content-Type': 'text/html'})
```



```
    response.end(page)
  }
})
.listen(3000, '127.0.0.1')
```

`./tutorial/t2-step-5.js`

Running it

```
% node t2.js
```

We see the form fields as before, but pressing buttons does make the page disappear.

The result of the get is shown in the fourth form field.

Both put and get results are shown in the bottom line.

This is what you will see, although not at the same time:

key

value

key

value

put B: 5

screens of `./tutorial/t2-step-5.js`

CONCLUSION

POTJS works with node.js as easily as it works in the browser. It doesn't get in the way and is a simple way to store state of a web app to a trustless, decentralized network.



FUNCTIONS

The focus of the functions are `get()` and `put()`. They are split in two by two main groups, for four different ways of calling. Additionally, there are `init`, `test` and support functions.

The groups are asynchronous / synchronous and typed / raw respectively. Asynchronous functions return promises, synchronous functions block and return a value, error or null. Typed functions mark the Javascript type in the storage, to automatically return the right type on retrieval. This can be boolean, number,¹ or string. Raw functions accept a Uint8Array of bytes to store and the right function has to be called to get the expected type back out. The synchronous functions' names end on `Sync`. The raw functions have `Raw` as a name component. The most relevant functions are `put()` and `get()`, which are asynchronous, typed functions. That means, `get()` returns a promise for the value to be retrieved and it will automatically be in the type that it was stored with `put()`.

Synchronous functions can be handy for prototyping and special situations but generally only work for tests in the browser using the in-memory persistence of the Go POT implementation, not when connecting to Swarm or a test network, and not when using node. It is possible that they might work well with the background threads of Web Workers but this has not been tested. Therefore, they should simply NOT be used in production. The asynchronous functions work in all circumstances.

Raw functions will be useful in special situations, whenever binary data is handled, but usually the vanilla (typed, asynchronous) functions `new`, `save`, `put` and `get` will be the first choice.

For details and examples, see file **Pot – (III) 31 August 2025 function reference.pdf**.

MAP INITIALIZATION

<code>pot.new</code>	create a new Swarm key-value-store, i.e., a map, async
<code>pot.newByReference</code>	create a new Swarm map from a reference of a prior save, async
<code>map.save</code>	store a Swarm KVS to the network, async
<code>pot.newSync</code>	create a new Swarm key-value-store, i.e., a map, sync
<code>pot.newByReferenceSync</code>	create a new Swarm map from a reference of a prior save, sync
<code>map.saveSync</code>	store a Swarm KVS to the network, sync

TYPE-AWARE

<code>put</code>	return a promise for null or Error. Asynchronous.
<code>get</code>	return a promise for the typed get, the type will be as put. Async.
<code>putSync</code>	return a promise for null or Error. Synchronous.
<code>getSync</code>	return a promise for the typed get, i.e., the type will be as put. Sync.

¹ Javascript does not have native integers and stores all numbers as IEEE 754 64-bit floats internally.



RAW BYTE ACCESS

<code>putRaw</code>	put a raw <code>Uint8Bytes</code> array, async.
<code>getRaw</code>	get a raw <code>Uint8Bytes</code> array, async.
<code>getBoolean</code>	get the raw value as Boolean. First byte 0 for false, all else true, async.
<code>getNumber</code>	get the raw value as floating point number. Must be 8 bytes. Async.
<code>getString</code>	get the raw value as string, async.
<code>putRawSync</code>	put a raw <code>Uint8Bytes</code> array, synchronous.
<code>getRawSync</code>	get a raw <code>Uint8Bytes</code> array, synchronous.
<code>getBooleanSync</code>	get the raw value as Boolean. First byte 0 for false, all else true, sync.
<code>getNumberSync</code>	get the raw value as floating point number. Must be 8 bytes. Sync.
<code>getStringSync</code>	get the raw value as string, synchronous.

POT INITIALIZATION

<code>pot.ready</code>	promise that resolves when pot.wasm is initialized. Include <code>potjs.js</code> .
<code>onWasmLoaded</code>	called, if it exists, by pot.wasm when it is initialized. Without <code>potjs.js</code> .

TESTING AND SUPPORT

These functions are not used in production. They serve to test the integrity of POT JS.

<code>log</code>	write to browser console via Go to verify a language-land roundtrip
<code>hello</code>	write hello to browser console to verify established WASM stream
<code>randKey</code>	32 random bytes for key testing
<code>randValue</code>	79 to 101 random bytes for value testing (range from Go POT)
<code>type_encoded_bytes</code>	JS type detection and value encoding with correct leading type byte
<code>type_decoded_value</code>	JS type detection of raw kvs value by leading type byte
<code>hangingPromise</code>	blocking promise (in Go) with time out for exception testing
<code>setFail</code>	trigger the next mock storage function called to return an error
<code>setPanic</code>	trigger the next mock storage function called to raise a panic
<code>setDelay</code>	trigger the next mock storage function called to stall for a given time
<code>setHang</code>	trigger the next mock storage function called to stall indefinitely



EXAMPLES

To run the examples, serve the main directory with ``npx http-server .`` and open ``http://127.0.0.1:8080/example1.html``.

Or use

```
make example1
```

etc. There are nine examples 1-9 that can be started this way.

example1.html	briefest example as listed above, in-memory storage
example2.html	interactive example, input fields, integrity
example3.html	example 2 dropping potjs.js for more control
example4.html	example 1 using synchronous access functions
example5.html	example 1 but with connection to a storage network
example6.html	example 5 with better connection to make rules
example7.js	example 1 for execution with node.js
example8.js	Single-source web app with node.js
example9.js	Identical to example 8, just called differently

EXAMPLE 1

A simple put and get, logging to console.

example1.html

```
<script src="wasm_exec.js"></script>
<script src="potjs.js"></script>

<script>
(async () => {
  await pot.ready()
  map = await pot.new()
  await map.put("hello", "POT!")
  value = await map.get("hello")

  console.log("key <hello> has:", value)
})();
```




```
value <input id=result>

<img src=favicon.ico>

</pre>
<script src="wasm_exec.js" integrity="sha384-
PWCs+V4BDf9yY1yjkD/p+9xNEs4iEbuVq+HezA0JiY3XL5GI6VyJXMsvnjwNbce"></script>
<script src="potjs.js" integrity="sha384-
dUfhLIycF6GUpRyXIlIiAAQR3rh3KsPxPdsgq4tP2rTe7grND7bXjAj4nawjq5Ht"></script>
<script>
var map
(async () => {
  await pot.ready()
  map = await pot.new()
})();
const field = (id) => { return document.getElementById(id) }
async function put() {
  key = field('key').value
  value = field('value').value
  await map.put(key, value)
}
async function get() {
  key = field('search').value
  value = await map.get(key)
  field('result').value = value
}
</script>
```

WHAT YOU SHOULD SEE

After entering a value for key and value, and hitting put. Then entering the same key in the lower screen area and hitting get should yield the value in the lowest field.



```
value <input id=value>
      <button onclick="put()"> put </button>

<hr />

key    <input id=search>
      <button onclick="get()"> get </button>
value  <input id=result>

</pre>
<script src="wasm_exec.js"></script>
<script>
  const go = new Go()
  var map;

  WebAssembly.instantiateStreaming(fetch("pot.wasm"), go.importObject)
    .then((r)=>{
      go.run(r.instance)
      map = pot.newSync()
    })

  const field = (id) => { return document.getElementById(id) }

  async function put() {
    key = field('key').value
    value = field('value').value
    await map.putSync(key, value)
  }

  async function get() {
    key = field('search').value
    value = await map.getSync(key)
    field('result').value = value
  }
</script>
```

EXAMPLE 4: SYNCHRONOUS

This page uses synchronous calls that can be helpful for prototyping but don't work for network connections (only in-memory = new() without parameters) and not for use with node.

**example4.html**

```
<script src="wasm_exec.js"></script>
<script src="potjs.js"></script>

<script>
function onWasmLoaded() {
    map = pot.newSync()
    map.putSync("hello", "POT!")
    value = map.getSync("hello")
    console.log("key <hello> has:", value)
}
</script>
```

EXAMPLE 5: NETWORK

This page connects to a local Swarm network.

The example is for illustration, the batch id would have to be updated. See example5.html (and 6).

example5.html

```
<script src="wasm_exec.js"></script>
<script src="potjs.js"></script>

<script>
(async () => {
    await pot.ready()
    map = await pot.new("http://localhost:1633",
        "6792a183adafdac3a0a1a1e65b435406aff8f4343f980b16cabafd4a8525c0aa")
    await map.put("hello", "POT!")
    value = await map.get("hello")
    console.log("key <hello> has:", value)
    ref = await map.save()
    console.log("tree root is:", ref)
})();
</script>
```



EXAMPLE 6: NETWORK II

Example 6 works like example 5 but can be run directly with ``make example6``.

See **`example6.html`**

EXAMPLE 7: NODE

`example7.js`

```
.  
  
fs = require("fs");  
require("./wasm_exec"); // note the ./  
  
var go = new Go();  
  
WebAssembly.instantiate(fs.readFileSync("pot.wasm"), go.importObject)  
  .then((r) => { go.run(r.instance) })  
  
onWasmLoaded = async () => {  
  console.log("wasm loaded-function called")  
  map = await global.pot.new()  
  await map.put("hello", "node")  
  value = await map.get("hello")  
  console.log("hello:", value)  
}
```

WHAT YOU SHOULD SEE

TERMINAL:

POT JS Example 7: Node



Check out the source in example7.js.

```
pot: » POTWASM
pot: » init done
wasm loaded-function called
pot: » initialize new P.O.T.
pot: slot ref: 1
pot: » ready
pot: » put hello: node
pot: » → 68656c6c6f00000000000000000000000000000000000000000000000000000000: 036e6f6465
pot: » get hello: node
pot: » ← 68656c6c6f00000000000000000000000000000000000000000000000000000000: 036e6f6465
hello: node
```

EXAMPLES 8 AND 9: WEB APP

These examples demonstrate a single-source web app. The page is served from the server script. The POT functions run on the node.js server.

Examples 8 and 9 are identical to make a point: that the storage destination for the POT can be switched out by parameters. In this case, from in-memory storage (8) to local network (9).

example8.js and example9.js

```
console.log(`
    POT JS Example 8: Node.js Web App Server
    This is a self-contained web app, serving
    a page to receive input, returning results.
`)

const http = require('http')
const qs = require('querystring')
const form = `<pre>

    POT JS Example 8: Node.js Web App

    <form method=post action="http://localhost:3000">

    key    <input name=key>

    value  <input name=value>

           <input type=submit name=button value=put>

<hr />

    key    <input name=search>
```



```
        <input type=submit name=button value=get>
    value <input name=result>
    </form>
</pre>

<script> console.log('see server log') </script>`

const fs = require("fs")
require("./lib/wasm_exec") // note the ./

var go = new Go()
var kvs

WebAssembly.instantiate(fs.readFileSync("lib/pot.wasm"), go.importObject)
    .then((r) => { go.run(r.instance) })
global.onWasmLoaded = () => {
    bee = process.argv[2]
    batch = process.argv[3]
    console.log(bee, batch)

    kvs = pot.newSync(bee, batch)
    console.log('srv: KVS initialized')

    // Notes:
    // * The "pot: " log entries are coming from Go pot.wasm.
    // * There is no catching of early calls of put() and get()
    // * onWasmLoaded could be defined async, for await pot.new()
    // * onWasmLoaded has to be added to global to get detected
}

async function put(key, value) {
    await kvs.put(key, value)
    return `put ${key}: ${value}`
}

async function get(search) {
    value = await kvs.get(search)
    return `get ${search}: ${value}`
    <script>
    document.getElementsByName('result')[0].value = `${value}`
    </script>
}

const server = http.createServer(function(request, response) {
    if (request.method == 'POST') {
        var body = ''
        request.on('data', function(data) {
            body += data
        })
        request.on('end', async function() {
            var log
            const post = qs.parse(body)
```



```
        if(post.button == 'put')
            log = await put(post.key, post.value)
        else
            log = await get(post.search)
        console.log("srv: " + log.match(/.*/)[0])
        response.writeHead(200, {'Content-Type': 'text/html'})
        response.end(form + '<hr><br><pre>\t\t' + log)
    })
}
else {
    response.writeHead(200, {'Content-Type': 'text/html'})
    response.end(form)
}
})
).listen(3000, '127.0.0.1')

console.log(`srv: listening at http://127.0.0.1:3000`)
```

WHAT YOU SHOULD SEE

BROWSER:

POT JS Example 8: Node.js Web App

key	A
value	123
	put

key	
	get
value	

put A: 123

The screen will refresh with fields empty on every button press.



BUILDING

There is **no need for building POT JS to use it.**

The main executable, the Go WASM file `pot.wasm`, and the auxiliary Javascript and HTML files are portable.

This chapter is about building anyways.

To build, run

```
GOOS=js GOARCH=wasm go build -o pot.wasm potjs.go nomock.go  
cp "$(go env GOROOT)/lib/wasm/wasm_exec.js" .
```

or use

```
make build
```



WHAT YOU SHOULD SEE

```
GOOS=js GOARCH=wasm go build -o pot.wasm potjs.go nomock.go
✓ created pot.wasm for production
```

CLEAN BUILD

To rebuild from scratch, including integrity hashes and rebuilding `go.mod`, use:

```
make clean build
```

WHAT YOU SHOULD SEE

```
rm -f go.mod
rm -f pot.wasm
rm -f wasm_exec.js
rm -f potjs.js.sha384 wasm_exec.js.sha384
rm -f .batch_creation .batch_id
go mod init potwasm
go: creating new go.mod: module potwasm
go: to add module requirements and sums:
    go mod tidy
go mod edit -replace github.com/ethersphere/proximity-order-
trie=github.com/ethersphere/proximity-order-trie@v1.0.0
go get
go: added github.com/beorn7/perks v1.0.1
go: added github.com/cespare/xxhash/v2 v2.2.0
go: added github.com/ethersphere/bee/v2 v2.5.0
go: added github.com/ethersphere/proximity-order-trie v1.0.0
```



```
go: added github.com/hashicorp/errwrap v1.0.0
go: added github.com/hashicorp/go-multierror v1.1.1
go: added github.com/prometheus/client_golang v1.18.0
go: added github.com/prometheus/client_model v0.6.0
go: added github.com/prometheus/common v0.47.0
go: added github.com/prometheus/procfs v0.12.0
go: added golang.org/x/crypto v0.23.0
go: added golang.org/x/sys v0.20.0
go: added google.golang.org/protobuf v1.33.0
cp "$(go env GOROOT)/lib/wasm/wasm_exec.js" .
openssl dgst -sha384 -binary potjs.js | openssl base64 -A > potjs.js.sha384
openssl dgst -sha384 -binary wasm_exec.js | openssl base64 -A >
wasm_exec.js.sha384
for fn in potjs.js.sha384 wasm_exec.js.sha384; do sed -i.bak -e "s/\\(\"${fn:0:-
7}\\\" integrity=\\)[^>]*\\/1\\\"sha384-\\${(cat ${fn})\\/\\[\\/]\\/\\}\\\"/"
example1.html ; rm -f example1.html.bak ; done
GOOS=js GOARCH=wasm go build -o pot.wasm potjs.go nomock.go
✓ created pot.wasm for production
```

REQUIREMENTS

POT JS includes the Go implementation of POT.

POT JS API

Tested with:

- go 1.24.0
- node.js 22.17.1
- chrome 138.0.7204.184 arm64

probably works with earlier versions.



GO POT

- go 1.24.0
- testify 1.8.4
- swarm bee 2.5.0
- crypto 0.23.0
- sync 0.14.0

Which will require

- perks 1.0.1
- xxhash 2.2.0
- go-spew 1.1.1
- errwrap 1.0.0
- go-multierror 1.1.1
- text v0.2.0
- go-diffliib 1.0.0
- prometheus
- x/sys 0.20.0
- protobuf 1.33.0
- yaml 3.0.1

See `go.mod`.



TESTS

To test the JS API, serve the main directory, e.g., with with `npx http-server` .
and open `http://127.0.0.1:8080/test.html?tag=in-mem`.

Or use

```
make test
```

It uses `test.js` and `test.css` to display the results from a suite of 142 tests across the available `put` and `get` functions, and more.

WHAT YOU SHOULD SEE

TERMINAL

```
GOOS=js GOARCH=wasm go build -o pot.wasm potjs.go nomock.go
```

```
✓ created pot.wasm for production
```

```
Q start http server (stop with 'make stop')
```

```
(npx http-server -c1 . &)
```

```
open "http://127.0.0.1:8080/test.html?tag=in-mem"
```

```
Starting up http-server, serving .
```

```
http-server version: 14.1.1
```

```
http-server settings:
```

```
CORS: disabled
```

```
Cache: 1 seconds
```

```
Connection Timeout: 120 seconds
```

```
Directory Listings: visible
```

```
AutoIndex: visible
```

```
Serve GZIP Files: false
```

```
Serve Brotli Files: false
```

```
Default File Extension: none
```

```
Available on:
```

```
http://127.0.0.1:8080
```

```
http://192.168.178.192:8080
```



Hit CTRL-C to stop the server

```
[2025-08-30T21:44:02.883Z] "GET /test.html?tag=in-mem" "Mozilla/5.0
(Macintosh; Intel Mac OS X 10_15_7) AppleWebKit/537.36 (KHTML, like Gecko)
Chrome/138.0.0.0 Safari/537.36"
(node:22323) [DEP0066] DeprecationWarning: OutgoingMessage.prototype._headers
is deprecated
(Use `node --trace-deprecation ...` to show where the warning was created)
[2025-08-30T21:44:02.904Z] "GET /test.css" "Mozilla/5.0 (Macintosh; Intel Mac OS
X 10_15_7) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/138.0.0.0
Safari/537.36"
[2025-08-30T21:44:02.906Z] "GET /wasm_exec.js" "Mozilla/5.0 (Macintosh; Intel
Mac OS X 10_15_7) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/138.0.0.0
Safari/537.36"
[2025-08-30T21:44:02.910Z] "GET /favicon.ico" "Mozilla/5.0 (Macintosh; Intel Mac
OS X 10_15_7) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/138.0.0.0
Safari/537.36"
[2025-08-30T21:44:02.989Z] "GET /test.js" "Mozilla/5.0 (Macintosh; Intel Mac OS
X 10_15_7) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/138.0.0.0
Safari/537.36"
[2025-08-30T21:44:02.990Z] "GET /kvs_test.js" "Mozilla/5.0 (Macintosh; Intel Mac
OS X 10_15_7) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/138.0.0.0
Safari/537.36"
[2025-08-30T21:44:02.997Z] "GET /pot.wasm" "Mozilla/5.0 (Macintosh; Intel Mac
OS X 10_15_7) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/138.0.0.0
Safari/537.36"
```

BROWSER



SWARM POT JS API TEST SUITE

IN-MEM

Sat Aug 30 2025 23:44:02 GMT+0200 (Central European Summer Time)

This is the test suite for the Javascript API to the Go implementation of the Proximity-Order-Trie (POT).

Also see: [example 1](#) [example 2](#) [example 3](#) [example 4](#) [read me](#)

NOTES

The test suite runs **in-memory** of the Go POT implementation.

Tests are using different random byte sequences for keys and values every run.

NETWORK

Bee node URL : (in-memory)

Batch ID : (none)

KVS TESTS

15 suites · 142 cases · 1325 assertions · passed with no errors.

Test Suite #1 ... EXAMPLE TEST ...

IN-MEM

Test setup test outside of main test files.

◆ case #1 » html-inline

test.html:109

· put and get K: V

test.html:110

✓ as expected, ⟨V⟩.

5ms

Test Suite #2 ... SIMPLE GETS AND PUTS OF KVS WITH ONE ITEM, SYNCHRONOUS ...

IN-MEM

BROWSER CONSOLE

...

```
wasm_exec.js:22 pot: ◆ case #140 » Cancel Delay
wasm_exec.js:22 pot: <object>
wasm_exec.js:22 pot: create hanging test promise and cancel it (delay, chain .catch)
wasm_exec.js:22 pot: sleeping
wasm_exec.js:22 pot: canceled!
wasm_exec.js:22 pot: ✓ expected error: 'Error: canceled'
wasm_exec.js:22 pot:
wasm_exec.js:22 pot: ◆ case #141 » Immediate Cancel II
```



```
wasm_exec.js:22 pot: <object>
wasm_exec.js:22 pot: create hanging test promise and cancel it immediately (chain
.catch)
wasm_exec.js:22 pot: sleeping
wasm_exec.js:22 pot: canceled!
wasm_exec.js:22 pot: ✓ expected error: 'Error: canceled'
wasm_exec.js:22 pot:
wasm_exec.js:22 pot: ●●● Test Suite #14 ●●● FAILURES ●●●►IN-MEM◄
wasm_exec.js:22 pot: Failure tests are available in extended API test mode. Run
`$make xt`.
wasm_exec.js:22 pot:
wasm_exec.js:22 pot: ●●● Test Suite #15 ●●● PROOFS ●●●►IN-MEM◄
wasm_exec.js:22 pot:
wasm_exec.js:22 pot: ♦ case #142 » Return a Proof
wasm_exec.js:22 pot: <object>
wasm_exec.js:22 pot: ● new map
wasm_exec.js:22 pot: » initialize new P.O.T.
wasm_exec.js:22 pot: slot ref: 101
wasm_exec.js:22 pot: ✓ no error raised.
wasm_exec.js:22 pot: ● get proof for K1
wasm_exec.js:22 pot: ✓ as expected, 'null'.
wasm_exec.js:22 pot:
wasm_exec.js:22 pot: ●●● tests cases run: 142 ● assertions: 1325 ●●●
wasm_exec.js:22 pot: ► no errors ◄
```

The standard tests run against the Go implementation of POT, like the use would be in production. The **extended tests**, however, focus on the JS AP to Go, add cancellation and time out cases. They do not interface with the Go POT code.

Latency emulation, promises, and connectivity as well as retention error conditions will be added to emulate the reality of an unreliable network as ultimate storage layer. Run the tests with `make test` and `make xt` respectively.

Note that `make xt` (specifically, `make mock` change the project configuration and build executables (especially a `pot.wasm`) that will not work for production. (They will appear to work but they sidestep Go POT.) Use `make unmock`, `make test` or `make build` to restore to the production target (i.e., build the real `pot.wasm`).

The **extended tests** use a separate, dedicated, in-memory mock storage to separate them from the Go POT implementation.

The tests are made for the browser as the final destination of the combined architecture, in either case (standard and extended tests) they are invoked by opening the file `test.html`. The very small file that is altered between the test modes is `testmode.js`, and `go.mod` to replace package the real Go POT with `mock`.



This test page and test framework is designed to bridge the language divide and allow for the emulation of exceptions in one degree of separation (caused in Go, caught from JS). The major relevance of the test harness is to help surface any friction between JS's and Go's resource release mechanisms (JS promises and Go channels) to detect possible leaks. Go's channels are not without peril – they can deadlock – and the challenge is aggravated by their position behind the JS API. The relevant code triggering the exceptional conditions resides in ``mock.go``. For its purposes, it has to be part of the ``main`` package rather than package ``pot`` in ``mock/``.

DEVELOPING

This chapter is about contributing to or changing POT JS itself.

Developing and testing at this point have been done on Mac only.



FILES

README.MD	subset of these instructions
potjs.go	Go JS interface
nomock.go	No-op version of test functions
mock.go	monkey patch mock of Go POT for extended testing
mock/	replacement of Go POT for extended testing
pot.go	
go.mod	
pkg/persister	copy of Go POT in-memory storage to satisfy dependencies
lib/	
pot.wasm	Go POT implementation compiled to WASM
wasm_exec.js	generic Go WASM wrapper (replace w/your Go version's)
potjs.js	Thin JS initialization convenience code
wasm_exec.js.sha384	SHA384 checksum for sub-component verification
potjs.js.sha384	SHA384 checksum for sub-component verification
doc/	
POT JS manual.odt	
POT JS function reference.pdf	
POT JS manual.pdf	
POT JS function reference.odt	
examples/	
example1.html	briefest example as listed above, in-memory storage
example2.html	interactive example, input fields, integrity
example3.html	example 2 dropping potjs.js for more control
example4.html	example 1 using synchronous access functions
example5.html	example 1 but with connection to a storage network
example6.html	example 5 with better connection to make rules
example7.js	example 1 for execution with node.js
example8.js	single-script node.js app, server and web page
example9.js	example 8 verbatim stared with different arguments
favicon.ico	Swarm logo to suppress browser errors
test/	
test.html	test main page for test, ext_test, locnet_test
kvs_test.js	test suites
test.js	generic test harness
test.css	generic test optics
go.mod	go module locations
go.sum	go module check sums
Makefile	build scripts
favicon.ico	Swarm logo to suppress browser errors



MAKE

The project comes with an extensive `Makefile` to support developing.

Below are the build rules for executables and for running tests of POT JS.

Note that building and any of the following is not required for using POT JS. The relevant executable files are portable and part of the repo. After cloning or downloading a distribution of POT JS, all relevant files are immediately usable.

RULES

Run with `make <rule>`

build	build executables
example<n>	start server and run example <n>. n = 1-8
test	explain test modes and run <code>node_inmem_test</code>
web_inmem_test	test api interaction with go pot in-memory persisting, web
web_inmem_stress	stress test with go pot in-memory persisting, web
web_sim_test	extended exceptions tests w/out go pot connection, web
web_locnet_test	standard tests with a locally installed Swarm network, web
web_locnet_stress	stress test with a locally installed Swarm network, web
node_inmem_test	test api interaction with go pot in-memory persisting, node
node_sim_test	extended exceptions tests w/out go pot connection, node
node_locnet_test	test with a locally installed Swarm network, node
clean	prepare for building from scratch
distclean	prepare for commit to repository, including build

SUPPORT & DEBUGGING

For day-to-day developing, these commands may be helpful.

serve	start local http server serving current directory
stop	stop local http server. Ctrl-c does not.
mock	prepare for extended exception tests
unmock	reset for production or non-extended tests
locnet_install	install the local test network
locnet_start	start the local test network on docker
locnet_batch	buy stamp batch (free)
locnet_tests	run test suites on local test network
locnet_stop	shut local test network down
locnet_logs	show the entire log of the queen node



DEVELOPER NOTES

NOTES ON DEBUGGING

Being wrapped in WASM to interface with Javascript, the Go executable is opaque. It cannot be debugged as there are no debuggers for WASM, and it becomes unavailable once it has panicked.

Consequently, developing benefits from being test-driven to unearth unexpected problems.

A wide array of tests are available in `test/kvs_test.js`. They include examples of failure test of varying nature.

Logging directly to terminal or browser console can be done with the Go function `log()`. It uses the interface itself to have direct access to Javascript's `console.log`.

NOTE ON SYSCALL/JS

The connection between Go and Javascript through WASM is based on Go's `syscall/js` package. This package is officially labeled as experimental by its provider, Google:

"This package is EXPERIMENTAL. Its current scope is only to allow tests to run, but not yet to provide a comprehensive API for users. It is exempt from the Go compatibility promise."

<https://pkg.go.dev/syscall>

This is a stark warning going beyond Google's typical caution. It may explain the incompleteness of `syscall/js`, e.g., the lack of an option to directly throw exceptions. What remains unclear is why this imperfect state has been going on for so long.

This also makes it look possible that, e.g., the `node.js` WASM crashes that report deadlocks are not in fact always deadlocks but sometimes a misfiring, overzealous deadlock detection. The Go WASM executable stops at any rate. The insight would not be the path to a solution.



INITIALIZATION

Starting out, the Go Wasm executable has to be loaded, both for a HTML5 application or when using POT JS with node. In the browser this can be handle conveniently by including **potjs.js**, which also provides the wait function **pot.ready()** The core of **potjs.js** are only a few lines of code and they can alternatively be programmed directly in your source code, omitting **potjs.js**, as shown in **example2.html**. In some situations that might give helpfully more fine-grained access to design the start-up sequence (the example happens to use **newSync()**):

```
WebAssembly.instantiateStreaming(fetch("pot.wasm"), go.importObject)
    .then((r)=>{
        go.run(r.instance)
        map = pot.newSync()
        ...
    })
```

Generally, only after the **pot.wasm** executable has loaded – and in the course, started and is running – is the global **pot** object created and the POT JS functions described above become operational. Before that point, the **pot** object and the functions do not exist and trying to use them will cause the according JS exceptions to be thrown.

But if **potjs.js** is used, it creates the global **pot** object earlier, before **pot.wasm** is done loading and starting up, and provides through **pot.ready()** a promise that can be used to wait for **pot.wasm** to complete loading. But **pot** and **pot.ready()** are the only elements of the API that already exist at that point, no other function does until the promise of **pot.ready()** resolves.

```
await pot.ready()
map = await pot.new()
...
```

Without **potjs.js**, **onWasmLoaded()** can be created instead, which will be called by **pot.wasm** as soon as it is ready:

```
function async onWasmLoaded() {
    I      map = await pot.new()
    ...
}
```

The **pot.wasm** executable loads quickly. Most of the time, it will not be strictly needed to use **pot.ready()** or **onWasmLoaded()**, as demonstrated by **example2.html**. The interaction coming from the user will practically always happen only after **pot.wasm** has long been loaded.

This can be a source of errors though in the case of a network hic-up, and interoperation in a node.js program will generally be too fast to ignore the need to wait for **pot.wasm** to finish loading.



TYPES

A Javascript developer will make assumptions about how types work. To provide the least surprising solution,² Javascript types are automatically converted to and back from the raw binary storage format values are stored in to come back as-stored.

The Go POT implementation stores raw binary data. In Javascript the equivalent would be **Uint8Array**. But that is not idiomatic to normal Javascript use. **Uint8Arrays** cannot be used for keys,³ and cannot be compared with each other as would be expected. They are generally less practical as values for a lot of use cases in Javascript, where the expectation would be that sending a variable of a certain type to a key-value store should later get you that variable in that type back, rather than some raw data that has to be type cast to be what it once was.

Javascript being weak-typed does not help, it rather heightens expectations regarding automation of type handling and on-the-fly casting.

To achieve type-awareness, type encoding has been implemented that can put and get Javascript values without losing their types. It writes a first byte to any **put** (that does not have **Raw** in its name) that reflects the JS type. This makes data stored with **put**() mostly incompatible with any get function that has **Raw** in its name.

But this is not the only way for a user to deal with types. There are *raw* access functions that deal with types on *getting*: **getBoolean()**, **getNumber()**, **getString()**. They are for reading data stored with **putRaw()**, where only one byte is stored for Booleans, 8 for numbers, etc. without the leading type byte.

This dual API for type-aware storing is separate to a third one that just stores raw **Uint8Arrays**, using **putRaw()**, and then **getRaw()**. This leaves the task to the user to cast to the right type.

NUMBERS

Javascript numbers are stored to Swarm as IEEE 754 floating point standard byte code.

The reason is that the universal number type in Javascript, *even integers* (other than the special case of **BigNums**), are internally stored as 64-bit floats. Direct access to the bits representing these numbers guarantees lossless conversion, especially in edge cases.⁴

² en.wikipedia.org/wiki/Principle_of_least_astonishment – “In user interface design and software design, [1] the **principle of least astonishment** (POLA), also known as *principle of least surprise*, [a] proposes that a component of a system should behave in a way that most users will expect it to behave, and therefore not astonish or surprise users.”

³ Because they do not have a natural order in Javascript.

⁴ The alternative of storing numbers as strings works well, too, but goes through a much more involved process of conversion that can be assumed to be much more time and memory-consuming. While in the light of this context this does not matter too much, it might also be more prone to errors in edge cases such as the likes of **10/3**, **-0**, and *multiple* variations of **NaN** in IEEE 754.



The principally desirable representation of *integers* by their hexadecimal byte corollary was renounced as it would have meant special casing the number conversion, i.e., handling integers and floats differently depending on their face value not by any distinction Javascript itself knows or cares about. It would make some Javascript numbers into something they are not (integers), for little tangible advantage other than the hypothetical portability of POT storage between clients of different languages.

If cross-system portability of POT data access becomes a goal, then the higher robustness of an integer representation for integers would be convincing – *if* the input could reliably be known to have been meant as an integer in the first place, which in Javascript could be difficult to ascertain. Instead, an additional type marker could be added that identifies integers and allows Javascript to read them but not write them.

BIG NUMBERS

Javascript Big Numbers could not be implemented at this point because the Go `syscall/js` package – being officially incomplete, see above – can currently not handle them. It seems likely that `syscall/js` could be extended to make `BigInts` work if desired. There are receipts for it online.

While modding the standard Go package for WASM communication with JS opens a can of worms, it seems important enough eventually to allow for `BigInts` to be stored in Swarm natively.

TESTS

To accommodate for the dual origination of errors – on the JS or Go side – the combined test suite utilizes the same JS ↔ WASM ↔ Go channel that the API itself uses to trigger, evaluate and log the tests, jostling between languages. A number of functions were added to enable black box testing. They are no ops in production, neutered via Go build directives.

To be able to test its reaction to delays, stalls, exceptions and cancellations, and to insulate tests of the JS API from any potential problems with the Go POT implementation itself, which is not yet battle-hardened or extensively tested, the ‘extended’ tests implement their own mock back end (`mock.go`). This is a second in-memory storage variant, separate from the in-memory storage the Go POT implementation itself offers per default and that is used in the ‘standard’ tests.

This mock back end, besides being helpful for debugging, exists to emulate fringe conditions that could not otherwise be tested but must be expected when the Go POT package operates connected to the Swarm network. E.g., mock delays are essential to test the basic user cancellation and time out design that has to satisfy both Javascript and Go language idiosyncrasies to prevent resource leaks in Go from dangling sub routines that were not freed when a request did not succeed. As a special complication, both runtimes have their own garbage collector, which always add opaqueness but, in the instance, have to be made to work together in their estimation of what resource can be



discarded. In this regard, Go channels are a special challenge, as well as a potential source of deadlocks.

ERROR HANDLING

The divergent error handling philosophies of Javascript and Go had to be balanced. I.e., a Javascript programmer does not expect errors coming back as return values – like in Go – but as exceptions, all the while Go cannot trigger Javascript exceptions through WASM. (It can **return** a value of type Error as JS-native Error type return value but not **throw** it directly, due to the incompleteness it seems of `syscall/js`).

While **throw** is not available to Go, a middle ground is provided by JS Promises that enable – when programmed in Go instead of in JS – by the use of their **reject** function a means to trigger an exception in Javascript. This constitutes a convincing additional reason for why the API functions that return promises are preferable. It allows for the more seamless transportation of errors from inside Go to Javascript in the expected way for a JS programmer.

Not all errors on the Go side can be caught and translated into Javascript exceptions in this way. Some are returned as Javascript Error object instead of the expected return value.

A JS API IS IMPLEMENTED IN GO

POT JS, while being a Javascript API to Go code, is intentionally and necessarily programmed almost exclusively in Go. It would not work the other way around, i.e., by implementing more – or all – of its functionality in Javascript. But it is also desirable that it has no Javascript layer to speak of.

The exception, the small `potjs.js` script is a dozen lines convenience code that replaces a few lines of initialization code that one otherwise had to write for oneself, if `potjs.js` was not used (see `examples/example2.html`). This is an option, `potjs.js` can be left out. In effect, the WASM executable, all written in Go, and nothing written in Javascript, constitutes all that is required to use POT JS.

There is no alternative to this design. But eventually this focus on Go is not a disadvantage. The following explains why it is necessary but also desirable to have POT JS programmed almost exclusively in Go and details how that is the cleaner solution.

◇

POT JS is really Javascript without Javascript code: even though POT JS is written in Go, what this Go code creates are Javascript objects and functions. For all intents and purposes, POT JS, at runtime,



is mostly Javascript. The Go code creates Javascript runtime elements that constitute the actual API. That is, methods like `kvs.put()` are functions written in Go but executed by the Javascript runtime like native Javascript functions. The Go runtime's part is just to create them.

There is no way to do the opposite using `syscall/js`. I.e., there is no way to create native Go objects from Javascript. `syscall/js` is a Go package after all, it extends Go, not Javascript. There are translators that create Go code from Javascript code, at compile time. But that is not the same as creating runtime objects for one language in the other at runtime, which is needed to create an API as tight and fast as POT JS.

That `syscall/js` works in this direction, Go to Javascript, is plausible, because the calls are coming from Javascript to Go. We want a gate from Javascript to WASM Go code, not the other way around. This is why it makes sense that the connecting elements of the API are created in Go – using `syscall/js` functions – to create Javascript objects and Javascript functions. In a pedantic sense, while the code is all Go, the API actually is fully Javascript. Just created by Go code, not Javascript code. Eventually, Javascript does not 'realize' that it is operating on 'non-native' Javascript objects that are created using Go and `syscall/js`.

Apart from that, there is a reason why at least some Go code is required and the mirror image to write the entire API in Javascript would not be possible: there are two typical classes of Go objects in play, employed by Go POT, as any Go project would: contexts and channels. Because they cannot be transferred over to Javascript that does not know the concept of channels (contexts are special channels), they have to be managed on the Go side. This is where `syscall/js` incompleteness might be hurting. Maybe there could be a way to hand handles to channels over to Javascript. This would ver likely require manual handling of garbage collection on the Go side though to prevent the channels from being discarded as unused because the Go runtime has no visibility on the Javascript side. The overhead of keeping track of contexts and channels – either by keeping the objects, or by protecting them from premature garbage collection – necessarily has to be implemented on the Go side.

Therefore, even in its slimmest form, using `syscall/js`, one would always end up having at least some Go code in the mix. The API could never be all Javascript the way that it is now (almost) all Go.

This also trumps another reservation that might be raised: that it should seem much cleaner if one could avoid adding a main package to the Go implementation of POT in order to create a Javascript API, and to instead let Go POT remain untouched, as is, with no additional Go code added just for this specific API. Convincing as this view is, it is not feasible because of the way `syscall/js` works. It is a given that API-specific Go code has to be added. It can't work to just wrap Go POT into WASM and be done, all the rest being in Javascript. There has to be some Go code that creates the bridge; it can't be Javascript code.

And that Go code has to be part of the WASM. Thus only compiling Go POT to WASM won't work. One way around it would be to make the WASM act like a server, which would be slow, not the implementation of a Javascript API, but a general interface. And it would require adding code to Go POT just the same. But to be exact, Go POT is not changed, it is just made the main component of the API project POT JS. What is more unsatisfying is merely the question of how to organize the repos.



So, much of the objects and functions the Go code creates are Javascript. Thus, much of POT JS is really Javascript, just not Javascript code. Something must be 'the bridge' and these Go-created Javascript objects are it.

◇

Now, if the question was asked from a high level, whether having virtually NO Javascript code can be a good choice for a Javascript API, the answer is that the nature of syscall/js to mainly offer the possibility to 'program Javascript in Go', but not vice-versa, determines all else. However, even those aspects that would appear to unquestioningly lend themselves to be implemented in a complementary Javascript layer, rather than in the Go code, turn out to only work when programmed in Go, instead of in Javascript.

This is a major challenge that adds to the picture: transacting between Javascript and Go can deadlock the Go code when certain functionality is written in Javascript, instead of in Go. This even includes the creation of something as close to home as Javascript promises.

As an epitome of Javascript programming, it must seem strange that POT JS creates them in Go. However, it simply doesn't work in the way that would look more intuitive, i.e., creating a Javascript layer that defines the promises, which's executors then call into the Go WASM functionality synchronously. That this does not work, as much as it would seem that it should, can easily be confirmed by trying it out. Below is some background that may help to explain why this is so.

In the end, the answer to why POT JS is mostly programmed in Go is, it is not a choice.

But beyond these hard facts that favour coding POT JS in Go, there are reasons, given below, why it can be regarded as optimal design. The right choice, if it was not inescapable.

◇

From a high-level it is preferable to have code only, or mostly, on one side – Javascript or Go – and to not cross the language barrier multiple times, to keep things robust and avoid unknown unknowns. Keeping things mostly on one side can minimize error sources and overhead that may occur unwittingly when switching between languages, as well as the loss of original state that this entails (channels on the Go side, exceptions for Javascript). This is why it looks preferable, independently of the limitations that partially dictate the answer, to keep the bulk of code either on the Go or the Javascript side.

The way syscall/js works, this predisposes the Go side then.

Keeping things simple – by avoiding language switch overs – becomes more relevant for the disclaimer that comes with syscall/js, that it is "experimental and not for production." There seem to be no complains that it is not stable. It may be Google's typical traditional caution. But it encourages to keep things simple and straight forward and to avoid demanding constructs where possible. Keeping it all on the Go side then, after some code on the Go side is unavoidable in the first place, appears to be the right choice to increase robustness.

But even if all that wasn't acceptable as convincing argument for pushing everything into Go, it turns out there is a technical killer argument: as mentioned, it does not work to have asynchronicity being



taken care of on the Javascript side. It does not work to have the promise wrapping for asynchronous calls be on the Javascript side. And when using WASM with node, it's not only the fetch call that is locking up – as the syscall/js documentation warns – but every synchronous call deadlocks (sic), including when using in-memory storage as persister, which is not using a fetch internally. It does not work to create the promises in Javascript for the purpose of a Javascript-side layer. They have to be implemented in Go, as POT JS is doing. Specifically, what does not work is to wrap sync calls to Go WASM in Javascript promise executors on the Javascript side. But using 'the same' logic creating the Javascript promises on the Go side, works:

<https://github.com/brainiac-five/potJavascript/blob/86fc8af3ea6b0f148bed1efb34d8dd00190bd1b3/potJavascript.go#L50>

The syscall/js documentation is not clear that this would be required to avoid deadlocks. There is a description on how deadlocks should be avoided by using go routines. But it is not explained why creating the asynchronicity on the Javascript side should be less effective. Under certain conditions, this deadlock happens every time. What causes it seems to not only be the browser's main fetch thread, because it also affects node.js, and even more profoundly. With node.js, The deadlocks happen reliably unless the Javascript promises are created on the Go side. Which in fact entails a go routine to uncouple the promise executor from the synchronous program flow. Just as the syscall/js documentation seems to propose. While the Javascript asynchronicity inherent in the promise creation, empirically, does not suffice.

This might be because in a 'go <executor>' call the go routine call's mechanics are truly multithread, implemented such that if the operating system allows, go routines might run on parallel threads. Maybe this is what is preventing the whole mechanism from locking up by virtue of a stronger decoupling effected by a go routine call. In that interpretation, the fact that doing the same on the Javascript code side – wrapping sync API calls into Javascript promises – always locks up could be explained by the fact that in Javascript nothing is ever truly parallel, as a basic strategy to keep Javascript programmers safe even while the paradigm is strongly async (except Web Workers, which add exactly that: multithreading). Go routines though are designed to possibly run in parallel if the OS and hardware allows for it. Conversely, this thesis is weakened by the circumstance that Go in WASM is said to always run on only one process.

Regardless, calling from Javascript into Go and then Go calling back to Javascript implicitly by making a fetch call seems to only ever work by go routine decoupling. When using node.js, there seems to be an additional cause for reliable deadlock in play when not decoupling calls with a go routine. Always building such a go routine into a Javascript promise makes for a very desirable architecture though that has no lamentable drawbacks. It even has the precious advantage that such Go-native promises provide the only way to trigger native Javascript exceptions from Go.

As the promises are the 'most outside' hull of calls though and seeing that even they cannot be implemented on the Javascript side, little else can.

But as noted, because for the sake of robustness it looks desirable to have as much code as possible on one side, and to avoid crossing language lines within one call, the necessary design also looks desirable. Even if it is surprising that eventually there is no real Javascript layer.

This is why POT JS is implemented almost entirely in Go, and why this is a desirable outcome, too.





ROADMAP

Possible future improvements:

- **FUNCTION TIMEOUTS**
- **PROOF RETRIEVAL FUNCTION**
- **TREE WALK FUNCTIONS**
- **GO-SIDE RESOURCE TRACKING INSTRUMENTATION**
- **JS-NATIVE PERSISTERS**
- **USE OF JS NEW OPERATOR**
- **INTEGRATION TESTS**