

ANEXO V

PRUEBAS Y VERIFICACIÓN: AJUSTES REALIZADOS (1.5.3)



Panel del pfSense mostrando la creación y asignación de múltiples VLANs (10, 20, 30, 40, 50, 100) en las interfaces em1 y em2 correspondientes.

Restaurar sesión x pfSense.home.arpa - Int...

192.168.1.1/interfaces_vlan.php

pfSense COMMUNITY EDITION

System ▾ Interfaces ▾ Firewall ▾ Services ▾ VPN ▾ Status ▾ Diagnostics ▾ Help ▾

WARNING: The 'admin' account password is set to the default value. [Change the password in the User Manager.](#)

Interfaces / VLANs

Interface Assignments Interface Groups Wireless **VLANs** QinQs PPPs GREs GIFs Bridges LAGGs


Interface	VLAN tag	Priority	Description	Actions
em1 (lan)	10		VLAN ADMINISTRACION	
em2 (opt1)	20		VLAN TECNICA	
em1 (lan)	30		VLAN REUNIONES	
em1 (lan)	40		VLAN INVITADOS	
em1 (lan)	50		VLAN IMPESC	
em1 (lan)	100		VLAN DMZ	

+ Add

pfSense is developed and maintained by Netgate. © 2024. View license

Aplicaciones pfSense.home.arpa - Int... 2026-04-21 09:36 gns3

Sección del firewall mostrando los “aliases” creados para identificar fácilmente las distintas redes (Administración, DMZ, IMPESC, Invitados, Reuniones y Técnica).



The screenshot shows the pfSense Community Edition web interface. The browser address bar displays `192.168.1.1/firewall_aliases.php?tab=ip`. The navigation menu includes System, Interfaces, Firewall, Services, VPN, Status, Diagnostics, and Help. A warning message states: "WARNING: The 'admin' account password is set to the default value. Change the password in the User Manager." The main content area is titled "Firewall / Aliases / IP" and features tabs for IP, Ports, URLs, and All. The "IP" tab is selected, showing a table of Firewall Aliases IP.

Name	Type	Values	Description	Actions
A_ADMINISTRACION	Network(s)	192.168.10.0/24	ALIAS ADMINISTRACION	  
A_DMZ	Network(s)	10.0.100.0/24	ALIAS DMZ	  
A_IMPESC	Network(s)	192.168.50.0/24	ALIAS IMPESC	  
A_INVITADOS	Network(s)	192.168.40.0/24	ALIAS INVITADOS	  
A_REUNIONES	Network(s)	192.168.30.0/24	ALIAS REUNIONES	  
A_TECNICA	Network(s)	192.168.20.0/24	ALIAS TECNICA	  

At the bottom right of the table, there are buttons for "+ Add" and "Import".

Configuración del servidor DHCP habilitado para la interfaz **Administración**, operando bajo la subred 192.168.10.0/24, con un rango de IPs automáticas desde 192.168.10.2/24 hasta 192.168.10.200/24.

The screenshot shows the pfSense web interface in a browser window. The address bar shows the URL `192.168.1.1/services_dhcp.php?if=opt1`. The top navigation bar includes tabs for LAN, ADMINISTRACION (selected), TECNICA, REUNIONES, INVITADOS, IMPESC, and DMZ. The main content area is titled 'General DHCP Options' and contains several configuration sections:

- DHCP Backend:** ISC DHCP
- Enable:** ☒ Enable DHCP server on ADMINISTRACION interface
- BOOTP:** ☐ Ignore BOOTP queries
- Deny Unknown Clients:** A dropdown menu is set to 'Allow all clients'. Below it, a text block explains the behavior of the 'Allow all clients' setting.
- Ignore Denied Clients:** ☐ Ignore denied clients rather than reject. A note states this option is not compatible with failover.
- Ignore Client Identifiers:** ☐ Do not record a unique identifier (UID) in client lease data if present in the client DHCP request. A note explains this option's use for dual booting.

Below the 'General DHCP Options' section is the 'Primary Address Pool' section:

- Subnet:** 192.168.10.0/24
- Subnet Range:** 192.168.10.1 - 192.168.10.254
- Address Pool Range:** Two input fields are shown. The first is '192.168.10.2' with the label 'From' below it. The second is '192.168.10.200' with the label 'To' below it.

The bottom of the browser window shows the taskbar with the date and time '2026-04-21 09:50' and the username 'gns3'.

Configuración del servidor DHCP habilitado para la interfaz **Técnica**, operando bajo la subred 192.168.20.0/24, con un rango de IPs automáticas desde 192.168.20.2/24 hasta 192.168.20.200/24.

The screenshot shows the pfSense web interface in a browser window. The address bar displays `192.168.1.1/services_dhcp.php?if=opt2`. The top navigation bar includes tabs for LAN, ADMINSTRACION, **TECNICA** (selected), REUNIONES, INVITADOS, IMPESC, and DMZ. The main content area is titled 'General DHCP Options' and contains the following settings:

- DHCP Backend:** ISC DHCP
- Enable:** ☒ Enable DHCP server on TECNICA interface
- BOOTP:** ☐ Ignore BOOTP queries
- Deny Unknown Clients:** (dropdown menu)
When set to **Allow all clients**, any DHCP client will get an IP address within this scope/range on this interface. If set to **Allow known clients from any interface**, any DHCP client with a MAC address listed in a static mapping on **any** scope(s)/interface(s) will get an IP address. If set to **Allow known clients from only this interface**, only MAC addresses listed in static mappings on this interface will get an IP address within this scope/range.
- Ignore Denied Clients:** ☐ Ignore denied clients rather than reject
This option is not compatible with failover and cannot be enabled when a Failover Peer IP address is configured.
- Ignore Client Identifiers:** ☐ Do not record a unique identifier (UID) in client lease data if present in the client DHCP request
This option may be useful when a client can dual boot using different client identifiers but the same hardware (MAC) address. Note that the resulting server behavior violates the official DHCP specification.

Below the 'General DHCP Options' section is the 'Primary Address Pool' section:

- Subnet:** 192.168.20.0/24
- Subnet Range:** 192.168.20.1 - 192.168.20.254
- Address Pool Range:** (From) (To)

The bottom status bar shows the date and time as 2026-04-21 09:52 and the user as gns3.

Configuración del servidor DHCP habilitado para la interfaz **Reuniones**, operando bajo la subred 192.168.30.0/24, con un rango de IPs automáticas desde 192.168.30.2/24 hasta 192.168.30.200/24.

The screenshot shows the pfSense web interface for configuring the DHCP service on the 'Reuniones' interface. The browser address bar shows '192.168.1.1/services_dhcp.php?if=opt3'. The 'REUNIONES' tab is selected in the top navigation bar.

General DHCP Options

DHCP Backend	ISC DHCP
Enable	☒ Enable DHCP server on REUNIONES interface
BOOTP	☐ Ignore BOOTP queries
Deny Unknown Clients	Allow all clients When set to Allow all clients, any DHCP client will get an IP address within this scope/range on this interface. If set to Allow known clients from any interface, any DHCP client with a MAC address listed in a static mapping on any scope(s)/interface(s) will get an IP address. If set to Allow known clients from only this interface, only MAC addresses listed in static mappings on this interface will get an IP address within this scope/range.
Ignore Denied Clients	☐ Ignore denied clients rather than reject This option is not compatible with failover and cannot be enabled when a Failover Peer IP address is configured.
Ignore Client Identifiers	☐ Do not record a unique identifier (UID) in client lease data if present in the client DHCP request This option may be useful when a client can dual boot using different client identifiers but the same hardware (MAC) address. Note that the resulting server behavior violates the official DHCP specification.

Primary Address Pool

Subnet	192.168.30.0/24
Subnet Range	192.168.30.1 - 192.168.30.254
Address Pool Range	192.168.30.2 From 192.168.30.200 To

The bottom of the screen shows a taskbar with the date '2026-04-21 09:54' and the username 'gns3'.

Configuración del servidor DHCP habilitado para la interfaz **Invitados**, operando bajo la subred 192.168.40.0/24, con un rango de IPs automáticas desde 192.168.40.2/24 hasta 192.168.40.200/24.

The screenshot shows the pfSense web interface for configuring the DHCP server on the 'Invitados' interface. The browser address bar shows '192.168.1.1/services_dhcp.php?if=opt4'. The navigation menu at the top includes LAN, ADMINISTRACION, TECNICA, REUNIONES, INVITADOS (selected), IMPESC, and DMZ.

General DHCP Options

DHCP Backend	ISC DHCP
Enable	☒ Enable DHCP server on INVITADOS interface
BOOTP	☐ Ignore BOOTP queries
Deny Unknown Clients	Allow all clients When set to Allow all clients, any DHCP client will get an IP address within this scope/range on this interface. If set to Allow known clients from any interface, any DHCP client with a MAC address listed in a static mapping on any scope(s)/interface(s) will get an IP address. If set to Allow known clients from only this interface, only MAC addresses listed in static mappings on this interface will get an IP address within this scope/range.
Ignore Denied Clients	☐ Ignore denied clients rather than reject This option is not compatible with failover and cannot be enabled when a Failover Peer IP address is configured.
Ignore Client Identifiers	☐ Do not record a unique identifier (UID) in client lease data if present in the client DHCP request This option may be useful when a client can dual boot using different client identifiers but the same hardware (MAC) address. Note that the resulting server behavior violates the official DHCP specification.

Primary Address Pool

Subnet	192.168.40.0/24	
Subnet Range	192.168.40.1 - 192.168.40.254	
Address Pool Range	From 192.168.40.2	To 192.168.40.200

The bottom of the screen shows the system tray with the date '2026-04-21 10:01' and the user 'gns3'.

Configuración del servidor DHCP habilitado para la interfaz **IMPESC**, operando bajo la subred 192.168.50.0/24, con un rango de IPs automáticas desde 192.168.50.2/24 hasta 192.168.50.200/24.

The screenshot shows the pfSense web interface in a browser window. The address bar displays '192.168.1.1/services_dhcp.php?if=opt5'. The top navigation bar includes tabs for LAN, ADMINISTRACION, TECNICA, REUNIONES, INVITADOS, **IMPESC** (selected), and DMZ. The main content area is titled 'General DHCP Options' and contains several configuration sections:

- DHCP Backend:** ISC DHCP
- Enable:** ☒ Enable DHCP server on IMPESC interface
- BOOTP:** ☐ Ignore BOOTP queries
- Deny Unknown Clients:** A dropdown menu is set to 'Allow all clients'. Below it, a text block explains the behavior of the 'Allow all clients' setting.
- Ignore Denied Clients:** ☐ Ignore denied clients rather than reject. A note states this option is not compatible with failover.
- Ignore Client Identifiers:** ☐ Do not record a unique identifier (UID) in client lease data if present in the client DHCP request. A note explains this option's use and its deviation from the DHCP specification.

Below the 'General DHCP Options' section is the 'Primary Address Pool' section:

- Subnet:** 192.168.50.0/24
- Subnet Range:** 192.168.50.1 - 192.168.50.254
- Address Pool Range:** Two input fields are shown. The 'From' field contains '192.168.50.2' and the 'To' field contains '192.168.50.200'.

The bottom of the screen shows a taskbar with the date '2026-04-21 09:58' and the username 'gns3'.

Configuración del servidor DHCP habilitado para la interfaz **DMZ**, operando bajo la subred 10.0.100.0/24, con un rango de IPs automáticas desde 10.0.100.2/24 hasta 10.0.100.200/24.

The screenshot shows the pfSense web interface in a browser window. The address bar displays `192.168.1.1/services_dhcp.php?if=opt6`. The top navigation bar includes tabs for LAN, ADMINSTRACION, TECNICA, REUNIONES, INVITADOS, IMPESC, and DMZ, with DMZ currently selected. The main content area is titled "General DHCP Options" and contains several configuration sections:

- DHCP Backend:** ISC DHCP
- Enable:** ☒ Enable DHCP server on DMZ interface
- BOOTP:** ☐ Ignore BOOTP queries
- Deny Unknown Clients:** A dropdown menu is set to "Allow all clients". Below it, a text block explains the behavior of the "Allow all clients" setting.
- Ignore Denied Clients:** ☐ Ignore denied clients rather than reject. A note states this option is not compatible with failover.
- Ignore Client Identifiers:** ☐ Do not record a unique identifier (UID) in client lease data if present in the client DHCP request. A note explains this option's use and its deviation from the DHCP specification.

Below the "General DHCP Options" section is the "Primary Address Pool" section:

- Subnet:** 10.0.100.0/24
- Subnet Range:** 10.0.100.1 - 10.0.100.254
- Address Pool Range:** Two input fields are shown. The "From" field contains "10.0.100.2" and the "To" field contains "10.0.100.200".

The bottom of the browser window shows a taskbar with the date "2026-04-21 09:59" and the username "gns3".

Panel de “Server Options” y “DNS Server Settings” donde se han introducido servidores DNS externos como los de Google (8.8.8.8 / 8.8.4.4) y Cloudflare (1.1.1.1).

Server Options			
WINS Servers	WINS Server 1		
	WINS Server 2		
DNS Servers	8.8.8.8		
	1.1.1.1		
	8.8.4.4		
	DNS Server 4		

DNS Server Settings			
DNS Servers	8.8.8.8	Google	 Delete
	8.8.4.4	Google	 Delete
	1.1.1.1	Cloudflare	 Delete

Address

Enter IP addresses to be used by the system for DNS resolution. These are also used for the DHCP service, DNS Forwarder and DNS Resolver when it has DNS Query Forwarding enabled.

Hostname

Enter the DNS Server Hostname for TLS Verification in the DNS Resolver (optional).

Opciones avanzadas de red del sistema establecido “Kea DHCP” como el backend encargado de repartir direcciones IP a los distintos equipos de la red.

The screenshot shows the pfSense web interface in a browser window. The address bar displays `192.168.1.1/system_advanced_network.php`. The top navigation bar includes links for System, Interfaces, Firewall, Services, VPN, Status, Diagnostics, and Help. A warning message at the top states: "WARNING: The 'admin' account password is set to the default value. Change the password in the User Manager." The breadcrumb trail is "System / Advanced / Networking". The "Networking" tab is selected in the sub-menu. The "DHCP Options" section is active, showing the "Server Backend" as "Kea DHCP" (selected). Below this, there are checkboxes for "RADVD Debug" (Log all radvd log levels), "DHCP6 Debug" (Start DHCP6 client in debug mode), and "Do not allow PD/Address release" (dhcp6c will send a release to the ISP on exit, some ISPs then release the allocated address or prefix. This option prevents that signal ever being sent). The "DHCP6 DUID" section has a dropdown menu set to "Raw DUID: As stored in DUID file or seen in firewall logs". A note explains that a DHCPv6 Unique Identifier (DUID) is used by the firewall when requesting an IPv6 address, and by default, the firewall automatically creates a dynamic DUID-LLT which is not saved in the firewall configuration. To ensure the same DUID is retained, a DUID should be entered in this section. The bottom status bar shows the date and time as "2026-04-21 10:04" and the user "gns3".

pfSense COMMUNITY EDITION

System / Advanced / Networking

Admin Access Firewall & NAT **Networking** Miscellaneous System Tunables Notifications

DHCP Options

Server Backend ☒ Kea DHCP ☐ ISC DHCP (Deprecated) ☐ Ignore Deprecation Warning

ISC DHCP has reached end-of-life and will be removed from a future version of pfSense. Kea DHCP is the newer, modern DHCP distribution from ISC that includes the most-requested features.

RADVD Debug ☐ Log all radvd log levels

DHCP6 Debug ☐ Start DHCP6 client in debug mode

Do not allow PD/Address release ☐ dhcp6c will send a release to the ISP on exit, some ISPs then release the allocated address or prefix. This option prevents that signal ever being sent

DHCP6 DUID Raw DUID: As stored in DUID file or seen in firewall logs

A DHCPv6 Unique Identifier (DUID) is used by the firewall when requesting an IPv6 address.

By default, the firewall automatically creates a dynamic DUID-LLT which is not saved in the firewall configuration. To ensure that the same DUID is retained by the firewall at all times, enter a DUID in this section. The new DUID will take effect after a reboot or when the WAN interface(s) are reconfigured by the firewall.

Aplicaciones pfSense.home.arpa - Sys... 2026-04-21 10:04 gns3

Configuración general del “DNS Resolver”, habilitado para responder peticiones en el puerto 53 en las redes locales.

The screenshot displays the pfSense web interface for configuring the General DNS Resolver Options. The browser address bar shows the URL `192.168.1.1/services_unbound.php`. The configuration page has a dark header with the title "General DNS Resolver Options".

The configuration options are as follows:

- Enable:** A checkbox labeled "Enable DNS resolver" is checked.
- Listen Port:** A text input field contains the value "53". Below it, a note states: "The port used for responding to DNS queries. It should normally be left blank unless another service needs to bind to TCP/UDP port 53."
- Enable SSL/TLS Service:** A checkbox labeled "Respond to incoming SSL/TLS queries from local clients" is unchecked. Below it, a note states: "Configures the DNS Resolver to act as a DNS over SSL/TLS server which can answer queries from clients which also support DNS over TLS. Activating this option disables automatic interface response routing behavior, thus it works best with specific interface bindings."
- SSL/TLS Certificate:** A dropdown menu is set to "GUI default (69e21908388e6)". Below it, a note states: "The server certificate to use for SSL/TLS service. The CA chain will be determined automatically."
- SSL/TLS Listen Port:** A text input field contains the value "853". Below it, a note states: "The port used for responding to SSL/TLS DNS queries. It should normally be left blank unless another service needs to bind to TCP/UDP port 853."
- Network Interfaces:** A list box contains the following interfaces: LAN, ADMINSTRACION, TECNICA, REUNIONES, INVITADOS, IMPESC, DMZ, and WAN IPv6 Link-Local. Below the list, a note states: "Interface IP addresses used by the DNS Resolver for responding to queries from clients. If an interface has both IPv4 and IPv6 addresses, both are used. Queries to addresses not selected in this list are discarded. The default behavior is to respond to queries on every available IPv4 and IPv6 address."
- Outgoing Network Interfaces:** A list box contains the same interfaces as the Network Interfaces section. Below the list, a note states: "Utilize different network interface(s) that the DNS Resolver will use to send queries to authoritative servers and receive their replies. By default all

The bottom of the screenshot shows the pfSense desktop environment with a taskbar containing icons for "Aplicaciones", "pfSense.home.arpa - Se...", and a system tray showing the date "2026-04-21", time "10:08", and the user "gns3".

a

Reglas de Firewall específicas para la pestaña **Administración**, controlando hacia qué otras redes tiene permitido o denegado el acceso.

WARNING: The 'admin' account password is set to the default value. [Change the password in the User Manager.](#)

Firewall / Rules / ADMINISTRACION

Floating WAN LAN **ADMINISTRACION** TECNICA REUNIONES INVITADOS IMPESC DMZ

Rules (Drag to Change Order)											
☐	States	Protocol	Source	Port	Destination	Port	Gateway	Queue	Schedule	Description	Actions
☐	✓	0/0 B	IPv4 TCP/UDP	A_ADMINISTRACION	*	This Firewall (self)	53 (DNS)	*	none	PERMITIR DNS	
☐	✓	0/0 B	IPv4 *	A_ADMINISTRACION	*	A_DMZ	*	none		Acceso DMZ	
☐	✓	0/0 B	IPv4 *	A_ADMINISTRACION	*	A_IMPESC	*	none		Acceso IMPESC	
☐	✗	0/0 B	IPv4 *	A_ADMINISTRACION	*	A_TECNICA	*	none		Acceso TECNICA	
☐	✗	0/0 B	IPv4 *	A_ADMINISTRACION	*	A_INVITADOS	*	none		Acceso INVITADOS	
☐	✗	0/0 B	IPv4 *	A_ADMINISTRACION	*	A_REUNIONES	*	none		Acceso REUNIONES	
☐	✓	0/0 B	IPv4 *	A_ADMINISTRACION	*	*	*	none		Acceso INTERNET	

Add
 Add
 Delete
 Toggle
 Copy
 Save
 Separator

2026-04-21 11:29 gns3

Reglas de Firewall específicas para la pestaña **Técnica**, controlando hacia qué otras redes tiene permitido o denegado el acceso.

WARNING: The 'admin' account password is set to the default value. [Change the password in the User Manager.](#)

Firewall / Rules / TECNICA

Floating WAN LAN ADMINSTRACION **TECNICA** REUNIONES INVITADOS IMPESC DMZ

Rules (Drag to Change Order)

	States	Protocol	Source	Port	Destination	Port	Gateway	Queue	Schedule	Description	Actions
☐	✓	0/0 B	IPv4 TCP/UDP	A_TECNICA	*	This Firewall (self)	53 (DNS)	*	none	PERMITIR DNS	
☐	✓	0/0 B	IPv4 *	A_TECNICA	*	A_DMZ	*	*	none	Acceso DMZ	
☐	✓	0/0 B	IPv4 *	A_TECNICA	*	A_IMPESC	*	*	none	Acceso IMPESC	
☐	✗	0/0 B	IPv4 *	A_TECNICA	*	A_ADMINISTRACION	*	*	none	Acceso ADMINISTRACION	
☐	✗	0/0 B	IPv4 *	A_TECNICA	*	A_REUNIONES	*	*	none	Acceso REUNIONES	
☐	✗	0/0 B	IPv4 *	A_TECNICA	*	A_INVITADOS	*	*	none	Acceso INVITADOS	
☐	✓	0/0 B	IPv4 *	A_TECNICA	*	*	*	*	none	Acceso INTERNET	

Add
 Add
 Delete
 Toggle
 Copy
 Save
 Separator

2026-04-21 11:39 gns3

Reglas de Firewall específicas para la pestaña **Reuniones**, controlando hacia qué otras redes tiene permitido o denegado el acceso.

WARNING: The 'admin' account password is set to the default value. [Change the password in the User Manager.](#)

Firewall / Rules / REUNIONES

Floating WAN LAN ADMINSTRACION TECNICA **REUNIONES** INVITADOS IMPESC DMZ

Rules (Drag to Change Order)

☐	States	Protocol	Source	Port	Destination	Port	Gateway	Queue	Schedule	Description	Actions
☐	✓ 0/0 B	IPv4 TCP/UDP	A_REUNIONES	*	This Firewall (self)	53 (DNS)	*	none		PERMITIR DNS	
☐	✓ 0/0 B	IPv4 *	A_REUNIONES	*	A_IMPESC	*	*	none		Acceso IMPESC	
☐	✓ 0/0 B	IPv4 *	A_REUNIONES	*	A_DMZ	*	*	none		Acceso DMZ	
☐	✗ 0/0 B	IPv4 *	A_REUNIONES	*	A_ADMINISTRACION	*	*	none		Acceso ADMINISTRACION	
☐	✗ 0/0 B	IPv4 *	A_REUNIONES	*	A_TECNICA	*	*	none		Acceso TECNICA	
☐	✗ 0/0 B	IPv4 *	A_REUNIONES	*	A_INVITADOS	*	*	none		Acceso INVITADOS	
☐	✓ 0/0 B	IPv4 *	A_REUNIONES	*	*	*	*	none		Acceso INTERNET	

Add
 Add
 Delete
 Toggle
 Copy
 Save
 Separator

Aplicaciones pfSenseBAO.home.arpa... Terminal - gns3@Client... 2026-04-21 11:43 gns3

Reglas de Firewall específicas para la pestaña **Invitados**, controlando hacia qué otras redes tiene permitido o denegado el acceso.

WARNING: The 'admin' account password is set to the default value. [Change the password in the User Manager.](#)

Firewall / Rules / INVITADOS

Floating WAN LAN ADMINSTRACION TECNICA REUNIONES INVITADOS IMPESC DMZ

Rules (Drag to Change Order)											
☐	States	Protocol	Source	Port	Destination	Port	Gateway	Queue	Schedule	Description	Actions
☐	✓	0/0 B	IPv4 TCP/UDP	A_INVITADOS	*	This Firewall (self)	53 (DNS)	*	none	PERMITIR DNS	
☐	✓	0/0 B	IPv4 *	A_INVITADOS	*	A_DMZ	*	*	none	Acceso DMZ	
☐	✗	0/0 B	IPv4 *	A_INVITADOS	*	A_ADMINISTRACION	*	*	none	Acceso ADMINISTRACION	
☐	✗	0/0 B	IPv4 *	A_INVITADOS	*	A_REUNIONES	*	*	none	Acceso REUNIONES	
☐	✗	0/0 B	IPv4 *	A_INVITADOS	*	A_TECNICA	*	*	none	Acceso TECNICA	
☐	✗	0/0 B	IPv4 *	A_INVITADOS	*	A_IMPESC	*	*	none	Acceso IMPESC	
☐	✓	0/0 B	IPv4 *	A_INVITADOS	*	*	*	*	none	Acceso INTERNET	

Add
 Add
 Delete
 Toggle
 Copy
 Save
 Separator

2026-04-21 11:47 gns3

Reglas de Firewall específicas para la pestaña **IMPESC**, controlando hacia qué otras redes tiene permitido o denegado el acceso.

The screenshot shows the pfSense web interface for the IMPESC interface. A warning message at the top states: "WARNING: The 'admin' account password is set to the default value. Change the password in the User Manager." The breadcrumb trail is "Firewall / Rules / IMPESC". The "IMPESC" tab is selected in the top navigation bar. Below the tabs, a table titled "Rules (Drag to Change Order)" lists two rules:

☐	States	Protocol	Source	Port	Destination	Port	Gateway	Queue	Schedule	Description	Actions
☐	✓	0/0 B	IPv4 TCP/UDP	A_IMPESC	*	This Firewall (self)	53 (DNS)	*	none	PERMITIR DNS	Anchor Edit Copy Delete Toggle
☐	✓	0/0 B	IPv4 *	A_IMPESC	*	*	*	none		Acceso INTERNET	Anchor Edit Copy Delete Toggle

Below the table are buttons for "Add" (up and down arrows), "Delete", "Toggle", "Copy", "Save", and "Separator".

The footer of the interface states: "pfSense is developed and maintained by Netgate. © ESF 2004 - 2026 View license."

The system tray at the bottom shows the date and time as "2026-04-21 11:49" and the user "gns3".

Reglas de Firewall específicas para la pestaña **DMZ**, controlando hacia qué otras redes tiene permitido o denegado el acceso.

The screenshot shows the pfSense web interface for the Firewall Rules configuration. The browser address bar shows the URL `192.168.2.1/firewall_rules.php?if=opt6`. The top navigation bar includes links for System, Interfaces, Firewall, Services, VPN, Status, Diagnostics, and Help. A warning message at the top states: "WARNING: The 'admin' account password is set to the default value. Change the password in the User Manager."

The main content area is titled "Firewall / Rules / DMZ". Below this, there are tabs for different rule sets: Floating, WAN, LAN, ADMINSTRACION, TECNICA, REUNIONES, INVITADOS, IMPESC, and DMZ. The DMZ tab is currently selected.

The "Rules (Drag to Change Order)" table displays the following rules:

	States	Protocol	Source	Port	Destination	Port	Gateway	Queue	Schedule	Description	Actions
☐	✓	0/0 B	IPv4 TCP/UDP	A_DMZ	*	This Firewall (self)	53 (DNS)	*	none	PERMITIR DNS	
☐	✓	0/0 B	IPv4 *	A_DMZ	*	*	*	none		Acceso INTERNET	

Below the table, there are buttons for "Add" (up arrow), "Add" (down arrow), "Delete", "Toggle", "Copy", "Save", and "Separator".

The footer of the interface states: "pfSense is developed and maintained by Netgate. © ESF 2004 - 2026 View license."

The bottom status bar shows the system time as 2026-04-21 11:50 and the user as gns3.

Configuración del servidor VPN de OpenVPN escuchando en la interfaz WAN por el puerto UDP 1194. Los usuarios obtendrán una IP del rango 10.8.0.X/24 al conectarse.

pfSense COMMUNITY EDITION

System ▾ Interfaces ▾ Firewall ▾ Services ▾ VPN ▾ Status ▾ Diagnostics ▾ Help ▾

WARNING: The 'admin' account password is set to the default value. [Change the password in the User Manager.](#)

VPN / OpenVPN / Servers

Servers Clients Client Specific Overrides Wizards Client Export

Interface	Protocol / Port	Tunnel Network	Mode / Crypto	Description	Actions
WAN	UDP4 / 1194 (TUN)	10.8.0.0/24	Mode: Remote Access (SSL/TLS + User Auth) Data Ciphers: AES-128-CBC, AES-256-CBC, AES-256-GCM Digest: SHA256 D-H Params: 2048 bits	ServerVPN BAO	

+ Add

pfSense is developed and maintained by Netgate. © ESF 2004 - 2026 View license.

Aplicaciones pfSenseBAO.home.arpa... Terminal - gns3@Client... 2026-04-21 12:36 gns3

Reglas de la interfaz WAN en el Firewall, mostrando la apertura explícita del puerto 1194 para permitir el acceso OpenVPN desde el exterior.

pfSense BAO.home.arpa - x

192.168.2.1/firewall_rules.php?if=wan

System Interfaces Firewall Services VPN Status Diagnostics Help

WARNING: The 'admin' account password is set to the default value. [Change the password in the User Manager.](#)

Firewall / Rules / WAN

Floating WAN LAN ADMINSTRACION TECNICA REUNIONES INVITADOS IMPESC DMZ OpenVPN

Rules (Drag to Change Order)

☐	States	Protocol	Source	Port	Destination	Port	Gateway	Queue	Schedule	Description	Actions
☒	0/35 KiB	*	RFC 1918 networks	*	*	*	*	*		Block private networks	
☒	0/0 B	*	Reserved Not assigned by IANA	*	*	*	*	*		Block bogon networks	
☐	✓ 0/0 B	IPv4 UDP	*	*	*	1194 (OpenVPN)	*	none		Acceso OPENVPN desde WAN	

Add Add Delete Toggle Copy Save Separator

pfSense is developed and maintained by Netgate. © ESF 2004 - 2026 View license.

Aplicaciónes: pfSenseBAO.home.arpa... Terminal - gns3@Client... 2026-04-21 12:38 gns3

Resumen de las reglas de Firewall dentro de la propia pestaña “OpenVPN”, dictando a qué redes internas pueden acceder los clientes conectados a la VPN.

pfSenseBAO.home.arpa - x

192.168.2.1/firewall_rules.php?if=openvpn

pfSense COMMUNITY EDITION

System ▾ Interfaces ▾ Firewall ▾ Services ▾ VPN ▾ Status ▾ Diagnostics ▾ Help ▾

WARNING: The 'admin' account password is set to the default value. [Change the password in the User Manager.](#)

Firewall / Rules / OpenVPN

Floating WAN LAN ADMINISTRACION TECNICA REUNIONES INVITADOS IMPESC DMZ OpenVPN

Rules (Drag to Change Order)

☐	States	Protocol	Source	Port	Destination	Port	Gateway	Queue	Schedule	Description	Actions
☐	✓	0/0 B	IPv4 TCP/UDP	*	*	This Firewall (self)	53 (DNS)	*	none	PERMITE DNS	
☐	✗	0/0 B	IPv4 *	*	A_ADMINISTRACION	*	*	none		Acceso ADMINISTRACION	
☐	✗	0/0 B	IPv4 *	*	A_REUNIONES	*	*	none		Acceso REUNIONES	
☐	✗	0/0 B	IPv4 *	*	A_INVITADOS	*	*	none		Acceso INVITADOS	
☐	✗	0/0 B	IPv4 *	*	A_IMPESC	*	*	none		Acceso IMPESC	
☐	✓	0/0 B	IPv4 *	*	A_TECNICA	*	*	none		Acceso TECNICA	
☐	✓	0/0 B	IPv4 *	*	A_DMZ	*	*	none		Acceso DMZ	
☐	✓	0/0 B	IPv4 *	*	*	*	*	none		Acceso INTERNET	

Add
 Add
 Delete
 Toggle
 Copy
 Save
 Separator

Aplicaciones Firefox-esr Descargas - Thunar

2026-04-21 13:53 gns3