

ANEXO V

PRUEBAS Y VERIFICACIÓN: AJUSTES REALIZADOS (1.5.3)



Restaurar sesión x pfSense.home.arpa - Int...

192.168.1.1/interfaces_vlan.php

pfSense COMMUNITY EDITION

System ▾ Interfaces ▾ Firewall ▾ Services ▾ VPN ▾ Status ▾ Diagnostics ▾ Help ▾

WARNING: The 'admin' account password is set to the default value. [Change the password in the User Manager.](#)

Interfaces / VLANs

Interface Assignments Interface Groups Wireless **VLANs** QinQs PPPs GREs GIFs Bridges LAGGs

VLAN Interfaces

Interface	VLAN tag	Priority	Description	Actions
em1 (lan)	10		VLAN ADMINISTRACION	 
em2 (opt1)	20		VLAN TECNICA	 
em1 (lan)	30		VLAN REUNIONES	 
em1 (lan)	40		VLAN INVITADOS	 
em1 (lan)	50		VLAN IMPESC	 
em1 (lan)	100		VLAN DMZ	 

  Add

pfSense is developed and maintained by Netgate. © 2004 - 2026. View license

Aplicaciones pfSense.home.arpa - Int... 2026-04-21 09:36 gns3

Restaurar sesión x pfSense.home.arpa - Fire x

192.168.1.1/firewall_aliases.php?tab=ip

pfSense
COMMUNITY EDITION

System ▾ Interfaces ▾ Firewall ▾ Services ▾ VPN ▾ Status ▾ Diagnostics ▾ Help ▾

WARNING: The 'admin' account password is set to the default value. [Change the password in the User Manager.](#)

Firewall / Aliases / IP

IP Ports URLs All

Firewall Aliases IP

Name	Type	Values	Description	Actions
A_ADMINISTRACION	Network(s)	192.168.10.0/24	ALIAS ADMINISTRACION	  
A_DMZ	Network(s)	10.0.100.0/24	ALIAS DMZ	  
A_IMPESC	Network(s)	192.168.50.0/24	ALIAS IMPESC	  
A_INVITADOS	Network(s)	192.168.40.0/24	ALIAS INVITADOS	  
A_REUNIONES	Network(s)	192.168.30.0/24	ALIAS REUNIONES	  
A_TECNICA	Network(s)	192.168.20.0/24	ALIAS TECNICA	  



 Add  Import

pfSense is developed and maintained by Netgate. © 2004 - 2026. View license

Aplicaciones x pfSense.home.arpa - Fir... 2026-04-21 09:40 gns3

pfSense.home.arpa - Ser x +

192.168.1.1/services_dhcp.php?if=opt1

LAN ADMINSTRACION TECNICA REUNIONES INVITADOS IMPESC DMZ

General DHCP Options

DHCP Backend	ISC DHCP
Enable	☒ Enable DHCP server on ADMINSTRACION interface
BOOTP	☐ Ignore BOOTP queries
Deny Unknown Clients	Allow all clients When set to Allow all clients, any DHCP client will get an IP address within this scope/range on this interface. If set to Allow known clients from any interface, any DHCP client with a MAC address listed in a static mapping on any scope(s)/interface(s) will get an IP address. If set to Allow known clients from only this interface, only MAC addresses listed in static mappings on this interface will get an IP address within this scope/range.
Ignore Denied Clients	☐ Ignore denied clients rather than reject This option is not compatible with failover and cannot be enabled when a Failover Peer IP address is configured.
Ignore Client Identifiers	☐ Do not record a unique identifier (UID) in client lease data if present in the client DHCP request This option may be useful when a client can dual boot using different client identifiers but the same hardware (MAC) address. Note that the resulting server behavior violates the official DHCP specification.

Primary Address Pool

Subnet	192.168.10.0/24
Subnet Range	192.168.10.1 - 192.168.10.254
Address Pool Range	192.168.10.2 From 192.168.10.200 To

Aplicaciones pfSense.home.arpa - Se... 2026-04-21 09:50 gns3

pfSense.home.arpa - Ser x

192.168.1.1/services_dhcp.php?if=opt2

LAN ADMINSTRACION **TECNICA** REUNIONES INVITADOS IMPESC DMZ

General DHCP Options

DHCP Backend	ISC DHCP
Enable	☒ Enable DHCP server on TECNICA interface
BOOTP	☐ Ignore BOOTP queries
Deny Unknown Clients	Allow all clients When set to Allow all clients, any DHCP client will get an IP address within this scope/range on this interface. If set to Allow known clients from any interface, any DHCP client with a MAC address listed in a static mapping on any scope(s)/interface(s) will get an IP address. If set to Allow known clients from only this interface, only MAC addresses listed in static mappings on this interface will get an IP address within this scope/range.
Ignore Denied Clients	☐ Ignore denied clients rather than reject This option is not compatible with failover and cannot be enabled when a Failover Peer IP address is configured.
Ignore Client Identifiers	☐ Do not record a unique identifier (UID) in client lease data if present in the client DHCP request This option may be useful when a client can dual boot using different client identifiers but the same hardware (MAC) address. Note that the resulting server behavior violates the official DHCP specification.

Primary Address Pool

Subnet	192.168.20.0/24
Subnet Range	192.168.20.1 - 192.168.20.254
Address Pool Range	192.168.20.2 From 192.168.20.200 To

Aplicaciones pfSense.home.arpa - Se... 2026-04-21 09:52 gns3

pfSense.home.arpa - Ser x

192.168.1.1/services_dhcp.php?if=opt3

LAN ADMINSTRACION TECNICA **REUNIONES** INVITADOS IMPESC DMZ

General DHCP Options

DHCP Backend	ISC DHCP
Enable	☒ Enable DHCP server on REUNIONES interface
BOOTP	☐ Ignore BOOTP queries
Deny Unknown Clients	Allow all clients When set to Allow all clients, any DHCP client will get an IP address within this scope/range on this interface. If set to Allow known clients from any interface, any DHCP client with a MAC address listed in a static mapping on any scope(s)/interface(s) will get an IP address. If set to Allow known clients from only this interface, only MAC addresses listed in static mappings on this interface will get an IP address within this scope/range.
Ignore Denied Clients	☐ Ignore denied clients rather than reject This option is not compatible with failover and cannot be enabled when a Failover Peer IP address is configured.
Ignore Client Identifiers	☐ Do not record a unique identifier (UID) in client lease data if present in the client DHCP request This option may be useful when a client can dual boot using different client identifiers but the same hardware (MAC) address. Note that the resulting server behavior violates the official DHCP specification.

Primary Address Pool

Subnet	192.168.30.0/24
Subnet Range	192.168.30.1 - 192.168.30.254
Address Pool Range	192.168.30.2 From 192.168.30.200 To

Aplicaciónes pfSense.home.arpa - Se... 2026-04-21 09:54 gns3

pfSense.home.arpa - Ser x

192.168.1.1/services_dhcp.php?if=opt4

LAN ADMINSTRACION TECNICA REUNIONES **INVITADOS** IMPESC DMZ

General DHCP Options

DHCP Backend	ISC DHCP
Enable	☒ Enable DHCP server on INVITADOS interface
BOOTP	☐ Ignore BOOTP queries
Deny Unknown Clients	Allow all clients When set to Allow all clients, any DHCP client will get an IP address within this scope/range on this interface. If set to Allow known clients from any interface, any DHCP client with a MAC address listed in a static mapping on any scope(s)/interface(s) will get an IP address. If set to Allow known clients from only this interface, only MAC addresses listed in static mappings on this interface will get an IP address within this scope/range.
Ignore Denied Clients	☐ Ignore denied clients rather than reject This option is not compatible with failover and cannot be enabled when a Failover Peer IP address is configured.
Ignore Client Identifiers	☐ Do not record a unique identifier (UID) in client lease data if present in the client DHCP request This option may be useful when a client can dual boot using different client identifiers but the same hardware (MAC) address. Note that the resulting server behavior violates the official DHCP specification.

Primary Address Pool

Subnet	192.168.40.0/24
Subnet Range	192.168.40.1 - 192.168.40.254
Address Pool Range	192.168.40.2 From 192.168.40.200 To

Aplicaciones pfSense.home.arpa - Se... 2026-04-21 10:01 gns3

pfSense.home.arpa - Ser x

192.168.1.1/services_dhcp.php?if=opt5

LAN ADMINSTRACION TECNICA REUNIONES INVITADOS **IMPESC** DMZ

General DHCP Options

DHCP Backend	ISC DHCP
Enable	☒ Enable DHCP server on IMPESC interface
BOOTP	☐ Ignore BOOTP queries
Deny Unknown Clients	Allow all clients When set to Allow all clients, any DHCP client will get an IP address within this scope/range on this interface. If set to Allow known clients from any interface, any DHCP client with a MAC address listed in a static mapping on any scope(s)/interface(s) will get an IP address. If set to Allow known clients from only this interface, only MAC addresses listed in static mappings on this interface will get an IP address within this scope/range.
Ignore Denied Clients	☐ Ignore denied clients rather than reject This option is not compatible with failover and cannot be enabled when a Failover Peer IP address is configured.
Ignore Client Identifiers	☐ Do not record a unique identifier (UID) in client lease data if present in the client DHCP request This option may be useful when a client can dual boot using different client identifiers but the same hardware (MAC) address. Note that the resulting server behavior violates the official DHCP specification.

Primary Address Pool

Subnet	192.168.50.0/24	
Subnet Range	192.168.50.1 - 192.168.50.254	
Address Pool Range	192.168.50.2 From	192.168.50.200 To

Aplicaciones pfSense.home.arpa - Se... 2026-04-21 09:58 gns3

pfSense.home.arpa - Ser x +

192.168.1.1/services_dhcp.php?if=opt6

LAN ADMINSTRACION TECNICA REUNIONES INVITADOS IMPESC **DMZ**

General DHCP Options

DHCP Backend	ISC DHCP
Enable	☒ Enable DHCP server on DMZ interface
BOOTP	☐ Ignore BOOTP queries
Deny Unknown Clients	Allow all clients When set to Allow all clients, any DHCP client will get an IP address within this scope/range on this interface. If set to Allow known clients from any interface, any DHCP client with a MAC address listed in a static mapping on any scope(s)/interface(s) will get an IP address. If set to Allow known clients from only this interface, only MAC addresses listed in static mappings on this interface will get an IP address within this scope/range.
Ignore Denied Clients	☐ Ignore denied clients rather than reject This option is not compatible with failover and cannot be enabled when a Failover Peer IP address is configured.
Ignore Client Identifiers	☐ Do not record a unique identifier (UID) in client lease data if present in the client DHCP request This option may be useful when a client can dual boot using different client identifiers but the same hardware (MAC) address. Note that the resulting server behavior violates the official DHCP specification.

Primary Address Pool

Subnet	10.0.100.0/24
Subnet Range	10.0.100.1 - 10.0.100.254
Address Pool Range	10.0.100.2 From 10.0.100.200 To

Aplicaciónes pfSense.home.arpa - Se... 2026-04-21 09:59 gns3

Server Options**WINS Servers****DNS Servers****DNS Server Settings****DNS Servers** Delete Delete Delete**Address**

Enter IP addresses to be used by the system for DNS resolution. These are also used for the DHCP service, DNS Forwarder and DNS Resolver when it has DNS Query Forwarding enabled.

Hostname

Enter the DNS Server Hostname for TLS Verification in the DNS Resolver (optional).

pfSense.home.arpa - Sys x

192.168.1.1/system_advanced_network.php

pfSense
COMMUNITY EDITION

System ▾ Interfaces ▾ Firewall ▾ Services ▾ VPN ▾ Status ▾ Diagnostics ▾ Help ▾

WARNING: The 'admin' account password is set to the default value. [Change the password in the User Manager.](#)

System / **Advanced** / Networking ?

Admin Access Firewall & NAT **Networking** Miscellaneous System Tunables Notifications

DHCP Options

Server Backend	☒ Kea DHCP	☐ ISC DHCP (Deprecated)	☐ Ignore Deprecation Warning
ISC DHCP has reached end-of-life and will be removed from a future version of pfSense. Kea DHCP is the newer, modern DHCP distribution from ISC that includes the most-requested features.			
RADVD Debug	☐ Log all radvd log levels		
DHCP6 Debug	☐ Start DHCP6 client in debug mode		
Do not allow PD/Address release	☐ dhcp6c will send a release to the ISP on exit, some ISPs then release the allocated address or prefix. This option prevents that signal ever being sent		
DHCP6 DUID	Raw DUID: As stored in DUID file or seen in firewall logs ▾ A DHCPv6 Unique Identifier (DUID) is used by the firewall when requesting an IPv6 address. By default, the firewall automatically creates a dynamic DUID-LLT which is not saved in the firewall configuration. To ensure that the same DUID is retained by the firewall at all times, enter a DUID in this section. The new DUID will take effect after a reboot or when the WAN interface(s) are reconfigured by the firewall.		

Aplicaciones: pfSense.home.arpa - Sy... 2026-04-21 10:04 gns3

Browser tabs: pfSense.home.arpa - Ser x

Address bar: 192.168.1.1/services_unbound.php 90%

General DNS Resolver Options

Enable ☒ Enable DNS resolver

Listen Port 53
The port used for responding to DNS queries. It should normally be left blank unless another service needs to bind to TCP/UDP port 53.

Enable SSL/TLS Service ☐ Respond to incoming SSL/TLS queries from local clients
Configures the DNS Resolver to act as a DNS over SSL/TLS server which can answer queries from clients which also support DNS over TLS. Activating this option disables automatic interface response routing behavior, thus it works best with specific interface bindings.

SSL/TLS Certificate GUI default (69e21908388e6)
The server certificate to use for SSL/TLS service. The CA chain will be determined automatically.

SSL/TLS Listen Port 853
The port used for responding to SSL/TLS DNS queries. It should normally be left blank unless another service needs to bind to TCP/UDP port 853.

Network Interfaces

LAN
ADMINISTRACION
TECNICA
REUNIONES
INVITADOS
IMPESC
DMZ
WAN IPv6 Link-Local

Interface IP addresses used by the DNS Resolver for responding to queries from clients. If an interface has both IPv4 and IPv6 addresses, both are used. Queries to addresses not selected in this list are discarded. The default behavior is to respond to queries on every available IPv4 and IPv6 address.

Outgoing Network Interfaces

LAN
ADMINISTRACION
TECNICA
REUNIONES
INVITADOS
IMPESC
DMZ
WAN IPv6 Link-Local

Utilize different network interface(s) that the DNS Resolver will use to send queries to authoritative servers and receive their replies. By default all

Footer: Aplicacións pfSense.home.arpa - Se... 2026-04-21 10:08 gns3

pfSenseBAO.home.arpa - x

192.168.2.1/firewall_rules.php?if=opt1

pfSense COMMUNITY EDITION

System ▾ Interfaces ▾ Firewall ▾ Services ▾ VPN ▾ Status ▾ Diagnostics ▾ Help ▾

WARNING: The 'admin' account password is set to the default value. [Change the password in the User Manager.](#)

Firewall / Rules / ADMINSTRACION

Floating WAN LAN ADMINSTRACION TECNICA REUNIONES INVITADOS IMPESC DMZ

Rules (Drag to Change Order)

☐	States	Protocol	Source	Port	Destination	Port	Gateway	Queue	Schedule	Description	Actions
☐	✓	0/0 B	IPv4 TCP/UDP	A_ADMINISTRACION	*	This Firewall (self)	53 (DNS)	*	none	PERMITIR DNS	
☐	✓	0/0 B	IPv4 *	A_ADMINISTRACION	*	A_DMZ	*	*	none	Acceso DMZ	
☐	✓	0/0 B	IPv4 *	A_ADMINISTRACION	*	A_IMPESC	*	*	none	Acceso IMPESC	
☐	✗	0/0 B	IPv4 *	A_ADMINISTRACION	*	A_TECNICA	*	*	none	Acceso TECNICA	
☐	✗	0/0 B	IPv4 *	A_ADMINISTRACION	*	A_INVITADOS	*	*	none	Acceso INVITADOS	
☐	✗	0/0 B	IPv4 *	A_ADMINISTRACION	*	A_REUNIONES	*	*	none	Acceso REUNIONES	
☐	✓	0/0 B	IPv4 *	A_ADMINISTRACION	*	*	*	*	none	Acceso INTERNET	

Add
 Add
 Delete
 Toggle
 Copy
 Save
 Separator

Aplicacions pfSenseBAO.home.arpa... Terminal - gns3@Client... 2026-04-21 11:29 gns3

pfSenseBAO.home.arpa - x

192.168.2.1/firewall_rules.php?if=opt2

pfSense COMMUNITY EDITION

System ▾ Interfaces ▾ Firewall ▾ Services ▾ VPN ▾ Status ▾ Diagnostics ▾ Help ▾

WARNING: The 'admin' account password is set to the default value. [Change the password in the User Manager.](#)

Firewall / Rules / TECNICA

Floating WAN LAN ADMINISTRACION **TECNICA** REUNIONES INVITADOS IMPESC DMZ

Rules (Drag to Change Order)

	States	Protocol	Source	Port	Destination	Port	Gateway	Queue	Schedule	Description	Actions
☐	✓	0/0 B	IPv4 TCP/UDP	A_TECNICA	*	This Firewall (self)	53 (DNS)	*	none	PERMITIR DNS	
☐	✓	0/0 B	IPv4 *	A_TECNICA	*	A_DMZ	*	*	none	Acceso DMZ	
☐	✓	0/0 B	IPv4 *	A_TECNICA	*	A_IMPESC	*	*	none	Acceso IMPESC	
☐	✗	0/0 B	IPv4 *	A_TECNICA	*	A_ADMINISTRACION	*	*	none	Acceso ADMINISTRACION	
☐	✗	0/0 B	IPv4 *	A_TECNICA	*	A_REUNIONES	*	*	none	Acceso REUNIONES	
☐	✗	0/0 B	IPv4 *	A_TECNICA	*	A_INVITADOS	*	*	none	Acceso INVITADOS	
☐	✓	0/0 B	IPv4 *	A_TECNICA	*	*	*	*	none	Acceso INTERNET	

Add
 Add
 Delete
 Toggle
 Copy
 Save
 Separator

Aplicaciones pfSenseBAO.home.arpa... Terminal - gns3@Client... 2026-04-21 11:39 gns3

pfSenseBAO.home.arpa - x

192.168.2.1/firewall_rules.php?if=opt3

pfSense
COMMUNITY EDITION

System ▾ Interfaces ▾ Firewall ▾ Services ▾ VPN ▾ Status ▾ Diagnostics ▾ Help ▾

WARNING: The 'admin' account password is set to the default value. [Change the password in the User Manager.](#)

Firewall / Rules / REUNIONES

Floating WAN LAN ADMINISTRACION TECNICA REUNIONES INVITADOS IMPESC DMZ

Rules (Drag to Change Order)

☐	States	Protocol	Source	Port	Destination	Port	Gateway	Queue	Schedule	Description	Actions
☐	✓	0/0 B	IPv4 TCP/UDP	A_REUNIONES	*	This Firewall (self)	53 (DNS)	*	none	PERMITIR DNS	    
☐	✓	0/0 B	IPv4 *	A_REUNIONES	*	A_IMPESC	*	*	none	Acceso IMPESC	    
☐	✓	0/0 B	IPv4 *	A_REUNIONES	*	A_DMZ	*	*	none	Acceso DMZ	    
☐	✗	0/0 B	IPv4 *	A_REUNIONES	*	A_ADMINISTRACION	*	*	none	Acceso ADMINISTRACION	   
☐	✗	0/0 B	IPv4 *	A_REUNIONES	*	A_TECNICA	*	*	none	Acceso TECNICA	   
☐	✗	0/0 B	IPv4 *	A_REUNIONES	*	A_INVITADOS	*	*	none	Acceso INVITADOS	   
☐	✓	0/0 B	IPv4 *	A_REUNIONES	*	*	*	*	none	Acceso INTERNET	    

 Add  Add  Delete  Toggle  Copy  Save  Separator

Aplicaciónes pfSenseBAO.home.arpa... Terminal - gns3@Client... 2026-04-21 11:43 gns3

pfSenseBAO.home.arpa - x

192.168.2.1/firewall_rules.php?if=opt4

pfSense COMMUNITY EDITION

System ▾ Interfaces ▾ Firewall ▾ Services ▾ VPN ▾ Status ▾ Diagnostics ▾ Help ▾

WARNING: The 'admin' account password is set to the default value. [Change the password in the User Manager.](#)

Firewall / Rules / INVITADOS

Floating WAN LAN ADMINISTRACION TECNICA REUNIONES INVITADOS IMPESC DMZ

Rules (Drag to Change Order)

☐	States	Protocol	Source	Port	Destination	Port	Gateway	Queue	Schedule	Description	Actions
☐	✓	0/0 B	IPv4 TCP/UDP	A_INVITADOS	*	This Firewall (self)	53 (DNS)	*	none	PERMITIR DNS	
☐	✓	0/0 B	IPv4 *	A_INVITADOS	*	A_DMZ	*	*	none	Acceso DMZ	
☐	✗	0/0 B	IPv4 *	A_INVITADOS	*	A_ADMINISTRACION	*	*	none	Acceso ADMINISTRACION	
☐	✗	0/0 B	IPv4 *	A_INVITADOS	*	A_REUNIONES	*	*	none	Acceso REUNIONES	
☐	✗	0/0 B	IPv4 *	A_INVITADOS	*	A_TECNICA	*	*	none	Acceso TECNICA	
☐	✗	0/0 B	IPv4 *	A_INVITADOS	*	A_IMPESC	*	*	none	Acceso IMPESC	
☐	✓	0/0 B	IPv4 *	A_INVITADOS	*	*	*	*	none	Acceso INTERNET	

Add
 Add
 Delete
 Toggle
 Copy
 Save
 Separator

Aplicaciónes pfSenseBAO.home.arpa... Terminal - gns3@Client... 2026-04-21 11:47 gns3

pfSenseBAO.home.arpa - x

192.168.2.1/firewall_rules.php?if=opt5

pfSense
COMMUNITY EDITION

System ▾ Interfaces ▾ Firewall ▾ Services ▾ VPN ▾ Status ▾ Diagnostics ▾ Help ▾

WARNING: The 'admin' account password is set to the default value. [Change the password in the User Manager.](#)

Firewall / Rules / IMPESC

Floating WAN LAN ADMINISTRACION TECNICA REUNIONES INVITADOS IMPESC DMZ

Rules (Drag to Change Order)

☐	States	Protocol	Source	Port	Destination	Port	Gateway	Queue	Schedule	Description	Actions
☐	✓ 0/0 B	IPv4 TCP/UDP	A_IMPESC	*	This Firewall (self)	53 (DNS)	*	none		PERMITIR DNS	Anchor Edit Copy Toggle Delete X
☐	✓ 0/0 B	IPv4 *	A_IMPESC	*	*	*	*	none		Acceso INTERNET	Anchor Edit Copy Toggle Delete X

[↑ Add](#) [↓ Add](#) [Delete](#) [Toggle](#) [Copy](#) [Save](#) [+ Separator](#)

pfSense is developed and maintained by Netgate. © ESF 2004 - 2026 View license.

Aplicaciónes: pfSenseBAO.home.arpa... Terminal - gns3@Client... 2026-04-21 11:49 gns3

pfSenseBAO.home.arpa - x

192.168.2.1/firewall_rules.php?if=opt6

pfSense COMMUNITY EDITION

System ▾ Interfaces ▾ Firewall ▾ Services ▾ VPN ▾ Status ▾ Diagnostics ▾ Help ▾

WARNING: The 'admin' account password is set to the default value. [Change the password in the User Manager.](#)

Firewall / Rules / DMZ

Floating WAN LAN ADMINSTRACION TECNICA REUNIONES INVITADOS IMPESC DMZ

Rules (Drag to Change Order)

☐	States	Protocol	Source	Port	Destination	Port	Gateway	Queue	Schedule	Description	Actions
☐	✓ 0/0 B	IPv4 TCP/UDP	A_DMZ	*	This Firewall (self)	53 (DNS)	*	none		PERMITIR DNS	     
☐	✓ 0/0 B	IPv4 *	A_DMZ	*	*	*	*	none		Acceso INTERNET	     

 Add  Add  Delete  Toggle  Copy  Save  Separator

pfSense is developed and maintained by Netgate. © ESF 2004 - 2026 [View license.](#)

Aplicacions pfSenseBAO.home.arpa... Terminal - gns3@Client... 2026-04-21 11:50 gns3

pfSenseBAO.home.arpa - x

192.168.2.1/vpn_openvpn_server.php

pfSense
COMMUNITY EDITION

System ▾ Interfaces ▾ Firewall ▾ Services ▾ VPN ▾ Status ▾ Diagnostics ▾ Help ▾

WARNING: The 'admin' account password is set to the default value. [Change the password in the User Manager.](#)

VPN / OpenVPN / Servers

Servers Clients Client Specific Overrides Wizards Client Export

OpenVPN Servers

Interface	Protocol / Port	Tunnel Network	Mode / Crypto	Description	Actions
WAN	UDP4 / 1194 (TUN)	10.8.0.0/24	Mode: Remote Access (SSL/TLS + User Auth) Data Ciphers: AES-128-CBC, AES-256-CBC, AES-256-GCM Digest: SHA256 D-H Params: 2048 bits	ServerVPN BAO	  

+ Add

pfSense is developed and maintained by Netgate. © ESF 2004 - 2026 View license.

Aplicacions pfSenseBAO.home.arpa... Terminal - gns3@Client... 2026-04-21 12:36 gns3

pfSenseBAO.home.arpa - x

192.168.2.1/firewall_rules.php?if=wan

pfSense
COMMUNITY EDITION

System ▾ Interfaces ▾ Firewall ▾ Services ▾ VPN ▾ Status ▾ Diagnostics ▾ Help ▾

WARNING: The 'admin' account password is set to the default value. [Change the password in the User Manager.](#)

Firewall / Rules / WAN

Floating WAN LAN ADMINISTRACION TECNICA REUNIONES INVITADOS IMPESC DMZ OpenVPN

Rules (Drag to Change Order)

☐	States	Protocol	Source	Port	Destination	Port	Gateway	Queue	Schedule	Description	Actions
☒	0/35 KiB	*	RFC 1918 networks	*	*	*	*	*		Block private networks	
☒	0/0 B	*	Reserved Not assigned by IANA	*	*	*	*	*		Block bogon networks	
☐	0/0 B	IPv4 UDP	*	*	*	1194 (OpenVPN)	*	none		Acceso OPENVPN desde WAN	

Add Add Delete Toggle Copy Save Separator

pfSense is developed and maintained by Netgate. © ESF 2004 - 2026 View license.

Aplicaciónes pfSenseBAO.home.arpa... Terminal - gns3@Client... 2026-04-21 12:38 gns3

pfSenseBAO.home.arpa - x

192.168.2.1/firewall_rules.php?if=openvpn

pfSense COMMUNITY EDITION

System ▾ Interfaces ▾ Firewall ▾ Services ▾ VPN ▾ Status ▾ Diagnostics ▾ Help ▾

WARNING: The 'admin' account password is set to the default value. [Change the password in the User Manager.](#)

Firewall / Rules / OpenVPN

Floating WAN LAN ADMINISTRACION TECNICA REUNIONES INVITADOS IMPESC DMZ OpenVPN

Rules (Drag to Change Order)

☐	States	Protocol	Source	Port	Destination	Port	Gateway	Queue	Schedule	Description	Actions
☐	✓ 0/0 B	IPv4 TCP/UDP	*	*	This Firewall (self)	53 (DNS)	*	none		PERMITE DNS	
☐	✗ 0/0 B	IPv4 *	*	*	A_ADMINISTRACION	*	*	none		Acceso ADMINISTRACION	
☐	✗ 0/0 B	IPv4 *	*	*	A_REUNIONES	*	*	none		Acceso REUNIONES	
☐	✗ 0/0 B	IPv4 *	*	*	A_INVITADOS	*	*	none		Acceso INVITADOS	
☐	✗ 0/0 B	IPv4 *	*	*	A_IMPESC	*	*	none		Acceso IMPESC	
☐	✓ 0/0 B	IPv4 *	*	*	A_TECNICA	*	*	none		Acceso TECNICA	
☐	✓ 0/0 B	IPv4 *	*	*	A_DMZ	*	*	none		Acceso DMZ	
☐	✓ 0/0 B	IPv4 *	*	*	*	*	*	none		Acceso INTERNET	

Add
 Add
 Delete
 Toggle
 Copy
 Save
 Separator

Aplicaciones Firefox-esr Descargas - Thunar

2026-04-21 13:53 gns3