

# Python for scientific research

## Number crunching with NumPy and SciPy

Bram Kuijper

University of Exeter, Penryn Campus, UK

March 27, 2019



Researcher  
Development



- 1 Declare variables using built-in data types and execute operations on them
- 2 Use flow control commands to dictate the order in which commands are run and when
- 3 Encapsulate programs into reusable functions, modules and packages
- 4 Use string manipulation and regex to work with textual data
- 5 Interact with the file system
- 6 **Next:** Number crunching using NumPy/SciPy

=====

# Motivation

- We are typically faced by numerical tasks, such as, computing Pearson's correlation coefficient or generating random numbers

# Motivation

- We are typically faced by numerical tasks, such as, computing Pearson's correlation coefficient or generating random numbers
- The NumPy (numeric python) package provides a comprehensive set of mathematical data structures (e.g vector, matrix) and functions (e.g trigonometry, random number generators)

# Motivation

- We are typically faced by numerical tasks, such as, computing Pearson's correlation coefficient or generating random numbers
- The `NumPy` (numeric python) package provides a comprehensive set of mathematical data structures (e.g vector, matrix) and functions (e.g trigonometry, random number generators)
- The `SciPy` (scientific python) library builds on top of `NumPy` to provide a collection of numerical algorithms for:

# Motivation

- We are typically faced by numerical tasks, such as, computing Pearson's correlation coefficient or generating random numbers
- The NumPy (numeric python) package provides a comprehensive set of mathematical data structures (e.g vector, matrix) and functions (e.g trigonometry, random number generators)
- The SciPy (scientific python) library builds on top of NumPy to provide a collection of numerical algorithms for:
  - Statistics (e.g correlation coefficients) using `scipy.stats`

# Motivation

- We are typically faced by numerical tasks, such as, computing Pearson's correlation coefficient or generating random numbers
- The `NumPy` (numeric python) package provides a comprehensive set of mathematical data structures (e.g vector, matrix) and functions (e.g trigonometry, random number generators)
- The `SciPy` (scientific python) library builds on top of `NumPy` to provide a collection of numerical algorithms for:
  - Statistics (e.g correlation coefficients) using `scipy.stats`
  - Signal processing (e.g Fourier transform, filtering) using `scipy.fftpack` and `scipy.signal`



# Motivation

- We are typically faced by numerical tasks, such as, computing Pearson's correlation coefficient or generating random numbers
- The `NumPy` (numeric python) package provides a comprehensive set of mathematical data structures (e.g vector, matrix) and functions (e.g trigonometry, random number generators)
- The `SciPy` (scientific python) library builds on top of `NumPy` to provide a collection of numerical algorithms for:
  - Statistics (e.g correlation coefficients) using `scipy.stats`
  - Signal processing (e.g Fourier transform, filtering) using `scipy.fftpack` and `scipy.signal`
  - Solving differential equations, using `scipy.integrate`

# Motivation

- We are typically faced by numerical tasks, such as, computing Pearson's correlation coefficient or generating random numbers
- The `NumPy` (numeric python) package provides a comprehensive set of mathematical data structures (e.g vector, matrix) and functions (e.g trigonometry, random number generators)
- The `SciPy` (scientific python) library builds on top of `NumPy` to provide a collection of numerical algorithms for:
  - Statistics (e.g correlation coefficients) using `scipy.stats`
  - Signal processing (e.g Fourier transform, filtering) using `scipy.fftpack` and `scipy.signal`
  - Solving differential equations, using `scipy.integrate`
  - Optimisation using `scipy.optimize`

# Motivation

- We are typically faced by numerical tasks, such as, computing Pearson's correlation coefficient or generating random numbers
- The `NumPy` (numeric python) package provides a comprehensive set of mathematical data structures (e.g vector, matrix) and functions (e.g trigonometry, random number generators)
- The `SciPy` (scientific python) library builds on top of `NumPy` to provide a collection of numerical algorithms for:
  - Statistics (e.g correlation coefficients) using `scipy.stats`
  - Signal processing (e.g Fourier transform, filtering) using `scipy.fftpack` and `scipy.signal`
  - Solving differential equations, using `scipy.integrate`
  - Optimisation using `scipy.optimize`
  - ...

# A taste of NumPy: vectors

- Example of a NumPy vector

```
1 import numpy as np
2
3 # 1D array/vector
4 x = np.array([1, 3, 4, 2])
5 x.min() # return min of array
6 x.max() # return max of array
7 x.sum() # sum all elements in array
```

# A taste of NumPy: vectors

- Example of a NumPy vector

```
1 import numpy as np
2
3 # 1D array/vector
4 x = np.array([1, 3, 4, 2])
5 x.min() # return min of array
6 x.max() # return max of array
7 x.sum() # sum all elements in array
```

- Note that `np.array` is different from a list

# A taste of NumPy: vectors

- Example of a NumPy vector

```
1 import numpy as np
2
3 # 1D array/vector
4 x = np.array([1, 3, 4, 2])
5 x.min() # return min of array
6 x.max() # return max of array
7 x.sum() # sum all elements in array
```

- Note that `np.array` is different from a list
  - For example, operations like `list.reverse()` do not work

# A taste of NumPy: vectors

- Example of a NumPy vector

```
1 import numpy as np
2
3 # 1D array/vector
4 x = np.array([1, 3, 4, 2])
5 x.min() # return min of array
6 x.max() # return max of array
7 x.sum() # sum all elements in array
```

- Note that `np.array` is different from a list
  - For example, operations like `list.reverse()` do not work
- Easy, however, to cast `np.array` to a list

# A taste of NumPy: vectors

- Example of a NumPy vector

```
1 import numpy as np
2
3 # 1D array/vector
4 x = np.array([1, 3, 4, 2])
5 x.min() # return min of array
6 x.max() # return max of array
7 x.sum() # sum all elements in array
```

- Note that `np.array` is different from a list
  - For example, operations like `list.reverse()` do not work
- Easy, however, to cast `np.array` to a list

```
1 x_list = list(x) # [1, 3, 4, 2 ]
2 x_list.reverse() # now x_list is [2, 4, 3, 1]
```



# A taste of NumPy: matrices and linear algebra

- Specifying the matrix:

$$\mathbf{x} = \begin{bmatrix} 1 & 2 & 3 \\ 4 & 5 & 6 \\ 7 & 8 & 9 \end{bmatrix}$$

# A taste of NumPy: matrices and linear algebra

- Specifying the matrix:

$$\mathbf{x} = \begin{bmatrix} 1 & 2 & 3 \\ 4 & 5 & 6 \\ 7 & 8 & 9 \end{bmatrix}$$

```
1 import numpy as np
2 # 2D array (i.e., a matrix)
3 x = np.array([[1, 2, 3], [4, 5, 6], [7, 8, 9]])
```

# A taste of NumPy: matrices and linear algebra

- Specifying the matrix:

$$\mathbf{x} = \begin{bmatrix} 1 & 2 & 3 \\ 4 & 5 & 6 \\ 7 & 8 & 9 \end{bmatrix}$$

```
1 import numpy as np
2 # 2D array (i.e., a matrix)
3 x = np.array([[1, 2, 3], [4, 5, 6], [7, 8, 9]])
4 x*x # element-by-element multiplication (Kronecker
      product)
```

# A taste of NumPy: matrices and linear algebra

- Specifying the matrix:

$$\mathbf{x} = \begin{bmatrix} 1 & 2 & 3 \\ 4 & 5 & 6 \\ 7 & 8 & 9 \end{bmatrix}$$

```
1 import numpy as np
2 # 2D array (i.e., a matrix)
3 x = np.array([[1, 2, 3], [4, 5, 6], [7, 8, 9]])
4 x*x # element-by-element multiplication (Kronecker
      product)
5 x.shape # return dimensions of matrix
```

# A taste of NumPy: matrices and linear algebra

- Specifying the matrix:

$$\mathbf{x} = \begin{bmatrix} 1 & 2 & 3 \\ 4 & 5 & 6 \\ 7 & 8 & 9 \end{bmatrix}$$

```
1 import numpy as np
2 # 2D array (i.e., a matrix)
3 x = np.array([[1, 2, 3], [4, 5, 6], [7, 8, 9]])
4 x*x # element-by-element multiplication (Kronecker
      # product)
5 x.shape # return dimensions of matrix
6 np.dot(x, x) # matrix multiplication (dot product)
```

# A taste of NumPy: linear algebra

- Calculate eigenvalues and eigenvectors

```
1 import numpy as np
2
3 # declare a 2x2 matrix
4 x = np.array([[1, 2], [3, 4]])
```

# A taste of NumPy: linear algebra

- Calculate eigenvalues and eigenvectors

```
1 import numpy as np
2
3 # declare a 2x2 matrix
4 x = np.array([[1, 2], [3, 4]])
5
6 # calculate eigenvalues
7 eival = np.linalg.eigvals(x) # [-0.37228132
   5.37228132]
```

# A taste of NumPy: linear algebra

- Calculate eigenvalues and eigenvectors

```
1 import numpy as np
2
3 # declare a 2x2 matrix
4 x = np.array([[1, 2], [3, 4]])
5
6 # calculate eigenvalues
7 eival = np.linalg.eigvals(x) # [-0.37228132
    5.37228132]
8
9 # calculate eigenvalues and right eigenvectors
10 eival, eivec = np.linalg.eig(x)
11 # eigenvalues (eival):
12 # [-0.37228132  5.37228132]
13 # [-0.37228132  5.37228132]
14 #
15 # eigenvectors (eivec):
16 # [-0.82456484 -0.41597356]
17 # [ 0.56576746 -0.90937671]]
```



# A taste of NumPy

```
1 # Generate random numbers
2 np.random.rand() # from a uniform distribution
3 np.random.randn() # from a normal distribution
4 np.random.randn(5, 5) # 5 x 5 matrix of random numbers
5
6 # Create number sequences
7 np.arange(0, 1, 0.1) # 0 to 1 (but not including 1) in steps
   of 0.1
8 np.linspace(0, 1, 100) # 100 values between 0 and 1
9 np.logspace(0, 1, 10) # 10 values between 100 and 101
```

# A taste of SciPy

```
1 import scipy.stats as sp
2
3 # Create two random arrays
4 x1 = np.random.randn(30)
5 x2 = np.random.randn(30)
6
7 # Correlation coefficientss
8 sp.pearsonr(x1, x2) # pearson correlation
9 sp.spearmanr(x1, x2) # spearman correlation
10 sp.kendalltau(x1, x2) # kendall correlation
11
12 # Statistical tests
13 sp.ttest_ind(x1, x2) # independent t-test
14 sp.mannwhitneyu(x1, x2) # Mann-Whitney rank test
15 sp.wilcoxon(x1, x2) # Wilcoxon signed-rank test
16
17 # Least-squares regression
18 sp.linregress(x1, x2)
```

# Predator prey equations (Lotka Volterra)

$$\frac{du}{dt} = \alpha u - \beta uv$$

$$\frac{dv}{dt} = -\gamma v + \delta uv$$

Where:

- $u$ : is the number of prey (e.g rabbits)
- $v$ : is the number of predators (e.g foxes)
- $\alpha$ : prey growth rate in the absence of predators
- $\beta$ : dying rate of prey due to predation
- $\gamma$ : dying rate of predators in the absence of prey
- $\delta$ : predator growth rate when consuming prey

# Predator prey equations in Python

$$\frac{du}{dt} = \alpha u - \beta uv$$

$$\frac{dv}{dt} = -\gamma v + \delta uv$$

```
1 def predator_prey(x, t):
2     """
3     Predator prey model (Lotka Volterra)
4     """
5     # Constants
6     alpha = 1
7     beta = 0.1
8     gamma = 1.5
9     delta = 0.075
10
11     # x = [u, v] describes prey and predator populations
12     u, v = x
13
14     # Define differential equation (u = x[0], v = x[1])
15     du = alpha*u - beta*u*v
16     dv = -gamma*v + delta*u*v
17
18     return du, dv
```

# Solve differential equations

```
1 from scipy.integrate import odeint
2
3 time = np.linspace(0, 35, 1000) # time vector
4 init = [10, 5] # initial condition: 10 prey, 5 predators
5 x = odeint(predator_prey, init, time) # solve
```

# Solve differential equations

```
1 from scipy.integrate import odeint
2
3 time = np.linspace(0, 35, 1000) # time vector
4 init = [10, 5] # initial condition: 10 prey, 5 predators
5 x = odeint(predator_prey, init, time) # solve
6 # returns 2-dimensional np.array():
7 # [[10.          5.          ]
8 #  [10.17902694  4.87146722]
9 #  [10.36582394  4.74852012]
10 #  ...
11 #  [36.19731528  5.37939637]
12 #  [36.77291203  5.61756101]
13 #  [37.32525798  5.87497465]]
```

# Solve differential equations

```
1 from scipy.integrate import odeint
2
3 time = np.linspace(0, 35, 1000) # time vector
4 init = [10, 5] # initial condition: 10 prey, 5 predators
5 x = odeint(predator_prey, init, time) # solve
6 # returns 2-dimensional np.array():
7 # [[10.          5.          ]
8 #  [10.17902694   4.87146722]
9 #  [10.36582394   4.74852012]
10 #  ...
11 #  [36.19731528   5.37939637]
12 #  [36.77291203   5.61756101]
13 #  [37.32525798   5.87497465]]
14
15 # open a matplotlib figure
16 import matplotlib.pyplot as plt
```

# Solve differential equations

```
1 from scipy.integrate import odeint
2
3 time = np.linspace(0, 35, 1000) # time vector
4 init = [10, 5] # initial condition: 10 prey, 5 predators
5 x = odeint(predator_prey, init, time) # solve
6 # returns 2-dimensional np.array():
7 # [[10.          5.          ]
8 #  [10.17902694   4.87146722]
9 #  [10.36582394   4.74852012]
10 #  ...
11 #  [36.19731528   5.37939637]
12 #  [36.77291203   5.61756101]
13 #  [37.32525798   5.87497465]]
14
15 # open a matplotlib figure
16 import matplotlib.pyplot as plt
17
18 fig = plt.figure()
```




# Solve differential equations

```
1 from scipy.integrate import odeint
2
3 time = np.linspace(0, 35, 1000) # time vector
4 init = [10, 5] # initial condition: 10 prey, 5 predators
5 x = odeint(predator_prey, init, time) # solve
6 # returns 2-dimensional np.array():
7 # [[10.          5.          ]
8 #  [10.17902694   4.87146722]
9 #  [10.36582394   4.74852012]
10 #  ...
11 #  [36.19731528   5.37939637]
12 #  [36.77291203   5.61756101]
13 #  [37.32525798   5.87497465]]
14
15 # open a matplotlib figure
16 import matplotlib.pyplot as plt
17
18 fig = plt.figure()
19 plt.plot(time, x[:,0], "r", time, x[:,1], "b")
```

# Solve differential equations

```
1 from scipy.integrate import odeint
2
3 time = np.linspace(0, 35, 1000) # time vector
4 init = [10, 5] # initial condition: 10 prey, 5 predators
5 x = odeint(predator_prey, init, time) # solve
6 # returns 2-dimensional np.array():
7 # [[10.          5.          ]
8 #  [10.17902694  4.87146722]
9 #  [10.36582394  4.74852012]
10 #  ...
11 #  [36.19731528  5.37939637]
12 #  [36.77291203  5.61756101]
13 #  [37.32525798  5.87497465]]
14
15 # open a matplotlib figure
16 import matplotlib.pyplot as plt
17
18 fig = plt.figure()
19 plt.plot(time, x[:,0], "r", time, x[:,1], "b")
20 plt.xlabel("Time")
21 plt.ylabel("Population size of predator and prey")
22 fig.savefig("graph.pdf")
```

# Solve differential equations: resulting graph



# Fourier transform

```
1 from scipy.fftpack import fftfreq, fft
2
3 # Create frequency vector
4 N = len(time)
5 freq = fftfreq(N, np.mean(np.diff(time)))
6 freq = freq[range(int(N/2))]
7
8 # Compute Fast Fourier Transform
9 y = fft(x[:, 0])/N # compute and normalise fft
10 y = y[range(int(N/2))] # keep only positive frequencies
```

# Fourier transform

