

Special class Test (21-02-2026) BRAMMANAYAGAN-S

① `==` compares value / `5 == "5" → True`

`===` compares value & data type

`5 === "5" → False` (mostly used in web dev)

② `var` → can be Redeclared, re-assigned, hoisted, functional scope

`let` → cannot be re-declared, ^{can be} re-assigned, TDZ, block scope

`const` → cannot be re-declared, re-assigned, TDZ, block scope (constant values used in web dev)

③ Storing, `var` key's variable name, while function and `let`, `const` → variable name in TDZ, storing these in top of the scope is known as hoisting

④ `map()` is array method used to change every value in an array eg: `arr.map(m) ⇒ m * 2`
this multiply every element in arr with 2

⑤ `null` → explicit (given by developer/us)
`Undefined` → implicit (return by computer)

⑥ Spread operator used to spread array like `(...)` three dot notation used and every element in array is spreaded mostly used like
eg: `[...arr1, 2, 7, 9]`

10) Function declaration → Traditional method

```
function add () {  
    return/consde.log()  
}
```

add() → but function declaration is fully hoisted and when we call add() before function in line of execution too it works because the function is fully hoisted in top of the scope

Function Expression → Modern ES6 method

```
const add = function () { } }
```

not fully hoisted in top of the scope

12) Truthy and falsy

[]
all other
than falsy
are
Truthy

0
undefined
null
NaN
""

false &
True values

11) Diff Arrow

- * return not used
- * Sometimes `{ }` not needed
- * Modern/Smart function

Normal function

- * `return/console.log()` must used
 - * `{ }` must
 - * Traditional
-