

Haven PMC API

Version 1.0.0 · OpenAPI 3.1.1

The Haven Property Management Company (PMC) API exposes a firm's leasing conversations, receptionist calls, and aggregate metrics. Authenticate every request with the per-firm API key issued by Haven, sent as a bearer token.

Base URL

`https://pmc.tools.usehaven.ai`

Production

Authentication

Per-firm API key issued by Haven (format `hav_<env>_<key>`). Send as `Authorization: Bearer <key>`.

`Authorization: Bearer <your-api-key>`

Conventions

- **Format.** All requests and responses use JSON. Timestamps are ISO 8601 date-time strings (UTC).
- **Pagination.** List endpoints accept `limit` (max 100) and `cursor` query parameters. When more results exist, the response includes a `nextCursor`; pass it back as `cursor` to fetch the next page. A null `nextCursor` means the last page.
- **Nullable fields.** Fields marked *nullable* may return `null` when no value is available.

Scope: What You Can and Can't Do

What you can do

- Retrieve your firm's leasing conversations: prospect contact details, property of interest, lead source, tour status, and pipeline phase.
- Pull the full event history for any conversation, including call summaries and recordingUrl links.
- List receptionist calls with outcomes, transfer destinations, durations, summaries, and escalation flags.
- Read call recordings and follow-up message content for quality review.
- Get aggregate receptionist metrics for any date range: total calls, AI-handled, transfers, AI resolution rate, and knowledge-gap count.
- Sync any of this into your own CRM, dashboard, or reporting tools, paging through results with limit and cursor.

What this API can't do

- Change anything. The API is read-only (every endpoint is a GET); you cannot create, edit, or delete records.
- Send messages, schedule tours, or take actions on a prospect's behalf.
- Configure, retrain, or change the behavior of the AI Workers.
- Receive real-time push or webhooks. You poll for new data; there is no event subscription in this version.
- Access another firm's data. Your API key is scoped to your firm only.
- Reach data outside these endpoints (billing, owner, resident-portal, and maintenance records are not exposed here).

Endpoints

GET /v1/leasing/conversations

List the firm's leasing conversations

Operation ID: leasing.list

Parameters

Parameter	In	Type	Required
limit	query	integer	No
cursor	query	string	No

Response 200 — conversations[] item

Field	Type	Required
conversationId	string	Yes
prospectId	string	Yes
firmId	string	Yes
firstName	string · nullable	No
lastName	string · nullable	No
email	string · nullable	Yes
phoneNumber	string · nullable	Yes
leadSource	string · nullable	Yes

Field	Type	Required
propertyOfInterestPath	string · nullable	Yes
propertyAddress	string · nullable	Yes
propertyType	string · nullable	Yes
callSummary	string · nullable	Yes
smsThread	string[]	Yes
emailThread	string[]	Yes
lastActiveAt	date-time	Yes
lastChannelUsed	string · nullable	Yes
tourScheduled	boolean	Yes
scheduledTourStartTime	date-time · nullable	Yes
scheduledTourEndTime	date-time · nullable	Yes
tourTimezone	string · nullable	Yes
tourStatus	string · nullable	Yes
assignedLeasingAgent	string · nullable	Yes
recentTourHistory	string[]	Yes
leadClassification	string · nullable	Yes
pipelinePhase	string · nullable	Yes
handledBy	string · nullable	Yes
firstContactAt	date-time	Yes
lastActivityAt	date-time	Yes
escalationFlag	boolean	Yes
flagType	string · nullable	Yes
flagDate	date-time · nullable	Yes
flagResolved	boolean · nullable	No
pendingFollowUp	boolean	Yes

GET`/v1/leasing/conversations/{conversationId}/history`

Get one leasing conversation history

Operation ID: `leasing.history`

Parameters

Parameter	In	Type	Required
<code>conversationId</code>	path	string	Yes

Response 200 — `events[]` item

Field	Type	Required
<code>id</code>	string	Yes
<code>type</code>	string	Yes
<code>channel</code>	string · nullable	Yes
<code>createdAt</code>	date-time	Yes
<code>content</code>	string · nullable	Yes
<code>summary</code>	string · nullable	Yes
<code>recordingUrl</code>	string · nullable	Yes

GET`/v1/receptionist/calls`

List the firm's receptionist calls

Operation ID: `receptionist.listCalls`

Parameters

Parameter	In	Type	Required
<code>limit</code>	query	integer	No
<code>cursor</code>	query	string	No

Response 200 — `calls[]` item

Field	Type	Required
<code>callId</code>	string	Yes
<code>callDateTime</code>	date-time	Yes
<code>callerPhone</code>	string · nullable	Yes
<code>callerName</code>	string · nullable	Yes
<code>marketLocation</code>	string · nullable	No
<code>callOutcome</code>	string · nullable	Yes

Field	Type	Required
transferDestination	string · nullable	Yes
callDurationSec	number · nullable	No
timeToAnswerSec	number · nullable	No
callSummary	string · nullable	Yes
callRecordingUrl	string · nullable	Yes
callTopic	string · nullable	No
propertyReferenced	string · nullable	Yes
policyQuestionFlag	boolean	Yes
smsFollowUpSent	boolean	Yes
followUpMessageContent	string · nullable	Yes
escalationFlag	boolean	Yes
escalationReason	string · nullable	No
linkedLeasingConversationId	string · nullable	Yes
conversationId	string	Yes
firmId	string	Yes

GET

/v1/metrics

Get the firm's period-windowed receptionist metrics

Operation ID: metrics.get

Parameters

Parameter	In	Type	Required
periodStart	query	date-time	Yes
periodEnd	query	date-time	Yes

Response 200 — metrics

Field	Type	Required
firmId	string	Yes
periodStart	date-time	Yes
periodEnd	date-time	Yes
totalCalls	number	Yes
callsHandledByAi	number	Yes

Field	Type	Required
callsTransferred	number	Yes
callsAbandoned	number · nullable	No
aiResolutionRate	number · nullable	Yes
knowledgeGapCount	number	Yes