AKKI · ESTATE · FEATURE & COMPONENT BRIEF

Registry

The surface that answers three questions about the instance: what data you hold, what compute is connected to it, and which models are answering on it. Read-only by design, with one write path — Connect.

Version 7 · prototype reference: Akki Prototype v7.dc.html · Estate group

---

1. Purpose and scope

Registry is the instance's inventory. Everything on it is a measurement taken at the seam, never an estimate, and every figure traces to a census. It answers "what do we actually have?" for three classes of asset — data, compute, and models — and it is the only page in the Estate group that admits new assets into the instance.

In scope: holdings, composition, condition, rights class, extraction progress, cluster capacity and utilisation, GPU workflow status, connected LLMs and locally trained models, acceptance state, spend and call volumes, and the connection journey for anything new.

Out of scope: rule-making and enforcement (Govern), watch and security posture (Grey Mirror, The Watch), model training runs and agent construction (Build), and anything that changes a rule. Registry reports; it does not govern.

2. The page pattern

Every Registry tab uses one structure, and this structure is now the house pattern for comparable pages elsewhere in the product:

LEFT COLUMN (FLUID) → RIGHT COLUMN (300PX)

Topline: section title, one-liner, 3×3 stat grid → Headliner panel (editorial deck)

— full-width divider —

Visual: section title, dataset dropdown, one-liner, bar chart → Context panel

— full-width divider —

Table: section title, filter chips, one-liner, table, "view the full record" → Context panel

Rules that hold across every instance of the pattern:

- The right column always speaks to the block beside it, and is vertically centred against that block so the relationship reads without a label.
- The headliner sits on the same plane as the topline, in the same shape and type treatment on every page.

- Every section title carries a one-line introduction to the thing below it.
- Dividers cut the full width, across both columns, so sections read as bands rather than stacked cards.
- Unmeasured shares are drawn with the same weight as measured ones — hatched, labelled "not yet measured", never omitted.

3. Tabs

3.1 Data Connected

The estate as last read by the census.

- **Topline (9):** held in total, sources connected, share measured, data types present, languages observed, share already verified, share carrying PII, licensed for external use, not yet measured.
- **Headliner:** holdings sentence with measured figures ruled and one editorial phrase in crimson; census provenance line with run time and a link to how the estate is measured.
- **Visual:** composition by language / data type / rights class / condition.
- **Table:** source, size, rights pill, extracted %, with a meta line carrying type, languages, condition and measurement date.
- **Right panels:** "Reading the mix" beside the chart; "What your data can do" — the opportunity list — beside the table.

3.2 Compute Connected

What hardware is attached and what it is carrying.

- **Topline (9):** clusters attached, GPUs, capacity this month, committed to work, free to allocate, jobs waiting, workflows this month, utilisation, runs receipted.
- **Visual:** hours by door / by week / by state.
- **Table:** GPU workflows — workflow, door, allocation, status pill, progress — filtered All / Ongoing / Complete / Failed, five rows, with a narrative that changes per filter.
- **Right panels:** headliner beside the topline; "Reading the load" beside the chart; "The connection" — attachment date, location, interconnect, access, runtime, last measured — beside the workflow table, because that is the table it explains.

3.3 LLMs & Trained Models

Bought-in models and models trained here, on one record.

- **Topline (9):** models connected, calls this month, refused at the shield, median answer time, spend, context masked, acceptance checks, models retired, drift testing (not yet measured).
- **Visual:** calls by model / spend by model / refusals by reason.

- **Table:** model, origin (bought-in vs trained here), calls, status pill (in service / evaluating / retired), share; filters All / In service / Evaluating / Retired. Retired models keep their row.
- **Right panels:** headliner; "Reading the mix"; "How a model enters, and leaves" — six acceptance checks, re-run on a cadence, failure removes it the same day.

4. Components

COMPONENT	BEHAVIOUR AND RULES
Tab bar	Three uppercase tabs, 2px active underline, with the *+ Connect* button pushed right on the same plane. Tab state resets its tab's chart and filter selections.
Stat grid	Always 3×3. Each cell: uppercase label, serif value, one-line note. Any unmeasurable cell reads "Not yet measured" rather than being dropped.
Headliner panel	24px serif deck, vertically centred against the stat grid. Measured figures get a thin neutral rule; exactly one editorial phrase per deck is crimson. Sub-line carries provenance.
Chart block	Horizontal bars: label, track, value. Dataset switched by a native select. Hatched fill for unmeasured. Caption states the denominator.
Filter chips	One row, right-aligned to the section title. Active chip is navy. Filtering also swaps the narrative line under the table.
Record table	Four or five columns maximum plus a meta line per row, so the table survives the narrowed column. Capped at five rows with a "view the full record" link.
Context panel	Uppercase title, 2–3 sentences of interpretation, optionally a short list. Never repeats the sentence already on screen; it says what the numbers mean.
Announcement row	A newly connected asset appears at the top of its tab's table with a sage "Just connected" pill and the meta "not yet measured".

5. Connect — the one write path

A right-hand drawer holding a conversation, not a form. Akki asks; the operator answers in their own words or taps a suggestion chip. The drawer assumes no universal shape: the questions branch on what is being connected, and the outcome is not assumed to succeed.

1. **What:** a data source, an LLM, a trained model, or compute. Free text is interpreted; an unreadable answer is asked again rather than guessed.

2. **How:** methods differ by kind — private link, on-premise mount, scheduled batch; in-seam hosted, on-premise weights, sandbox only; registry or imported weights; on-premise or co-located cluster.
3. **Credentials:** issued by the operator, or minted by Akki and recorded against whoever takes them.
4. **Name:** nothing connects unnamed.
5. **Attempt:** a summary, then a real attempt.

Failure is a first-class outcome. A failed attempt shows the handshake step by step — route, TLS, credentials, read — with the failing step in crimson and the untried step greyed, and states plainly that nothing crossed and nothing was written. The conversation continues: retry as-is, change the credentials arrangement, switch the method, or ask for the handshake log. Attempts are numbered.

Success ends the conversation: "Connection successful", the asset is announced in its tab, the drawer offers a single Close, and a toast names where it landed. The new asset is unmeasured until the next census and is drawn that way.

6. Content rules

- Sentences first, measures second. Every block leads with a plain sentence; the numbers sit behind it or beneath it.
- No figure without provenance. Each tab states what it was measured against and when.
- Gaps are drawn. "Not yet measured" is a value, never an omission or a zero.
- Refusals and failures are reported as work done, not work lost.
- One emphasis per deck. Everything cannot be important.
- Read-only means read-only: no control on this page changes a rule, and the page says so where it matters.

7. States and edges

- **Empty tab:** a tab with nothing connected still shows its topline with zeroes and an unmeasured note, plus the Connect prompt.
- **Stale census:** when the census is older than its cadence, the provenance line carries the age and the estate figures stay as last measured.
- **Failed workflow:** a run that hits its ceiling halts; nothing past the ceiling is billed and the halt keeps its row.
- **Retired model:** row retained, status greyed, share zero.
- **Role scope:** Registry is visible to the Compliance Owner and Operator. A Watch Officer sees the Watch group instead.
- **Narrow viewport:** nested grids collapse before the content column does; tables reflow to their meta line rather than shrinking type.

8. Open questions

- Should "view the full record" open a full-page record view, or a drawer with the same table unfiltered?
- Does an opportunity in "What your data can do" link into Build, and does that carry the measurement with it?
- Who may run a census, and should Registry expose a "run census" action or leave it to Ceremonies?
- Drift testing is currently unmeasured on the models tab — what would make it measurable, and who owns the cadence?