

SPA Conference 2016

Real-World Big Data in Action

Nick Rozanski
Eoin Woods
Chris Cooper-Bland



Number 2 in an occasional series

Goals of Today

Goals of Today

- Learn why Big Data is important
- Look at some of the techniques and technologies that underpin Big Data implementations
- Install, configure and run some Big Data software (Hadoop, Spark and Hive)
- Do some data science on real Big Data datasets

What Today *Isn't* About

- Detailed explanation of how Big Data works
- Learning how to configure Big Data software in real production environments
- I am not a Big Data technology expert!

Agenda

Agenda

- Introduction to Big Data (15 minutes)
- Exercise 1: Hadoop (60 minutes including setup)
- Exercise 2: Spark (30 minutes)
- Exercise 3: Hive (45 minutes)

Real-World Big Data in Action

Introduction to Big Data

History and Background

The Origins of Big Data

The “Three V’s”

- First proposed by META Group analyst Doug Laney in 2001 (<https://blogs.gartner.com/doug-laney/files/2012/01/ad949-3D-Data-Management-Controlling-Data-Volume-Velocity-and-Variety.pdf>)
- Driven by the (then) looming growth in e-commerce and the strain this would impose on computer systems

Volume

- The increase in depth and breadth of data

Velocity

- The speed at which data needs to be made available for use

Variety

- Problems caused by incompatible data formats, non-aligned data structures and inconsistent data semantics
- Subsequent analysts have added additional V’s such as **Variability** and **Veracity** (data quality)

A Brief (and Partial) History of Big Data

Hadoop

- Doug Cutting and others started working on a web crawler called Nutch in 2002
- This eventually morphed into Hadoop and was adopted by Yahoo! in 2006
- It became a top-level Apache project and was adopted by Last.fm, Facebook and others
- The Yahoo web map comprised 100 billion nodes and 1 trillion edges by 2009
- Hadoop continued to break records for volume and velocity: in 2014, a team from Databricks sorted 100TB of data in 1,406 seconds on 207 nodes (4.27TB per min)
- Facebook is rumoured to manage 100 PB (that's 21 million DVDs, or 70 billion 3.5" floppy disks)
- Hadoop is a made-up name (the name of Doug Cutting's daughter's yellow toy elephant)


Spark

- Started at UC Berkeley's AMPLab in 2009 and open sourced in 2010
- A Top-Level Apache Project since 2014
- Now used at many organisations (<https://cwiki.apache.org/confluence/display/SPARK/Powered+By+Spark>)

Hive

- Originally developed at Facebook around 2007-8
- Now used at Netflix, FINRA (UK regulator), CNET, Digg, eHarmony, [last.fm](https://cwiki.apache.org/confluence/display/Hive/PoweredBy) ...
(<https://cwiki.apache.org/confluence/display/Hive/PoweredBy>)

Today's Big Data Landscape



All Big Data tools are required by EU Law to have ridiculous names

- Sqoop (data integration)
- Oozie (workflow)
- Pig (scripting)
- Impala (MPP SQL query engine)
- Flume (data ingestion)
- Parquet (columnar storage)
- ZooKeeper (distributed application management)

A Simple Big Data Stack

Hive

- scaleable data warehousing infrastructure providing a SQL abstraction on top of Spark and Hadoop

scalable warehousing
relational abstraction




Spark

- scaleable in-memory cluster computing framework with implicit data parallelism and fault-tolerance

scalable in-memory computation
streaming execution



cheap compute power



cheap storage

Hadoop

- provides massively scalable file management and batch execution on a commodity hardware platform

scalable storage
batch execution



The MapReduce Paradigm

MapReduce


- Paper published by Google in 2004 (<http://research.google.com/archive/mapreduce.html>)
- Describes how they rewrote their production indexing system using MapReduce
- Provides automatic parallelization and distribution, fault-tolerance, I/O scheduling and status monitoring

Map Reduce Steps

- *Map step*: master breaks up query and distributes portions across a massive number of computers
- *Reduce step*: results collated and returned to requestor

Benchmark

- scan 10 billion 100-byte records to extract records matching a rare pattern (92K matching records); once started up 1800 machines read 1 TB of data at peak of ~31 GB/s



Real-World Big Data in Action

Hadoop

A Big Data Virtual
Filesystem



Hadoop Overview

YARN (Yet Another Resource Negotiator)

- YARN is the new cluster resource management system introduced in Hadoop v2
- it includes the following components:

Resource Manager

- orchestrates the division of resources to NodeManagers

NameNode

- provides metadata services

NodeManagers

- monitor and launch containers

ApplicationMaster


- manages an instance of an application

DataNodes

- provide replicated storage services across the cluster

Containers

- runs an application on a node



<https://www.ibm.com/developerworks/library/bd-hadoopyarn/>

HDFS (Hadoop Distributed Filesystem)

- distributed, scalable, and portable file-system for Hadoop
- stores large files (gigabytes to terabytes or more) across multiple machines using commodity hardware
- achieves reliability by replicating the data across multiple hosts
- presents a POSIX-like filesystem API

Exercise 1: Hadoop

Goals of This Exercise

1. Install the Big Data software (Hadoop, Spark and Hive)
2. Configure the Big Data software
3. Start Hadoop and check it is running
4. Format the Hadoop filesystem
5. Load a file into Hadoop
6. Browse the Hadoop filesystem


Real-World Big Data in Action

Spark

A Big Data Cluster
Computing Framework



Spark Overview



<https://spark.apache.org/docs/latest/cluster-overview.html>

- Spark has a master / slave architecture in which a *Driver* on the Spark Master communicates with a large number of *Executors* on Spark Workers (aka slaves)
- The Driver and Executors are together termed a *Spark application*
- Spark primitives support in-memory computing which can bring performance advantages over Hadoop for some workloads

Spark Applications

- Spark applications run as independent sets of processes on a cluster, coordinated by a `SparkContext` object in the main program
- the `SparkContext` connects to a cluster manager such as YARN
- Spark acquires *executors* on cluster (processes that run computations and store data for your application)
- It then sends the application code to the executors
- Finally, the `SparkContext` sends tasks to the executors to run

RDDs and Data Frames

RDDs

- The central data abstraction in Spark is the *Resilient Distributed Dataset* (RDD): a fault-tolerant collection of objects that is partitioned across multiple nodes in a cluster and can be operated on in parallel
- A Spark program typically has the following structure:
 - load one or more RDDs from an external source, such as Hadoop
 - performs one or more transformations on the RDDs
 - perform one or more actions on the resulting RDDs (such as computing a result or saving to persistent storage)

DataFrames

- A DataFrame is a distributed collection of data organized into named columns
- It is conceptually equivalent to a table in a relational database
- A program can access a DataFrame programmatically, or using Spark SQL / Hive SQL
- DataFrames claim to offer:
 - The ability to scale from kilobytes of data on a single laptop to petabytes on a large cluster
 - Support for a wide array of data formats and storage systems
 - State-of-the-art optimization and code generation through the Spark SQL Catalyst optimizer
 - Seamless integration with all big data tooling and infrastructure via Spark
 - APIs for Python, Java, Scala, and R
- (see <https://databricks.com/blog/2015/02/17/introducing-dataframes-in-spark-for-large-scale-data-science.html>)

Spark Programming

YADA

- yada



TO DO

Exercise 2: Spark

Goals of This Exercise

1. Start Hadoop and Spark and check they are running
2. Start the Spark client
3. Load the Hadoop file into a Spark RDD
4. Do some data science!

Real-World Big Data in Action

Hive


A Big Data data warehousing
infrastructure



Hive Overview

Hive Capabilities

- Performs query analysis of large datasets stored in HDFS
- Driven by a SQL-like language called HiveQL
- Supports indexing to accelerate queries
- Based on schema on read (when query issued)
- Some update support (concurrency, locking, transactionality etc.) but not designed for online processing
- Incorporates a cost-base optimiser called Apache Calcite



<https://cwiki.apache.org/confluence/display/Hive/Design>

Hive Architecture

- Hive transparently converts queries to MapReduce, Spark or Tez jobs
- Hive usually moves data into its repository in HDFS (managed tables)
- External tables leave data in place (we will use these today for simplicity)
- Hive metadata is stored in a repository called the *metastore*
 - For this session we will use Apache Derby (a small-footprint embedded RDBMS)
 - In production you would typically use MySQL

Exercise 3: Hive

Goals of This Exercise

1. Start Hadoop, Spark and Hive and check they are running
2. Start the Hive client
3. Create an external Hive table from a Hadoop file
4. Do some data science!

Real-World Big Data in Action

Next Steps

Bigger Big Data
Other Big Data Tools

Next Steps

- Multiple slaves
- Cloudera VM
- Other Big Data tools
- Spark machine learning
- Spark graphical analysis



TO DO

Real-World Big Data in Action

Appendix

Further Information

Useful Links

Hadoop FAQ

- <http://wiki.apache.org/hadoop/FAQ>

Hadoop Filesystem commands Reference

- <http://hadoop.apache.org/docs/current/hadoop-project-dist/hadoop-common/FileSystemShell.html>

Set Up Hadoop Cluster

- https://hadoop.apache.org/docs/r2.7.2/hadoop-project-dist/hadoop-common/SingleCluster.html#Prepare_to_Start_the_Cluster

Pyspark sqlContext Reference

- <https://spark.apache.org/docs/latest/api/python/#pyspark.sql.DataFrame>

Hive SQL Reference

- <https://cwiki.apache.org/confluence/display/Hive/LanguageManual+DDL>
- <https://cwiki.apache.org/confluence/display/Hive/LanguageManual+DML>

TO DO