



2026

ALTIGO · VERTICAL MOBILITY

PRODUCT CATALOGUE

ESCALATOR

COMPANY

ALTIGO SDN. BHD.
REG. 562238-H

CONTACT

+604-283 7005
+604-283 6772

DIGITAL

WWW.AKKALLIANCE.COM
ALTIGOELEVATOR@GMAIL.COM

THE CATALOGUE

CONTENTS



01	Company Introduction	Who we are	03	07	Safety & Detection Devices	Protection	09
02	Intelligent Control & Comfort	Technology	04	08	Planning & Civil	The chapter	10
03	Technical Advantages	Engineering	05	09	Logical Positioning, by Traffic	Planning guide	11
04	Four Platforms, One Structure	The range	06	10	Construction Parameters	Civil	12
05	Standard & Optional Parts	Components	07	11	Contact Us	Altigo Sdn. Bhd.	13
06	Comprehensive Safety Guarantee	Safety	08				

THE COMPANY

COMPANY INTRODUCTION



Moving people, elevating places.

Imagine stepping into a building where every ride is smooth, every moment effortless and every floor easily reached. At **Altigo** we believe transport should never be merely a means to an end — it should be an experience that elevates the day and simplifies the journey.

Altigo is more than an elevator and escalator supplier. We are a partner in modern vertical mobility, combining advanced drive technology, exacting craftsmanship and a firm commitment to safety and sustainability, so our products meet the demands of fast-paced urban life.

Welcome to Altigo, where innovation meets reliability. Residential, commercial or industrial — we deliver solutions that transform spaces and elevate lives. Trust us to move you forward, every day, with ease and confidence.

Innovation


VVVF drives, IoT monitoring and energy regeneration built in.

Reliability

Engineered and tested for smooth, quiet, dependable everyday service.

Sustainability

Lower running energy and a longer service life across the range.



ALTIGO · VERTICAL MOBILITY

TECHNOLOGY · HUMAN-CENTRED

INTELLIGENT CONTROL & COMFORT



Built around human-centred design and refined through exhaustive testing, so every ride feels **safe, stable and effortless**.

01



High-performance control system

A modular, compact and integrated controller runs more steadily and pushes energy saving to its peak. CPU + DSP redundant architecture with built-in lightning protection guarantees reliability, and the system is fully EMC compliant.

CPU + DSP · EMC COMPLIANT

02

Energy saving & regeneration

By sensing passenger flow the escalator adjusts its speed curve to save energy across the whole travel. VLR technology monitors the drive's DC busbar voltage and feeds regenerated energy back to the grid.

VLR REGENERATION



03

Convenient remote monitoring

An RS485 / BAS interface links the escalator to your building management system for real-time fault reporting — convenient for maintenance and ready for intelligent building control.

RS485 / BAS



STEP 01

Sense

Entry sensors read passenger flow at both landings, continuously.

STEP 02

Adapt

The VVVF drive reshapes the speed curve to match demand across the travel.

STEP 03

Recover

VLR returns braking energy to the building grid instead of burning it as heat.

STEP 04

Report

Status and fault codes reach the BMS over RS485 / BAS in real time.

TECHNICAL ADVANTAGES

Environmental protection sits at the centre of our engineering: a new **integrated converter and micro-computer control board** that saves space while raising drive efficiency.

01



Multiple safety protection

Safety devices are fitted at every component of the escalator. Rigorous device testing and powerful fault diagnosis in the control system raise overall safety performance across the whole travel.

10 STANDARD DEVICES

02



Comfortable ride feeling

An escalator-specific VVVF drive with new-generation AC vector and voltage-regulator speed control delivers smooth acceleration and deceleration, for a more stable and comfortable ride.

VVVF · AC VECTOR

03



High-performance traction machine

The ET125 / ET160 ZC-toothed reducer is high-torque, compact, low-noise and steady. The CG26 worm-helical reducer combines worm and helical gearing for very high efficiency.

ET125 / ET160 · CG26

< 57_{dB}

Running noise,
commercial platform

> 92%

CG26 worm-helical
reducer efficiency

0.5_{m/s}

Rated travel speed
across the range

11–37_{kW}

Drive power band,
by duty class

30° / 35°

Inclination angle,
project dependent

THE RANGE

FOUR PLATFORMS, ONE STRUCTURE.



Every Altigo unit shares one **integrated structure**. Choose the duty class by where it lives — a boutique mall, a metro concourse, an airport pier — and how hard it has to work.

DUTY CLASS 01

Commercial

Malls, hotels and offices. Smooth ZC-toothed drive, under 57 dB.

DUTY CLASS 02

Public Transport

Stations and transit hubs. Double-drive option for busier runs.

DUTY CLASS 03

Heavy Duty

Airports and high-footfall transit. CG26 drive above 92% efficiency.

DUTY CLASS 04

Moving Walk

Level and gentle-incline conveyors for concourses and retail.

MAX RISE

6_m

0 22 m

Series	HD-B
Angle	30° / 35°
Speed	0.5 M/S

MAX RISE

12_m

0 22 m

Series	HD-G
Angle	30°
Drive	SINGLE / DUAL

MAX RISE

22_m

0 22 m

Series	MR · TRACTION 2:1
Angle	30°
Power	11-37 KW

MAX RISE

7.5_m

0 22 m

Series	MR · TRACTION 2:1
Angle	10° / 12°
Pallet	800 / 1000 MM

Energy regeneration

VLR feeds braking energy back to the grid; speed adapts to passenger flow.

Multiple safety

Devices at every component, with strong fault diagnosis built in.

Remote monitored

RS485 / BAS link for real-time fault and maintenance data.

CPU + DSP control

Redundant control, full EMC compliance, compact integrated cabinet.

INTEGRATED STRUCTURE

STANDARD & OPTIONAL PARTS



An escalator's function need not scale with its complexity. Our integrated structure keeps the equipment precise and efficient, and makes installation and commissioning simpler and faster.

PART	STANDARD CONFIGURATION	OPTIONAL CONFIGURATION
Balustrade	Transparent glass	Inclined stainless steel
Landing board	Stainless steel series	Aluminium series
Step	Stainless steel series	Aluminium series
Pallets	Stainless steel series	Aluminium series
Handrail colour	Black	Brown Red Green Blue
Traction machine	Worm gear drive	Worm helical gear drive

NOTE — step and pallet width, handrail and balustrade type are selected per project. Aluminium series and inclined stainless steel balustrade are available as options across the whole duty range.




YOUR TRAFFIC SAFETY

COMPREHENSIVE SAFETY GUARANTEE



From children to the elderly, a broad set of safety features helps **every passenger** get on and off safely.

Numbers 1–8 mark where each feature sits on the unit.



1 Emergency Stop Button

Stops the escalator immediately and prevents a more severe incident.

2 Direction Indicator Light

Running direction and restriction signs at the handrail entry guide passengers.

3 Skirt Panel Brush

Prevents clothing being caught between skirt panel and step edge.

4 Step Boundary Lights

Green fluorescence at the step edges helps passengers read step level.

5 Handrail Lighting

Set into the handrail support: soft light adds beauty to a running escalator.

6 Skirt Panel Lights

Elegant lighting highlights the escalator and creates a safer, calmer ride.

7 Newel

The newel frame angle is 20°, reducing the risk of children or items being caught.

8 Anti-slip Step

Grooved steps improve anti-slip performance and visibility for greater safety.

SAFETY & DETECTION DEVICES

Standard devices

10 FITTED

- 01 Skirt brush & guard
- 02 Comb plate guard
- 03 Handrail entry & exit guard
- 04 Emergency stop button
- 05 Speed / overspeed monitor
- 06 Step sag detector
- 07 Step chain break & elongation detector
- 08 Driving chain safety device
- 09 Missing step detector
- 10 Handrail anti-static device

Optional devices

8 AVAILABLE

- 01 Automatic lubrication
- 02 Water level detection
- 03 Truss & comb plate heating
- 04 Auxiliary brake — standard above 6 m rise
- 05 Running indicator
- 06 Stop-on-empty energy mode
- 07 Skirt deflector device
- 08 Anti-reverse protection

Every standard device is proven at the factory and again at commissioning. Trips and fault states are reported through the [RS485 / BAS link](#), so building maintenance sees the cause, not just the stop.



TRUSS · STEP ASSEMBLY

Part Two

PLANNING & CIVIL

Where the unit sits in the building, and the openings it needs.

1400

Exterior truss width, millimetres

1460

Minimum well width, millimetres

30°

Standard inclination across the range

10 Logical positioning, by traffic

11 Construction parameters

12 Contact

ALTiGO

ALTIGO · VERTICAL MOBILITY

LOGICAL POSITIONING, BY TRAFFIC



Arrangement follows the building — traffic volume, flow direction and footprint. **Five layouts** cover most cases, from a single run linking two levels to crisscross banks that move crowds through several floors at once.

ONE-WAY

Single unit

Links two levels. Best where traffic runs mainly one way; reversible by time of day.



ONE-WAY

Continuous

Stacked runs, same direction, no detour. Links three sales levels; needs more space.



ONE-WAY

Interrupted

Offset runs force a short walk between levels, leading shoppers past displays.



TWO-WAY

Parallel

Up and down side by side. For heavy two-way flow; economical with three or more units.



TWO-WAY

Crisscross


Compact X-banks for large stores and transit; minimises travel time between levels.




CONSTRUCTION PARAMETERS




ESCALATOR ELEVATION & CIVIL ENVELOPE



CROSS-SECTION · WIDTHS



PLAN · LANDING & SUPPORTS



DIMENSION KEY

A	Step / pallet width	600 · 800 · 1000
B	Handrail centre distance	1038
C	Exterior truss width	1400
D	Minimum well width	1460
H	Rise, floor to floor	per project
L	Overall length / support span	per project
θ	Inclination angle	30° · 35°
P	Pit depth, lower landing	1100
R	Support reactions, upper & lower	R1 · R2

All dimensions in millimetres. 30° is standard across the range; 35° is available on the HD-B commercial platform. Moving walks run at 10° / 12°.

Figures are indicative. Final civil openings, support reactions and pit depths are issued per project with the approved shop drawings.



CONTACT US

COMPANY

ALTIGO SDN. BHD.

REG. 562238-H

WEBSITE

WWW.AKKALLIANCE.COM

EMAIL

ALTIGOELEVATOR@GMAIL.COM

PHONE

+604-283 7005 / +604-283 6772

ADDRESS

**NO. 54-3-3, WISMA SRI MATA,
JALAN VAN PRAAGH, 11600 PENANG, MALAYSIA**