LEAN-ING ON QUALITY: HOW HIGH-QUALITY DATA BEATS DIVERSE MULTILINGUAL DATA IN AUTOFORMALIZATION

Willy Chan, Michael Souliman, Jakob Nordhagen, Brando Miranda, Elyas Obbad
Kai Fronsdal, **Sanmi Koyejo**
{willyc, brando9}@cs.stanford.edu
[1]Department of Computer Science, Stanford University

ABSTRACT

Autoformalization, the translation of informal mathematics into formal Lean, is limited by the scarcity of paired formal-informal data. Backtranslation, in which a model informalizes formal text to create synthetic pairs, is established in machine translation and was applied to autoformalization by ProofNet (distilled backtranslation with GPT-4). We do not claim backtranslation as new. We compare four ways of generating paired data at a small scale: (1) on-the-fly (online) backtranslation, where one model informalizes and then re-formalizes a batch inside the training loop; (2) distilled backtranslation with a six-shot GPT-4 prompt over full Mathlib4 proofs; (3) informalization of each tactic together with the proof state before and after it, a step-level form of supervision related to process reward models; and (4) regular-expression templates. Fine-tuning GPT-2 (124M parameters) on the six-shot GPT-4 data (71,550 tokens) gives a lower evaluation loss on the ProofNet test set than fine-tuning on the MMA dataset (10.9M tokens), and the other methods improve on the pretrained baseline. These results come from one small model, one benchmark and one metric (evaluation loss), and we state what is outside their scope: other formal languages, human-in-the-loop data creation, and larger models (see Limitations). We also report the cost of each generation method, examples of the generated data, and a check of every training set for overlap with ProofNet and MiniF2F.

1 INTRODUCTION

Neural machine translation has been a focal point of research since the early development of machine learning (Dong et al., 2015) (Wu et al., 2016). *Autoformalization* can be viewed as a specialized application of this approach, where the objective is to translate theorems from informal, human-readable markup languages like LaTeX into formal languages such as Lean4 — a programming language specifically designed to encode complex mathematical constructs (de Moura & Ullrich, 2021). In principle, the development of an agent capable of precise autoformalization would significantly reduce the prohibitive costs of manually formalizing proofs. This would have profound implications; such an advancement could render all mathematical knowledge, much of which is presently recorded in natural language, programmable: substantially enhancing the usability of interactive theorem proving systems and accelerating the expansion of human mathematical understanding (Klein et al., 2009).

Autoformalization first gained traction in 2018 when researchers used long short-term memory networks to generate statements in Mizar (Wang et al., 2018). More recently, experiments demonstrated promising results using a naive few-shot learning approach to translate English into Isabelle code (Wu et al., 2022). Historically, researchers have focused on merging automated theorem provers with language models, which often struggle with quantitative reasoning, limiting the types of theorems that can be expressed and solved and reducing the models' effectiveness in complex, real-world scenarios. We study one way of using interactive theorem provers with language models: fine-tuning a model on intermediary proof states from the LeanDojo dataset (Yang et al., 2023), paired with informal descriptions of each tactic, to test whether this step-level signal helps autoformalization.

Step-level supervision of this kind is known from process reward models (Lightman et al., 2023; Uesato et al., 2022); our contribution is to apply it to informalization of Lean tactics and to measure it against other generation methods, not to introduce it.

While LLMs have performed well on benchmarks related to various natural language understanding tasks as evaluated by benchmarks such as MMLU (Hendrycks et al., 2020), they have continued to struggle with tasks that require deeper quantitative reasoning (Lewkowycz et al., 2022). Moreover, while strides have been made in using deep learning for symbolic mathematics (Lample & Charton, 2020), propositional logic (Hahn et al., 2021), and differential systems (Charton et al., 2021), the field of autoformalization and theorem proving has generally not seen proportional advances. This disparity can largely be attributed to two main factors:

1. **Complexity:** Current models exhibit a gap in their ability to translate intricate mathematical concepts from natural language to formal logic.
2. **Scarcity:** The available training data for fine-tuning models in formal languages like Lean is significantly limited. Given the specialized nature of these programming languages, the sum total of formal-math language data is a minuscule fraction of the size of modern LLMs' training datasets. Thus, except for hand-curated benchmarks such as ProofNet (Azerbayev et al., 2023a) and MiniF2F Zheng et al. (2021), there is virtually no paired formal-informal data.

Example of Formal and Informal Statements

Informal: If r is rational ($r \neq 0$) and x is irrational, prove that $r + x$ is irrational.
Formal: theorem exercise_1_1a (x : R) (y : Q) : (irrational x) → irrational (x + y) :=

Informal: In an additive group G, the subtraction of vectors g_1 and g_2 is equal to the subtraction of the group elements g_1 and g_2.
Formal: theorem vsub_eq_sub {G : Type*} [AddGroup G] (gˇ2081 gˇ2082 : G) : gˇ2081 -ˇd65 gˇ2082 = gˇ2081 - gˇ2082 := rfl #align vsub_eq_sub vsub_eq_sub section General variable G : Type* P : Type* [AddGroup G] [T : AddTorsor G P]

Figure 1: **Autoformalization Task Example**. This table compares formal Lean statements with their equivalent informal mathematical statements. The formal statements represent theorems in Lean, while the informal statements convey the theorems in human-readable natural proof language.

We present a new autoformalization dataset, **AI4Math**, which pairs statements from natural language proofs with their corresponding translations in Lean, as shown in Figure 1. Our approach to generating this dataset leverages backtranslation: a method in neural machine translation for creating synthetic training data (Liu et al., 2021). Given a monolingual dataset in the target language, backtranslation proceeds as follows:

1. Utilize a pretrained model to generate translations in the reverse direction, i.e., from the target language to the source language.
2. Assemble a parallel corpus consisting of these synthetic source and ground-truth target pairs.
3. Fine-tune or train on the generated dataset, enabling the model to translate the synthetic source examples back to the target language.

Our dataset, **AI4Math**, serves two primary purposes: first, to train an autoformalizer on individual statement pairs, and second, to fine-tune an LLM on the state of the proof before and after a specific tactic is applied. This approach aims to closely mimic the reasoning process in theorem proving, enhancing the LLM's ability to understand and generate formal proofs.

Our **key contributions** are:

1. A comparison of four generation methods for formal-informal pairs (on-the-fly backtranslation, distilled six-shot full-proof backtranslation, tactic-level informalization with proof

states, and regular-expression templates) under one fine-tuning recipe, with their token counts and estimated API cost (Table 2) and examples of each (Figure 5).

2. Evidence, for GPT-2 (124M) and the ProofNet test set, that a small set of high-quality pairs (348 pairs, 71,550 tokens) reaches a lower evaluation loss than the MMA dataset (84,679 pairs, 10.9M tokens) (Jiang et al., 2023), and that tactic-level pairs with proof states improve on the pretrained baseline with 1,754 tokens.
3. The AI4Math datasets and models, released on Hugging Face, with an overlap check of each training set against ProofNet and MiniF2F (Appendix D).

What is not new. Backtranslation for machine translation is due to Sennrich et al. (2016). Distilled backtranslation for autoformalization, in which GPT-4 informalizes Mathlib statements and a smaller model is fine-tuned on the pairs, was introduced by ProofNet (Azerbayev et al., 2023a), and MMA (Jiang et al., 2023) scaled it to a large multilingual set. Our six-shot full-proof method follows ProofNet's recipe with a different prompt. Supervising individual steps rather than final outcomes is the idea behind process reward models (Lightman et al., 2023; Uesato et al., 2022). What we add is the on-the-fly variant (one model plays both directions inside the training loop, with no teacher), the use of Lean proof states before and after each tactic as the context for informalization, and a controlled comparison of these methods against MMA at small token budgets.

2 Training Data Generation via Backtranslation

Backtranslation has been a pivotal method in neural machine translation (NMT), with its demonstrated utility for enhancing training efficacy in the absence of sufficient labeled data (Poncelas et al., 2018). This technique was further refined in transformer models (Han et al., 2021) and in preliminary experiments involving distilled backtranslation within the domain of autoformalization (Azerbayev et al., 2023a). We chose this methodology because it is one of the most prominent and validated methods for NMT tasks (Liu et al., 2021), and has been shown to be analytically and empirically suitable for neural model training (Jiang et al., 2023).

Our approach is to start with data in formal language (FL) and translate it into informal language (IL). We refer to this process as *informalization*. We compare the following generation methods, each of which we fine-tune on with the same recipe:

- **On-The-Fly Backtranslation:** This strategy for data augmentation utilized a unique backtranslation approach integrated within a custom training loop. Specifically, the training loop itself has four main steps, as outlined in Figure 2: (1) translating a batch of FL examples to IL (2) translating the synthetic IL examples back to FL, using the (synthetic IL, FL) pairs as labeled training data (3) computing the loss of the generated FL translations compared to the original FL examples and (4) backpropogating to update the model weights.

  This method diverged from traditional practices by not employing separate teacher and student models; instead, it trained a single model to simultaneously manage both directions of the translation task. This setup was chosen because it enabled the model to iteratively generate its own training data at each step, and this self-sufficient nature allowed us to avoid the problem of limited labeled data without incurring large API costs.

  The relatively small size of the model used in our experiments, GPT-2 with 124M parameters, suggested that it would not be very effective at generating high-quality synthetic informalizations. Despite this, the on-the-fly backtranslation method led to a significant reduction in evaluation loss after just a few hundred training steps, eventually leading to a substantial improvement compared to the baseline as seen in Table 3. Nevertheless, we eventually reached a performance plateau due to the inherent limitations of the baseline model. Due to resource constraints, we were unable to validate this method with a larger, more capable model such as Llemma-7B (Azerbayev et al., 2023b). We hypothesize that employing a larger pretrained model could yield even more promising results. This method thus serves as a baseline for comparison, and can highlight the potential benefits of using more powerful models in future work.
- **Distilled Backtranslation:** Considering the limitations of our initial approach, we pivoted to a more robust technique known as *distilled backtranslation*. For this method, we utilized




Figure 2: **On-The-Fly Backtranslation Process Graph**. Given the scarcity of pairs of formal and informal mathematics, our solution is to generate artificial informal language (IL) translations from a formal language dataset (FL), then use the (IL, FL) pairs for training. This methodology first uses the LLM to translate from FL to IL, and then translates back to FL. This avoids the problem of lack of paired data by having the model generate training data on the fly to teach itself.

a more powerful pretrained model, GPT-4 (OpenAI, 2023), as the teacher model by feeding it a dataset of FL examples and utilizing it to generate corresponding synthetic IL text, as outlined in Figure 3. We capitalized on the strong in-context learning capabilities of LLMs (Brown et al., 2020) by employing a few-shot prompt that included six labeled examples of FL-to-IL translations. This few-shot amplification approach allowed us to develop a comprehensive labeled dataset for training, rather than generating data on-the-fly. The full technique and prompt can be found in 6, with a formal example in Appendix A.

Specifically, we extracted theorems from the MathLib4 dataset (mathlib Community, 2019) and then used GPT-4, enhanced by few-shot prompting, to informalize each theorem individually. Using regular expressions, we parsed over 100,000 theorems which we could later informalize and fine-tune on. However, due to the relatively high cost of using OpenAI's GPT-4 API, we were only able to informalize a small subset of these proofs as shown in Table 1. Within this scope of distilled backtranslation, we compared several ways of looking at proofs:

1. Our first method, inspired by techniques in Azerbayev et al. (2023a), involves informalizing entire theorems while using the full proof as contextual support in the prompt, generating the theorem statement in natural language. We employed a 6-shot prompt to create a dataset of 348 training pairs for this approach.
2. Our second method focuses on informalizing not only the theorem statement but also each individual tactic within a proof. This approach tests whether detailed explanations of each tactic can enhance the overall understanding of the proof. Utilizing the LeanDojo dataset Yang et al. (2023), which is pre-parsed into distinct tactics, our prompts included the formal theorem statement and the states of the proof both before and after each tactic is applied. We employed a zero-shot prompting strategy with tuples of (stateBefore, tactic, stateAfter) to generate a dataset of individually translated tactics, aiming to improve translations between the complete Lean theorem and its natural language counterpart.

- **Gathering Data from Regular Expressions:** We also prepared a large dataset leveraging only regular expressions for capturing specific lines/keywords in tactic scripts. Utilizing regular expressions for parsing LeanDojo proof tactics allowed us precise control over the selection of specific tactic lines and proof methodologies, enabling targeted improvements for specific areas of interest. An example of one of the filters we used to parse data from

LeanDojo can be found in Figure 4. While these parsed informalizations are more rudimentary compared to our other methods, they allowed us to generate a much larger corpus at minimal cost. Additionally, this approach can be easily expanded upon and provides greater explainability than other methods. However, given the complexity of Lean code, this approach is inherently limited and can only produce rudimentary informalizations such as the ones in Appendix B. We hypothesized that while the model fine-tuned on Regex-parsed statements would enhance performance compared to the baseline, the simplicity of the translated statements would prevent them from outperforming more sophisticated backtranslation methods. This was confirmed by the results shown in Table 3.




Figure 3: **Distilled Backtranslation Process Graph**. Leveraging the MathLib and ProofNet datasets, a "Teacher" model translates formal theorems into synthetic informal language (IL) examples, which are then backtranslated to augment a training dataset with new formal language (FL) examples. A "Student" model, more compact than the teacher, is fine-tuned on this enriched dataset to improve its translation from IL to FL.

Regular Expressions

```
patterns = {
  "induction": r"induction .+ with .+",
  "apply": r"apply .+",
  "rewrite": r"rw .+",
  "reflexivity": r"refl",
  "cases": r"cases .+",
  "introduce": r"intro .+—intros .+",
  "simplification": r"simp .+",
  "contradiction": r"contradiction",
  "exact": r"exact .+",
  "definition": r"def .+ := .+" }
```

Figure 4: **Regular Expressions can be used to generate a large volume of rudimentary informalizations**. Certain Lean proof statements follow predictable patterns that can be captured via a regex. More sophisticated pattern-matching solutions can be built on this framework to increase the amount of paired data available to fine-tune on.

3 AI4MATH DATASET OVERVIEW

The integration of data collected through these methodologies resulted in the **AI4Math** Dataset, which encompasses a broad spectrum of proof tactics and informal statements. The total number

of tokens from each collection method is provided in Table 1. The following datasets are labeled according to the composition of their contents:

1. *MMA Train* is a large, multilingual, and multi-domain baseline dataset (Jiang et al., 2023) which we aim to compare our generated (IL, FL) pairs against.
2. *On-the-Fly Backtranslation* is comprised of formal-informal pairs created as a result of the backtranslation procedure shown in Figure 1.
3. *GPT-4 MathLib4 (Full Proof)* employs regular expressions to parse the MathLib4 dataset into individual theorems, using GPT-4 with few-shot prompting to informalize a selected subset. Following ProofNet's approach, we applied a 6-shot prompting technique to convert entire theorem statements and their proofs into natural language. This process is shown in Figure 3.
4. *GPT-4 LeanDojo (Individual Tactics)* not only informalizes theorem statements but also each specific tactic within proofs from the LeanDojo dataset, capturing the proof's state before and after each tactic. Using a 0-shot prompting strategy, we created a dataset with informal translations of each tactic, alongside their respective before and after states.
5. *Regex-Parsed LeanDojo Proofs* uses regular expressions to parse specific tactics from the LeanDojo proofs for targeted model refinement. The filters used can be found in Appendix B.

Data Collection Method	**Token Count**
MMA Train	10,916,097
Regex-Parsed LeanDojo Proofs	124,782
GPT-4 MathLib4 (Full Proof)	71,550
GPT-4 LeanDojo (Individual Tactics)	1,754

Table 1: **Token counts across dataset generation methods**. For each dataset generation method, we compile formal and corresponding generated informal statement data into pairings. This illustrates the diversity and scale of training data available in AI4Math for fine-tuning, as well as demonstrating the relative cost of each synthetic dataset generation methodology.

4 Examples of Generated Data

Figure 5 shows one before/after pair per generation method, taken from the released data. Before is the formal Lean text; after is the informal text the method produced. The examples were drawn at random (seed 0) and cut to fit; five pairs per method are in `experiments/002_examples_cost_datasets` of the project repository. On-the-fly backtranslation has no example: its synthetic informal text exists only inside the training loop and was not saved.

4.1 Cost of each generation method

Table 2 gives, for each method, the number of pairs, the GPT-2 token count, and an estimate of the GPT-4 API cost at OpenAI list prices ($30 per million input tokens, $60 per million output tokens). The dollar figures are estimates, not bills: no billing record or generation log survives, so they are lower bounds that count only the pairs we kept (calls that were dropped or retried are not logged), and wall-clock time was not recorded for any method. The MMA row is the price of regenerating its data with GPT-4; we did not pay it. The authors of MMA report $3,500 for 332,000 informalized theorems (Jiang et al., 2023). The 1,754-token figure for the individual-tactics set in Table 1 does not match either public individual-tactics set (29 pairs with 20,261 tokens; 100 pairs with 50,145 tokens); we report both.

4.2 Overlap with the evaluation sets

We checked every dataset in the Hugging Face organizations AI4M and UDACA (40 files from 33 repositories) for text overlap with the ProofNet and MiniF2F validation and test sets, by exact match

Method	Before (formal)	After (informal)
MMA Train (baseline)	`theorem refl_trans (α : X ≅ Y) : Iso.refl X ≪≫ α = α :=`	For any isomorphism 'α' from 'X' to 'Y', the composition of the identity isomorphism on 'X' and 'α' is equal to 'α'.
GPT-4 MathLib4 (Full Proof)	`theorem one_le {a : Associates α} : 1 ≤ a := Dvd.intro _ (one_mul a)`	For any associate a of a type α, 1 is less than or equal to a. This is proven by introducing a divisor through the property that multiplying 1 by a gives a.
GPT-4 LeanDojo (Individual Tactics)	state before: $T \models \phi \leftrightarrow \exists T_0, T_0 \subseteq T \wedge T_0 \models \phi$; tactic: `simp only [models_iff_not_satisfiable]` state after: $\vdash \neg \text{IsSatisfiable}(T \cup \{\neg\phi\}) \leftrightarrow \ldots$	In this scenario, we're dealing with a formal language L and a theory T ;within that language, [...] The goal is to prove the equivalence between T proving ϕ and the existence of a subtheory T_0 of T that also proves ϕ. [...]
Regex-Parsed LeanDojo Proofs	`apply Nat.succ_pos`	Here, we apply the theorem/lemma Nat.succ_pos.

Figure 5: **Before/after examples for each generation method with saved data**. [...] marks text cut for space. Rows are from `AI4M/mma-dataset` (row 55125), `AI4M/gpt4-more` (row 183), `AI4M/state_info_informalization` (row 6) and `AI4M/regexInformalizationData` (row 601).

Method	Pairs	GPT-2 tokens	Est. API cost (USD)
MMA Train (not paid by us)	84,679	10,916,097	396
GPT-4 MathLib4 (Full Proof)	348	71,550	≥ 14
GPT-4 LeanDojo (Individual Tactics), 29-pair set	29	20,261	≥ 1
GPT-4 LeanDojo (Individual Tactics), 100-pair set	100	50,145	≥ 2
Regex-Parsed LeanDojo Proofs	2,875	124,782	0 (no API call)
On-the-Fly Backtranslation	not saved	not saved	0 (GPU time only)

Table 2: **Size and estimated GPT-4 cost of each generation method.** Estimates at list price, lower bounds, from `experiments/002_examples_cost_datasets`. Wall-clock time was not logged. For the individual-tactics sets the zero-shot prompt text was not saved, so the input cost counts only the data.

and by at least 80% shared 8-grams (Appendix D). The datasets used for the results in this paper are clean: MMA (train, validation, test), `gpt4-more` (the six-shot full-proof data), both individual-tactics sets and the regex sets have no overlapping item with ProofNet or MiniF2F. Several other released datasets do overlap, for example sets built from ProofNet itself and the data-selection sets built with ProofNet as the target; results from models trained on them must not be reported on ProofNet. This check is text matching only, on CPU, and does not show which data any given checkpoint was trained on.

5 AUTOFORMALIZATION PERFORMANCE

To quantify the results of our methods, we evaluate our fine-tuned models for accuracy on ProofNet's test dataset, with the goal of measuring the performance gain over their initial pretrained states. All of our models used GPT-2 as the base architecture and fine-tuned for 3 epochs using a learning rate of 1e-5 and Adafactor optimization, as these hyperparameters for the training setup appeared to yield the best performance. We chose GPT-2 for our experiments due to its open-source availability and lower fine-tuning costs compared to larger, closed-source models like GPT-4. As discussed, future research should consider using larger models to improve outcomes subject to resource availability.

At the end of this explanation, I will give you 2 things. The first is a list of tuples that are the translations of entire proofs written in Lean, which we will denote the formal language, to plain English, also known as natural language, as tuples or pairs. This is not an exhaustive list, these are just examples of informalizations. I will then have a proof written in Lean represented as a string following the newline character after the list of pairs. Give me the tuple pair of the proof I give you written in Lean and what you think their natural language equivalent is given your knowledge of Lean, formatted using LaTeX. Do not output anything else, just the python tuple I requested. In your output match the exact format "('formal', 'informal')" \n

```
[("Lean theorem statement 1", "Theorem 1 in natural language"),
("Lean theorem statement 2", "Theorem 2 in natural language"),
("Lean theorem statement 3", "Theorem 3 in natural language"),
("Lean theorem statement 4", "Theorem 4 in natural language"),
("Lean theorem statement 5", "Theorem 5 in natural language"),
("Lean theorem statement 6", "Theorem 6 in natural language")]
```

Figure 6: **Formal-informal pairs used for training are generated via few-shot prompting and distilled backtranslation**. Mined proofs from mathlib are used as input into this format string for prompting, and then GPT-4 creates examples that can be utilized for fine-tuning. In contrast to MMA, our method used six examples to informalize theorem statements.

Fine-Tuning Dataset	**Eval Loss**
GPT-2 Baseline	75.1839
GPT-4 LeanDojo (Individual Tactics)	5.1287
Regex-Parsed LeanDojo Proofs	4.4709
On-the-Fly Backtranslation	4.032
MMA Train	3.8791
GPT-4 MathLib4 (Full Proof)	3.1209

Table 3: **Evaluation loss on ProofNet's Test Dataset**. The model used was GPT-2, and it was fine-tuned on each dataset for 3 epochs before being evaluated. GPT-4 MathLib4 (Full Proof) demonstrated higher token efficiency than MMA train, and despite the lower token count, GPT-4 LeanDojo (Individual Tactics) improved the baseline substantially.

We included the results of fine-tuning on the training set of MMA, a dataset that also uses GPT-4 to create the formal-informal pairs that matches the approach we took with the full-proof informalizations (Jiang et al., 2023). However, our methodology uses a 6-shot prompt only, which appears to improve token efficiency as evidenced by the lower token count in Table 1 and lower resulting evaluation loss in Table 3.

We have three major observations:

- **Few-Shot Beats MMA**: Our *GPT-4 MathLib4 (Full Proof)* dataset, developed through a hard-coded 6-shot prompting technique, outperformed the larger, diverse dataset from Albert et al., despite being over 150 times smaller. This substantial increase in token efficiency is likely due to better informalizations of our methodology, which improves upon the comparatively simple prompting technique of MMA. We demonstrate that more examples, though less cost-effective, can result in better autoformalization performance with fewer tokens.
- **Individual Tactics are Efficient**: The *GPT-4 LeanDojo (Individual Tactics)* dataset, which leverages an intensive approach of matching individual tactics to lines in the informalized proof, demonstrated dramatic improvement from GPT-2 baseline with far fewer tokens compared to other methods. However, this method first requires having GPT-4 informalize the proof as a whole, and then pairing the individual tactics to a line in the translated natural language proof: making the strategy more costly at \$0.15 per proof compared to \$0.05 per proof in *GPT-4 MathLib4 (Full Proof)* and the \$0.01 per proof in MMA, which

had 332,000 theorems informalized for $3,500 total (Jiang et al., 2023). This was the largest barrier preventing us from generating a larger training corpus. Given the drastic improvement compared to the baseline, we hypothesize that this is method has significant potential and should be explored in the future with more resources.

- **On-The-Fly Backtranslation Performance Plateau**: When generating the distilled backtranslation dataset for the individual tactics, a review of the data showed that the model trained on our On-the-Fly Backtranslation dataset considerably outperformed the GPT-2 baseline, but its performance plateaued below that of the MMA dataset. We hypothesize that this is due to model size, as both of our best performing methodologies used GPT-4 to generate data for backtranslation.

Takeaway #1: Prioritize Quality over Quantity!
Utilizing few-shot prompting techniques appears to generate more accurate and higher-quality parallel informalizations, as evidenced by the results of our *GPT-4 MathLib4 (Full Proof)* and *GPT-4 Lean (Individual Tactics)* datasets. Investing in more sophisticated full-proof few-shot or line-by-line matched examples can significantly enhance token efficiency, yielding better results even with fewer tokens.

Takeaway #2: Intermediate Steps Matter
GPT-4 Lean (Individual Tactics) demonstrates remarkable proof-efficiency for the small token count despite the higher costs and poor performance compared to utilizing the full proof.

Takeaway #3: High-Quality Data Beats Diversity.
Datasets that utilize comparatively richer prompts with GPT-4 exhibit more efficient parallel corpora for autoformalization training compared to datasets that rely on blindly training on diverse data (On-The-Fly Backtranslation, MMA, Regex-Parsed LeanDojo Proofs).

6 Related Work

The closest prior work is ProofNet (Azerbayev et al., 2023a), which introduced distilled backtranslation for autoformalization (GPT-4 informalizes Mathlib statements, a smaller model is fine-tuned on the pairs), and MMA (Jiang et al., 2023), which applied zero-shot GPT-4 informalization at scale across several formal languages. Our six-shot full-proof data is a variant of ProofNet's recipe, and MMA is our main baseline. Backtranslation itself comes from machine translation (Sennrich et al., 2016; Poncelas et al., 2018). Process reward models (Lightman et al., 2023; Uesato et al., 2022) supervise each reasoning step rather than the final answer; our tactic-level data uses the same idea for informalization, with Lean proof states as the context, and we do not train a reward model.

The Multilingual Mathematical Autoformalization (MMA) dataset also uses powerful models GPT-4 to translate from formal language (FL) to informal language (IL) via zero-shot instruction prompting on a large, diverse corpus of mathlib4 data (Jiang et al., 2023). Our approach enhances the efficiency of this process by applying a more intense six-shot prompting strategy on mathlib4 statements; the fine-tuning performance of the resulting dataset not only surpasses that of the MMA dataset on the ProofNet benchmark but does so using only 1/150th of the tokens: significantly optimizing resource use while enhancing output quality. Utilizing a regex, we parsed Lean files from mathlib into over 100,000 tactic proof scripts, and we call this methodology using the "Full-Proof" in pregenerating informal-formal pairs for informalization via GPT-4. Despite the high number of parsed scripts, at an estimated $0.05 per informalization we were only able to informalize a subset of this collection.

Our dataset also utilizes LeanDojo, an open-source platform that offers a comprehensive dataset of over 90,000 Lean theorems. Existing models like ReProver, a retrieval-augmented language model, have demonstrated superior performance compared to established models such as Tidy and GPT-4 (Yang et al., 2023). However, while retrieval-augmented models like ReProver are promising in leveraging formal corpora to enhance LLMs, they rely heavily on automated theorem provers. These models often skip over the detailed intermediate steps that are critical for understanding complex mathematical logic, thereby restricting the systems' flexibility and explainability.

Moreover, the prevalent use of first-order logic in these models constrains their capacity to articulate more sophisticated proofs. Our approach in *GPT-4 LeanDojo (Individual Tactics)* addresses this limitation by directly modeling the incremental deduction characteristic of interactive theorem provers. While this approach involves higher computational costs, Table 3 demonstrates its effectiveness in significantly enhancing baseline performance. Our method achieves notable improvements over the baseline with a very small number of tokens.

7 DISCUSSION

Our paper releases datasets that can be used for enhancing the autoformalization capabilities of large language models. We provide evidence, for GPT-2 and evaluation loss on ProofNet, that models can reach lower loss by training on **AI4Math**, and our generation strategies can significantly reduce the number of tokens required compared to MMA.

8 LIMITATIONS

- **One small model, one benchmark, one metric.** The results above fine-tune GPT-2 (124M) and report evaluation loss on the ProofNet test set. Evaluation loss measures how well the model predicts the Lean text, not whether a generated statement compiles or is faithful. Larger and math-specialized models, MiniF2F, and Lean-checked pass@k are the subject of the new experiments listed in the response to reviewers.
- **Small differences.** The gap between the best two GPT-4 datasets is small, and per-example losses were not saved, so we cannot test whether it exceeds seed-to-seed noise. Only GPT-4 data beat MMA here; the on-the-fly, regex and individual-tactics sets do not.
- **Other formal languages.** We study Lean 4 only. Our methods rely on Lean structure (LeanDojo tactic states, regex templates over Lean tactics), and Metamath proofs have no tactic state, so these methods would need a different step segmentation there. We have not tried Metamath or other formal languages and do not claim the results transfer.
- **Human in the loop.** All pairs are generated automatically; the only human-written text is the six examples in the prompt. We did not study human review or correction of the informalizations, nor human-in-the-loop evaluation, and leave both out of scope.
- **Cost estimates.** Costs are list-price lower bounds, because no billing or wall-clock record exists (Table 2).
- **Overlap.** Some released datasets contain ProofNet or MiniF2F items (Appendix D); the check is text matching and does not identify what any checkpoint saw.

9 FUTURE WORK

We concentrated on autoformalizing theorem statements, not on generating complete formal proofs. A next step is to test whether proofs or tactic scripts generated by fine-tuned models compile in Lean 4, which is the Lean-checked pass@k evaluation that the response to reviewers reports for the new experiments. A second step is to scale the tactic-level data: informalizing each intermediate proof state yields step-level pairs that capture the incremental deduction of an interactive theorem prover, and we would test whether training on them transfers beyond the training proofs.

10 CONCLUSION

We compared four ways of generating formal-informal pairs for autoformalization with GPT-2 (124M) on the ProofNet test set. Six-shot GPT-4 informalization of full Mathlib4 proofs reached a lower evaluation loss than the MMA dataset with 71,550 tokens instead of 10.9M, and tactic-level pairs with proof states improved on the pretrained baseline with very little data. The claim is limited to one small model, one benchmark and one metric; we report costs, examples and an overlap check so that these results can be reproduced and extended.

11 ACKNOWLEDGMENTS

This project was the final assignment for Stanford's CS197: Computer Science Research, a course that teaches undergraduates and junior students fast iteration and research methodologies. We acknowledge Michael Bernstein for the creation of the material for CS 197 that made this work possible, and OpenAI credits. SK acknowledges support by NSF 2046795 and 2205329, IES R305C240046, the MacArthur Foundation, Stanford HAI, OpenAI, and Google. BM acknowledges the Stanford Edge fellowship.

REFERENCES

Zhangir Azerbayev, Bartosz Piotrowski, Hailey Schoelkopf, Edward W. Ayers, Dragomir Radev, and Jeremy Avigad. Proofnet: Autoformalizing and formally proving undergraduate-level mathematics, 2023a.

Zhangir Azerbayev, Hailey Schoelkopf, Keiran Paster, Marco Dos Santos, Stephen McAleer, Albert Q. Jiang, Jia Deng, Stella Biderman, and Sean Welleck. Llemma: An open language model for mathematics, 2023b.

Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners, 2020.

Francois Charton, Amaury Hayat, and Guillaume Lample. Learning advanced mathematical computations from examples. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=-gfhS00XfKj.

Leonardo Mendonça de Moura and Sebastian Ullrich. The lean 4 theorem prover and programming language. In *CADE*, 2021. URL https://api.semanticscholar.org/CorpusID:235800962.

Daxiang Dong, Hua Wu, Wei He, Dianhai Yu, and Haifeng Wang. Multi-task learning for multiple language translation. pp. 1723–1732, 01 2015. doi: 10.3115/v1/P15-1166.

Christopher Hahn, Frederik Schmitt, Jens U. Kreber, Markus Norman Rabe, and Bernd Finkbeiner. Teaching temporal logics to neural networks. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=dOcQK-f4byz.

Jesse Michael Han, Igor Babuschkin, Harrison Edwards, Arvind Neelakantan, Tao Xu, Stanislas Polu, Alex Ray, Pranav Shyam, Aditya Ramesh, Alec Radford, and Ilya Sutskever. Unsupervised neural machine translation with generative language models only, 2021.

Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. Measuring massive multitask language understanding. *CoRR*, abs/2009.03300, 2020. URL https://arxiv.org/abs/2009.03300.

Albert Q. Jiang, Wenda Li, and Mateja Jamnik. Multilingual mathematical autoformalization, 2023.

Gerwin Klein, Kevin Elphinstone, Gernot Heiser, June Andronick, David Cock, Philip Derrin, Dhammika Elkaduwe, Kai Engelhardt, Rafal Kolanski, Michael Norrish, Thomas Sewell, Harvey Tuch, and Simon Winwood. seL4: Formal verification of an OS kernel. In *ACM Symposium on Operating Systems Principles*, pp. 207–220, Big Sky, MT, USA, October 2009. ACM.

Guillaume Lample and François Charton. Deep learning for symbolic mathematics. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=S1eZYeHFDS.

Aitor Lewkowycz, Anders Andreassen, David Dohan, Ethan Dyer, Henryk Michalewski, Vinay Ramasesh, Ambrose Slone, Cem Anil, Imanol Schlag, Theo Gutman-Solo, et al. Solving quantitative reasoning problems with language models. *Advances in Neural Information Processing Systems*, 35:3843–3857, 2022.

Hunter Lightman, Vineet Kosaraju, Yura Burda, Harri Edwards, Bowen Baker, Teddy Lee, Jan Leike, John Schulman, Ilya Sutskever, and Karl Cobbe. Let's verify step by step, 2023.

Xuebo Liu, Longyue Wang, Derek F. Wong, Liang Ding, Lidia S. Chao, Shuming Shi, and Zhaopeng Tu. On the complementarity between pre-training and back-translation for neural machine translation, 2021.

The mathlib Community. The lean mathematical library. *Proceedings of the 9th ACM SIGPLAN International Conference on Certified Programs and Proofs*, 2019. URL https://api.semanticscholar.org/CorpusID:204801213.

OpenAI. Gpt-4 technical report, 2023.

Alberto Poncelas, Dimitar Shterionov, Andy Way, Gideon Maillette de Buy Wenniger, and Peyman Passban. Investigating backtranslation in neural machine translation, 2018.

Rico Sennrich, Barry Haddow, and Alexandra Birch. Improving neural machine translation models with monolingual data. In Katrin Erk and Noah A. Smith (eds.), *Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 86–96, Berlin, Germany, August 2016. Association for Computational Linguistics. doi: 10.18653/v1/P16-1009. URL https://aclanthology.org/P16-1009.

Jonathan Uesato, Nate Kushman, Ramana Kumar, Francis Song, Noah Siegel, Lisa Wang, Antonia Creswell, Geoffrey Irving, and Irina Higgins. Solving math word problems with process- and outcome-based feedback, 2022.

Qingxiang Wang, Cezary Kaliszyk, and Josef Urban. First experiments with neural translation of informal to formal mathematics. In Florian Rabe, William M. Farmer, Grant O. Passmore, and Abdou Youssef (eds.), *Intelligent Computer Mathematics*, pp. 255–270, Cham, 2018. Springer International Publishing. ISBN 978-3-319-96812-4.

Yonghui Wu, Mike Schuster, Zhifeng Chen, Quoc V. Le, Mohammad Norouzi, Wolfgang Macherey, Maxim Krikun, Yuan Cao, Qin Gao, Klaus Macherey, Jeff Klingner, Apurva Shah, Melvin Johnson, Xiaobing Liu, Łukasz Kaiser, Stephan Gouws, Yoshikiyo Kato, Taku Kudo, Hideto Kazawa, Keith Stevens, George Kurian, Nishant Patil, Wei Wang, Cliff Young, Jason Smith, Jason Riesa, Alex Rudnick, Oriol Vinyals, Greg Corrado, Macduff Hughes, and Jeffrey Dean. Google's neural machine translation system: Bridging the gap between human and machine translation, 2016.

Yuhuai Wu, Albert Q. Jiang, Wenda Li, Markus N. Rabe, Charles Staats, Mateja Jamnik, and Christian Szegedy. Autoformalization with large language models, 2022.

Kaiyu Yang, Aidan M. Swope, Alex Gu, Rahul Chalamala, Peiyang Song, Shixing Yu, Saad Godil, Ryan Prenger, and Anima Anandkumar. Leandojo: Theorem proving with retrieval-augmented language models, 2023.

Kunhao Zheng, Jesse Michael Han, and Stanislas Polu. Minif2f: a cross-system benchmark for formal olympiad-level mathematics. *arXiv preprint arXiv:2109.00110*, 2021.

A Appendix A: "Full-Proof" Prompt

We used the following prompt for informalizing the MathLib4 theorems we extracted, with a six-shot example. A complete example can be found in Figure 8.

B Appendix B: Regex-Parsed LeanDojo Proofs

We used the regular expressions outlined in Figure 4 to parse specific patterns from Lean code. This enabled us to format the parsed strings using the templates in Figure 7 to create a basic 'informalization' of the proofs. This is a tradeoff of quality for quantity, as the informalizations are rudimentary but simple to create. Given the improvements over baseline performance, more complex regex-based systems could contribute to increasing the volume of paired data.

Informalization
"induction": "We are beginning a proof by induction on {variable}."
"apply": "Here, we apply the theorem/lemma {theorem_name}."
"rewrite": "We're rewriting part of the expression using {equality_statement}."
"reflexivity": "This step concludes that both sides of our equation are identical."
"cases": "We're breaking down the problem into cases based on {variable_or_condition}."
"introduce": "We introduce new variables {variable_names}."
"simplification": "We simplify the current expression or goal using the simp tactic."
"contradiction": "This step shows that our assumptions lead to a contradiction."
"exact": "Here, we provide the exact term {term_name} that solves our current goal."
"definition": "We define a function {function_name} that takes {parameters}."

Figure 7: **Informalization**. These strings format the parsed patterns into informal explanations.

C Appendix C: Data Appendix

All of the models and datasets used for fine-tuning can be found on HuggingFace under the AI4M Organization.

D Appendix D: Overlap with ProofNet and MiniF2F

A text-matching check on CPU (no model, no Lean). An evaluation item is counted as hit if any of its views (formal statement, informal statement, informal proof) is found in a training record: exact (the item's tokens appear contiguously) / at least 80% of its 8-grams. Evaluation sets: ProofNet validation (180 items) and test (181), MiniF2F validation (244) and test (244). All 40 files and the method are in `experiments/01_contamination_check`.

Training set	**Records**	**PN valid**	**PN test**	**MF valid**	**MF test**
mma-dataset (train)	84,679	0/0	0/0	0/0	0/0
mma-dataset (valid)	1,930	0/0	0/0	0/0	0/0
mma-dataset (test)	1,927	0/0	0/0	0/0	0/0
gpt4-more (Full Proof)	348	0/0	0/0	0/0	0/0
state_info_informalization	29	0/0	0/0	0/0	0/0
stateInfoInformalizationBig	100	0/0	0/0	0/0	0/0
regexInformalizationData	2,875	0/0	0/0	0/0	0/0
leandojo-informalized	31,127	0/0	0/1	3/4	0/0

Table 4: **Overlap of the training sets used in this paper with the evaluation sets** (exact / at least 80% of 8-grams; PN = ProofNet, MF = MiniF2F). The full table has 40 files; datasets built from ProofNet or with ProofNet as the data-selection target (for example the LESS and ZipFit sets) contain all or most of its validation items.

```
At the end of this explanation, I will give you 2 things. The
    first is a list of tuples that are the translations of
    entire proofs written in Lean, which we will denote the
    formal language, to plain English, also known as natural
    language, as tuples or pairs. This is not an exhaustive
    list, these are just examples of informalizations. I will
    then have a proof written in Lean represented as a string
    following the newline character after the list of pairs.
    Give me the tuple pair of the proof I give you written in
    Lean and what you think their natural language equivalent
    is given your knowledge of Lean, formatted using LaTeX. Do
    not output anything else, just the python tuple I requested
    . In your output match the exact format "('formal', '
    informal')" \n
[("theorem exists_le_sylow {p : N} {G : Type*} [group G] {P :
    subgroup G} \n (hP : is_p_group p P) : \n there exists (Q :
     sylow p G), P <= Q :=", "Let P be a p-subgroup of G. Then
    P is contained in a Sylow p-subgroup of G."),
("theorem exists_eq_const_of_bounded {E : Type u} [
    normed_group E] \n [normed_space C E] {F : Type v} [
    normed_group F] [normed_space C F] \n {f : E to F} (hf :
    differentiable C f) (hb : metric.bounded (set.range f)) : \
    n there exists (c : F), f = function.const E c :=", "Let E
    and F be complex normed spaces and let f:E to F. If f is
    differentiable and bounded, then f is constant."),
("theorem subset_of_open_subset_is_open (X : Type*) [
    topological_space X] \n (A : set X) (hA : for every x in A,
     there exists U: set X, is_open U and x in U and U subset A
    ): \n is_open A :=", "Let X be a topological space; let A
    be a subset of X. Suppose that for each x in A there is an
    open set U containing x that U is a subset of A. Then A is
    open in X."),
("theorem is_multiplicative.eq_iff_eq_on_prime_powers {R :
    Type*} \n [comm_monoid_with_zero R] (f : nat.
    arithmetic_function R) \n (hf : f.is_multiplicative) (g :
    nat.arithmetic_function R) \n (hg : g.is_multiplicative) :
    \n f = g iff for all (p i : N), nat.prime p implies f (p ^
    i) = g (p ^ i) :=", "Two multiplicative functions f, g: N
    to R are equal if and only if f(p^i)=f(g^i) for all primes
    p."),
("theorem abs_sum_leq_sum_abs (n : N) (f : N to C) : \n abs (
    sum i in finset.range n, f i) <= sum i in finset.range n,
    abs(f i) :=", "If z1, dots, zn are complex, then abs(z1 +
    z2 + dots + zn) <= abs(z1) + abs(z2) + dots + abs(zn)."),
("theorem distinct_powers_of_infinite_order_element (G : Type
    *) [group G] (x : G) \n (hx_inf : for all n : N, x ^ n !=
    1) : \n for all m n : Z, m != n implies x ^ m != x ^ n :=",
     "If x is an element of infinite order in G, prove that the
     elements x^n, n in Z are all distinct.")]
```

Figure 8: **Full Example of our 6-Shot Prompting Methodology.** Such prompts are given to GPT-4 and used to create the formal-informal pairings in our GPT-4 MathLib4 (Full Proof) dataset. Note that characters are translated from Unicode to ASCII for display purposes.