Correlation Alone Does Not Identify a Judge's Conditional Rating Distribution

Anonymous submission

Abstract

A judge can predict the correct mean rating while assigning the wrong conditional distribution to every input. Correlation between scalar judge and human scores cannot distinguish such forecasts. We argue for evaluating the conditional rating distribution with proper probability losses, alongside scalar association and agreement diagnostics. A binomial construction gives five candidate distributions with identical conditional means and distinct expected cross-entropy, Brier score and ranked probability score. With one synthetic rating per item, cross-entropy selects the true distribution in 249 of 256 replications. Pearson, Spearman, Kendall and scalar mean squared error retain all five candidates as ties throughout. We enumerate these ties, reproduce the older marginal-histogram example, and retain inconclusive historical theorem-judge evidence. The result supports distribution-aware evaluation without implying human generalization, universal finite-sample superiority, or that psychometric methods are unnecessary.

Introduction

A scalar agreement statistic does not determine whether a judge predicts how human ratings vary across inputs. G-Eval evaluates text judges using correlation with human judgments (Liu et al. 2023). MT-Bench and Chatbot Arena also study agreement with human preferences and document judge biases (Zheng et al. 2023). These comparisons answer useful questions, but do not by themselves identify a conditional rating distribution.

We take the distribution as the target when the evaluation requires probabilities for each possible rating. Proper scoring rules provide an established framework for this target (Gneiting and Raftery 2007). Our contribution is a controlled identification study that makes the information discarded by scalar criteria explicit. We do not claim a new proper scoring rule.

The study separates three questions: population identification, selection with sparse ratings, and agreement of scalar means. It compares the same candidates and splits under probability-loss and correlation selection. A separate permutation control shows why matching aggregate histograms cannot establish correct item conditioning.

This is an anonymized submission for review purposes only. Distribution, citation, or public sharing of this manuscript is strictly prohibited. Copyright and publication details will appear in the final version if accepted.

We make the following contributions:

1. We construct conditional distributions that share their means but differ under proper probability losses.
2. We evaluate selection using one, two and three synthetic ratings per item, reporting every tied minimizer and common test metric.
3. We preserve historical null findings and identify the limits of transferring this synthetic result to human-rated judges.

What Scalar Criteria Identify

Let $p(r \mid x)$ be the distribution of a specified rating population and let a judge report $q(r \mid x)$. Write $\mu_q(x) = \sum_r r q(r \mid x)$. Pearson correlation measures linear association between scalar summaries; Spearman and Kendall measure ordering with their respective tie conventions. A strictly increasing transformation preserves ranks, but compression into two bins generally introduces ties and can change rank correlation. None of these statistics identifies the full conditional distribution when different forecasts share μ_q.

Squared error also has a narrower target. For any scalar prediction $a(x)$,

$$\mathbb{E}[(a - R)^2 \mid x] = (a - \mathbb{E}[R \mid x])^2 \tag{1}$$

$$+ \operatorname{Var}(R \mid x). \tag{2}$$

It identifies the conditional mean under finite second moments, not an arbitrary conditional distribution. Scaling a bounded rating to $[0, 1]$ changes the units, not that identification property.

These limitations do not establish that every psychometric method is unnecessary. Construct validity concerns the interpretation supported by a body of evidence, rather than a single agreement coefficient (Cronbach and Meehl 1955). Choosing whose judgments to model and whether the rating task measures the intended construct remain necessary even with a proper probability loss.

Evaluate Conditional Probability Forecasts

For ratings $r \in \{0, \ldots, 5\}$ and input $x = (y, y^*)$, consider

$$\min_{\theta} \ \mathbb{E}_x\big[D_{\mathrm{KL}}(p(\cdot \mid x) \,\|\, q_\theta(\cdot \mid x))\big]. \tag{3}$$

The target p is a population distribution, not a sparse empirical histogram. Cross-entropy (CE), $\mathbb{E}_{x,R}[-\log q_\theta(R \mid x)]$,

differs from Eq. 3 by an entropy term independent of θ. One observed rating per item supplies a valid conditional log-loss observation. It does not require marginal pooling and does not identify an unconstrained distribution at that item without shared structure or further assumptions.

We also evaluate the Brier score and ranked probability score (RPS), using the loss orientation of proper scoring rules (Gneiting and Raftery 2007):

$$L_{\mathrm{Brier}}(q, r) = \sum_{j=0}^{5} (q_j - \mathbf{1}\{r = j\})^2, \tag{4}$$

$$L_{\mathrm{RPS}}(q, r) = \frac{1}{5} \sum_{j=0}^{4} (Q_j - \mathbf{1}\{r \le j\})^2, \tag{5}$$

where $Q_j = \sum_{k=0}^{j} q_k$. Their expected excess losses over the oracle are $\sum_j (q_j - p_j)^2$ and $\frac{1}{5} \sum_{j=0}^{4} (Q_j - P_j)^2$. These vanish only when the categorical distributions agree. CE has excess loss $D_{\mathrm{KL}}(p \| q)$, assuming forecast support covers the population support.

Empirical evaluation averages losses over observed ratings, including with one rating per input. A histogram of two or three ratings remains a noisy estimate, and pooling marginal histograms discards the input–rating association. Probability fitting also does not remove finite-sample selection error, model misspecification, or optimization failure. We retain Pearson, Spearman and Kendall as diagnostics, with normalized scalar error and signed bias when score levels matter.

Controlled Conditional Identification

Our new experiment uses $p(r \mid t) = \mathrm{Binomial}(5, t)$ for a fixed symmetric grid inside $[0.1, 0.9]$. Define

$$q_\lambda(r \mid t) = (1 - \lambda) p(r \mid t) + \lambda[(1 - t)\delta_0 + t\delta_5]. \tag{6}$$

For $\lambda \in \{0, .25, .5, .75, .95\}$, every forecast has mean $5t$. Consequently all five receive identical scalar correlations and squared errors on every realized rating dataset. Their conditional distributions differ whenever $\lambda > 0$. The excess proper losses are strictly positive; Brier and RPS excess losses scale as λ^2.

We use twelve symmetric parameter-band families, holding out six/three/three families for train/validation/test, with 96/48/48 items respectively. The nine-candidate pool adds $p(r \mid 1 - t)$, constant binomial and uniform forecasts, and a Laplace-smoothed train-rating constant. Only the final constant is fitted; every criterion selects from the same nine candidates using validation ratings. The reversed conditional preserves each split's aggregate histogram exactly by symmetry.

We generate 256 independent rating replications, each providing three ratings per item, and compare their one-, two- and three-rating prefixes. The procedure and source hashes were committed before measurement. All 768 conditions and 5,376 selections completed without missing selections. With one rating, CE selects the oracle in 249/256 replications, and Brier and RPS each select it in 245/256. Their mean exact test CE values are 1.331 [1.329, 1.334] and 1.333 [1.330, 1.336], respectively. Intervals are 95% Student-t Monte Carlo intervals across independent rating replications on fixed items; no hypothesis test was specified. All three proper losses select the oracle in 256/256 two-rating and three-rating replications, which does not prove zero selection error beyond these replications.

Candidate	CE	Brier	RPS	nMSE
q_0	1.328	.699	.104	.038
$q_{.25}$	1.446	.733	.109	.038
$q_{.50}$	1.689	.835	.125	.038
$q_{.75}$	2.164	1.004	.152	.038
$q_{.95}$	3.348	1.188	.181	.038
Reversed conditional	4.215	1.113	.384	.282

Table 1: **Identical mean predictions can have different distributional losses.** Exact expectations on the fixed synthetic test grid; CE uses nats and nMSE normalizes ratings by five. These deterministic expectations need no sampling interval.

Pearson, Spearman, Kendall and nMSE retain all five mixture candidates in every replication. We enumerate the full tie set with tolerance 10^{-12} rather than select by array order. Their exact test CE spans 1.328–3.348; uniform tie-breaking has expected CE 1.995. A tie policy that always picks the oracle attains CE 1.328, so superiority is not independent of tie policy. These are losses of individual selected forecasts, not of an averaged distribution.

The reversed conditional has identical marginal probabilities but conditional KL 2.887 nats. The five mixtures have zero normalized mean bias, mean 0.5, and normalized individual-rating MAE 0.157. Their correlations with the population conditional mean are all one, but Pearson correlation with a future individual rating is 0.786. Population-mean agreement is therefore distinct from agreement with noisy individual ratings.

Historical toy. We reproduced the original seed-0 marginal-histogram example without modifying its code or frozen output. Its noisy and two-bin judges have Pearson 0.900/0.877, Spearman 0.900/0.878, marginal KL 0.001/3.420, and nMSE 0.023/0.216. It is a single-seed marginal illustration, not conditional judge selection; the two-bin transform introduces ties.

Historical Theorem-Judge Evidence

The companion repository reports a retrospective comparison on 75 artifacts, 25 tasks, 19 families and 195 expert ratings (Trustworthy-Theorem-Judges Contributors 2026a). We import only public aggregates and preserve their limitations. Across five seeded five-fold family partitions (25 outer folds reusing those 75 artifacts), cached-histogram CE selection had held-out CE 8.868 versus 8.098 for Spearman selection. The difference was $+0.770$ $[-0.895, 1.317]$, using a 95% family-bootstrap interval that repeats selection. On the original historical split (15 validation artifacts selecting over 30 test artifacts, 10 tasks and 78 ratings), CE selection had test CE 9.133 versus 8.710 ($+0.423$). Those historical ratings, test outcomes and candidate prompts had prior exposure,

and neither denominator establishes a CE advantage.

A separate fitted-head comparison favored CE fitting by -0.370 $[-0.690, -0.080]$ in test CE, conditional on fitted heads. However, 215/225 Pearson fits failed to converge, including 24/25 final refits. This limits any objective-level interpretation of the comparison. Neither the Wasserstein nor the kernel-distance follow-up resolved an advantage over Spearman selection. All intervals are descriptive; no confirmatory hypothesis test was specified.

The separately completed weighted-probability and stable-Pearson follow-up resolved the earlier numerical comparator issue (Trustworthy-Theorem-Judges Contributors 2026b). All 50 primary fits passed checks and all 900 secondary fits converged. Its weighted-loss difference was -0.010409 $[-0.061911, +0.005933]$, with both mixtures refitted in 998/1,000 valid family-bootstrap draws. Two numerical certificate failures were retained without replacement; the interval conditions on successful draws. It still does not establish an advantage. Our synthetic experiment neither reruns this condition nor replaces its conclusions. Fresh human returns were not independently checked from cloud for this report; we do not infer that they are absent. Natural-output generalization still requires matched probability forecasts, an explicit rater population, stable comparison procedures and appropriately held-out evidence.

Scope and Limitations

The construction deliberately includes the oracle and changes distribution shape without changing the mean. It demonstrates nonidentification by scalar summaries, not the prevalence of this failure among natural judges. The family split holds out synthetic parameter bands; it is not evidence of transfer across real tasks, solvers, raters or model families. Independent binomial ratings omit rater heterogeneity and dependence. The study trains no language model and uses no new provider calls.

One observed rating can score a conditional forecast, but learning a flexible conditional distribution requires data and shared structure. Neither a high correlation nor low finite-sample proper loss establishes that an entire human population has been learned. When only a conditional mean or ranking is required, scalar objectives may be appropriate for that narrower target. When the distribution is required, report proper probability losses and keep association, absolute error and bias as complementary diagnostics.

Conclusion

Correlation alone does not identify a judge's conditional rating distribution. Proper probability losses identify that target in the population under their assumptions; sparse data and optimization still determine empirical selection quality. Our controlled study supports this distinction while preserving inconclusive historical evidence.

References

Cronbach, L. J.; and Meehl, P. E. 1955. Construct Validity in Psychological Tests. *Psychological Bulletin*, 52(4): 281–302.

Gneiting, T.; and Raftery, A. E. 2007. Strictly Proper Scoring Rules, Prediction, and Estimation. *Journal of the American Statistical Association*, 102(477): 359–378.

Liu, Y.; Iter, D.; Xu, Y.; Wang, S.; Xu, R.; and Zhu, C. 2023. G-Eval: NLG Evaluation using GPT-4 with Better Human Alignment. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing (EMNLP)*.

Trustworthy-Theorem-Judges Contributors. 2026a. Cached Objective Comparison: Results and Limitations. Public aggregate experiment report. Revision 5aef572d30048; experiment 06.

Trustworthy-Theorem-Judges Contributors. 2026b. Weighted Training Results. Public aggregate experiment report. Revision ea5d84238f6f; experiment 06, training follow-up 11-08-2026.

Zheng, L.; Chiang, W.-L.; Sheng, Y.; Zhuang, S.; Wu, Z.; Zhuang, Y.; Lin, Z.; Li, Z.; Li, D.; Xing, E. P.; Zhang, H.; Gonzalez, J. E.; and Stoica, I. 2023. Judging LLM-as-a-Judge with MT-Bench and Chatbot Arena. In *Advances in Neural Information Processing Systems (Datasets and Benchmarks Track)*.