



Chapel: Productive, Multiresolution Parallel Programming

Brad Chamberlain, Chapel Team, Cray Inc.

ATPESC 2016
August 3rd, 2016



COMPUTE | STORE | ANALYZE

Safe Harbor Statement

This presentation may contain forward-looking statements that are based on our current expectations. Forward looking statements may include statements about our financial guidance and expected operating results, our opportunities and future potential, our product development and new product introduction plans, our ability to expand and penetrate our addressable markets and other statements that are not historical facts. These statements are only predictions and actual results may materially vary from those projected. Please refer to Cray's documents filed with the SEC from time to time concerning factors that could affect the Company and these forward-looking statements.



Motivation for Chapel

Q: Can a single language be...

- ...as productive as Python?
- ...as fast as Fortran?
- ...as portable as C?
- ...as scalable as MPI?
- ...as fun as <your favorite language here>?

A: We believe so.





Chapel: Putting the “Whee!” back in HPC Programming

Brad Chamberlain, Chapel Team, Cray Inc.

ATPESC 2016
August 3rd, 2016



The Challenge

Q: So why don't we have such languages already?

A: Technical challenges?

- while they exist, we don't think this is the main issue...

A: Due to a lack of...

- ...long-term efforts
- ...resources
- ...community will
- ...co-design between developers and users
- ...patience

Chapel is our attempt to reverse this trend



Chapel: Putting the “We” back in HPC Programming

Brad Chamberlain, Chapel Team, Cray Inc.

ATPESC 2016
August 3rd, 2016



What is Chapel?

Chapel: A productive parallel programming language

- extensible
- portable
- open-source
- a collaborative effort
- a work-in-progress

Goals:

- Support general parallel programming
 - “any parallel algorithm on any parallel hardware”
- Make parallel programming far more productive



What does “Productivity” mean to you?

Recent Graduates:

“something similar to what I used in school: Python, Matlab, Java, ...”

Seasoned HPC Programmers:

“that sugary stuff that I don’t need because I ~~was born to suffer~~
want full control
to ensure performance”

Computational Scientists:

“something that lets me express my parallel computations
without having to wrestle with architecture-specific details”

Chapel Team:

“something that lets computational scientists express what they want,
without taking away the control that HPC programmers need,
implemented in a language as attractive as recent graduates want.”




STREAM Triad: a trivial parallel computation

Given: m -element vectors A, B, C

Compute: $\forall i \in 1..m, A_i = B_i + \alpha \cdot C_i$

In pictures:




STREAM Triad: a trivial parallel computation

Given: m -element vectors A, B, C

Compute: $\forall i \in 1..m, A_i = B_i + \alpha \cdot C_i$

In pictures, in parallel:




STREAM Triad: a trivial parallel computation

Given: m -element vectors A, B, C

Compute: $\forall i \in 1..m, A_i = B_i + \alpha \cdot C_i$

In pictures, in parallel (distributed memory):




STREAM Triad: a trivial parallel computation

Given: m -element vectors A, B, C

Compute: $\forall i \in 1..m, A_i = B_i + \alpha \cdot C_i$

In pictures, in parallel (distributed memory multicore):



STREAM Triad: MPI

MPI

```
#include <hpcc.h>

static int VectorSize;
static double *a, *b, *c;

int HPCC_StarStream(HPCC_Parms *params) {
    int myRank, commSize;
    int rv, errCount;
    MPI_Comm comm = MPI_COMM_WORLD;

    MPI_Comm_size( comm, &commSize );
    MPI_Comm_rank( comm, &myRank );


    rv = HPCC_Stream( params, 0 == myRank );
    MPI_Reduce( &rv, &errCount, 1, MPI_INT, MPI_SUM,
                0, comm );

    return errCount;
}

int HPCC_Stream(HPCC_Parms *params, int doIO) {
    register int j;
    double scalar;

    VectorSize = HPCC_LocalVectorSize( params, 3,
                                       sizeof(double), 0 );

    a = HPCC_XMALLOC( double, VectorSize );
    b = HPCC_XMALLOC( double, VectorSize );
    c = HPCC_XMALLOC( double, VectorSize );
}
```



```
if (!a || !b || !c) {
    if (c) HPCC_free(c);
    if (b) HPCC_free(b);
    if (a) HPCC_free(a);
    if (doIO) {
        fprintf( outFile, "Failed to allocate memory
(%d).\n", VectorSize );
        fclose( outFile );
    }
    return 1;
}

for (j=0; j<VectorSize; j++) {
    b[j] = 2.0;
    c[j] = 0.0;
}

scalar = 3.0;

for (j=0; j<VectorSize; j++)
    a[j] = b[j]+scalar*c[j];

HPCC_free(c);
HPCC_free(b);
HPCC_free(a);
```



STREAM Triad: MPI+OpenMP

```
#include <hpcc.h>
#ifndef _OPENMP
#include <omp.h>
#endif

static int VectorSize;
static double *a, *b, *c;

int HPCC_StarStream(HPCC_Parms *params) {
    int myRank, commSize;
    int rv, errCount;
    MPI_Comm comm = MPI_COMM_WORLD;

    MPI_Comm_size( comm, &commSize );
    MPI_Comm_rank( comm, &myRank );

    rv = HPCC_Stream( params, 0 == myRank );
    MPI_Reduce( &rv, &errCount, 1, MPI_INT, MPI_SUM,
                0, comm );

    return errCount;
}

int HPCC_Stream(HPCC_Parms *params, int doIO) {
    register int j;
    double scalar;

    VectorSize = HPCC_LocalVectorSize( params, 3,
                                       sizeof(double), 0 );

    a = HPCC_XMALLOC( double, VectorSize );
    b = HPCC_XMALLOC( double, VectorSize );
    c = HPCC_XMALLOC( double, VectorSize );
}

```

MPI + OpenMP

```
if (!a || !b || !c) {
    if (c) HPCC_free(c);
    if (b) HPCC_free(b);
    if (a) HPCC_free(a);
    if (doIO) {
        fprintf( outFile, "Failed to allocate memory
(%d).\n", VectorSize );
        fclose( outFile );
    }
    return 1;
}

#ifndef _OPENMP
#pragma omp parallel for
#endif
for (j=0; j<VectorSize; j++) {
    b[j] = 2.0;
    c[j] = 0.0;
}

scalar = 3.0;

#ifndef _OPENMP
#pragma omp parallel for
#endif
for (j=0; j<VectorSize; j++)
    a[j] = b[j]+scalar*c[j];

HPCC_free(c);
HPCC_free(b);
HPCC_free(a);

```



STREAM Triad: MPI+OpenMP vs. CUDA

MPI + OpenMP

```
#ifdef _OPENMP
#include <omp.h>
#endif

static int VectorSize;
static double *a, *b, *c;

int HPCC_StarStream(HPCC_Params *params) {
    int myRank, commSize;
    int rv, errCount;
    MPI_Comm comm = MPI_COMM_WORLD;
    MPI_Comm_size( comm, &commSize );
    MPI_Comm_rank( comm, &myRank );
    rv = HPCC_Stream( params, 0 == myRank );
    MPI_Reduce( &rv, &errCount, 1, MPI_INT, MPI_SUM, 0, comm );
    return errCount;
}

int HPCC_Triad(HPCC_Params *params, FILE *outFile)
{
    int i, j, k;
    double scalar;
    VectorSize = HPCC_LocalVectorSize( params, 3, sizeof(double), 0 );
    a = HPCC_XMALLOC( double, VectorSize );
    b = HPCC_XMALLOC( double, VectorSize );
    c = HPCC_XMALLOC( double, VectorSize );
    if (!a || !b || !c) {
        if (c) HPCC_free(c);
        if (b) HPCC_free(b);
        if (a) HPCC_free(a);
        if (doIO) {
            fprintf( outFile, "Failed to allocate memory (%d).\n", VectorSize );
            fclose( outFile );
        }
        return 1;
    }
    #ifdef _OPENMP
    #pragma omp parallel for
    #endif
    for (j=0; j<VectorSize; j++) {
        b[j] = 2.0;
        c[j] = 0.0;
    }
    scalar = 3.0;
    #ifdef _OPENMP
    #pragma omp parallel for
    #endif
    for (j=0; j<VectorSize; j++)
        a[j] = b[j]+scalar*c[j];
    HPCC_free(c);
    HPCC_free(b);
    HPCC_free(a);
    return 0;
}
```

CUDA

```
#define N 2000000

int main() {
    float *d_a, *d_b, *d_c;
    float scalar;

    cudaMalloc((void**)&d_a, sizeof(float)*N);
    cudaMalloc((void**)&d_b, sizeof(float)*N);
    cudaMalloc((void**)&d_c, sizeof(float)*N);

    dim3 dimBlock(128);
    if( N % dimBlock.x != 0 ) dimGrid

    set_array<<<dimGrid,dimBlock>>>(d_b, .5f, N);
    set_array<<<dimGrid,dimBlock>>>(d_c, .5f, N);

    scalar=3.0f;
    STREAM_Triad<<<dimGrid,dimBlock>>>(d_b, d_c, d_a, scalar, N);
    cudaThreadSynchronize();

    cudaFree(d_a);
    cudaFree(d_b);
    cudaFree(d_c);

    __global__ void set_array(float *a, float value, int len) {
        int idx = threadIdx.x + blockIdx.x * blockDim.x;
        if (idx < len) a[idx] = value;
    }

    __global__ void STREAM_Triad( float *a, float *b, float *c,
                                float scalar, int len) {
        int idx = threadIdx.x + blockIdx.x * blockDim.x;
        if (idx < len) c[idx] = a[idx]+scalar*b[idx];
    }
```

COMPUTE

STORE

ANALYZE

Why so many programming models?

HPC tends to approach programming models bottom-up:

Given a system and its core capabilities...

...provide features that can access the available performance.

- portability? generality? programmability? ...not strictly required.

Type of HW Parallelism	Programming Model	Unit of Parallelism
Inter-node	MPI	executable
Intra-node/multicore	OpenMP / pthreads	iteration/task
Instruction-level vectors/threads	pragmas	iteration
GPU/accelerator	CUDA / Open[CL MP ACC]	SIMD function/task

benefits: lots of control; decent generality; easy to implement
downsides: lots of user-managed detail; brittle to changes

Rewinding a few slides...

MPI + OpenMP

```
#ifdef _OPENMP
#include <omp.h>
#endif

static int VectorSize;
static double *a, *b, *c;

int HPCC_StarStream(HPCC_Params *params) {
    int myRank, commSize;
    int rv, errCount;
    MPI_Comm comm = MPI_COMM_WORLD;
    MPI_Comm_size( comm, &commSize );
    MPI_Comm_rank( comm, &myRank );
    rv = HPCC_Stream( params, 0 == myRank );
    MPI_Reduce( &rv, &errCount, 1, MPI_INT, MPI_SUM, 0, comm );
    return errCount;
}

int HPCC_LocalVectorSize(HPCC_Params *params, int len)
{
    double scalar;
    VectorSize = HPCC_LocalVectorSize( params, 3, sizeof(double), 0 );
    a = HPCC_XMALLOC( double, VectorSize );
    b = HPCC_XMALLOC( double, VectorSize );
    c = HPCC_XMALLOC( double, VectorSize );

    if (!a || !b || !c) {
        if (c) HPCC_free(c);
        if (b) HPCC_free(b);
        if (a) HPCC_free(a);
        if (doIO) {
            fprintf( outFile, "Failed to allocate memory (%d).\n", VectorSize );
            fclose( outFile );
        }
        return 1;
    }

    #ifdef _OPENMP
    #pragma omp parallel for
    #endif
    for (j=0; j<VectorSize; j++) {
        b[j] = 2.0;
        c[j] = 0.0;
    }
    scalar = 3.0;

    #ifdef _OPENMP
    #pragma omp parallel for
    #endif
    for (j=0; j<VectorSize; j++)
        a[j] = b[j]+scalar*c[j];

    HPCC_free(c);
    HPCC_free(b);
    HPCC_free(a);
    return 0;
}
```

CUDA

```
#define N 2000000

int main() {
    float *d_a, *d_b, *d_c;
    float scalar;

    cudaMalloc((void**)&d_a, sizeof(float)*N);
    cudaMalloc((void**)&d_b, sizeof(float)*N);
    cudaMalloc((void**)&d_c, sizeof(float)*N);

    dim3 dimBlock(128);
    if( N % dimBlock.x != 0 ) dimGrid

    set_array<<<dimGrid, dimBlock>>>(d_b, .5f, N);
    set_array<<<dimGrid, dimBlock>>>(d_c, .5f, N);

    scalar=3.0f;
    STREAM_Triad<<<dimGrid, dimBlock>>>(d_b, d_c, d_a, scalar, N);
    cudaThreadSynchronize();

    cudaFree(d_a);
    cudaFree(d_b);
    cudaFree(d_c);

    __global__ void set_array(float *a, float value, int len) {
        int idx = threadIdx.x + blockIdx.x * blockDim.x;
        if (idx < len) a[idx] = value;
    }

    __global__ void STREAM_Triad( float *a, float *b, float *c,
                                float scalar, int len) {
        int idx = threadIdx.x + blockIdx.x * blockDim.x;
        if (idx < len) c[idx] = a[idx]+scalar*b[idx];
    }
```

COMPUTE

STORE

ANALYZE

STREAM Triad: Chapel

MPI + OpenMP

```
#include <hpcc.h>
#ifndef _OPENMP
#include <omp.h>
#endif

static int VectorSize;
static double *a, *b, *c;

int HPCC_StarStream(HPCC_Params *params,
int myRank, commSize;
int rv, errCount;
MPI_Comm comm = MPI_COMM_WORLD;
MPI_Comm size( comm, &commSize );
MPI_Comm_rank( comm, &myRank );
rv = HPCC_Stream( params, 0 == myRank );
MPI_Reduce( &rv, &errCount, 1, MPI_
return errCount;
}

int HPCC_Stream(HPCC_Params *params,
register int j;
double scalar;
VectorSize = HPCC_LocalVectorSize();
a = HPCC_XMALLOC( double, VectorSize );
b = HPCC_XMALLOC( double, VectorSize );
c = HPCC_XMALLOC( double, VectorSize );

if (!a || !b || !c) {
    if (c) HPCC_free(c);
    if (b) HPCC_free(b);
    if (a) HPCC_free(a);
    if (doIO) {
        fprintf( outFile, "Failed to allocate memory (%d).\n" VectorSize );
        cudaThreadSynchronize();
        fclose( outFile );
    }
}
```

Chapel

```
config const m = 1000,
alpha = 3.0;


const ProblemSpace = {1..m} dmapped ...;

var A, B, C: [ProblemSpace] real;

B = 2.0;
C = 3.0;

A = B + alpha * C;
```

the special sauce



Philosophy: Good, *top-down* language design can tease system-specific implementation details away from an algorithm, permitting the compiler, runtime, applied scientist, and HPC expert to each focus on their strengths.



COMPUTE

STORE

ANALYZE

Outline

- ✓ Motivation
- Survey of Chapel Concepts
 - Chapel Project and Characterizations
 - Chapel Resources




Chapel's Multiresolution Philosophy

Multiresolution Design: Support multiple tiers of features


- higher levels for programmability, productivity
- lower levels for greater degrees of control

Chapel language concepts



- build the higher-level concepts in terms of the lower
- permit the user to intermix layers arbitrarily

Base Language



Base Language Features, by example

```
iter fib(n) {
    var current = 0,
        next = 1;

    for i in 1..n {
        yield current;
        current += next;
        current <=> next;
    }
}
```

```
config const n = 10;

for f in fib(n) do
    writeln(f);
```

```
0  
1  
1  
2  
3  
5  
8  
...
```

Base Language Features, by example

CLU-style iterators

```
iter fib(n) {
    var current = 0,
        next = 1;

    for i in 1..n {
        yield current;
        current += next;
        current <=gt; next;
    }
}
```

```
config const n = 10;

for f in fib(n) do
    writeln(f);
```

```
0  
1  
1  
2  
3  
5  
8  
...
```

Base Language Features, by example

```
iter fib(n) {
    var current = 0,
        next = 1;

    for i in 1..n {
        yield current;
        current += next;
        current <=> next;
    }
}
```

Configuration declarations
(to avoid command-line argument parsing)
./a.out -n=1000000

```
config const n = 10;

for f in fib(n) do
    writeln(f);
```

```
0
1
1
2
3
5
8
...
...
```

Base Language Features, by example

Static type inference for:

- arguments
- return types
- variables

```
iter fib(n) {
    var current = 0,
        next = 1;

    for i in 1..n {
        yield current;
        current += next;
        current <=gt; next;
    }
}
```

```
config const n = 10;

for f in fib(n) do
    writeln(f);
```

```
0  
1  
1  
2  
3  
5  
8  
...
```

Base Language Features, by example

```
iter fib(n) {
    var current = 0,
        next = 1;

    for i in 1..n {
        yield current;
        current += next;
        current <=> next;
    }
}
```

```
config const n = 10;

for (i,f) in zip(0..#n, fib(n)) do
    writeln("fib #", i, " is ", f);
```

```
fib #0 is 0
fib #1 is 1
fib #2 is 1
fib #3 is 2
fib #4 is 3
fib #5 is 5
fib #6 is 8
...
```

Zippered iteration

Base Language Features, by example

Range types and operators

```
iter fib(n) {  
    var current = 0  
    next = 1;  
  
    for i in 1..n {  
        yield current;  
        current += next;  
        current <=gt; next;  
    }  
}
```

```
config const n = 10;  
  
for (i,f) in zip(0..#n, fib(n)) do  
    writeln("fib #", i, " is ", f);
```

```
fib #0 is 0  
fib #1 is 1  
fib #2 is 1  
fib #3 is 2  
fib #4 is 3  
fib #5 is 5  
fib #6 is 8  
...
```

Base Language Features, by example

```
iter fib(n) {
    var current = 0,
        next = 1;

    for i in 1..n {
        yield current;
        current += next;
        current <=> next;
    }
}
```

tuples

```
config const n = 10;

for (i,f) in zip(0..#n, fib(n)) do
    writeln("fib #", i, " is ", f);
```

```
fib #0 is 0
fib #1 is 1
fib #2 is 1
fib #3 is 2
fib #4 is 3
fib #5 is 5
fib #6 is 8
...
```

Base Language Features, by example

```
iter fib(n) {
    var current = 0,
        next = 1;

    for i in 1..n {
        yield current;
        current += next;
        current <=> next;
    }
}
```

```
config const n = 10;

for (i,f) in zip(0..#n, fib(n)) do
    writeln("fib #", i, " is ", f);
```


```
fib #0 is 0
fib #1 is 1
fib #2 is 1
fib #3 is 2
fib #4 is 3
fib #5 is 5
fib #6 is 8
...
```

Other Base Language Features

- **interoperability features**
- **OOP** (value- and reference-based)
- **overloading, where clauses**
- **argument intents, default values, match-by-name**
- **compile-time features for meta-programming**
 - e.g., compile-time functions to compute types, values; reflection
- **modules** (for namespace management)
- **rank-independent programming features**
- ...



Task Parallelism



Task Parallelism: Begin Statements

```
// create a fire-and-forget task for a statement
begin writeln("hello world");
writeln("goodbye");
```

Possible outputs:

hello world
goodbye

goodbye
hello world

Task Parallelism: Coforall Loops

```
// create a task per iteration
coforall t in 0..#numTasks {
    writeln("Hello from task ", t, " of ", numTasks);
} // implicit join of the numTasks tasks here

writeln("All tasks done");
```

Sample output:

```
Hello from task 2 of 4
Hello from task 0 of 4
Hello from task 3 of 4
Hello from task 1 of 4
All tasks done
```



Task Parallelism: Data-Driven Synchronization

- **atomic variables:** support atomic operations
 - e.g., compare-and-swap; atomic sum, multiply, etc.
 - similar to C/C++

- **sync variables:** store full-empty state along with value
 - by default, reads/writes block until full/empty, leave in opposite state




Other Task Parallel Concepts

- **cobegins**: create tasks using compound statements
- **single variables**: like sync variables, but write-once
- **sync statements**: join unstructured tasks
- **serial statements**: conditionally squash parallelism



Locality Control



The Locale Type

Definition:

- Abstract unit of target architecture
- Supports reasoning about locality
 - defines “here vs. there” / “local vs. remote”
- Capable of running tasks and storing variables
 - i.e., has processors and memory

Typically: A compute node (multicore processor or SMP)



Getting started with locales

- Specify # of locales when running Chapel programs

```
% a.out --numLocales=8
```

```
% a.out -nl 8
```

- Chapel provides built-in locale variables

```
config const numLocales: int = ...;  
const Locales: [0..#numLocales] locale = ...;
```

Locales



- main () starts execution as a task on locale #0

Locale Operations

- Locale methods support queries about the target system:

```
proc locale.physicalMemory(...) { ... }  
proc locale.numCores { ... }  
proc locale.id { ... }  
proc locale.name { ... }
```

- On-clauses support placement of computations:

```
writeln("on locale 0");  
on Locales[1] do  
    writeln("now on locale 1");  
writeln("on locale 0 again");
```

```
on A[i,j] do  
    bigComputation(A);  
  
on node.left do  
    search(node.left);
```

Parallelism and Locality: Orthogonal in Chapel

- This is a **parallel**, but local program:

```
coforall i in 1..msgs do  
    writeln("Hello from task ", i);
```

- This is a **distributed**, but serial program:


```
writeln("Hello from locale 0!");  
on Locales[1] do writeln("Hello from locale 1!");  
on Locales[2] do writeln("Hello from locale 2!");
```

- This is a **distributed parallel** program:

```
coforall i in 1..msgs do  
    on Locales[i%numLocales] do  
        writeln("Hello from task ", i,  
               " running on locale ", here.id);
```

Chapel: Scoping and Locality


```
var i: int;
```



COMPUTE | STORE | ANALYZE


Chapel: Scoping and Locality

```
var i: int;  
on Locales[1] {
```




Chapel: Scoping and Locality

```
var i: int;  
on Locales[1] {  
    var j: int;
```




Chapel: Scoping and Locality

```
var i: int;  
on Locales[1] {  
    var j: int;  
    coforall loc in Locales {  
        on loc {
```



Chapel: Scoping and Locality

```
var i: int;  
on Locales[1] {  
    var j: int;  
    coforall loc in Locales {  
        on loc {  
            var k: int;  
            ...  
        }  
    }  
}
```




Locales (think: "compute nodes")

Chapel: Scoping and Locality

```
var i: int;  
on Locales[1] {  
    var j: int;  
    coforall loc in Locales {  
        on loc {  
            var k: int;  
            k = 2*i + j;  
        }  
    }  
}
```

OK to access i , j , and k wherever they live

$k = 2*i + j;$




Chapel: Scoping and Locality

```
var i: int;  
on Locales[1] {  
    var j: int;  
    coforall loc in Locales {  
        on loc {  
            var k: int;  
            k = 2*i + j;  
        }  
    }  
}
```


here, *i* and *j* are remote, so
the compiler + runtime will
transfer their values

$k = 2*i + j;$




Chapel: Locality queries

```
var i: int;  
on Locales[1] {  
    var j: int;  
    coforall loc in Locales {  
        on loc {  
            var k: int;  
  
            ...here...           // query the locale on which this task is running  
            ...j.locale...      // query the locale on which j is stored  
        }  
    }  
}  
}
```




Reasoning about Communication

- Though implicit, users can reason about communication
 - semantic model is explicit about where data is placed / tasks execute
 - execution-time queries support reasoning about locality
 - e.g., `here`, `x.locale`
 - tools should also play a role here
 - e.g., *chplvis*, contained in the release (developed by Phil Nelson, WWU)




Data Parallelism




Data Parallelism By Example: STREAM Triad

```
const ProblemSpace = {1..m};
```




```
var A, B, C: [ProblemSpace] real;
```



```
forall (a,b,c) in zip(A,B,C) do  
  a = b + alpha*c;
```

Data Parallelism By Example: STREAM Triad

```
const ProblemSpace = {1..m};
```



```
var A, B, C: [ProblemSpace] real;
```



```
A = B + alpha * C; // equivalent to the zippered forall
```

Other Data Parallel Features

- **Rich Domain/Array Types:**

- multidimensional
- strided
- sparse
- associative

- **Slicing:** Refer to subarrays using ranges/domains

```
... A[2..n-1, lo..#b] ...  
... A[ElementsOfInterest] ...
```


- **Promotion:** Call scalar functions with array arguments

```
... pow(A, B) ... // equivalent to: forall (a,b) in zip(A,B) do pow(a,b)
```

- **Reductions/Scans:** Apply operations across collections

```
... + reduce A ...  
... myReduceOp reduce A ...
```

Domain Maps




STREAM Triad: Chapel (multicore)

```
const ProblemSpace = {1..m};
```




```
var A, B, C: [ProblemSpace] real;
```




```
A = B + alpha * C;
```

No domain map specified \Rightarrow use default layout
• current locale owns all domain indices and array values
• computation will execute using local processors only


STREAM Triad: Chapel (multilocale, cyclic)



```
const ProblemSpace = {1..m}
    dmapped Cyclic(startIdx=1);
```




```
var A, B, C: [ProblemSpace] real;
```




```
A = B + alpha * C;
```


STREAM Triad: Chapel (multilocale, blocked)



```
const ProblemSpace = {1..m}
dmapped Block (boundingBox={1..m}) ;
```



```
var A, B, C: [ProblemSpace] real;
```



```
A = B + alpha * C;
```

STREAM Triad: Chapel

MPI + OpenMP

```
#include <hpcc.h>
#ifndef _OPENMP
#include <omp.h>
#endif

static int VectorSize;
static double *a, *b, *c;

int HPCC_StarStream(HPCC_Params *params,
int myRank, commSize;
int rv, errCount;
MPI_Comm comm = MPI_COMM_WORLD;
MPI_Comm size( comm, &commSize );
MPI_Comm_rank( comm, &myRank );
rv = HPCC_Stream( params, 0 == myRank );
MPI_Reduce( &rv, &errCount, 1, MPI_
return errCount;
}

int HPCC_Stream(HPCC_Params *params,
register int j;
double scalar;
VectorSize = HPCC_LocalVectorSize();
a = HPCC_XMALLOC( double, VectorSize );
b = HPCC_XMALLOC( double, VectorSize );
c = HPCC_XMALLOC( double, VectorSize );

if (!a || !b || !c) {
    if (c) HPCC_free(c);
    if (b) HPCC_free(b);
    if (a) HPCC_free(a);
    if (doIO) {
        fprintf( outFile, "Failed to allocate memory (%d).\n" VectorSize );
        cudaThreadSynchronize();
        fclose( outFile );
    }
}
```

Chapel

```
config const m = 1000,
alpha = 3.0;


const ProblemSpace = {1..m} dmapped ...;

var A, B, C: [ProblemSpace] real;

B = 2.0;
C = 3.0;



A = B + alpha * C;
```

the special sauce






Philosophy: Good, *top-down* language design can tease system-specific implementation details away from an algorithm, permitting the compiler, runtime, applied scientist, and HPC expert to each focus on their strengths.

Chapel Has Several Domain/Array Types




LULESCH: a DOE Proxy Application


Goal: Solve one octant of the spherical Sedov problem (blast wave) using Lagrangian hydrodynamics for a single material



pictures courtesy of Rob Neely, Bert Still, Jeff Keasler, LLNL



LULESCH in Chapel



COMPUTE

STORE

ANALYZE

LULESCH in Chapel

1288 lines of source code

plus 266 lines of comments
 487 blank lines

(the corresponding C+MPI+OpenMP version is nearly 4x bigger)

This can be found in the Chapel release in examples/benchmarks/lulesh/



COMPUTE

STORE

ANALYZE

LULESCH in Chapel

This is the only representation-dependent code.
It specifies:


- data structure choices:
 - structured vs. unstructured mesh
 - local vs. distributed data
 - sparse vs. dense materials arrays
- a few supporting iterators

Domain maps insulate the rest of the application
("the science") from these choices




Domain Maps

Domain maps are “recipes” that instruct the compiler how to map the global view of a computation...




...to the target locales' memory and processors:



Chapel's Domain Map Philosophy

- 1. Chapel provides a library of standard domain maps**
 - to support common array implementations effortlessly
- 2. Expert users can write their own domain maps in Chapel**
 - to cope with any shortcomings in our standard library



- 3. Chapel's standard domain maps are written using the same end-user framework**
 - to avoid a performance cliff between “built-in” and user-defined cases

Two Other Thematically Similar Features

1) **parallel iterators:** Permit users to specify forall-loop policies

- e.g., parallelism, work decomposition, and locality
 - including zippered forall loops

2) **locale models:** Permit users to target new architectures

- e.g., how to manage memory, create tasks, communicate, ...

Like domain maps, these are...

...written in Chapel by expert users

...exposed to the end-user via higher-level abstractions

Chapel is Extensible

Advanced users can create their own...

- ...parallel loop schedules...
- ...array layouts and distributions...
- ...models of the target architecture...

...as Chapel code, without modifying the compiler.

Why? To create a future-proof language.

This has been our main research challenge: How to create a language that does not lock these policies into the implementation without sacrificing performance?

Language Summary

HPC programmers deserve better programming models

Higher-level programming models can help insulate algorithms from parallel implementation details

- yet, without necessarily abdicating control
- Chapel does this via its multiresolution design
 - domain maps, parallel iterators, and locale models are all examples
 - avoids locking crucial policy decisions into the language definition

We believe Chapel can greatly improve productivity

...for current and emerging HPC architectures

...for HPC users and mainstream uses of parallelism at scale



Outline

- ✓ Motivation
- ✓ Survey of Chapel Concepts
- Chapel Project and Characterizations
- Chapel Resources



A Year in the Life of Chapel

- **Two major releases per year** (April / October)
 - ~a month later: detailed release notes available online
- **CHIUW: Chapel Implementers and Users Workshop** (May/June)
 - held three years so far, typically at IPDPS
 - CHIUW 2017 proposal being submitted this week
- **SC** (Nov)
 - tutorials, BoFs, panels, posters, educator sessions, exhibits, ...
 - annual **CHUG** (Chapel Users Group) happy hour
 - for **SC16**:
 - full-day **Chapel tutorial** (Sunday)
 - **Chapel Lightning Talks BoF** proposal submitted
 - likely to be additional events as well...
- **Talks, tutorials, collaborations, social media, ...** (year-round)



Chapel is Portable

- Chapel is designed to be hardware-independent
- The current release requires:
 - a C/C++ compiler
 - a *NIX environment (Linux, OS X, BSD, Cygwin, ...)
 - POSIX threads
 - RDMA, MPI, or UDP (for distributed memory execution)
- Chapel can run on...
 - ...laptops and workstations
 - ...commodity clusters
 - ...the cloud
 - ...HPC systems from Cray and other vendors
 - ...modern processors like Intel Xeon Phi, GPUs*, etc.

* = academic work only; not yet supported in the official release

Chapel is Open-Source


- Chapel's development is hosted at GitHub
 - <https://github.com/chapel-lang>
- Chapel is licensed as Apache v2.0 software
- Instructions for download + install are online
 - see <http://chapel.cray.com/download.html> to get started

The Chapel Team at Cray (Summer 2016)





Chapel is a Collaborative Effort



THE GEORGE
WASHINGTON
UNIVERSITY
WASHINGTON, DC



Lawrence Berkeley
National Laboratory



(and several others...)

<http://chapel.cray.com/collaborations.html>



COMPUTE

STORE

ANALYZE

Chapel is a Work-in-Progress

- **Currently being picked up by early adopters**
 - Last two releases got ~3500 downloads total in a year
 - Users who try it generally like what they see
- **Most current features are functional and working well**
 - some areas need improvements, particularly object-oriented features
- **Performance is improving, but remains hit-or-miss**
 - shared memory performance is often competitive with C+OpenMP
 - distributed memory performance continues to need more work
- **We are actively working to address these lacks**

A notable early adopter

Chapel in the (Cosmological) Wild

1:00 – 2:00

Nikhil Padmanabhan, Yale University Professor, Physics & Astronomy

Abstract: This talk aims to present my personal experiences using Chapel in my research. My research interests are in observational cosmology; more specifically, I use large surveys of galaxies to constrain the evolution of the

The image shows a screenshot of a YouTube search results page. At the top, the YouTube logo is visible along with a search bar containing the text "Search". Below the search bar, there is a navigation menu with options: "Videos", "Playlists", and "Channels". On the left side, there is a thumbnail for a video titled "CHIUW 2016 keynote: "Chapel in the (Cosmological) Wild", Nikhil Padmanabhan". The thumbnail shows a man standing in front of a projection screen displaying a complex, multi-colored visualization. The video duration is indicated as "56:14". The main title of the video is "CHIUW 2016 keynote: "Chapel in the (Cosmological) Wild", Nikhil Padmanabhan". Below the title, it says "Chapel Parallel Programming Language". Underneath that, it indicates the video was posted "1 month ago" and has "86 views". A descriptive text block below the video summary states: "This is Nikhil Padmanabhan's keynote talk from CHIUW 2016: the 3rd Annual Chapel Implementers and Users workshop. The slides are availabl...".

Chapel is a Work-in-Progress

- **Currently being picked up by early adopters**
 - Last two releases got ~3500 downloads total in a year
 - Users who try it generally like what they see
- **Most current features are functional and working well**
 - some areas need improvements, particularly object-oriented features
- **Performance is improving, but can be hit-or-miss**
 - shared memory performance is often competitive with C+OpenMP
 - distributed memory performance continues to need more work
- **We are actively working to address these lacks**



Chapel's 5-year push

- Based on positive user response to Chapel in its research phase, Cray undertook a five-year effort to improve it
 - we've just completed our third year
- Focus Areas:
 1. Improving **performance** and scaling
 2. **Fixing** immature aspects of the language and implementation
 - e.g., strings, memory management, error handling, ...
 3. **Porting** to emerging architectures
 - Intel Xeon Phi, accelerators, heterogeneous processors and memories, ...
 4. Improving **interoperability**
 5. Growing the Chapel user and developer **community**
 - including non-scientific computing communities
 6. Exploring transition of Chapel **governance** to a neutral, external body



Outline

- ✓ Motivation
- ✓ Survey of Chapel Concepts
- ✓ Chapel Project and Characterizations
- Chapel Resources



Chapel Websites

Project page: <http://chapel.cray.com>


- overview, papers, presentations, language spec, ...

GitHub: <https://github.com/chapel-lang>

- download Chapel; browse source repository; contribute code

Facebook: <https://www.facebook.com/ChapelLanguage>


Twitter: <https://twitter.com/ChapelLanguage>



The screenshot shows the Chapel Programming Language Facebook page. It features a large green and blue 'C' logo. The page highlights include:

- Syntactic constructs for creating task parallelism: `coforall` (concurrent `forall`): creates a task per iteration.
- Control over locality/affinity: `onLoc`: on-clauses; data-driven migration of tasks.
- Static type inference (optionally): Supports programmability with performance.
- Modules for namespace management: `use`; `extern` and `import` provide static distributions.
- Chapel Programming Language** Computers/Technology

A central callout box contains the text: "Chapel Programming Language is on Facebook. To connect with Chapel Programming Language, sign up for Facebook today." Below this are snippets of Chapel code and terminal output showing task execution.



The screenshot shows the Chapel Language Twitter account (@ChapelLanguage). It has 4 tweets, 1 follower, and 19 following. A recent tweet from March 8, 2016, states: "Chapel is a productive parallel programming language designed for large-scale computing whose development is being led by @cray_inc". It includes a link to chapel.sourceforge.net/perf/chapcs/. Below the tweet is a line graph titled "Binary Trees Shootout Benchmark (n=20)" comparing memory allocators: `binary-trees_jemalloc`, `binary-trees_tcmalloc`, and `binary-trees-freeWithLocking`.



COMPUTE


STORE

ANALYZE

Suggested Reading

Chapel chapter from *Programming Models for Parallel Computing*

- a detailed overview of Chapel's history, motivating themes, features
- published by MIT Press, November 2015
- edited by Pavan Balaji (Argonne)
- chapter is now also available [online](#)



Other Chapel papers/publications available at <http://chapel.cray.com/papers.html>

Chapel Blog Articles

[Chapel: Productive Parallel Programming](#), Cray Blog, May 2013.

- *a short-and-sweet introduction to Chapel*

[Chapel Springs into a Summer of Code](#), Cray Blog, April 2016.

- *coverage of recent events*

[Six Ways to Say “Hello” in Chapel](#) (parts [1](#), [2](#), [3](#)), Cray Blog, Sep-Oct 2015.

- *a series of articles illustrating the basics of parallelism and locality in Chapel*

[Why Chapel?](#) (parts [1](#), [2](#), [3](#)), Cray Blog, Jun-Oct 2014.

- *a series of articles answering common questions about why we are pursuing Chapel in spite of the inherent challenges*

[\[Ten\] Myths About Scalable Programming Languages](#), IEEE TCSC Blog (index available on [chapel.cray.com](#) “blog articles” page), Apr-Nov 2012.

- *a series of technical opinion pieces designed to argue against standard reasons given for not developing high-level parallel languages*

Chapel Mailing Lists

low-traffic / read-only:

chapel-announce@lists.sourceforge.net: announcements about Chapel

community lists:

chapel-users@lists.sourceforge.net: user-oriented discussion list

chapel-developers@lists.sourceforge.net: developer discussions

chapel-education@lists.sourceforge.net: educator discussions

chapel-bugs@lists.sourceforge.net: public bug forum

(subscribe at SourceForge: <http://sourceforge.net/p/chapel/mailman/>)

To contact the Cray team:

chapel_info@cray.com: contact the team at Cray

chapel_bugs@cray.com: for reporting non-public bugs



Chapel: Productive, Multiresolution Parallel Programming

Questions?



COMPUTE

| STORE

| ANALYZE

Legal Disclaimer

Information in this document is provided in connection with Cray Inc. products. No license, express or implied, to any intellectual property rights is granted by this document.

Cray Inc. may make changes to specifications and product descriptions at any time, without notice.

All products, dates and figures specified are preliminary based on current expectations, and are subject to change without notice.

Cray hardware and software products may contain design defects or errors known as errata, which may cause the product to deviate from published specifications. Current characterized errata are available on request.

Cray uses codenames internally to identify products that are in development and not yet publically announced for release. Customers and other third parties are not authorized by Cray Inc. to use codenames in advertising, promotion or marketing and any use of Cray Inc. internal codenames is at the sole risk of the user.

Performance tests and ratings are measured using specific systems and/or components and reflect the approximate performance of Cray Inc. products as measured by those tests. Any difference in system hardware or software design or configuration may affect actual performance.

The following are trademarks of Cray Inc. and are registered in the United States and other countries: CRAY and design, SONEXION, and URIKA. The following are trademarks of Cray Inc.: ACE, APPRENTICE2, CHAPEL, CLUSTER CONNECT, CRAYPAT, CRAYPORT, ECOPHLEX, LIBSCI, NODEKARE, THREADSTORM. The following system family marks, and associated model number marks, are trademarks of Cray Inc.: CS, CX, XC, XE, XK, XMT, and XT. The registered trademark LINUX is used pursuant to a sublicense from LMI, the exclusive licensee of Linus Torvalds, owner of the mark on a worldwide basis. Other trademarks used in this document are the property of their respective owners.





CRAY
THE SUPERCOMPUTER COMPANY