
PIPELINE LANGUAGE RESOURCE MANUAL

BY TEAM PIPE DREAM:
BRANDON BAKHSHAI (BAB2209)
BEN LAI (BL2633)
JEFFREY SERIO (JJS2240)
SOMYA VASUDEVAN (SV2500)

Contents

Introduction	iii
1 Chapter	1
1.1 Section	1
1.1.1 subsection	1
2 Data Types	2
2.1 Primitive Types	2
2.2 Complex Types	2
3 Lexical Conventions	3
3.1 Identifiers	3
3.2 Literals	3
3.3 Tokens	3
3.4 Punctuation	3
4 Expressions and Operatos	4
4.1 Assignment	4
4.2 Arithmetic Operations	4
4.3 Boolean Expressions	4
4.4 Pointers and References	4
4.5 Array access	4
4.6 Operator Precedence and Associativity	4
5 Statements	5
5.1 Declaration	5
5.2 Expressions and Assignment	5
5.3 Control Flow	5
5.3.1 Conditionals	5
5.3.2 Loops	5
6 Functions and the Standard Library	6
6.1 Anatomy of a Function	6
6.1.1 Declaration	6
6.1.2 Definition	6
6.1.3 Return values	6
6.1.4 Function in a pipeline	6
6.2 Built-in Functions	6
6.3 Standard Library	6

7	Asynchronous Programming with Pipeline	7
7.1	My First Pipeline	7
7.2	And Then There Were Two	7
7.3	Brief Summary of the Architecture?	8
8	Tools for Web Developement	9
8.1	Comprehensive List of Tools for Web Development	9
8.1.1	subsection	9
A	Chapter	10
A.1	Section	10
A.1.1	subsection	10

Introduction

This is some text

Chapter 1

Chapter

This is some text

1.1 Section

1.1.1 subsection

subsubsection

Chapter 2

Data Types

This is some text

2.1 Primitive Types

2.2 Complex Types

Chapter 3

Lexical Conventions

3.1 Identifiers

3.2 Literals

3.3 Tokens

3.4 Punctuation

Chapter 4

Expressions and Operatos

4.1 Assignment

4.2 Arithmetic Operations

4.3 Boolean Expressions

4.4 Pointers and References

4.5 Array access

4.6 Operator Precedence and Associativity

Chapter 5

Statements

5.1 Declaration

5.2 Expressions and Assignment

5.3 Control Flow

5.3.1 Conditionals

5.3.2 Loops

Chapter 6

Functions and the Standard Library

6.1 Anatomy of a Function

6.1.1 Declaration

6.1.2 Definition

6.1.3 Return values

6.1.4 Function in a pipeline

6.2 Built-in Functions

6.3 Standard Library

Chapter 7

Asynchronous Programming with Pipeline

Async control flow is incredibly useful when dealing with I/O operations, which are the foundation of web-based programming. When restricted to a single-threaded and single-process model, I/O operations in a programming language are blocking and a program can wait for an unbounded time. Introduce multi-threading or multi-process models, and a programming language becomes much more complex. The single-threaded asynchronous control flow model simplifies dealing with I/O operations such that the program does not halt because of them.

7.1 My First Pipeline

Consider the following example pipeline:

```
readFile('/home/user/you/data.txt')  
| processData(_)  
| saveProcessedData(_, '/home/user/you/processedData.txt')
```

Formally, the definition of a pipeline is as such:

```
function0(Type param0, ..., Type paramN) |  
function1(_, Type param0, ..., Type paramN) |  
function2(_, Type param0, ..., Type paramN) | ... |  
functionN(_, Type param0, ..., Type paramN)
```

How to interpret the above: "Type" references some actual type "Type param1, ..., Type paramN" references some (potentially zero-length) sequence of parameters to a function "_" acts as a placeholder for whatever value will be provided by the function one to the left in the pipeline

Note that:

The first function in the pipeline, function0, has no placeholder "_" because it has no function one to the left from which to take a value. The sequence of parameters can be of any finite length, including zero.

7.2 And Then There Were Two

Consider the terms "pipelineX" to refer to a sequence of functions arranged in a pipeline as detailed in the section "My First Pipeline," where X is a number serving as a unique ID for the pipeline. Now consider the two distinct pipelines, "pipeline0" and "pipeline1." Both pipelines contain functions which are blocking, waiting for the results of an I/O operation. The two pipelines are arranged as such in code:

```
pipeline0;
```

```
pipeline1;
```

Let's mimic the flow of a real program as it executes the two lines above. "Pipeline0" is executed and runs until there is a blocking operation. As soon as a blocking operation is encountered, the program moves it off to a worker thread, and then on the main thread continues on to execute "pipeline1."

Now we have a handful of different cases to consider.

7.3 Brief Summary of the Architecture?

Functions in a pipeline do not return. Rather, an entire pipeline may be thought of a series of nested functions, where what might be mistaken for the return value is simply passed as a parameter to the next nested function, and so on.

Therefore, if there is data you wish to manipulate or use after a function yields it, this manipulation/use should be done within the same pipeline.

The same state is kept throughout an entire pipeline

This is some text

Chapter 8

Tools for Web Developement

Pipeline is a language designed for backend web development. As such, there are certain tools necessary for the backend web programmer.

8.1 Comprehensive List of Tools for Web Development

8.1.1 subsection

subsubsection

Appendix A

The Pipe Directive