Small Signal Transistors

TO-92 Case (Continued)



TYPE NO.	DESCRIPTION	LEAD	V _{CBO}	V _{CEO}	V _{EBO}	I _{CBO} @ (nA)	V _{CB}	h _{FE} @V _{CE}		@V _{CE}	@I _C	V _{CE} (SAT)@IC		c _{ob}	fT	NF	t _{off}
			(V)	(V)	(V)	*ICES	(V)		*hFE	(V)	(mA)	(V)	(mA)	(pF)	(MHz)	(dB)	
			MIN	*V _{CES}	MIN	*ICEV MAX		MIN	(1kHZ) MAX					*C _{rb}	*TYP MIN	MAX	MAX
PN3641	NPN AMPL/SWITCH	EBC	60	30	5.0	50*	50	40	120	10	150	0.22	150	8.0	150	IVIAA	150
PN3642	NPN AMPL/SWITCH	EBC	60	45	5.0	50*	50	40	120	10	150	0.22	150	8.0	150		150
PN3643	NPN AMPL/SWITCH	EBC	60	30	5.0	50*	50	100	300	10	150	0.22	150	8.0	250		150
PN3644	PNP AMPL/SWITCH	EBC	45	45	5.0	35*	30	100	300	10	150	1.0	300	8.0	200		100
PN3645	PNP AMPL/SWITCH	EBC	60	60	5.0	35*	50	100	300	10	150	1.0	300	8.0	200		100
PN3646	NPN SAT SWITCH	EBC	40	15	5.0	500*	20	30	120	0.40	30	0.50	300	5.0	350		28
PN3694	NPN AMPL/SWITCH	EBC	45	45	4.0	50	30	100	400	10	10			6.0	200		
PN4033	PNP AMPL/SWITCH	EBC	80	80	5.0	50	60	100	300	5.0	100	0.5	500	20			50
PN4249	PNP LOW NOISE	EBC	60	60	5.0	10	40	100	300	5.0	0.10	0.25	10	6.0	40	3.0	
PN4250A	PNP LOW NOISE	EBC	60	60	5.0	10	50	250	700	5.0	0.10	0.25	10	6.0	50	2.0	
PN4258	PNP SAT SWITCH	EBC	12	12	4.5	10*	6.0	30	120	3.0	10	0.50	50	3.0	700		20
PN4274	NPN SAT SWITCH	EBC	30	12	4.5	400*	20	35	120	1.0	10	0.50	100	4.0	400		12
PN4275	NPN SAT SWITCH	EBC	40	15	4.5	400*	20	35	120	1.0	10	0.50	100	4.0	400		12
PN4354	PNP AMPL/SWITCH	EBC	60	60	5.0	50	50	50	500	10	10	0.50	500	30	100	3.0	400
PN4355	PNP AMPL/SWITCH	EBC	60	60	5.0	50	50	100	400	10	10	1.0	1,000	30	100	3.0	400
PN4356	PNP AMPL/SWITCH	EBC	80	80	5.0	50	50	50	250	10	10	0.50	500	30	100	3.0	400
PN4916	PNP AMPL/SWITCH	EBC	30	30	5.0	25	15	70	200	1.0	10	0.30	50	4.5	400	4.0	
PN4917	PNP AMPL/SWITCH	EBC	30	30	5.0	25	15	150	300	1.0	10	0.30	50	4.5	450	4.0	
PN5127	NPN AMPL/SWITCH	EBC	20	12	3.0	50	10	15	300	10	2.0	0.30	10	3.5	150		
PN5128	NPN AMPL/SWITCH	EBC	15	12	3.0	50	10	35	350	10	50	0.25	150	10	150		
PN5129	NPN AMPL/SWITCH	EBC	15	12	3.0	50	10	35	350	10	50	0.25	150	10			
PN5130	NPN RF OSC	EBC	30	12	1.0	50	10	15	250	10	8.0	0.60	10	1.7		400	
PN5131	NPN AMPL/SWITCH	EBC	20	15	3.0	50	10	30	50	1.0	10	1.0	10	6.0	100		
PN5132	NPN AMPL/SWITCH	EBC	20	20	3.0	50	10	30	400	10	10	2.0	10	3.5	200	4.0	
PN5133	NPN LOW NOISE	EBC	20	18	3.0	50	15	60	1,000	5.0	1.0	0.40	1.0	5.0	40		
PN5134	NPN SAT SWITCH	EBC	20	10	3.5	10,000	15	20	150	1.0	10	0.25	10	4.0			18
PN5135	NPN AMPL/SWITCH	EBC	30	25	4.0	300	15	50	600	10	10	1.0	100	25	40		
PN5136	NPN AMPL/SWITCH	EBC	30	20	3.0	100	20	20	400	1.0	150	0.25	150	35	40		
PN5137	NPN AMPL/SWITCH	EBC	30	20	3.0	100	20	20	400	1.0	150	0.25	150	35	40		
PN5138	PNP AMPL/SWITCH	EBC	30	30	5.0	50	20	50	800	10	0.10	0.30	10	7.0	30		
PN5139	PNP AMPL/SWITCH	EBC	20	20	5.0	50*	15	40		1.0	10	0.50	50	5.0	300		200
PN5142	PNP AMPL/SWITCH	EBC	20	20	4.0	50*	12	30		1.0	50	2.0	300	10			200
PN5143	PNP AMPL/SWITCH	EBC	20	20	4.0	50*	12	30		1.0	50	2.0	300	10			200
PN5825	NPN AMPL/SWITCH	EBC	50	40	5.0	50	40	100	200	5.0	2.0	0.125	10	4.0	90		
PN5826	NPN AMPL/SWITCH	EBC	50	40	5.0	50	40	150	300	5.0	2.0	0.125	10	4.0	90		
PN5827	NPN AMPL/SWITCH	EBC	50	40	5.0	50	40	250	500	5.0	2.0	0.125	10	4.0	90		
PN5828	NPN AMPL/SWITCH	EBC	50	40	5.0	50	40	400	800	5.0	2.0	0.125	10	4.0	90		
PN5910	PNP SAT SWITCH	EBC	20	20	4.5	10*	10	30	120	0.30	10	0.50	50	3.0	700		20
PN6010	NPN AMPL/SWITCH	EBC	50	40	5.0	10	25	100	300	1.0	10	0.50	500	10	105	5.0	400

Devices are available lead formed, See pages 216 thru 219 for details. Also available in Ammopack or Tape & Reel, See pages 230 thru 235 for details.



(1-March 2012)

OUTSTANDING SUPPORT AND SUPERIOR SERVICES



PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- · Inventory bonding
- · Consolidated shipping options

- · Custom bar coding for shipments
- · Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- · Custom electrical curves
- Environmental regulation compliance
- · Customer specific screening
- · Up-screening capabilities

- · Special wafer diffusions
- · PbSn plating options
- Package details
- · Application notes
- · Application and design sample kits
- · Custom product and package development

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp. 145 Adams Avenue Hauppauge, NY 11788 USA Main Tel: (631) 435-1110

Main Fax: (631) 435-1824

Support Team Fax: (631) 435-3388 www.centralsemi.com

Worldwide Field Representatives: www.centralsemi.com/wwreps

Worldwide Distributors:

www.centralsemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centralsemi.com/terms

www.centralsemi.com (000)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Central Semiconductor:

PN3644 PN4249 PN5139 PN5133 PN5138 LEADFREE