

NANYANG TECHNOLOGICAL UNIVERSITY

Suggested Solutions

MH1401/CY1401 - Algorithms and Computing I

November 2016

TIME ALLOWED: 120 MINUTES

INSTRUCTIONS TO CANDIDATES

1. This examination paper contains **FOUR (4)** questions and comprises **SIX (6)** printed pages.
2. Answer **all** questions. The marks for each question are indicated at the beginning of each question.
3. Answer each question beginning on a **FRESH** page of the answer book.
4. This **IS NOT** and **OPEN BOOK** exam.
5. This paper has been converted from the original MATLAB exam to a PYTHON exam. All questions are the property of Nanyang Technological University.

Contents

Solutions (Brandon)	1
Solutions (Camille)	7

Suggested Solutions (Brandon)

QUESTION 1.

(28 marks)

- (a) `x = -1`
`while(x <= 0):`
`x = int(input("Input a positive integer"))`
- (b) 0
- (c) 18
- (d) `if x < -3 or x >= 3:`
`y = f(x,1)`
`else:`
`if x < 0:`
`y = f(x,3)`
`else:`
`if x == 0:`
`y = f(x,4)`
`else:`
`y = f(x,2)`

QUESTION 2.**(24 marks)**

```
(i) def income_tax(income):
    if income <= 20000:
        return 0
    elif income <= 40000:
        return 0.05 * income
    elif income <= 100000:
        return 0.1 * income
    elif income <= 200000:
        return 0.15 * income
    else:
        return 0.2 * income

(ii) def income_tax_sg(income):
    if income <= 20000:
        return 0
    elif income <= 40000:
        return 0.05 * (income-20000)
    elif income <= 100000:
        return 0.05 * 20000 + 0.1 * (income - 60000)
    elif income <= 200000:
        return 0.05 * 20000 + 0.1 * 60000 + 0.15 * \
            (income - 100000)
    else:
        return 0.05 * 20000 + 0.1 * 60000 + 0.15 * 100000 + \
            0.2 * (income - 200000)

# The '\' character splits code into multiple lines (making it
# more readable)
```

QUESTION 3.

(24 marks)

```
(i) def newton_sqrt(X,n):
    if X < 0 or n <= 0:
        return -1;
    if n == 1:
        R1 = 10;
        return R1;
    else:
        out = newton_sqrt(X,n-1)
        Rx = 0.5 * (out + X) / out
        return Rx;
```

*# Note that if they did not ask for recursion,
we can use the following for loop instead:*

```
# Non-recursion method:
def newton_sqrt(X,n):
    R1 = 10
    for i in range(1,n+1):
        if i-1 == 0:
            Rx = R1
        else:
            Rx = 0.5 * (R1 + x) / R1
            R1 = Rx
    return Rx
```

```
(ii) def newton_sqrt_approx(X,a):
    import math
    i = 0;
    dist=a+1;
    while (i <= 0 or dist > a):
        i+=1;
        temp = newton_sqrt(X,i)
        if temp == -1:
            return (-1,0)
        else:
            dist = abs(math.sqrt(X)-(newton_sqrt(X,i)))
    return (i,dist)
```

"""

The above implementation works by adding these lines:

x=int(input("Input a non-negative number X: "))

```

a=float(input("Input a positive number a: "))
(n,dist) = newton_sqrt_approx(x,a)
if n == -1:
    print("Invalid input(s)!")
else:
    print("%d iterations required, distance = %.6f" % \
(n,dist))
"""

```

QUESTION 4.**(24 marks)**

```
(i) def check_move(x,y):
    if x == []:
        return -1
    elif y== []:
        return 0
    elif x[-1] > y[-1]:
        return -1
    else:
        return 0

(ii) def check_victory(x):
    if len(x) != 5:
        return -1
    else:
        for i in range(len(x)-1):
            if x[i] <= x[i+1]:
                return -1
    return 0
```

```

(iii) vectorofrods = [[5,4,3,2,1],[],[]]
win = -1;
while(win != 0):
    movevalid = -1
    while (movevalid != 0):
        movefrom = int(input( \
            "Which rod do you want to move the disc from? "))
        moveto = int(input( \
            "Which rod do you want to move the disc to? "))
        movevalid = check_move(vectorofrods[movefrom],\
            vectorofrods[moveto])
        if (movevalid != 0):
            print("Invalid move, try again!\n")
            print("Current rod list:", vectorofrods)
        else:
            vectorofrods[moveto].append( \
                vectorofrods[movefrom].pop())
            print("Current rod list:", vectorofrods)
    win = check_victory(vectorofrods[moveto])
print("Congratulations to you for finishing MH1401!")

"""
Part (i), (ii), (iii) is a working implementation of
Tower of Hanoi. You can play it by copying the code
into Spyder and running it!

Good luck! :)
"""

```


Suggested Solutions (Camille)