

Figure 1: An single training example for predicting turbulent flow. Twenty frames of history are given at a single 50px by 50px region r of the turbulent flow and the network must predict the flow at the next time-step in the same region r .




Figure 2: (Left) Ground truth validation section of turbulent flow. (Remaining) Prediction of turbulent flow over, 1×10^8 , 2×10^8 , 3×10^8 , 4×10^8 , 5×10^8 training batches respectively. Despite never training on this window, the network is able to predict turbulent flow well for a single future time-step.

1 Previous Work

Previously, we constructed a data-pipeline that enables quickly taking continuous sections of the turbulent flow sequence while also calculating an approximate derivative with respect to the flow using finite differences.

2 Current Work

In this period we developed deep networks capable of predicting turbulence over a 2D flow generated in a shallow electrolyte layer. These networks predict turbulent flow well using only a single convolution over the history resulting in a latent embedding of only 125 features (5 features over a 5x5 grid see figure 1 or section 2.1 for more information.) Additionally we see that the prediction error is not strongly correlated with the edges of a region, which we would observe if the network was simply using local features. This suggests that the network has learned some non-local features over the entire turbulence trajectory.

2.1 Formulation

Let $P_t \in \mathbb{R}^{360 \times 279}$ be the turbulent flow at time $t \in \{1, 2, \dots, 1000\}$ and define a window $w_{(r,t)}$ of P_t in terms of a 50px by 50px region $r \in \{(u, v) \mid u \in \{0, \dots, 309\}, v \in \{0, \dots, 228\}\}$. For a particular region and time $(r, t) \in (\mathbb{R}^2, \mathbb{R})$ the input x is a series of windows in the past, given by:

$$x = \{w_{(r,i)} \mid t - 20 \leq i \leq t - 1\} \in \mathbb{R}^{50 \times 50 \times 20}$$

and our target y is a single window of the form:

$$y = \{w_{(r,i)} \mid i = t\} \in \mathbb{R}^{50 \times 50}$$

To train the network we randomly sample 5000 region, time pairs $S_i = \{(r, t) \mid i \in \{0, 1, \dots, 4999\}\}$ and withhold 500 for validation creating two datasets, $X_{val} = \{w_{(S_i)} \mid i < 500\}$ and $X_{train} = \{w_{(S_i)} \mid i \geq 500\}$. We then learn a convolutional network $f(x)$ to minimize the huber loss, $L(y, f(x))$ given by:

$$L(y, f(x)) = \begin{cases} \max(0, 1 - y f(x))^2 & \text{for } y f(x) \geq -1, \\ -4y f(x) & \text{otherwise.} \end{cases}$$

The network $f(x)$ is composed of a convolutional layer with 5 filters of size of 10px x 10px, and a filter stride of 5, proceeding a fully connected layer mapping the 125 convolutional features to 2500 (50 x 50) outputs \hat{y} . Training is conducted over 5×10^8 batches using the TensorFlow back-end and Adam optimizer.

2.2 Results

The network is able to achieve an average loss $L(y, f(x)) \leq 0.001$ and as shown in figure 2, the predicted turbulent flow matches the true distribution closely. Additionally, by observing the mean absolute difference, $\overline{Y_{(s_i)} - f(X_{(s_i)})}$ as shown in figure 3, we see that the predictive error is relatively uniform and not concentrated along the edges of the window. This demonstrates that

3 Future Work

Currently this architecture predicts a single time step from a history of twenty, in future work we aim to roll out the network using recurrent layers enabling the prediction of a sequence of turbulent flow from a fixed length of history. We also will begin predicting an entire section S_t from a single window $w_{(r,t)}$, as well as predicting a section S_t from a series of windows in the past, $x = \{w_{(r,i)} \mid t - 20 \leq i \leq t - 1\}$.




Figure 3: Mean absolute prediction error over validation set, $\frac{1}{|X_{val}|} \sum_{s_i \in X_{val}} |f(X_{(s_i)}) - Y_{(s_i)}|$, normalized from $[0, 1]$ black to white respectively for visualization. Note the lack of increased error on the edge of the window, suggesting large differences - not observable along the edges of the window - do not increase the prediction error in the current formulation.