Date: 5/19/2017

## POROSITY CALCULATION OF COMPACTED SALT SAMPLE USING VACUUM SEALING METHOD

**Scope:** To determine the bulk specific gravity & porosity of specimen of compacted salt

sample

Apparatus used: Corelok InstroTek, Inc

## **Test Specimen:**

Sample ID: 175\_13 (Oven dried) Sample Type: Salt, Core (Center)

Shape: Cylindrical

## **Calculation:**

Sample (Oven dried) weight in air,  $W_1 = 1014.200 \text{ g}$ Membrane (InstroTek provided) weight,  $W_p = 13.230 \text{ g}$ Sample weight in water (Submerged),  $W_2 = 535.910 \text{ g}$ 

Density of Water (g/cm $^3$ ) for 20.9°C (recorded 0.998 Bulk Specific Gravity of the sample,  $G_b = 2.134$  Using CoreGravity (Software)

So, bulk density,  $D_b = 2.130 \text{ g/cm}^3$ Sample volume,  $V = 476.210 \text{ cm}^3$ 

Figure 1: Salt Sample 175\_13 (Center)





Figure 2: Sample identification

Maximum Specific gravity,  $Gm = \left[W_1/\left(W_1\text{-}W_3\right)\right]x \; \rho_s = 2.157$ 

(Based on calculation for Sample 90\_05, where W3 = sample weight in Silica oil- pores filled with same fluid)

Hence we will assume, Gm = 2.157

% Porosity =  $(1 - G_b/G_m) \times 100 = 1.07\%$ 

## **Results:**

Therefore the sample volume =  $476.210 \text{ cm}^3$ Bulk Specific Gravity,  $G_b = 2.134$ And calculated Porosity = 1.07%