

Configure APACHE

1 = root@server:~# apt install apache2 apache2-doc

2 = Script /etc/apache2/sites-available/000-default.conf:

<VirtualHost *:80>

```
# The ServerName directive sets the request scheme, hostname and port that
# the server uses to identify itself. This is used when creating
# redirection URLs. In the context of virtual hosts, the ServerName
# specifies what hostname must appear in the request's Host: header to
# match this virtual host. For the default virtual host (this file) this
# value is not decisive as it is used as a last resort host regardless.
# However, you must set it for any further virtual host explicitly.
#ServerName www.example.com
```

```
ServerAdmin webmaster@localhost
```

```
DocumentRoot /var/www/html
```

```
# Available loglevels: trace8, ..., trace1, debug, info, notice, warn,
# error, crit, alert, emerg.
# It is also possible to configure the loglevel for particular
# modules, e.g.
#LogLevel info ssl:warn
```

```
ErrorLog ${APACHE_LOG_DIR}/error.log
```

```
CustomLog ${APACHE_LOG_DIR}/access.log combined
```

```
# For most configuration files from conf-available/, which are
# enabled or disabled at a global level, it is possible to
```

```
# include a line for only one particular virtual host. For example the
# following line enables the CGI configuration for this host only
# after it has been globally disabled with "a2disconf".
#Include conf-available/serve-cgi-bin.conf
</VirtualHost>
```

```
#####
#####
```

3 = Verificação Sintaxe Correta

```
root@server:~# apachectl -t
Syntax OK
```

4 = root@server:~# systemctl restart apache2

```
#####
#####
```