QJxx16xHx Series

HF RoHS



Description

This 16A high temperature Alternistor TRIAC, offered in TO-220AB, TO-220 isolated and TO-263 package, has 150°C maximum junction temperature and 200A I_{TSM}(60Hz). This series enables easier thermal management and higher surge handling capability in AC power control applications such as heater control, motor speed control, lighting controls, and static switching relays. Alternistor TRIAC operates in quadrants I, II, & III and offers high performance in applications requiring high commutation capability.

Main Features

Symbol	Value	Unit
$I_{T(RMS)}$	16	A
V_{DRM}/V_{RRM}	400 or 600	V
$I_{GT\ (Q1)}$	10 to 80	mA

Features & Benefits

- High T_J of 150°C
- Voltage capability up to 600V
- Surge capability of 200A at 60Hz half cycle
- Mechanically and thermally robust TO-220 and TO-218 clip-attach assembly
- Internally-isolated TO-220 and TO-218 packages
- Halogen free and RoHS compliant

Schematic Symbol



Applications

TRIAC is an excellent AC switch in applications such as heating, lighting, and motor speed controls.

Typical applications are

- Heater control such as coffee brewer, tankless water heater and infrared heater
- AC solid-state relays
- Light dimmers including incandescent and LED lighting
- Motor speed control in kitchen appliances, power tools, home/brow/white goods and light industrial applications as compressor motor control

Alternistor TRIAC is used with high inductive loads requiring the high commutation capability. Internally isolated packages offer better heat sinking with higher isolation voltage.

Revised: 07/26/17

Absolute Maximum Ratings — Alternistor Triac (3 Quadrants)

Symbol	Parameter			Value	Unit
$I_{T(RMS)}$	RMS on-state current (full sine wave)	QJxx16LHy	T_C = 115 °C	16	A
		QJxx16RHy QJxx16NHy	T_C = 130 °C		
I_{TSM}	Non repetitive surge peak on-state current (Single half cycle, T_J initial = 25°C)	f = 50Hz	t = 20 ms	167	A
		f = 60Hz	t = 16.7 ms	200	
I^2t	I^2t Value for fusing		t_p = 8.3 ms	166	A^2s
di/dt	Critical rate of rise of on-state current	f = 60Hz	T_J = 125 °C	100	A/μs
I_{GTM}	Peak gate trigger current	$t_p \leq$ 10μs; $I_{GT} \leq I_{GTM}$	T_J = 12 5°C	2.0	A
$P_{G(AV)}$	Average gate power dissipation		T_J = 125 °C	0.5	W
T_{stg}	Storage temperature range			-40 to 150	°C
T_J	Operating junction temperature range			-40 to 150	°C
V_{DSM}/V_{RSM}	Peak non-repetitive blocking voltage	Pw=100 μs		V_{DRM}/V_{RRM}+100	V

xx = voltage/10, y = sensitivity

Electrical Characteristics (T_J = 25°C, unless otherwise specified) — Alternistor Triac (3 Quadrants)

Symbol	Test Conditions	Quadrant		QJxx16xH2	QJx16xH3	QJx16xH4	QJx16xH6	Unit
I_{GT}	V_D = 12V R_L = 60Ω	I – II – III	MAX.	10	20	35	80	mA
V_{GT}		I – II – III	MAX.	1.3				V
V_{GD}	$V_D = V_{DRM}$ R_L = 3.3kΩ T_J = 150°C	I – II – III	MIN.	0.15				V
I_H	I_T = 100mA		MAX.	15	35	50	70	mA
dv/dt	$V_D = V_{DRM}$ Gate Open T_J = 150°C	600V	MIN.	-	250	350	850	V/μs
	V_D = 2/3 V_{DRM} Gate Open T_J = 150°C	600V	MIN.	50	300	400	925	
(dv/dt)c	(di/dt)c = 8.6 A/ms T_J = 150°C		MIN.	2	20	25	30	V/μs
t_{gt}	I_G = 2 x I_{GT} PW = 15μs I_T = 22.6 A(pk)		TYP.	3	3	3	5	μs

Static Characteristics

Symbol	Test Conditions			Value	Unit
V_{TM}	I_T = 22.6A t_p = 380μs		MAX	1.60	V
I_{DRM} / I_{RRM}	@ V_{DRM} / V_{RRM}	T_J = 25°C	MAX	5	μA
		T_J = 150°C		4	mA

Thermal Resistances

Symbol	Parameter		Value	Unit
$R_{\theta(J-C)}$	Junction to case (AC)	QJxx16RHy QJxx16NHy	0.90	°C/W
		QJxx16LHy	1.8	
$R_{\theta(J-A)}$	Junction to ambient	QJxx16RHy QJxx16NHy	45	°C/W
		QJxx16LHy	50	

xx = voltage/10; y = sensitivity

Revised: 07/13/17

Figure 1: Definition of Quadrants



Note: Alternistors will not operate in QIV

Figure 2: Normalized DC Gate Trigger Current for All Quadrants vs. Junction Temperature



Figure 3: Normalized DC Holding Current vs. Junction Temperature



Figure 4: Normalized DC Gate Trigger Voltage for All Quadrants vs. Junction Temperature



Figure 5: Power Dissipation (Typical) vs. RMS On-State Current



Figure 6: On-State Current vs. On-State Voltage (Typical)



Revised: 07/13/17

Figure 6: Maximum Allowable Case Temperature vs. RMS On-State Current



Figure 9: Surge Peak On-State Current vs. Number of Cycles



Supply Frequency: 60Hz Sinusoidal
Load: Resistive
RMS On-State [$I_{T(RMS)}$]: Max Rated Value at Specific Case Temperature

Notes:
1. Gate control may be lost during and immediately following surge current interval.
2. Overload may not be repeated until junction temperature has returned to steady-state rated value.

Soldering Parameters

Reflow Condition		Pb – Free assembly
Pre Heat	- Temperature Min ($T_{s(min)}$)	150°C
	- Temperature Max ($T_{s(max)}$)	200°C
	- Time (min to max) (t_s)	60 – 180 secs
Average ramp up rate (Liquidus Temp) (T_L) to peak		5°C/second max
$T_{S(max)}$ to T_L - Ramp-up Rate		5°C/second max
Reflow	- Temperature (T_L) (Liquidus)	217°C
	- Time (t_L)	60 – 150 seconds
Peak Temperature (T_P)		260$^{+0/-5}$ °C
Time within 5°C of actual peak Temperature (t_p)		20 – 40 seconds
Ramp-down Rate		5°C/second max
Time 25°C to peak Temperature (T_P)		8 minutes Max.
Do not exceed		280°C



Revised: 07/13/17

Physical Specifications

Terminal Finish	100% Matte Tin-plated
Body Material	UL Recognized epoxy meeting flammability rating V-0
Terminal Material	Copper Alloy

Design Considerations

Careful selection of the correct component for the application's operating parameters and environment will go a long way toward extending the operating life of the Thyristor. Good design practice should limit the maximum continuous current through the main terminals to 75% of the component rating. Other ways to ensure long life for a power discrete semiconductor are proper heat sinking and selection of voltage ratings for worst case conditions. Overheating, overvoltage (including dv/dt), and surge currents are the main killers of semiconductors. Correct mounting, soldering, and forming of the leads also help protect against component damage.

Environmental Specifications

Test	Specifications and Conditions
AC Blocking	MIL-STD-750, M-1040, Cond A Applied Peak AC voltage @ 150°C for 1008 hours
Temperature Cycling	MIL-STD-750, M-1051, 100 cycles; -40°C to +150°C; 15-min dwell time
Temperature/ Humidity	EIA / JEDEC, JESD22-A101 1008 hours; 160V - DC: 85°C; 85% rel humidity
High Temp Storage	MIL-STD-750, M-1031, 1008 hours; 150°C
Low-Temp Storage	1008 hours; -40°C
Resistance to Solder Heat	MIL-STD-750 Method 2031
Solderability	ANSI/J-STD-002, category 3, Test A
Lead Bend	MIL-STD-750, M-2036 Cond E
Moisture Sensitivity Level	Level 1, JEDEC-J-STD-020

Dimensions — TO-220AB (R-Package) — Non-Isolated Mounting Tab Common with Center Lead



Note: Maximum torque to be applied to mounting tab is 8 in-lbs. (0.904 Nm).

Dimension	Inches		Millimeters	
	Min	Max	Min	Max
A	0.380	0.420	9.65	10.67
B	0.105	0.115	2.66	2.92
C	0.230	0.250	5.84	6.35
D	0.590	0.620	14.99	15.75
E	0.142	0.147	3.61	3.73
F	0.110	0.130	2.79	3.30
G	0.540	0.575	13.72	14.61
H	0.025	0.035	0.64	0.89
J	0.195	0.205	4.95	5.21
K	0.095	0.105	2.41	2.67
L	0.060	0.075	1.52	1.91
M	0.085	0.095	2.16	2.41
N	0.018	0.024	0.46	0.61
O	0.178	0.188	4.52	4.78
P	0.045	0.060	1.14	1.52
R	0.038	0.048	0.97	1.22

Dimensions — TO-220AB (L-Package) — Isolated Mounting Tab





Note: Maximum torque to be applied to mounting tab is 8 in-lbs. (0.904 Nm).

Dimension	Inches		Millimeters	
	Min	Max	Min	Max
A	0.380	0.420	9.65	10.67
B	0.105	0.115	2.67	2.92
C	0.230	0.250	5.84	6.35
D	0.590	0.620	14.99	15.75
E	0.142	0.147	3.61	3.73
F	0.110	0.130	2.79	3.30
G	0.540	0.575	13.72	14.60
H	0.025	0.035	0.64	0.89
J	0.195	0.205	4.95	5.21
K	0.095	0.105	2.41	2.67
L	0.060	0.075	1.52	1.91
M	0.085	0.095	2.16	2.41
N	0.018	0.024	0.46	0.61
O	0.178	0.188	4.52	4.78
P	0.045	0.060	1.14	1.52
R	0.038	0.048	0.97	1.22

Dimensions — TO-263AB (N-Package) — D²Pak Surface Mount





Dimension	Inches		Millimeters	
	Min	Max	Min	Max
A	0.360	0.370	9.14	9.40
B	0.380	0.420	9.65	10.67
C	0.178	0.188	4.52	4.78
D	0.025	0.035	0.64	0.89
E	0.045	0.060	1.14	1.52
F	0.060	0.075	1.52	1.91
G	0.095	0.105	2.41	2.67
H	0.092	0.102	2.34	2.59
J	0.018	0.024	0.46	0.61
K	0.090	0.110	2.29	2.79
S	0.590	0.625	14.99	15.88
V	0.035	0.045	0.89	1.14
U	0.002	0.010	0.05	0.25
W	0.040	0.070	1.02	1.78

Product Selector

Part Number	Voltage		Gate Sensitivity Quadrants	Type	Package
	400V	600V	I – II – III		
QJxx16LH2	X	X	10 mA	Alternistor Triac	TO-220L
QJxx16RH2	X	X	10 mA	Alternistor Triac	TO-220R
QJxx16NH2	X	X	10 mA	Alternistor Triac	TO-263 D^2-PAK
QJxx16LH3	X	X	20 mA	Alternistor Triac	TO-220L
QJxx16RH3	X	X	20 mA	Alternistor Triac	TO-220R
QJxx16NH3	X	X	20 mA	Alternistor Triac	TO-263 D^2-PAK
QJxx16LH4	X	X	35 mA	Alternistor Triac	TO-220L
QJxx16RH4	X	X	35 mA	Alternistor Triac	TO-220R
QJxx16NH4	X	X	35 mA	Alternistor Triac	TO-263 D^2-PAK
QJxx16LH6	X	X	80 mA	Alternistor Triac	TO-220L
QJxx16RH6	X	X	80 mA	Alternistor Triac	TO-220R
QJxx16NH6	X	X	80 mA	Alternistor Triac	TO-263 D^2-PAK

Packing Options

Part Number	Marking	Weight	Packing Mode	Base Quantity
QJxx16L/RHyTP	QJxx16L/RHy	2.2 g	Tube Pack	500 (50 per tube)
QJxx16NHyTP	QJxx16NHy	1.6 g	Tube Pack	500 (50 per tube)
QJxx16NHyRP	QJxx16NHy	1.6 g	Embossed Carrier	500

xx = voltage/10; y = Sensitivity

Part Numbering System

QJ 60 16 L H4 56

COMPONENT TYPE
QJ: High T_J TRIAC or Alternistor

VOLTAGE RATING
40: 400V
60: 600V

CURRENT RATING
16: 16A

PACKAGE TYPE
L: TO-220 Isolated
R: TO-220 Non-Isolated
N: TO-263 (D^2-Pak)

LEAD FORM DIMENSIONS
xx: Lead Form Option

SENSITIVITY & TYPE
Alternistor Triac
H2: 10mA (QI, II, III)
H3: 20mA (QI, II, III)
H4: 35mA (QI, II, III)
H6: 80mA (QI, II, III)

Part Marking System

TO-220 AB - (L and R Package)
TO-263 AB - (N Package)



Date Code Marking
Y:Year Code
M: Month Code
XXX: Lot Trace Code

TO-263 Embossed Carrier Reel Pack (RP)

Meets all EIA-481-2 Standards



Revised: 07/13/17

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Littelfuse:

QJ6016NH4RP QJ4016LH6TP QJ6016LH2TP QJ6016LH6TP QJ6016NH2RP QJ4016RH4TP QJ4016RH3TP QJ4016NH3RP QJ4016LH3TP QJ6016RH2TP QJ4016NH2RP QJ6016RH6TP QJ6016RH3TP QJ4016RH2TP QJ4016NH6RP QJ6016LH4TP QJ4016LH4TP QJ6016NH3RP QJ4016NH4RP QJ6016RH4TP QJ6016LH3TP QJ4016RH6TP QJ6016NH6RP QJ4016LH2TP