

Implement a New Measure

The BRAPH 2 Developers

August 14, 2024

This is the developer tutorial for implementing a new measure. In this tutorial, you will learn how to create the generator file `*.gen.m` for a new measure, which can be compiled by `braph2genesis`. All measures are (direct or indirect) extensions of the element `Measure`. Here, you will use as examples the measures `Degree`, `DegreeAv`, `Distance`, and `Triangles`.

Contents

<i>Implementation of Unilayer Measures</i>	2
<i>Nodal Unilayer Measure (Degree)</i>	2
<i>Global Unilayer Measure (DegreeAv)</i>	5
<i>Binodal Unilayer Measure (Distance)</i>	8
<i>Implementation of Measure Parameters (Triangles)</i>	11

Implementation of Unilayer Measures

Nodal Unilayer Measure (Degree)

You will start by implementing in detail the measure Degree, which applies to most graphs and is a direct extension of the element Measure.

Code 1: Degree element header. The header section of the generator code in `_Degree.gen.m` provides the general information about the Degree element.

```

1 %% iheader!
2 Degree < Measure (m, degree) is the graph degree. ①
3
4 %%% idescription!
5 The degree of a node is the number of edges connected to the node within a
   layer.
6 Connection weights are ignored in calculations.
7
8 %%% ibuild!
9 1

```

① The element Degree is defined as a subclass of Measure. The moniker will be m.

Code 2: Degree element prop update. The `props_update` section of the generator code in `_Degree.gen.m` updates the properties of the Measure element. This defines the core properties of the measure.

```

1 %% iprops_update!
2
3 %%% iprop!
4 NAME (constant, string) is the name of the degree.
5 %%% idefault!
6 'Degree'
7
8 %%% iprop!
9 DESCRIPTION (constant, string) is the description of the degree.
10 %%% idefault!
11 'The degree of a node is the number of edges connected to the node within a
   layer. Connection weights are ignored in calculations.'
12
13 %%% iprop!
14 TEMPLATE (parameter, item) is the template of the degree.
15 %%% isettings!
16 'Degree'
17
18 %%% iprop!
19 ID (data, string) is a few-letter code of the degree.
20 %%% idefault!
21 'Degree ID'
22
23 %%% iprop!
24 LABEL (metadata, string) is an extended label of the degree.
25 %%% idefault!
26 'Degree label'
27
28 %%% iprop!
29 NOTES (metadata, string) are some specific notes about the degree.
30 %%% idefault!

```

```

31 'Degree notes'
32
33 %% iprop! ①
34 SHAPE (constant, scalar) is the measure shape __Measure.NODAL__.
35 %%%% idefault!
36 Measure.NODAL
37
38 %% iprop! ②
39 SCOPE (constant, scalar) is the measure scope __Measure.UNILAYER__.
40 %%%% idefault!
41 Measure.UNILAYER
42
43 %% iprop! ③
44 PARAMETRICITY (constant, scalar) is the parametricity of the measure
45 __Measure.NONPARAMETRIC__.
46 %%%% idefault!
47 Measure.NONPARAMETRIC
48
49 %% iprop! ④
50 COMPATIBLE_GRAPHHS (constant, classlist) is the list of compatible graphs.
51 %%%% idefault!
52 {'GraphWU' 'GraphBU' 'MultigraphBUD' 'MultigraphBUT' 'MultiplexWU' '
53   MultiplexBU' 'MultiplexBUD' 'MultiplexBUT' 'OrdMxWU' 'OrdMxBU'}
54
55 %% iprop! ⑤
56 M (result, cell) is the degree.
57 %%%% icalculate!
58 g = m.get('G'); ⑥
59 A = g.get('A'); ⑦
60
61 degree = cell(g.get('LAYERNUMBER'), 1); ⑧
62
63 parfor li = 1:1:g.get('LAYERNUMBER')
64   Aii = A{li, li};
65   Aii = binarize(Aii); ⑨
66   degree(li) = {sum(Aii, 2)}; ⑩
67 end
68
69 value = degree; ⑪

```

Code 3: Degree element tests. The tests section from the element generator `_Degree.gen.m`. A test should be prepared for each graph with which the measure is compatible. The test should at least verify in some simple cases that the value of the measure is correct.

```

1 %% itests!
2
3 %%%% iexcluded_props! ①
4 [Degree.PFM]
5
6 %% itest! ②
7 %%%% iname!
8 GraphWU
9 %%%% iprobability! ③
10 .01
11 %%%% icode!

```

① Measures have a *shape*:

Measure.GLOBAL (a value for the whole brain graph, e.g., average degree), Measure.NODAL (a value for each brain region, e.g., degree), or Measure.BINODAL (a value for each couple of brain regions, e.g., distance between couples of nodes).

② Measures have a *scope*:

Measure.SUPERGLOBAL (a result for the whole multi-layer graph, e.g., overlapping strength), Measure.UNILAYER (a result for each layer, e.g., average strength), or Measure.BILAYER (a result for each couple of layers).

③ Measures are either

Measure.NONPARAMETRIC (the usual case) or Measure.PARAMETRIC (depending on some parameter).

④ Each measure has a list of compatible graphs for which the measure can be used.

⑤ The property M contains the code to be executed to calculate the measure. Here is where most of the action happens.

⑥ retrieves the graph from the property G of the measure m.

⑦ retrieves the cell with the adjacency matrix (for graph) or 2D-cell array (for multigraph, multiplex, etc.).

⑧ preallocates the variable to contain the result of the measure calculation.

⑨ binarizes the adjacency matrix (removing diagonal).

⑩ calculates the degree of the node for layer li.

⑪ returns the calculated value of the measure degree assigning it to the output variable value.

① List of properties that are excluded from testing.

② Test for GraphWU. Similar tests should be implemented for each graph compatible with the measure.

③ assigns a low test execution probability.

```

12 B = [
13     0   .6  1
14     .6  0   0
15     1   0   0
16     ];
17
18 known_degree = {[2 1 1]'}; ④
19
20 g = GraphWU('B', B); ⑤
21
22 m_outside_g = Degree('G', g); ⑥
23 assert(isequal(m_outside_g.get('M'), known_degree), ... ⑦
24         [BRAPH2.STR ':Degree:' BRAPH2.FAIL_TEST], ...
25         [class(m_outside_g) ' is not being calculated correctly for ' class(g) '
26         '.'])
27
28 m_inside_g = g.get('MEASURE', 'Degree'); ⑧
29 assert(isequal(m_inside_g.get('M'), known_degree), ... ⑧
30         [BRAPH2.STR ':Degree:' BRAPH2.FAIL_TEST], ...
31         [class(m_inside_g) ' is not being calculated correctly for ' class(g) '
32         '.'])
33
34 ...

```

④ is the expected value of the measure calculated by external means.

⑤ creates the graph.

⑥ creates the measure.

⑦ tests that the value of the measure coincides with its expected value.

⑧ extracts the measure from the graph.

⑧ tests that the value of the measure extracted from the graph coincides with its expected value.

Global Unilayer Measure (*DegreeAv*)

You can now use `Degree` as the basis to implement the global measure `DegreeAv`. The parts of the code that are modified are highlighted.

Code 4: `DegreeAv` element header. The header section of the generator code in `_DegreeAv.gen.m` provides the general information about the `DegreeAv` element. ← [Code 1](#)

```

1 %% iheader!
2 DegreeAv < Degree (m, average degree) is the graph average degree. ①
3
4 %%% idescription!
5 The average degree of a graph is the average of all number of edges
   connected to a node within a layer.
6 Connection weights are ignored in calculations.
7
8 %%% ibuild!
9 1

```

① `DegreeAv` is a child of `Degree`.

Code 5: `DegreeAv` element prop update. The `props_update` section of the generator code in `_DegreeAv.gen.m` updates the properties of the `Degree` element. ← [Code 2](#)

```

1 %% iprops_update!
2
3 %%% iprop!
4 NAME (constant, string) is the name of the average degree.
5 %%% idefault!
6 'DegreeAv'
7
8 %%% iprop!
9 DESCRIPTION (constant, string) is the description of the average degree.
10 %%% idefault!
11 'The average degree of a graph is the average of all number of edges
   connected to a node within a layer. Connection weights are ignored in
   calculations.'
12
13 %%% iprop!
14 TEMPLATE (parameter, item) is the template of the average degree.
15 %%% isettings!
16 'DegreeAv'
17
18 %%% iprop!
19 ID (data, string) is a few-letter code of the average degree.
20 %%% idefault!
21 'DegreeAv ID'
22
23 %%% iprop!
24 LABEL (metadata, string) is an extended label of the average degree.
25 %%% idefault!
26 'DegreeAv label'
27
28 %%% iprop!
29 NOTES (metadata, string) are some specific notes about the average degree.
30 %%% idefault!
31 'DegreeAv notes'

```

```

32
33 %% iprop!
34 SHAPE (constant, scalar) is the measure shape __Measure.GLOBAL__.
35 %%%% idefault!
36 Measure.GLOBAL
37
38 %% iprop!
39 SCOPE (constant, scalar) is the measure scope __Measure.UNILAYER__.
40 %%%% idefault!
41 Measure.UNILAYER
42
43 %% iprop!
44 PARAMETRICITY (constant, scalar) is the parametricity of the measure
    __Measure.NONPARAMETRIC__.
45 %%%% idefault!
46 Measure.NONPARAMETRIC
47
48 %% iprop!
49 COMPATIBLE_GRAPHS (constant, classlist) is the list of compatible graphs.
50 %%%% idefault!
51 {'GraphWU' 'GraphBU' 'MultigraphBUD' 'MultigraphBUT' 'MultiplexWU' '
    MultiplexBU' 'MultiplexBUD' 'MultiplexBUT' 'OrdMxWU' 'OrdMxBU'}
52
53 %% iprop!
54 M (result, cell) is the average degree.
55 %%%% icalculate!
56 degree = calculateValue@Degree(m, prop); ①
57
58 g = m.get('G');
59
60 degree_av = cell(g.get('LAYERNUMBER'), 1);
61 parfor li = 1:1:g.get('LAYERNUMBER')
62     degree_av(li) = {mean(degree{li})};
63 end
64
65 value = degree_av;

```

① calculates the value of the degree calling its parent Degree.

Code 6: DegreeAv element tests. The tests section from the element generator `_DegreeAv.gen.m`. ← [Code 3](#)

```

1 %% itests!
2
3 %% iexcluded_props!
4 [DegreeAv.PFM]
5
6 %% itest!
7 %%%% iname!
8 GraphWU
9 %%%% iprobability!
10 .01
11 %%%% icode!
12 B = [
13     0   .6   1
14     .6   0   0
15     1   0   0
16 ];
17
18 known_degree_av = {mean([2 1 1])};
19
20 g = GraphWU('B', B);

```

```
21
22 m_outside_g = DegreeAv('G', g);
23 assert(isequal(m_outside_g.get('M'), known_degree_av), ...
24         [BRAPH2.STR ':DegreeAv:' BRAPH2.FAIL_TEST], ...)
25         [class(m_outside_g) ' is not being calculated correctly for ' class(g)
26         '.'])
27
28 m_inside_g = g.get('MEASURE', 'DegreeAv');
29 assert(isequal(m_inside_g.get('M'), known_degree_av), ...
30         [BRAPH2.STR ':DegreeAv:' BRAPH2.FAIL_TEST], ...)
31         [class(m_inside_g) ' is not being calculated correctly for ' class(g)
32         '.'])
33
34 ...
```

Binodal Unilayer Measure (Distance)

Now you will implement the binodal measure Distance. Again the differences in the code will be highlighted.

Code 7: Distance element header. The header section of the generator code in `_Distance.gen.m` provides the general information about the Distance element. ← [Code 1](#)

```

1 %% iheader!
2 Distance < Measure (m, distance) is the distance.
3
4 %%% idescription!
5 The distance of a graph is the shortest path between all pairs of nodes
   within a layer of the graph.
6 For weighted graphs, the distance is calculated with the Dijkstra algorithm
   using the inverse weight as the distance associated to the edge.
7
8 %%% ibuild!
9 1

```

Code 8: Distance element prop update. The `props_update` section of the generator code in `_Distance.gen.m` updates the properties of the Measure element. ← [Code 2](#)

```

1 %% iprops_update!
2
3 %%% iprop!
4 NAME (constant, string) is the name of the distance.
5 %%%% idefault!
6 'Distance'
7
8 %%% iprop!
9 DESCRIPTION (constant, string) is the description of the distance.
10 %%%% idefault!
11 'The distance of a graph is the shortest path between all pairs of nodes
   within a layer of the graph. For weighted graphs, the distance is
   calculated with the Dijkstra algorithm using the inverse weight as the
   distance associated to the edge.'
12
13 %%% iprop!
14 TEMPLATE (parameter, item) is the template of the distance.
15 %%%% isettings!
16 'Distance'
17
18 %%% iprop!
19 ID (data, string) is a few-letter code of the distance.
20 %%%% idefault!
21 'Distance ID'
22
23 %%% iprop!
24 LABEL (metadata, string) is an extended label of the distance.
25 %%%% idefault!
26 'Distance label'
27
28 %%% iprop!
29 NOTES (metadata, string) are some specific notes about the distance.
30 %%%% idefault!
31 'Distance notes'

```

```

32
33 %%% iprop!
34 SHAPE (constant, scalar) is the measure shape __Measure.BINODAL__.
35 %%% idefault!
36 Measure.BINODAL
37
38 %%% iprop!
39 SCOPE (constant, scalar) is the measure scope __Measure.UNILAYER__.
40 %%% idefault!
41 Measure.UNILAYER
42
43 %%% iprop!
44 PARAMETRICITY (constant, scalar) is the parametricity of the measure
    __Measure.NONPARAMETRIC__.
45 %%% idefault!
46 Measure.NONPARAMETRIC
47
48 %%% iprop!
49 COMPATIBLE_GRAPH (constant, classlist) is the list of compatible graphs.
50 %%% idefault!
51 {'GraphBD' 'GraphBU' 'GraphWD' 'GraphWU' 'MultigraphBUD' 'MultigraphBUT' '
    MultiplexBD' 'MultiplexBU' 'MultiplexWD' 'MultiplexWU' 'MultiplexBUD' '
    MultiplexBUT' 'OrdMxBD' 'OrdMxBU' 'OrdMxWD' 'OrdMxWU'}
52
53 %%% iprop!
54 M (result, cell) is the distance.
55 %%% icalculate!
56 g = m.get('G');
57 A = g.get('A');
58
59 distance = cell(g.get('LAYERNUMBER'), 1);
60 connectivity_type = g.get('CONNECTIVITY_TYPE', g.get('LAYERNUMBER'));
61 connectivity_type = diag(connectivity_type);
62 Aii_tmp = {};
63 for li = 1:1:g.get('LAYERNUMBER')
64     Aii_tmp{li} = A{li, li};
65 end
66 for li = 1:1:g.get('LAYERNUMBER')
67     Aii = Aii_tmp{li};
68     connectivity_layer = connectivity_type(li);
69
70     if connectivity_layer == Graph.WEIGHTED % weighted graphs
71         distance(li) = {getWeightedCalculation(Aii)}; ①
72     else % binary (i.e., non-weighted) graphs
73         distance(li) = {getBinaryCalculation(Aii)}; ②
74     end
75 end
76
77 value = distance;
78 %%% icalculate_callbacks! ③
79 function weighted_distance = getWeightedCalculation(A)
80     ...
81 end
82 function binary_distance = getBinaryCalculation(A)
83     ...
84 end

```

① and ② call some callback functions that are provided below in ③.

③ This section contains the callback functions for the calculation of the measure.

Code 9: **Distance element tests.** The tests section from the element generator `_Distance.gen.m`. ← [Code 3](#)

```

1 %% itests!
2
3 %%% iexcluded_props!
4 [Distance.PFM]
5
6 %%% itest!
7 %%% iiname!
8 GraphWU
9 %%% iprobability!
10 .01
11 %%% icode!
12 B = [
13     0     .1     .2   .25  0
14     .125  0     0    0   0
15     .2     .5     0   .25  0
16     .125 10     0    0   0
17     0     0     0    0   0
18 ];
19
20 known_distance = {[
21     0  5  5  4  Inf
22     5  0  2  1  Inf
23     5  2  0  3  Inf
24     4  1  3  0  Inf
25     Inf Inf Inf Inf 0
26 ]};
27
28 g = GraphWU('B', B);
29
30 m_outside_g = Distance('G', g);
31 assert(isequal(m_outside_g.get('M'), known_distance), ...
32     [BRAPH2.STR ':Distance:' BRAPH2.FAIL_TEST], ...
33     [class(m_outside_g) ' is not being calculated correctly for ' class(g)
34     '.'])
35
36 m_inside_g = g.get('MEASURE', 'Distance');
37 assert(isequal(m_inside_g.get('M'), known_distance), ...
38     [BRAPH2.STR ':Distance:' BRAPH2.FAIL_TEST], ...
39     [class(m_inside_g) ' is not being calculated correctly for ' class(g)
40     '.'])
41 ...

```

Implementation of Measure Parameters (Triangles)

Now, you will implement the (nodal unilayer) measure `Triangles`, which depends on a parameter `RULE`, which we add as a property of category parameter. The parts of the code that are modified are highlighted.

Code 10: Triangles element header. The header section of the generator code in `_Triangles.gen.m` provides the general information about the `Triangles` element. ← [Code 10](#)

```

1 %% iheader!
2 Triangles < Measure (m, triangles) is the triangles.
3
4 %%% idescription!
5 The triangles are calculated as the number of neighbors of a node that are
  also neighbors of each other within a layer.
6 In weighted graphs, the triangles are calculated as geometric mean of the
  weights of the edges forming the triangle.
7
8 %%% ibuild!
9 1

```

Code 11: Triangles element calculate. The calculate section of `_Triangles.gen.m` utilizes the rule property to select which algorithm it will use to calculate the `Triangles` element. ← [Code 11](#)

```

1
2 %% iprops_update!
3
4 %%% iprop!
5 NAME (constant, string) is the name of the triangles.
6 %%% idefault!
7 'Triangles'
8
9 %%% iprop!
10 DESCRIPTION (constant, string) is the description of the triangles.
11 %%% idefault!
12 'The triangles are calculated as the number of neighbors of a node that are
  also neighbors of each other within a layer. In weighted graphs, the
  triangles are calculated as geometric mean of the weights of the edges
  forming the triangle.'
13
14 ...
15
16 %%% iprop!
17 M (result, cell) is the triangles.
18 %%% icalculate!
19 g = m.get('G'); % graph from measure class
20 A = g.get('A'); % cell with adjacency matrix (for graph) or 2D-cell array (
  for multigraph, multiplex, etc.)
21 L = g.get('LAYERNUMBER');
22
23 triangles = cell(L, 1);
24
25 directionality_type = g.get('DIRECTIONALITY_TYPE', L);
26 for li = 1:L
27   Aii = A{li, li};

```

```

28
29 if directionality_type == Graph.UNDIRECTED % undirected graphs
30     triangles_layer = diag((Aii.^(1/3))^3) / 2;
31     triangles_layer(isnan(triangles_layer)) = 0; % Should return zeros, not
        NaN
32     triangles(li) = {triangles_layer};
33
34 else % directed graphs
35     directed_triangles_rule = m.get('RULE'); ①
36     switch lower(directed_triangles_rule)
37         case 'all' % all rule
38             triangles_layer = diag((Aii.^(1/3) + transpose(Aii).^(1/3))^3) / 2;
39         case 'middleman' % middleman rule
40             triangles_layer = diag(Aii.^(1/3) * ...
41                 transpose(Aii).^(1/3) * Aii.^(1/3));
42         case 'in' % in rule
43             triangles_layer = diag(transpose(Aii).^(1/3) * (Aii.^(1/3))^2);
44         case 'out' % out rule
45             triangles_layer = diag((Aii.^(1/3))^2 * transpose(Aii).^(1/3));
46         otherwise % {'cycle'} % cycle rule
47             triangles_layer = diag((Aii.^(1/3))^3);
48     end
49     triangles_layer(isnan(triangles_layer)) = 0; % Should return zeros, not
        NaN
50     triangles(li) = {triangles_layer};
51 end
52 end
53
54 value = triangles;
55
56 %% iprops!
57
58 %%% iprop!
59 RULE (parameter, option) is the rule to determine what is a triangle in a
        directed graph. ②
60 %%% isettings!
61 {'all' 'middleman' 'in' 'out' 'cycle'} ③
62 %%% idefault!
63 'cycle' ④

```

① gets the rule to calculate the measure Triangle. See below how this rule is defined in ②, ③, and ④.

② defines a parameter to determine how the measure is calculated. This property must be of category parameter.

③ defines the available triangle rule options, which are case sensitive.

④ defines the default option, in this case 'cycle'.