Metropolis–Hastings: A Multidisciplinary Story of Modeling and Simulation

PHYS 441

Abstract

The Metropolis–Hastings algorithm is now used in physics, statistics, computer science, engineering, and many other fields. Its origin is an unusually clear example of how modeling and simulation develop: a physical question motivated a mathematical reformulation; an algorithm made that reformulation practical; a program translated the algorithm into machine instructions; and a new computer made the calculation possible. This reading follows that development from Los Alamos in the 1940s and 1950s to Hastings's generalization in 1970. It also examines a historical complication: the familiar name of the algorithm does not fully describe the contributions of the people who created it.

1 Why this history belongs in a modeling course

A finished simulation can make its component parts look inevitable. We are given a model, write an algorithm, run a program, and interpret the output. The history of Metropolis–Hastings shows that these steps are neither automatic nor the work of a single discipline.

The original project required all of the following:

- a **physical model** of matter in thermal equilibrium;
- a **statistical description** of which configurations should be common and which should be rare;
- a **mathematical insight** that the desired average could be found without evaluating an enormous integral directly;
- an **algorithm** that generated configurations with the correct long-run frequencies;
- a **program** written for a machine with extremely limited memory;
- a functioning **electronic computer**; and
- scientific judgment about validation, approximation, and uncertainty.

Physics, computer science, mathematics, and engineering were not separate layers added after the fact. The method arose from their interaction.

2 The Los Alamos setting

Modern Monte Carlo computation grew out of the scientific environment created by the Manhattan Project. Many Los Alamos calculations involved systems with a vast number of possible histories or configurations: neutron transport, radiation transport, thermonuclear reactions, hydrodynamics, and equations of state. Exact analytic solutions were rarely available, while exhaustive numerical enumeration was impossible.

During the war, much numerical work was performed by teams of human "computers" and electromechanical machines. Electronic machines such as ENIAC then demonstrated that calculations could be performed at an unprecedented scale. Stanisław Ulam recognized that this new speed could revive statistical sampling methods that had previously required too much arithmetic. John von Neumann helped formulate and implement early applications, including neutron transport calculations [4].

The name *Monte Carlo* emphasized the use of random numbers and alluded to games of chance. Randomness, however, was not being used as a substitute for rigor. It was being engineered into a numerical method: repeat a random experiment, calculate an observable, and use the resulting statistics to estimate a quantity that is otherwise difficult to compute.

3 The people behind the 1953 paper

The landmark paper, "Equation of State Calculations by Fast Computing Machines," was published in 1953 by Nicholas Metropolis, Arianna W. Rosenbluth, Marshall N. Rosenbluth, Augusta H. Teller, and Edward Teller [1]. The author list brought together two married couples and the leader of the Los Alamos computing effort.

3.1 Nicholas Metropolis: physics and computing infrastructure

Nicholas Constantine Metropolis (1915–1999) trained as an experimental physicist at the University of Chicago. He worked with Enrico Fermi, joined the Manhattan Project at Los Alamos in 1943, and worked on equations of state for materials at high temperature and pressure. After the war, he became a major figure in scientific computing.

Metropolis directed the construction of the Los Alamos MANIAC computer, a stored-program machine based on the architecture developed by von Neumann and his collaborators. MANIAC began operating in 1952 and performed the calculation reported in the 1953 paper. Metropolis supplied far more than a piece of hardware: he led the group, secured institutional support, allocated scarce machine time, and helped create a setting in which physicists and programmers could turn new numerical ideas into working calculations [5].

3.2 Marshall Rosenbluth: the statistical-mechanical algorithm

Marshall Rosenbluth (1927–2003) was a theoretical physicist who later became a leading figure in plasma physics and controlled-fusion research. In his later account of the 1953 project, he credited Edward Teller with suggesting the use of Monte Carlo methods to take statistical-mechanical

ensemble averages. Rosenbluth then worked out the acceptance procedure that made this idea efficient [3].

The essential insight was to avoid drawing configurations uniformly and then assigning almost all of them negligible statistical weight. Instead, the algorithm would construct a random walk that spent more time in configurations with larger Boltzmann weight.

3.3 Arianna Rosenbluth: turning the method into a program

Arianna Wright Rosenbluth (1927–2020) was a physicist and programmer. She wrote the MANIAC implementation used for the published calculation. Programming an early computer was not a matter of translating a few lines of pseudocode into a high-level language. The machine had limited memory, primitive input and output, and no modern operating system or numerical library. The programmer had to understand the mathematics, the machine representation, the control flow, and the numerical limitations together.

Her work is a reminder that an algorithm is not yet a simulation. A simulation exists only after the algorithm has been expressed in a form that a real machine can execute and its results have been checked. Arianna Rosenbluth's role was underemphasized for decades, in part because programming was often treated as secondary labor and because women in early computing were frequently omitted from later accounts [6].

3.4 Augusta and Edward Teller: computation and physical motivation

Augusta "Mici" Teller (1909–2000) studied mathematics in Budapest and worked in the Los Alamos computations group during the Manhattan Project. She later worked with early computers at Argonne and Los Alamos. Accounts suggest that she participated in the initial programming effort, although Arianna Rosenbluth reported that she subsequently rewrote the program used for the calculation [3, 7].

Edward Teller (1908–2003) was a theoretical physicist deeply involved in nuclear and thermonuclear research. His interest in the project was scientifically natural. Statistical mechanics relates microscopic particle configurations to macroscopic properties such as pressure, temperature, and density. Equations of state are also essential in modeling matter under the extreme conditions found in shocks, dense plasmas, stellar interiors, and nuclear-weapon calculations.

The published demonstration was not itself a simulation of a nuclear weapon. It studied a simplified equilibrium system of interacting particles. It did, however, emerge from a laboratory in which equations of state, high-dimensional calculations, and the development of nuclear technology were closely connected.

4 The physical and mathematical problem

Consider a system of N interacting particles. A single state x specifies the positions of all particles, and $E(x)$ is the energy of that configuration. In the canonical ensemble, a configuration has probability density proportional to its Boltzmann factor,

$$\widetilde{\pi}(x) = \exp\left[-\frac{E(x)}{k_{\mathrm{B}}T}\right], \tag{1}$$

where T is temperature and k_{B} is Boltzmann's constant. The equilibrium expectation of an observable F is

$$\langle F \rangle = \frac{\displaystyle\int F(x) e^{-E(x)/(k_{\mathrm{B}}T)}\, dx}{\displaystyle\int e^{-E(x)/(k_{\mathrm{B}}T)}\, dx}. \tag{2}$$

If each of hundreds of particles contributes two or three coordinates, then the integral is hundreds-dimensional. A grid with only ten values per coordinate would require 10^{200} points for a 200-dimensional problem. This is the *curse of dimensionality*: increasing computational power alone cannot make such a grid practical.

Naive random sampling is also inefficient. Most randomly selected configurations may have particles unrealistically close together, producing very large energies and nearly zero Boltzmann weights. The computer spends almost all of its effort generating configurations that contribute almost nothing to Eq. (2).

5 The algorithmic leap

The 1953 method generates a sequence of configurations

$$X_0, X_1, X_2, \ldots$$

instead of selecting independent configurations uniformly. Starting from the current configuration x, it performs the following steps:

1. Select a particle and propose a small random displacement, producing a candidate configuration y.
2. Calculate the energy change $\Delta E = E(y) - E(x)$.
3. If $\Delta E \leq 0$, accept the move.
4. If $\Delta E > 0$, accept the move with probability $e^{-\Delta E/(k_{\mathrm{B}}T)}$.
5. If the proposal is rejected, record the old configuration again.

For a symmetric proposal, this is equivalent to accepting with probability

$$\alpha(x, y) = \min\left\{1, \frac{\widetilde{\pi}(y)}{\widetilde{\pi}(x)}\right\}. \tag{3}$$

The unknown normalization integral cancels in the ratio. More importantly, the accepted configurations occur with the desired equilibrium frequencies. After initialization effects have diminished, the integral in Eq. (2) can be estimated by the ordinary average

$$\langle F \rangle \approx \frac{1}{M} \sum_{t=1}^{M} F(X_t). \tag{4}$$

This is a profound change in the computational problem. Rather than evaluating an impossible integral, the machine performs local energy calculations and random accept–reject decisions. The answer emerges from the long-run behavior of the constructed Markov chain.

The original paper demonstrated the method using two-dimensional hard disks. The model was deliberately simple: disks could not overlap, and the calculation estimated an equation of state. Simplicity made the method testable while still addressing the collective behavior of many interacting particles.

6 From Metropolis to Metropolis–Hastings

The proposal in the 1953 calculation was symmetric. If the mechanism could propose y from x, the reverse displacement was equally likely. In 1970, W. Keith Hastings generalized the method to an arbitrary proposal density $q(y \mid x)$ [2]. The acceptance probability became

$$\alpha(x, y) = \min\left\{1, \frac{\widetilde{\pi}(y) q(x \mid y)}{\widetilde{\pi}(x) q(y \mid x)}\right\}. \tag{5}$$

The extra ratio corrects for a proposal mechanism that favors one direction. When the proposal is symmetric, $q(y \mid x) = q(x \mid y)$, the proposal terms cancel, and Eq. (5) reduces to the original Metropolis rule in Eq. (3).

Hastings transformed a powerful statistical-physics procedure into a broadly applicable sampling framework. The method now supports Bayesian inference, molecular simulation, lattice field theory, reliability analysis, inverse problems, uncertainty quantification, and many other applications.

7 Whose algorithm is it?

The familiar name creates a misleadingly simple story. Historical recollections do not agree in every detail. Edward Teller later described a strongly collaborative effort, while Marshall Rosenbluth assigned the central algorithmic and programming work primarily to himself and Arianna. Later historical work generally supports the conclusion that the Rosenbluths made contributions much larger than the usual name suggests [3].

Why, then, did "Metropolis algorithm" become standard? Metropolis was first author, led the computing group, and made MANIAC available. Naming a result after the first author was natural, and a short name spread more easily than the full author list. The episode illustrates several features of scientific credit:

- the name attached to a method need not identify its sole inventor;
- programming and implementation may be undervalued relative to theory;
- institutional leadership can be essential even when it is not the same as inventing the central formula; and
- later recollections must be compared critically rather than treated as perfectly objective records.

The aim is not to replace one heroic inventor with another. The better lesson is that the method was produced by a network of complementary contributions.

8 A timeline of the development

Period	Development
1940s	Los Alamos uses large-scale numerical calculation for neutron transport, weapons physics, and equations of state. Ulam and von Neumann develop modern Monte Carlo ideas for electronic computers.
1948–1952	Metropolis leads the construction of MANIAC at Los Alamos.
1952–1953	Teller, the Rosenbluths, the Tellers, and Metropolis develop and run the statistical-mechanics calculation on MANIAC.
1953	The five-author paper introduces the acceptance algorithm using a two-dimensional hard-disk equation-of-state calculation.
1970	Hastings publishes the general acceptance rule for asymmetric proposals.
Later decades	MCMC becomes central to computational physics and statistics, then spreads throughout science and engineering.

9 Lessons for physics, computer science, and engineering

For physics: The probability distribution was not an arbitrary curve. It came from the canonical ensemble and encoded physical assumptions about equilibrium, energy, and temperature. A simulation cannot be better than the model and approximations on which it is based.

For mathematics and statistics: Stationarity and detailed balance explain why the acceptance rule targets the desired distribution. Convergence, autocorrelation, and sampling error determine whether a finite run provides a useful estimate.

For computer science: The project required an algorithm whose local operations were feasible on real hardware, a random-number mechanism, a careful implementation, and data handling under severe memory constraints. Complexity was changed by reformulating the task rather than merely running the original calculation faster.

For engineering: MANIAC had to be designed, constructed, maintained, and operated reliably. The method also required tradeoffs: proposal size versus acceptance, physical realism versus tractability, and accuracy versus available machine time.

For everyone: Modeling and simulation form a feedback loop. Physical questions inspire mathematical structures; mathematical structures suggest algorithms; hardware constraints reshape algorithms; computational results expose weaknesses in models; and validation sends the team back around the loop.

10 Questions for discussion

1. Which contribution was most essential: the physical question, Teller's ensemble idea, Rosenbluth's acceptance rule, Arianna Rosenbluth's program, or Metropolis's computer? Can this question have a unique answer?
2. Why is a high-dimensional integral not solved simply by building a computer that is ten or one hundred times faster?
3. In what sense is the Markov chain an artificial process rather than a simulation of the particles' real-time motion?
4. What evidence would you require before trusting an equation of state computed by this method?
5. Which forms of scientific labor are most likely to disappear from a method's name or from its standard textbook account?
6. Identify a modern modeling problem in which advances in physics, algorithms, software, and hardware remain inseparable.

References

[1] N. Metropolis, A. W. Rosenbluth, M. N. Rosenbluth, A. H. Teller, and E. Teller, "Equation of State Calculations by Fast Computing Machines," *Journal of Chemical Physics* **21**, 1087–1092 (1953), doi:10.1063/1.1699114.

[2] W. K. Hastings, "Monte Carlo Sampling Methods Using Markov Chains and Their Applications," *Biometrika* **57**, 97–109 (1970), doi:10.1093/biomet/57.1.97.

[3] J. E. Gubernatis, "Marshall Rosenbluth and the Metropolis Algorithm," *Physics of Plasmas* **12**, 057303 (2005), doi:10.1063/1.1887186.

[4] N. Metropolis, "The Beginning of the Monte Carlo Method," *Los Alamos Science* **15**, 125–130 (1987), `https://mcnp.lanl.gov/pdf_files/Article_1987_LAS_Metropolis_125--130.pdf`.

[5] H. L. Anderson, "Metropolis, Monte Carlo, and the MANIAC," *Los Alamos Science* **14**, 96–108 (1986), `https://mcnp.lanl.gov/pdf_files/Article_1986_LAS_Anderson_96--108.pdf`.

[6] S. Chen, "Arianna Rosenbluth and the Metropolis Monte Carlo Algorithm," *APS News* (2022), `https://www.aps.org/apsnews/2022/03/rosenbluth-metropolis-monte-carlo-algorithm`.

[7] Atomic Heritage Foundation, "Augusta 'Mici' Teller," `https://ahf.nuclearmuseum.org/ahf/profile/augusta-mici-teller/`.