

Quote

Quote To

Name Brian Rashap
Company CNM
Phone
Email brashap@cnm.edu

Quote Information

Quote # 250207Q9
Date 2025-02-07
Expiration Date 2025-04-08
Issued By Dan Kim
Payment Terms T/T in advance
Lead Time 5 Weeks
Incoterms EXW
Currency USD

No	Description	QTY	U/PRICE	Subtotal	Discount	Total
1	PNEUMATIC OPTICAL TABLE MODEL: DVIO-I-2412M-300t-H Consisting of;	1	\$ 8,012	\$ 8,012	\$ -	\$ 8,012
1-1	OPTICAL TABLE TOP MODEL: DVIO-B-2412M-300t Dimensions: 2400 x 1200 mm Thickness: 300 mm Weight: 476 mm Core: Steel honeycomb core structure, 0.25 mm thick foil Core Cell Size: 2.9 cm ² Core Shear Modulus: 19339 kgf/cm ² (275,000 psi) Surface Flatness: ±0.03 mm Top Skin: 4.0 mm thick 430 series ferromagnetic stainless steel Bottom Skin: 4.5 mm thick steel Side Walls: 2.0 mm thick steel plate with highly damped composite wood Mounting Holes: M6-1.0 Mounting Hole Grid: 25 mm grid Mounting Hole Borders: 37.5 mm Mounting Holes Sealing: 21 mm deep clean cylindrical cap Damping: Broadband damping Performance Specifications Natural Frequency: 200 Hz Compliance: 85 n m/N Natural frequency and compliance are measured on 2000 x 1200 x 300 mm *Natural frequency and compliance vary with dimensions of optical table tops.	1				
1-2	PNEUMATIC SUPPORT (Tie-Bar Type) MODEL: DVIO-S-2412I-H Design Features Vibration Isolation System: Pneumatic Isolation Support Height: TBA Frame Material: Steel Frame Structure: Welded Joints Number of Isolators: 4 EA Leveling Valves: 3 EA Leveling Foot: 4 EA Casters: 4 EA Performance Specifications Resonant Frequency: Vertical/Horizontal = 1.2 Hz – 3.0 Hz Vibration Isolation at 10 Hz: Vertical/Horizontal: 80% – 99 % Maximum Load Capacity: 1000 kg Leveling Repeatability of ±1.0 mm Height Adjustment Range of ±25 mm	1				
2	OVERHEAD SHELF SYSTEM MODEL: DOTS-8 Inner dimensions: 2500 x 550 x 1828 mm Outer dimensions: 2634 x 661 x 1908 mm Hanging shelves: (550 x 550 x 6mm) 3pcs Electrical sockets: 110V 8 pcs, 220V 8 pcs Circuit breaker: 30A Rated voltage: 110V/220V Rated residual current: 30mA Rated non-operating current: 15mA Rated breaking current: 1.5kA	1	\$ 2,585	\$ 2,585	\$ -	\$ 2,585
Total						\$ 10,597

Note

* Five (5) Year Limited Warranty from the original shipment date

* Country of Origin : South Korea / H.S CODE : 9031.80-9099



Sungkuk Kim
Sales Manager