



Universidade de Brasília

# Brasília Military Middle School 2017

Arthur Botelho, Henrique Quirino, Luiz Eduardo Reis

1 Contest

2 Theory

3 Math

4 Geometry

5 Graph

6 Data structures

7 Strings

8 DP

9 Various

Contest (1)

template.cpp 28 lines

```
#include <bits/stdc++.h>
using namespace std;
// Ours
#define endl '\n'
#define debug(x...) cout<<"["#x"]": ", [] (auto...$) { ((cout<<$<<" ";
    ),...); } (x),cout<<endl
// KACTL
typedef long long ll;
typedef long double ld;
#define sz(x) (int)x.size()
#define all(x) x.begin(), x.end()
#define vi vector<int>
#define pii pair<int, int>
#define rep(i, a, b) for(int i = (a); i < (b); i++)
#define pb push_back
#define eb emplace_back

constexpr int oo = (((unsigned int)-1)>>2);

void solve(){
    int n; cin >> n;
}

int main() {
    cin.tie(0)->sync_with_stdio(0);
    int t = 1;
    // cin >> t;
    while (t--) solve();
}
```

.bashrc 21 lines

```
teste() {
    for f in "$2"/*; do
        echo "=== $f"
        cat $f
        echo "=== Out"
        $1 < $f
    done
}
```

```
1 # teste ./b bf
stress() {
1     for ((i=1; ; i++)) do
        echo "Test $i"
        echo $i | $1 > gen_in
        $2 < gen_in > main_out
        $3 < gen_in > brute_out
        if ! diff -w main_out brute_out > /dev/null; then
2             return 1
6         fi
        done
11 }
# stress "python3 gen.py" ./main ./brute
```

.vimrc 5 lines

```
set autoindent smartindent ts=4 sw=4 rnu nu
" Select region and then type :Hash to hash your selection.
" Useful for verifying that there aren't mistypes.
ca Hash w !cpp -dD -P -fpreprocessed \ | tr -d '[:space:]' \
\ | md5sum \ | cut -c-6
```

hash.sh 3 lines

```
# Hashes a file, ignoring all whitespace and comments. Use for
# verifying that code was correctly typed.
cpp -dD -P -fpreprocessed | tr -d '[:space:]' | md5sum |cut -c-6
```

Makefile 1 lines

```
CXXFLAGS := -std=c++20 -Wall -Wextra -Wshadow -Wconversion -
fsanitize=address,undefined -g3
```

Theory (2)

2.1 Geometry

2.1.1 Trigonometry

$$\sin v + \sin w = 2 \sin \frac{v + w}{2} \cos \frac{v - w}{2}$$
$$\cos v + \cos w = 2 \cos \frac{v + w}{2} \cos \frac{v - w}{2}$$

$$(V + W) \tan(v - w)/2 = (V - W) \tan(v + w)/2$$

where  $V, W$  are lengths of sides opposite angles  $v, w$ .

$$a \cos x + b \sin x = r \cos(x - \phi)$$
$$a \sin x + b \cos x = r \sin(x + \phi)$$

where  $r = \sqrt{a^2 + b^2}, \phi = \text{atan2}(b, a)$ .

2.1.2 Triangles

Side lengths:  $a, b, c$

Semiperimeter:  $p = \frac{a + b + c}{2}$

Circumradius:  $R = \frac{abc}{4A}$

Inradius:  $r = \frac{A}{p}$

Length of median (divides triangle into two equal-area triangles):

$$m_a = \frac{1}{2} \sqrt{2b^2 + 2c^2 - a^2}$$

Length of bisector (divides angles in two):

$$s_a = \sqrt{bc \left[ 1 - \left( \frac{a}{b + c} \right)^2 \right]}$$

Law of tangents:  $\frac{a + b}{a - b} = \frac{\tan \frac{\alpha + \beta}{2}}{\tan \frac{\alpha - \beta}{2}}$

2.1.3 Quadrilaterals

With side lengths  $a, b, c, d$ , diagonals  $e, f$ , diagonals angle  $\theta$ , area  $A$  and magic flux  $F = b^2 + d^2 - a^2 - c^2$ :

$$4A = 2ef \cdot \sin \theta = F \tan \theta = \sqrt{4e^2 f^2 - F^2}$$

For cyclic quadrilaterals the sum of opposite angles is  $180^\circ$ ,  $ef = ac + bd$ , and  $A = \sqrt{(p - a)(p - b)(p - c)(p - d)}$ .

2.2 Combinatorics

2.2.1 Permutations

Cycles

Let  $g_S(n)$  be the number of  $n$ -permutations whose cycle lengths all belong to the set  $S$ . Then

$$\sum_{n=0}^\infty g_S(n) \frac{x^n}{n!} = \exp \left( \sum_{n \in S} \frac{x^n}{n} \right)$$

Derangements

Permutations of a set such that none of the elements appear in their original position.

$$D(n) = (n - 1)(D(n - 1) + D(n - 2)) = nD(n - 1) + (-1)^n = \left\lfloor \frac{n!}{e} \right\rfloor$$

2.2.2 Partitions and subsets

Partition function

Number of ways of writing  $n$  as a sum of positive integers, disregarding the order of the summands.

$$p(0) = 1, \quad p(n) = \sum_{k \in \mathbb{Z} \setminus \{0\}} (-1)^{k+1} p(n - k(3k - 1)/2)$$

$$p(n) \sim 0.145/n \cdot \exp(2.56\sqrt{n})$$

|        |   |   |   |   |   |   |    |    |    |    |     |      |      |
|--------|---|---|---|---|---|---|----|----|----|----|-----|------|------|
| $n$    | 0 | 1 | 2 | 3 | 4 | 5 | 6  | 7  | 8  | 9  | 20  | 50   | 100  |
| $p(n)$ | 1 | 1 | 2 | 3 | 5 | 7 | 11 | 15 | 22 | 30 | 627 | ~2e5 | ~2e8 |

Lucas' Theorem

Let  $n, m$  be non-negative integers and  $p$  a prime. Write  $n = n_k p^k + \dots + n_1 p + n_0$  and  $m = m_k p^k + \dots + m_1 p + m_0$ . Then  $\binom{n}{m} \equiv \prod_{i=0}^k \binom{n_i}{m_i} \pmod{p}$ .

2.2.3 General purpose numbers  
Bernoulli numbers

EGF of Bernoulli numbers is  $B(t) = \frac{t}{e^t-1}$  (FFT-able).  
 $B[0,\dots] = [1, -\frac{1}{2}, \frac{1}{6}, 0, -\frac{1}{30}, 0, \frac{1}{42}, \dots]$

Sums of powers:

$$\sum_{i=1}^n n^m = \frac{1}{m+1} \sum_{k=0}^m \binom{m+1}{k} B_k \cdot (n+1)^{m+1-k}$$

Euler-Maclaurin formula for infinite sums:

$$\begin{aligned} \sum_{i=m}^\infty f(i) &= \int_m^\infty f(x)dx - \sum_{k=1}^\infty \frac{B_k}{k!} f^{(k-1)}(m) \\ &\approx \int_m^\infty f(x)dx + \frac{f(m)}{2} - \frac{f'(m)}{12} + \frac{f'''(m)}{720} + O(f^{(5)}(m)) \end{aligned}$$

Stirling numbers of the first kind

Number of permutations on  $n$  items with  $k$  cycles.

$$\begin{aligned} c(n,k) &= c(n-1,k-1) + (n-1)c(n-1,k), \quad c(0,0) = 1 \\ \sum_{k=0}^n c(n,k)x^k &= x(x+1)\dots(x+n-1) \end{aligned}$$

$c(8,k) = 8, 0, 5040, 13068, 13132, 6769, 1960, 322, 28, 1$   
 $c(n,2) = 0, 0, 1, 3, 11, 50, 274, 1764, 13068, 109584, \dots$

Eulerian numbers

Number of permutations  $\pi \in S_n$  in which exactly  $k$  elements are greater than the previous element.  $k$   $j$ :s s.t.  $\pi(j) > \pi(j+1)$ ,  
 $k+1$   $j$ :s s.t.  $\pi(j) \geq j$ ,  $k$   $j$ :s s.t.  $\pi(j) > j$ .

$$E(n,k) = (n-k)E(n-1,k-1) + (k+1)E(n-1,k)$$

$$E(n,0) = E(n,n-1) = 1$$

$$E(n,k) = \sum_{j=0}^k (-1)^j \binom{n+1}{j} (k+1-j)^n$$

Stirling numbers of the second kind

Partitions of  $n$  distinct elements into exactly  $k$  groups.

$$S(n,k) = S(n-1,k-1) + kS(n-1,k)$$

$$S(n,1) = S(n,n) = 1$$

$$S(n,k) = \frac{1}{k!} \sum_{j=0}^k (-1)^{k-j} \binom{k}{j} j^n$$

Bell numbers

Total number of partitions of  $n$  distinct elements.  $B(n) = 1, 1, 2, 5, 15, 52, 203, 877, 4140, 21147, \dots$  For  $p$  prime,

$$B(p^m + n) \equiv mB(n) + B(n+1) \pmod{p}$$

2.3 Number Theory

2.3.1 Bézout's identity

For  $a \neq, b \neq 0$ , then  $d = \gcd(a,b)$  is the smallest positive integer for which there are integer solutions to

$$ax + by = d$$

If  $(x,y)$  is one solution, then all solutions are given by

$$\left(x + \frac{kb}{\gcd(a,b)}, y - \frac{ka}{\gcd(a,b)}\right), \quad k \in \mathbb{Z}$$

2.3.2 Highly composite numbers

Up to: number of divisors (number itself)

|           |                              |
|-----------|------------------------------|
| $10^2$    | : 12(60)                     |
| $10^3$    | : 32(840)                    |
| $10^4$    | : 64(7560)                   |
| $10^5$    | : 128(83160)                 |
| $10^6$    | : 240(720720)                |
| $10^7$    | : 448(8648640)               |
| $10^8$    | : 768(73513440)              |
| $10^9$    | : 1344(735134400)            |
| $10^{10}$ | : 2304(6983776800)           |
| $10^{11}$ | : 4032(97772875200)          |
| $10^{12}$ | : 6720(963761198400)         |
| $10^{13}$ | : 10752(9316358251200)       |
| $10^{14}$ | : 17280(97821761637600)      |
| $10^{15}$ | : 26880(866421317361600)     |
| $10^{16}$ | : 41472(8086598962041600)    |
| $10^{17}$ | : 64512(74801040398884800)   |
| $10^{18}$ | : 103680(897612484786617600) |

2.4 Graphs

2.4.1 Erdős–Gallai theorem

A simple graph with node degrees  $d_1 \geq \dots \geq d_n$  exists iff  $d_1 + \dots + d_n$  is even and for every  $k = 1 \dots n$ ,

$$\sum_{i=1}^k d_i \leq k(k-1) + \sum_{i=k+1}^n \min(d_i, k).$$

2.4.2 Maximum Independent Set

Just find a max clique of the complement. If the graph is bipartite, see MinimumVertexCover.h.

2.4.3 Min Cut

After running a max flow, the left side of a min-cut from  $s$  to  $t$  is given by all vertices reachable from  $s$ , only traversing edges with positive residual capacity.

Math (3)

3.1 Number Theory

3.1.1 Modular Arithmetic

ModMulLL.h

**Description:** Calculate  $a \cdot b \bmod c$  (or  $a^b \bmod c$ ) for  $0 \leq a, b \leq c \leq 7.2 \cdot 10^{18}$ .  
**Time:**  $\mathcal{O}(1)$  for modmul,  $\mathcal{O}(\log b)$  for modpow

```
#define MODMULLL_H
typedef unsigned long long ull;
ull modmul(ull a, ull b, ull M) {
    ll ret = a * b - M * ull(1LL / M * a * b);
    return ret + M * (ret < 0) - M * (ret >= (ll)M);
} // e9309c
ull modpow(ull b, ull e, ull mod) {
    ull ans = 1;
    for (; e; b = modmul(b, b, mod), e /= 2)
        if (e & 1) ans = modmul(ans, b, mod);
    return ans;
} // 100b91
```

ModLog.h

**Description:** Returns the smallest  $x > 0$  s.t.  $a^x = b \pmod{m}$ , or  $-1$  if no such  $x$  exists. modLog(a,1,m) can be used to calculate the order of  $a$ .  
**Time:**  $\mathcal{O}(\sqrt{m})$

```
#define MODLOG_H
ll modLog(ll a, ll b, ll m) {
    ll n = (ll) sqrt(m) + 1, e = 1, f = 1, j = 1;
    unordered_map<ll, ll> A;
    while (j <= n && (e = f = e * a % m) != b % m)
        A[e * b % m] = j++;
    if (e == b % m) return j;
    if (__gcd(m, e) == __gcd(m, b))
        rep(i,2,n+2) if (A.count(e = e * f % m))
            return n * i - A[e];
    return -1;
} // c040b8
```

ModSqrt.h

**Description:** Tonelli-Shanks algorithm for modular square roots. Finds  $x$  s.t.  $x^2 = a \pmod{p}$  ( $-x$  gives the other solution).  
**Time:**  $\mathcal{O}(\log^2 p)$  worst case,  $\mathcal{O}(\log p)$  for most  $p$

```
#define MODSQRT_H
ll sqrt(ll a, ll p) {
    a %= p; if (a < 0) a += p;
    if (a == 0) return 0;
    assert(modpow(a, (p-1)/2, p) == 1); // else no solution
    if (p % 4 == 3) return modpow(a, (p+1)/4, p);
    // a^(n+3)/8 or 2^(n+3)/8 * 2^(n-1)/4 works if p % 8 == 5
    ll s = p - 1, n = 2;
    int r = 0, m;
    while (s % 2 == 0) ++r, s /= 2;
    while (modpow(n, (p - 1) / 2, p) != p - 1) ++n;
    ll x = modpow(a, (s + 1) / 2, p);
    ll b = modpow(a, s, p), g = modpow(n, s, p);
    for (; r = m) {
        ll t = b;
        for (m = 0; m < r && t != 1; ++m) t = t * t % p;
        if (m == 0) return x;
        ll gs = modpow(g, 1LL << (r - m - 1), p);
```

```
    g = gs * gs % p; x = x * gs % p; b = b * g % p;
} // e3aa6f
} // 19a793
```

### CRT.h

**Description:** Chinese Remainder Theorem.

crt(a, m, b, n) computes  $x$  such that  $x \equiv a \pmod{m}$ ,  $x \equiv b \pmod{n}$ . If  $|a| < m$  and  $|b| < n$ ,  $x$  will obey  $0 \leq x < \text{lcm}(m, n)$ . Assumes  $mn < 2^{62}$ .  
**Time:**  $\log(n)$

|                                                                                                                                                                                                                                                                        |                   |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|
| "euclid.h"                                                                                                                                                                                                                                                             | 04d93a, 7L, 1m30s |
| <pre>ll crt(ll a, ll m, ll b, ll n) {     if (n &gt; m) swap(a, b), swap(m, n);     ll x, y, g = euclid(m, n, x, y);     assert((a - b) % g == 0); // else no solution     x = (b - a) % n * x % n / g * m + a;     return x &lt; 0 ? x + m*n/g : x; } // 04d93a</pre> |                   |

### 3.1.2 Primality and Divisibility

### FastEratosthenes.h

**Description:** Prime sieve for generating all primes smaller than LIM.

**Time:** LIM=1e9  $\approx$  1.5s

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                 |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| const int LIM = 1e6;                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | 6b2912, 20L, 4m |
| <pre>bitset&lt;LIM&gt; isPrime; vi eratosthenes() {     const int S = (int)round(sqrt(LIM)), R = LIM / 2;     vi pr = {2}, sieve(S+1); pr.reserve((int)(LIM/log(LIM)*1.1));     vector&lt;pii&gt; cp;     for (int i = 3; i &lt;= S; i += 2) if (!sieve[i]) {         cp.push_back({i, i * i / 2});         for (int j = i * i; j &lt;= S; j += 2 * i) sieve[j] = 1;     } // d22e52     for (int L = 1; L &lt;= R; L += S) {         array&lt;bool, S&gt; block{};         for (auto &amp;[p, idx] : cp)             for (int i=idx; i &lt; S+L; idx = (i+=p)) block[i-L] = 1;         rep(i,0,min(S, R - L))             if (!block[i]) pr.push_back((L + i) * 2 + 1);     } // 5b6623     for (int i : pr) isPrime[i] = 1;     return pr; } // 8ee6d2</pre> |                 |

### MillerRabin.h

**Description:** Deterministic Miller-Rabin primality test. Guaranteed to work for numbers up to  $7 \cdot 10^{18}$ ; for larger numbers, use Python and extend A randomly.

**Time:** 7 times the complexity of  $a^b \pmod{c}$ .

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                    |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|
| "ModMulLL.h"                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 60dcd1, 12L, 2m30s |
| <pre>bool isPrime(ull n) {     if (n &lt; 2    n % 6 % 4 != 1) return (n   1) == 3;     ull A[] = {2, 325, 9375, 28178, 450775, 9780504, 1795265022},         s = __builtin_ctzll(n-1), d = n &gt;&gt; s;     for (ull a : A) { // ^ count trailing zeroes         ull p = modpow(a%n, d, n), i = s;         while (p != 1 &amp;&amp; p != n-1 &amp;&amp; a % n &amp;&amp; i--)             p = modmul(p, p, n);         if (p != n-1 &amp;&amp; i != s) return 0;     } // edfaf1     return 1; } // 60dcd1</pre> |                    |

### PollardRho.h

**Description:** Pollard-rho randomized factorization algorithm. Returns prime factors of a number, in arbitrary order (e.g. 2299 -> {11, 19, 11}).

**Time:**  $\mathcal{O}\left(n^{1/4}\right)$ , less for numbers with small factors.

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                    |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|
| "ModMulLL.h", "MillerRabin.h"                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | d8d98d, 18L, 3m20s |
| <pre>ull pollard(ull n) {     ull x = 0, y = 0, t = 30, prd = 2, i = 1, q;     auto f = [&amp;](ull x) { return modmul(x, x, n) + i; };     while (t++ % 40    __gcd(prd, n) == 1) {         if (x == y) x = ++i, y = f(x);         if ((q = modmul(prd, max(x,y) - min(x,y), n))) prd = q;         x = f(x), y = f(f(y));     } // 989d40     return __gcd(prd, n); } // cd2ac3 vector&lt;ull&gt; factor(ull n) {     if (n == 1) return {};     if (isPrime(n)) return {n};     ull x = pollard(n);     auto l = factor(x), r = factor(n / x);     l.insert(l.end(), all(r));     return l; } // d54ba8</pre> |                    |

### euclid.h

**Description:** Finds two integers  $x$  and  $y$ , such that  $ax + by = \text{gcd}(a, b)$ . If you just need gcd, use the built in \_\_gcd instead. If  $a$  and  $b$  are coprime, then  $x$  is the inverse of  $a \pmod{b}$ .

|                                                                                                                           |                 |
|---------------------------------------------------------------------------------------------------------------------------|-----------------|
| ll euclid(ll a, ll b, ll &x, ll &y) {                                                                                     | 33ba8f, 5L, 50s |
| <pre>    if (!b) return x = 1, y = 0, a;     ll d = euclid(b, a % b, y, x);     return y -= a/b * x, d; } // 33ba8f</pre> |                 |

## 3.2 Discrete Math

### 3.2.1 Convolutions

### FastFourierTransform.h

**Description:**  $\text{fft}(a)$  computes  $f(k) = \sum_x a[x] \exp(2\pi i \cdot kx/N)$  for all  $k$ .  $N$  must be a power of 2. Useful for convolution:  $\text{conv}(a, b) = c$ , where  $c[x] = \sum a[i]b[x-i]$ . For convolution of complex numbers or more than two vectors: FFT, multiply pointwise, divide by  $n$ , reverse(start+1, end), FFT back. Rounding is safe if  $(\sum a_i^2 + \sum b_i^2) \log_2 N < 9 \cdot 10^{14}$  (in practice  $10^{16}$ ; higher for random inputs). Otherwise, use NTT/FFTMod.  
**Time:**  $\mathcal{O}(N \log N)$  with  $N = |A| + |B|$  ( $\sim 1$ s for  $N = 2^{22}$ )

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                    |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|
| typedef complex<double> C;                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 3dd197, 36L, 7m50s |
| <pre>typedef vector&lt;double&gt; vd; void fft(vector&lt;C&gt;&amp; a) {     int n = sz(a), L = 31 - __builtin_clz(n);     static vector&lt;complex&lt;long double&gt;&gt; R(2, 1); // (10% faster if double)     static vector&lt;C&gt; rt(2, 1);     for (static int k = 2; k &lt; n; k *= 2) {         R.resize(n); rt.resize(n);         auto x = polar(1.0L, acos(-1.0L) / k);         rep(i,k,2*k) rt[i] = R[i] = i&amp;1 ? R[i/2] * x : R[i/2];     } // a8a74e     vi rev(n);     rep(i,0,n) rev[i] = (rev[i / 2]   (i &amp; 1) &lt;&lt; L) / 2;     rep(i,0,n) if (i &lt; rev[i]) swap(a[i], a[rev[i]]);     for (int k = 1; k &lt; n; k *= 2)         for (int i = 0; i &lt; n; i += 2 * k) rep(j,0,k) {             auto x = (double *)&amp;rt[j+k], y = (double *)&amp;a[i+j+k];             C z(x[0]*y[0] - x[1]*y[1], x[0]*y[1] + x[1]*y[0]);             a[i + j + k] = a[i + j] - z;             a[i + j] += z;</pre> |                    |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |  |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| } // 69f11b } // 2258f7                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |  |
| <pre>vd conv(const vd&amp; a, const vd&amp; b) {     if (a.empty()    b.empty()) return {};     vd res(sz(a) + sz(b) - 1);     int L = 32 - __builtin_clz(sz(res)), n = 1 &lt;&lt; L;     vector&lt;C&gt; in(n), out(n);     copy(all(a), begin(in));     rep(i,0,sz(b)) in[i].imag(b[i]);     fft(in);     for (C&amp; x : in) x *= x;     rep(i,0,n) out[i] = in[-i &amp; (n - 1)] - conj(in[i]);     fft(out);     rep(i,0,sz(res)) res[i] = imag(out[i]) / (4 * n);     return res; } // 873509</pre> |  |

### FastFourierTransformMod.h

**Description:** Higher precision FFT, can be used for convolutions modulo arbitrary integers as long as  $N \log_2 N \cdot \text{mod} < 8.6 \cdot 10^{14}$  (in practice  $10^{16}$  or higher). Inputs must be in  $[0, \text{mod})$ .

**Time:**  $\mathcal{O}(N \log N)$ , where  $N = |A| + |B|$  (twice as slow as NTT or FFT)

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                 |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| "FastFourierTransform.h"                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | b82773, 22L, 5m |
| <pre>typedef vector&lt;ll&gt; vl; template&lt;int M&gt; vl convMod(const vl &amp;a, const vl &amp;b) {     if (a.empty()    b.empty()) return {};     vl res(sz(a) + sz(b) - 1);     int B=32-__builtin_clz(sz(res)), n=1&lt;&lt;B, cut=(int)(sqrt(M));     vector&lt;C&gt; L(n), R(n), outs(n), outl(n);     rep(i,0,sz(a)) L[i] = C((int)a[i] / cut, (int)a[i] % cut);     rep(i,0,sz(b)) R[i] = C((int)b[i] / cut, (int)b[i] % cut);     fft(L, fft(R);     rep(i,0,n) {         int j = -i &amp; (n - 1);         outl[j] = (L[i] + conj(L[j])) * R[i] / (2.0 * n);         outs[j] = (L[i] - conj(L[j])) * R[i] / (2.0 * n) / 1i;     } // cb3017     fft(outl, fft(outs);     rep(i,0,sz(res)) {         ll av = ll(real(outl[i])+.5), cv = ll(imag(outs[i])+.5);         ll bv = ll(imag(outl[i])+.5) + ll(real(outs[i])+.5);         res[i] = ((av % M * cut + bv) % M * cut + cv) % M;     } // 58fa4f     return res; } // c1f2f1</pre> |                 |

### NumberTheoreticTransform.h

**Description:**  $\text{ntt}(a)$  computes  $f(k) = \sum_x a[x]g^{xk}$  for all  $k$ , where  $g = \text{root}^{(\text{mod}-1)/N}$ .  $N$  must be a power of 2. Useful for convolution modulo specific nice primes of the form  $2^a b + 1$ , where the convolution result has size at most  $2^a$ . For arbitrary modulo, see FFTMod.  $\text{conv}(a, b) = c$ , where  $c[x] = \sum a[i]b[x-i]$ . For manual convolution: NTT the inputs, multiply pointwise, divide by  $n$ , reverse(start+1, end), NTT back. Inputs must be in  $[0, \text{mod})$ .

**Time:**  $\mathcal{O}(N \log N)$

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                    |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|
| "../math/ModPow.h"                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | a46443, 35L, 7m50s |
| <pre>const ll root = 62; // change mod to (119 &lt;&lt; 23) + 1 =     998244353 // For p &lt; 2^30 there is also e.g. 5 &lt;&lt; 25, 7 &lt;&lt; 26, 479 &lt;&lt; 21 // and 483 &lt;&lt; 21 (same root). The last two are &gt; 10^9. typedef vector&lt;ll&gt; vl; void ntt(vl &amp;a) {     int n = sz(a), L = 31 - __builtin_clz(n);     static vl rt(2, 1);     for (static int k = 2, s = 2; k &lt; n; k *= 2, s++) {         rt.resize(n);         ll z[] = {1, modpow(root, mod &gt;&gt; s)};</pre> |                    |

```
    rep(i,k,2*k) rt[i] = rt[i / 2] * z[i & 1] % mod;
} // f39127
vi rev(n);
rep(i,0,n) rev[i] = (rev[i / 2] | (i & 1) << L) / 2;
rep(i,0,n) if (i < rev[i]) swap(a[i], a[rev[i]]);
for (int k = 1; k < n; k *= 2)
    for (int i = 0; i < n; i += 2 * k) rep(j,0,k) {
        ll z = rt[j + k] * a[i + j + k] % mod, &ai = a[i + j];
        a[i + j + k] = ai - z + (z > ai ? mod : 0);
        ai += (ai + z >= mod ? z - mod : z);
    } // 9a8565
} // 3b763b
vl conv(const vl &a, const vl &b) {
    if (a.empty() || b.empty()) return {};
    int s = sz(a) + sz(b) - 1, B = 32 - __builtin_clz(s),
        n = 1 << B;
    int inv = modpow(n, mod - 2);
    vl L(a), R(b), out(n);
    L.resize(n), R.resize(n);
    ntt(L), ntt(R);
    rep(i,0,n)
        out[-i & (n - 1)] = (ll)L[i] * R[i] % mod * inv % mod;
    ntt(out);
    return {out.begin(), out.begin() + s};
} // 3876bf
```

**FastSubsetTransform.h**  
**Description:** Transform to a basis with fast convolutions of the form  $c[z] = \sum_{z=x\oplus y} a[x] \cdot b[y]$ , where  $\oplus$  is one of AND, OR, XOR. The size of  $a$  must be a power of two.  
**Time:**  $\mathcal{O}(N \log N)$

```
void FST(vi& a, bool inv) {
    for (int n = sz(a), step = 1; step < n; step *= 2) {
        for (int i = 0; i < n; i += 2 * step) rep(j,i,step) {
            int &u = a[j], &v = a[j + step]; tie(u, v) =
                inv ? pii(v - u, u) : pii(v, u + v); // AND
                inv ? pii(v, u - v) : pii(u + v, u); // OR
                pii(u + v, u - v); // XOR
        } // 7b7e71
    } // faec61
    if (inv) for (int& x : a) x /= sz(a); // XOR only
} // 57eeaf
vi conv(vi a, vi b) {
    FST(a, 0); FST(b, 0);
    rep(i,0,sz(a)) a[i] *= b[i];
    FST(a, 1); return a;
} // 3cbd18
```

### 3.2.2 Recurrences and Sums

**BerlekampMassey.h**  
**Description:** Recovers any  $n$ -order linear recurrence relation from the first  $2n$  terms of the recurrence. Useful for guessing linear recurrences after brute-forcing the first terms. Should work on any field, but numerical stability for floats is not guaranteed. Output will have size  $\leq n$ .  
**Usage:** berlekampMassey({0, 1, 1, 3, 5, 11}) // {1, 2}  
**Time:**  $\mathcal{O}(N^2)$

```
"../math/ModPow.h"
vector<ll> berlekampMassey(vector<ll> s) {
    int n = sz(s), L = 0, m = 0;
    vector<ll> C(n), B(n), T;
    C[0] = B[0] = 1; ll b = 1;
    rep(i,0,n) { ++m;
        ll d = s[i] % mod;
        rep(j,1,L+1) d = (d + C[j] * s[i - j]) % mod;
        if (!d) continue;
        T = C; ll coef = d * modpow(b, mod-2) % mod;
```

```
        rep(j,m,n) C[j] = (C[j] - coef * B[j - m]) % mod;
        if (2 * L > i) continue;
        L = i + 1 - L; B = T; b = d; m = 0;
    } // 8c2376
    C.resize(L + 1); C.erase(C.begin());
    for (ll& x : C) x = (mod - x) % mod;
    return C;
} // 96548b
```

**LinearRecurrence.h**  
**Description:** Generates the  $k$ 'th term of an  $n$ -order linear recurrence  $S[i] = \sum_j S[i - j - 1]tr[j]$ , given  $S[0 \dots \geq n - 1]$  and  $tr[0 \dots n - 1]$ . Faster than matrix multiplication. Useful together with Berlekamp–Massey.  
**Usage:** linearRec({0, 1}, {1, 1}, k) //  $k$ 'th Fibonacci number  
**Time:**  $\mathcal{O}(n^2 \log k)$

```
typedef vector<ll> Poly;
ll linearRec(Poly S, Poly tr, ll k) {
    int n = sz(tr);
    auto combine = [&](Poly a, Poly b) {
        Poly res(n * 2 + 1);
        rep(i,0,n+1) rep(j,0,n+1)
            res[i + j] = (res[i + j] + a[i] * b[j]) % mod;
        for (int i = 2 * n; i > n; --i) rep(j,0,n)
            res[i - 1 - j] = (res[i - 1 - j] + res[i] * tr[j]) % mod;
        res.resize(n + 1);
        return res;
    }; // 55c8ab
    Poly pol(n + 1), e(pol); pol[0] = e[1] = 1;
    for (++k; k; k /= 2) {
        if (k % 2) pol = combine(pol, e);
        e = combine(e, e);
    } // 8137be
    ll res = 0;
    rep(i,0,n) res = (res + pol[i + 1] * S[i]) % mod;
    return res;
} // 5948dc
```

**FloorModSum.h**  
**Description:** Floor sum and Mod sum.  
 $\text{modsum}(to, c, k, m) = \sum_{i=0}^{to-1} (ki + c) \% m$ .  $\text{divsum}$  is similar but for floored division.  
**Time:**  $\log(m)$ , with a large constant.

```
typedef unsigned long long ull;
// written in a weird way to deal with overflows correctly
ull sumsq(ull to) { return to / 2 * ((to-1) | 1); }
ull divsum(ull to, ull c, ull k, ull m) {
    ull res = k / m * sumsq(to) + c / m * to;
    k %= m; c %= m;
    if (!k) return res;
    ull to2 = (to * k + c) / m;
    return res + (to - 1) * to2 - divsum(to2, m-1 - c, m, k);
} // 78bfc8
ll modsum(ull to, ll c, ll k, ll m) {
    c = ((c % m) + m) % m;
    k = ((k % m) + m) % m;
    return to * c + k * sumsq(to) - m * divsum(to, c, k, m);
} // 5daf3e
```

## 3.3 Linear Algebra

### 3.3.1 Matrices

**Determinant.h**  
**Description:** Calculates determinant of a matrix. Destroys the matrix.  
**Time:**  $\mathcal{O}(N^3)$

```
double det(vector<vector<double>>& a) {
```

```
int n = sz(a); double res = 1;
rep(i,0,n) {
    int b = i;
    rep(j,i+1,n) if (fabs(a[j][i]) > fabs(a[b][i])) b = j;
    if (i != b) swap(a[i], a[b]), res *= -1;
    res *= a[i][i];
    if (res == 0) return 0;
    rep(j,i+1,n) {
        double v = a[j][i] / a[i][i];
        if (v != 0) rep(k,i+1,n) a[j][k] -= v * a[i][k];
    } // 4ec6a2
} // ee1466
return res;
} // bd5cec
```

**IntDeterminant.h**  
**Description:** Calculates determinant using modular arithmetics. Modulos can also be removed to get a pure-integer version.  
**Time:**  $\mathcal{O}(N^3)$

```
const ll mod = 12345;
ll det(vector<vector<ll>>& a) {
    int n = sz(a); ll ans = 1;
    rep(i,0,n) {
        rep(j,i+1,n) {
            while (a[j][i] != 0) { // gcd step
                ll t = a[i][i] / a[j][i];
                if (t) rep(k,i,n)
                    a[i][k] = (a[i][k] - a[j][k] * t) % mod;
                swap(a[i], a[j]);
                ans *= -1;
            } // e81b29
        } // 30d1b2
        ans = ans * a[i][i] % mod;
        if (!ans) return 0;
    } // f39a45
    return (ans + mod) % mod;
} // 5e85f0
```

**MatrixInverse.h**  
**Description:** Invert matrix  $A$ . Returns rank; result is stored in  $A$  unless singular (rank <  $n$ ). Can easily be extended to prime moduli; for prime powers, repeatedly set  $A^{-1} = A^{-1}(2I - AA^{-1}) \pmod{p^k}$  where  $A^{-1}$  starts as the inverse of  $A \bmod p$ , and  $k$  is doubled in each step.  
**Time:**  $\mathcal{O}(n^3)$

```
ebfff6, 32L, 5m40s
int matInv(vector<vector<double>>& A) {
    int n = sz(A); vi col(n);
    vector<vector<double>> tmp(n, vector<double>(n));
    rep(i,0,n) tmp[i][i] = 1, col[i] = i;
    rep(i,0,n) {
        int r = i, c = i;
        rep(j,i,n) rep(k,i,n)
            if (fabs(A[j][k]) > fabs(A[r][c]))
                r = j, c = k;
        if (fabs(A[r][c]) < 1e-12) return i;
        A[i].swap(A[r]); tmp[i].swap(tmp[r]);
        rep(j,0,n)
            swap(A[j][i], A[j][c]), swap(tmp[j][i], tmp[j][c]);
        swap(col[i], col[c]);
        double v = A[i][i];
        rep(j,i+1,n) {
            double f = A[j][i] / v;
            A[j][i] = 0;
            rep(k,i+1,n) A[j][k] -= f*A[i][k];
            rep(k,0,n) tmp[j][k] -= f*tmp[i][k];
        } // ebeea3
        rep(j,i+1,n) A[i][j] /= v;
```

```
    rep(j,0,n) tmp[i][j] /= v;
    A[i][i] = 1;
} // 26d90b
for (int i = n-1; i > 0; --i) rep(j,0,i) {
    double v = A[j][i];
    rep(k,0,n) tmp[j][k] -= v*tmp[i][k];
} // 03ae0c
rep(i,0,n) rep(j,0,n) A[col[i]][col[j]] = tmp[i][j];
return n;
} // ebfff6
```

3.3.2 Systems

SolveLinear.h

**Description:** Solves  $A * x = b$ . If there are multiple solutions, an arbitrary one is returned. Returns rank, or -1 if no solutions. Data in  $A$  and  $b$  is lost.  
**Time:**  $\mathcal{O}(n^2m)$

44c9ab, 35L, 5m30s

```
typedef vector<double> vd;
const double eps = 1e-12;
int solveLinear(vector<vd>& A, vd& b, vd& x) {
    int n = sz(A), m = sz(x), rank = 0, br, bc;
    if (n) assert(sz(A[0]) == m);
    vi col(m); iota(all(col), 0);
    rep(i,0,n) {
        double v, bv = 0;
        rep(r,i,n) rep(c,i,m)
            if ((v = fabs(A[r][c])) > bv)
                br = r, bc = c, bv = v;
        if (bv <= eps) {
            rep(j,i,n) if (fabs(b[j]) > eps) return -1;
            break;
        } // c92205
        swap(A[i], A[br]);
        swap(b[i], b[br]);
        swap(col[i], col[bc]);
        rep(j,0,n) swap(A[j][i], A[j][bc]);
        bv = 1/A[i][i];
        rep(j,i+1,n) {
            double fac = A[j][i] * bv;
            b[j] -= fac * b[i];
            rep(k,i+1,m) A[j][k] -= fac*A[i][k];
        } // 881860
        rank++;
    } // 0f0f0f
    x.assign(m, 0);
    for (int i = rank; i--;) {
        b[i] /= A[i][i];
        x[col[i]] = b[i];
        rep(j,0,i) b[j] -= A[j][i] * b[i];
    } // ed1d08
    return rank; // (multiple solutions if rank < m)
} // ade67b
```

SolveLinear2.h

**Description:** To get all uniquely determined values of  $x$  back from SolveLinear, make the following changes:

"SolveLinear.h" 08e495, 7L, 1m20s

```
rep(j,0,n) if (j != i) // instead of rep(j,i+1,n)
// ... then at the end:
x.assign(m, undefined);
rep(i,0,rank) {
    rep(j,rank,m) if (fabs(A[i][j]) > eps) goto fail;
    x[col[i]] = b[i] / A[i][i];
fail:; } // 87878c
```

SolveLinearBinary.h

**Description:** Solves  $Ax = b$  over  $\mathbb{F}_2$ . If there are multiple solutions, one is returned arbitrarily. Returns rank, or -1 if no solutions. Destroys  $A$  and  $b$ .  
**Time:**  $\mathcal{O}(n^2m)$

fa2d7a, 32L, 4m50s

```
typedef bitset<1000> bs;
int solveLinear(vector<bs>& A, vi& b, bs& x, int m) {
    int n = sz(A), rank = 0, br;
    assert(m <= sz(x));
    vi col(m); iota(all(col), 0);
    rep(i,0,n) {
        for (br=i; br<n; ++br) if (A[br].any()) break;
        if (br == n) {
            rep(j,i,n) if(b[j]) return -1;
            break;
        } // 80687c
        int bc = (int)A[br]._Find_next(i-1);
        swap(A[i], A[br]);
        swap(b[i], b[br]);
        swap(col[i], col[bc]);
        rep(j,0,n) if (A[j][i] != A[j][bc]) {
            A[j].flip(i); A[j].flip(bc);
        } // b44a9b
        rep(j,i+1,n) if (A[j][i]) {
            b[j] ^= b[i];
            A[j] ^= A[i];
        } // 87192e
        rank++;
    } // fe9281
    x = bs();
    for (int i = rank; i--;) {
        if (!b[i]) continue;
        x[col[i]] = 1;
        rep(j,0,i) b[j] ^= A[j][i];
    } // 8fdbb1
    return rank; // (multiple solutions if rank < m)
} // 26d73e
```

Tridiagonal.h

**Description:**  $x = \text{tridiagonal}(d, p, q, b)$  solves the equation system

$$\begin{pmatrix} b_0 \\ b_1 \\ b_2 \\ b_3 \\ \vdots \\ b_{n-1} \end{pmatrix} = \begin{pmatrix} d_0 & p_0 & 0 & 0 & \cdots & 0 \\ q_0 & d_1 & p_1 & 0 & \cdots & 0 \\ 0 & q_1 & d_2 & p_2 & \cdots & 0 \\ \vdots & \vdots & \vdots & \ddots & \ddots & \vdots \\ 0 & 0 & \cdots & q_{n-3} & d_{n-2} & p_{n-2} \\ 0 & 0 & \cdots & 0 & q_{n-2} & d_{n-1} \end{pmatrix} \begin{pmatrix} x_0 \\ x_1 \\ x_2 \\ x_3 \\ \vdots \\ x_{n-1} \end{pmatrix}.$$

This is useful for solving problems on the type

$$a_i = b_i a_{i-1} + c_i a_{i+1} + d_i, 1 \leq i \leq n,$$

where  $a_0, a_{n+1}, b_i, c_i$  and  $d_i$  are known.  $a$  can then be obtained from

$$\{a_i\} = \text{tridiagonal}(\{1, -1, -1, \dots, -1, 1\}, \{0, c_1, c_2, \dots, c_n\}, \{b_1, b_2, \dots, b_n, 0\}, \{a_0, d_1, d_2, \dots, d_n, a_{n+1}\}).$$

Fails if the solution is not unique.  
If  $|d_i| > |p_i| + |q_{i-1}|$  for all  $i$ , or  $|d_i| > |p_{i-1}| + |q_i|$ , or the matrix is positive definite, the algorithm is numerically stable and neither `tr` nor the check for `diag[i] == 0` is needed.  
**Time:**  $\mathcal{O}(N)$

8f9fa8, 26L, 4m20s

```
typedef double T;
vector<T> tridiagonal(vector<T> diag, const vector<T>& super,
    const vector<T>& sub, vector<T> b) {
    int n = sz(b); vi tr(n);
    rep(i,0,n-1) {
        if (abs(diag[i]) < 1e-9 * abs(super[i])) { // diag[i] == 0
            b[i+1] -= b[i] * diag[i+1] / super[i];
            if (i+2 < n) b[i+2] -= b[i] * sub[i+1] / super[i];
```

```
            diag[i+1] = sub[i]; tr[++i] = 1;
        } else { // 464c09
            diag[i+1] -= super[i]*sub[i]/diag[i];
            b[i+1] -= b[i]*sub[i]/diag[i];
        } // 62de5a
    } // ed9cce
    for (int i = n; i--;) {
        if (tr[i]) {
            swap(b[i], b[i-1]);
            diag[i-1] = diag[i];
            b[i] /= super[i-1];
        } else { // 0543e4
            b[i] /= diag[i];
            if (i) b[i-1] -= b[i]*super[i-1];
        } // aa91c6
    } // 28af28
    return b;
} // 06d549
```

3.4 Calculus

3.4.1 Functions

Integrate.h

**Description:** Simple integration of a function over an interval using Simpson's rule. The error should be proportional to  $h^4$ , although in practice you will want to verify that the result is stable to desired precision when epsilon changes.

4756fc, 6L, 1m20s

```
template<class F>
double quad(double a, double b, F f, const int n = 1000) {
    double h = (b - a) / 2 / n, v = f(a) + f(b);
    rep(i,1,n*2) v += f(a + i*h) * (i&1 ? 4 : 2);
    return v * h / 3;
} // ddcce2
```

IntegrateAdaptive.h

**Description:** Fast integration using an adaptive Simpson's rule.  
**Usage:** double sphereVolume = quad(-1, 1, [](double x) { return quad(-1, 1, [&](double y) { return quad(-1, 1, [&](double z) { return x\*x + y\*y + z\*z < 1; }));});});

92dd79, 12L, 2m50s

```
typedef double d;
#define S(a,b) (f(a) + 4*f((a+b) / 2) + f(b)) * (b-a) / 6
template <class F> d rec(F& f, d a, d b, d eps, d S) {
    d c = (a + b) / 2;
    d S1 = S(a, c), S2 = S(c, b), T = S1 + S2;
    if (abs(T - S) <= 15 * eps || b - a < 1e-10)
        return T + (T - S) / 15;
    return rec(f, a, c, eps / 2, S1) + rec(f, c, b, eps / 2, S2);
} // 10c680
template<class F> d quad(d a, d b, F f, d eps = 1e-8) {
    return rec(f, a, b, eps, S(a, b));
} // 7afc73
```

Simplex.h

**Description:** Solves a general linear maximization problem: maximize  $c^T x$  subject to  $Ax \leq b, x \geq 0$ . Returns -inf if there is no solution, inf if there are arbitrarily good solutions, or the maximum value of  $c^T x$  otherwise. The input vector is set to an optimal  $x$  (or in the unbounded case, an arbitrary solution fulfilling the constraints). Numerical stability is not guaranteed. For better performance, define variables such that  $x = 0$  is viable.  
**Usage:** vvd A = {{1,-1}, {-1,1}, {-1,-2}};  
vd b = {1,1,-4}, c = {-1,-1}, x;  
T val = LPSolver(A, b, c).solve(x);

**Time:**  $\mathcal{O}(NM * \#pivots)$ , where a pivot may be e.g. an edge relaxation.  $\mathcal{O}(2^n)$  in the general case.

aa5530, 60L, 11m20s

```
typedef double T; // long double, Rational, double + modkP>...
typedef vector<T> vd;
typedef vector<vd> vvd;
const T eps = 1e-8, inf = 1/.0;
#define MP make_pair
#define ltj(X) if(s == -1 || MP(X[j],N[j]) < MP(X[s],N[s])) s=j
struct LPSolver {
    int m, n; vi N, B; vvd D;
    LPSolver(const vvd& A, const vd& b, const vd& c) :
        m(sz(b)), n(sz(c)), N(n+1), B(m), D(m+2, vd(n+2)) {
        rep(i,0,m) rep(j,0,n) D[i][j] = A[i][j];
        rep(i,0,m) { B[i] = n+i; D[i][n] = -1; D[i][n+1] = b[i];}
        rep(j,0,n) { N[j] = j; D[m][j] = -c[j]; }
        N[n] = -1; D[m+1][n] = 1;
    } // 6ff8e9
    void pivot(int r, int s) {
        T *a = D[r].data(), inv = 1 / a[s];
        rep(i,0,m+2) if (i != r && abs(D[i][s]) > eps) {
            T *b = D[i].data(), inv2 = b[s] * inv;
            rep(j,0,n+2) b[j] -= a[j] * inv2;
            b[s] = a[s] * inv2;
        } // ca4460
        rep(j,0,n+2) if (j != s) D[r][j] *= inv;
        rep(i,0,m+2) if (i != r) D[i][s] *= -inv;
        D[r][s] = inv;
        swap(B[r], N[s]);
    } // 9cd0a8
    bool simplex(int phase) {
        int x = m + phase - 1;
        for (;;) {
            int s = -1;
            rep(j,0,n+1) if (N[j] != -phase) ltj(D[x]);
            if (D[x][s] >= -eps) return true;
            int r = -1;
            rep(i,0,m) {
                if (D[i][s] <= eps) continue;
                if (r == -1 || MP(D[i][n+1] / D[i][s], B[i])
                    < MP(D[r][n+1] / D[r][s], B[r])) r = i;
            } // 46853f
            if (r == -1) return false;
            pivot(r, s);
        } // 7d839b
    } // f15644
    T solve(vd &x) {
        int r = 0;
        rep(i,1,m) if (D[i][n+1] < D[r][n+1]) r = i;
        if (D[r][n+1] < -eps) {
            pivot(r, n);
            if (!simplex(2) || D[m+1][n+1] < -eps) return -inf;
            rep(i,0,m) if (B[i] == -1) {
                int s = 0;
                rep(j,1,n+1) ltj(D[i]);
                pivot(i, s);
            } // 683310
        } // b6553f
        bool ok = simplex(1); x = vd(n);
        rep(i,0,m) if (B[i] < n) x[B[i]] = D[i][n+1];
        return ok ? D[m][n+1] : inf;
    } // 396a95
}; // c57b35
```

3.4.2 Polynomials

PolyRoots.h

Description: Finds the real roots to a polynomial.  
Usage: polyRoots({{2,-3,1}},-1e9,1e9) // solve x^2-3x+2 = 0  
Time:  $\mathcal{O}(n^2 \log(1/\epsilon))$

e897c3, 40L, 6m10s

```
struct Poly {
    vector<double> a;
    double operator()(double x) const {
        double val = 0;
        for (int i = sz(a); i--;) (val *= x) += a[i];
        return val;
    } // ae76f3
    void diff() {
        rep(i,1,sz(a)) a[i-1] = i*a[i];
        a.pop_back();
    } // afcaea
    void divroot(double x0) {
        double b = a.back(), c; a.back() = 0;
        for(int i=sz(a)-1; i--;) c = a[i], a[i] = a[i+1]*x0+b, b=c;
        a.pop_back();
    } // 3f874a
}; // c9b7b0
vector<double> polyRoots(Poly p, double xmin, double xmax) {
    if (sz(p.a) == 2) { return {-p.a[0]/p.a[1]}; }
    vector<double> ret;
    Poly der = p;
    der.diff();
    auto dr = polyRoots(der, xmin, xmax);
    dr.push_back(xmin-1);
    dr.push_back(xmax+1);
    sort(all(dr));
    rep(i,0,sz(dr)-1) {
        double l = dr[i], h = dr[i+1];
        bool sign = p(l) > 0;
        if (sign ^ (p(h) > 0)) {
            rep(it,0,60) { // while (h - l > 1e-8)
                double m = (l + h) / 2, f = p(m);
                if ((f <= 0) ^ sign) l = m;
                else h = m;
            } // b69f41
            ret.push_back((l + h) / 2);
        } // fc22f0
    } // d15986
    return ret;
} // b00bfe
```

PolyInterpolate.h

Description: Given  $n$  points  $(x[i], y[i])$ , computes an  $n-1$ -degree polynomial  $p$  that passes through them:  $p(x) = a[0] * x^0 + \dots + a[n-1] * x^{n-1}$ . For numerical precision, pick  $x[k] = c * \cos(k/(n-1) * \pi), k = 0 \dots n-1$ .  
Time:  $\mathcal{O}(n^2)$

08bf48, 13L, 2m

```
typedef vector<double> vd;
vd interpolate(vd x, vd y, int n) {
    vd res(n), temp(n);
    rep(k,0,n-1) rep(i,k+1,n)
        y[i] = (y[i] - y[k]) / (x[i] - x[k]);
    double last = 0; temp[0] = 1;
    rep(k,0,n) rep(i,0,n) {
        res[i] += y[k] * temp[i];
        swap(last, temp[i]);
        temp[i] -= last * x[k];
    } // 4c74fe
    return res;
} // 285367
```

Geometry (4)

4.1 Geometric primitives

Point.h


Description: Class to handle points in the plane. T can be e.g. double or long long. (Avoid int.)

ef0c0e, 28L, 8m10s

```
template<class T> int sgn(T x) { return (x > 0) - (x < 0); }
template<class T>
struct Point {
    typedef Point P;
    T x, y;
    explicit Point(T _x=0, T _y=0) : x(_x), y(_y) {}
    bool operator<(P p) const { return tie(x,y) < tie(p.x,p.y); }
    bool operator==(P p) const { return tie(x,y)==tie(p.x,p.y); }
    P operator+(P p) const { return P(x+p.x, y+p.y); }
    P operator-(P p) const { return P(x-p.x, y-p.y); }
    P operator*(T d) const { return P(x*d, y*d); }
    P operator/(T d) const { return P(x/d, y/d); }
    T dot(P p) const { return x*p.x + y*p.y; }
    T cross(P p) const { return x*p.y - y*p.x; }
    T cross(P a, P b) const { return (a-*this).cross(b-*this); }
    T dist2() const { return x*x + y*y; }
    double dist() const { return sqrt((double)dist2()); }
    // angle to x-axis in interval [-pi, pi]
    double angle() const { return atan2(y, x); }
    P unit() const { return *this/dist(); } // makes dist()==1
    P perp() const { return P(-y, x); } // rotates +90 degrees
    P normal() const { return perp().unit(); }
    // returns point rotated 'a' radians ccw around the origin
    P rotate(double a) const {
        return P(x*cos(a)-y*sin(a),x*sin(a)+y*cos(a)); } // 4822a3
    friend ostream& operator<<(ostream& os, P p) {
        return os << "(" << p.x << "," << p.y << ")"; } // 9a9c95
}; // 6a5cce
```

lineDistance.h

Description:  
Returns the signed distance between point p and the line containing points a and b. Positive value on left side and negative on right as seen from a towards b. a==b gives nan. P is supposed to be Point<T> or Point3D<T> where T is e.g. double or long long. It uses products in intermediate steps so watch out for overflow if using int or long long. Using Point3D will always give a non-negative distance. For Point3D, call .dist on the result of the cross product.




"Point.h" f6bf6b, 4L, 50s

```
template<class P>
double lineDist(const P& a, const P& b, const P& p) {
    return (double) (b-a).cross(p-a) / (b-a).dist();
} // 00891c
```

SegmentDistance.h

Description:  
Returns the shortest distance between point p and the line segment from point s to e.  
Usage: Point<double> a, b(2,2), p(1,1);  
bool onSegment = segDist(a,b,p) < 1e-10;




"Point.h" 5c88f4, 6L, 1m20s

```
typedef Point<double> P;
double segDist(P& s, P& e, P& p) {
    if (s==e) return (p-s).dist();
    auto d = (e-s).dist2(), t = min(d,max(.0, (p-s).dot(e-s)));
    return ((p-s)*d-(e-s)*t).dist()/d;
} // ae751a
```

### SegmentIntersection.h

**Description:**  
If a unique intersection point between the line segments going from s1 to e1 and from s2 to e2 exists then it is returned. If no intersection point exists an empty vector is returned. If infinitely many exist a vector with 2 elements is returned, containing the endpoints of the common line segment. The wrong position will be returned if P is Point<ll> and the intersection point does not have integer coordinates. Products of three coordinates are used in intermediate steps so watch out for overflow if using int or long long.  
**Usage:** vector<P> inter = segInter(s1,e1,s2,e2);  
if (sz(inter)==1)  
cout << "segments intersect at " << inter[0] << endl;  
"Point.h", "OnSegment.h" 9d57f2, 13L, 3m10s


```
template<class P> vector<P> segInter(P a, P b, P c, P d) {
    auto oa = c.cross(d, a), ob = c.cross(d, b),
        oc = a.cross(b, c), od = a.cross(b, d);
    // Checks if intersection is single non-endpoint point.
    if (sgn(oa) * sgn(ob) < 0 && sgn(oc) * sgn(od) < 0)
        return {(a * ob - b * oa) / (ob - oa)};
    set<P> s;
    if (onSegment(c, d, a)) s.insert(a);
    if (onSegment(c, d, b)) s.insert(b);
    if (onSegment(a, b, c)) s.insert(c);
    if (onSegment(a, b, d)) s.insert(d);
    return {all(s)};
} // 9d57f2
```



### lineIntersection.h

**Description:**  
If a unique intersection point of the lines going through s1,e1 and s2,e2 exists {1, point} is returned. If no intersection point exists {0, (0,0)} is returned and if infinitely many exists {-1, (0,0)} is returned. The wrong position will be returned if P is Point<ll> and the intersection point does not have integer coordinates. Products of three coordinates are used in intermediate steps so watch out for overflow if using int or ll.  
**Usage:** auto res = lineInter(s1,e1,s2,e2);  
if (res.first == 1)  
cout << "intersection point at " << res.second << endl;  
"Point.h" a01f81, 8L, 1m50s

```
template<class P>
pair<int, P> lineInter(P s1, P e1, P s2, P e2) {
    auto d = (e1 - s1).cross(e2 - s2);
    if (d == 0) // if parallel
        return {-(s1.cross(e1, s2) == 0), P(0, 0)};
    auto p = s2.cross(e1, e2), q = s2.cross(e2, s1);
    return {1, (s1 * p + e1 * q) / d};
} // 47279a
```



### sideOf.h

**Description:** Returns where *p* is as seen from *s* towards *e*. 1/0/-1 ⇔ left/on line/right. If the optional argument *eps* is given 0 is returned if *p* is within distance *eps* from the line. P is supposed to be Point<T> where T is e.g. double or long long. It uses products in intermediate steps so watch out for overflow if using int or long long.  
**Usage:** bool left = sideOf(p1,p2,q)==1;  
"Point.h" 3af81c, 9L, 1m40s

```
template<class P>
int sideOf(P s, P e, P p) { return sgn(s.cross(e, p)); }

template<class P>
int sideOf(const P& s, const P& e, const P& p, double eps) {
    auto a = (e-s).cross(p-s);
    double l = (e-s).dist()*eps;
    return (a > l) - (a < -l);
} // 33fa03
```

### OnSegment.h


**Description:** Returns true iff p lies on the line segment from s to e. Use (segDist(s,e,p)<=epsilon) instead when using Point<double>.  
"Point.h" c597e8, 3L, 40s

```
template<class P> bool onSegment(P s, P e, P p) {
    return p.cross(s, e) == 0 && (s - p).dot(e - p) <= 0;
} // c597e8
```

### linearTransformation.h

**Description:**  
Apply the linear transformation (translation, rotation and scaling) which takes line p0-p1 to line q0-q1 to point r.  
"Point.h" 03a306, 6L, 1m40s

```
typedef Point<double> P;
P linearTransformation(const P& p0, const P& p1,
    const P& q0, const P& q1, const P& r) {
    P dp = p1-p0, dq = q1-q0, num(dp.cross(dq), dp.dot(dq));
    return q0 + P((r-p0).cross(num), (r-p0).dot(num))/dp.dist2();
} // 45ea01
```



### LineProjectionReflection.h

**Description:** Projects point p onto line ab. Set refl=true to get reflection of point p across line ab instead. The wrong point will be returned if P is an integer point and the desired point doesn't have integer coordinates. Products of three coordinates are used in intermediate steps so watch out for overflow.  
"Point.h" b5562d, 5L, 50s

```
template<class P>
P lineProj(P a, P b, P p, bool refl=false) {
    P v = b - a;
    return p - v.perp()*(1+refl)*v.cross(p-a)/v.dist2();
} // 4b716b
```

### Angle.h

**Description:** A class for ordering angles (as represented by int points and a number of rotations around the origin). Useful for rotational sweeping. Sometimes also represents points or vectors.  
**Usage:** vector<Angle> v = {w[0], w[0].t360() ...}; // sorted  
int j = 0; rep(i,0,n) { while (v[j] < v[i].t180()) ++j; }  
sweeps j such that (j-i) represents the number of positively oriented triangles with vertices at 0 and i  
"Point.h" 0f0602, 35L, 7m50s

```
struct Angle {
    int x, y;
    int t;
    Angle(int x, int y, int t=0) : x(x), y(y), t(t) {}
    Angle operator-(Angle b) const { return {x-b.x, y-b.y, t}; }
    int half() const {
        assert(x || y);
        return y < 0 || (y == 0 && x < 0);
    } // c935fb
    Angle t90() const { return {-y, x, t + (half() && x >= 0)}; }
    Angle t180() const { return {-x, -y, t + half()}; }
    Angle t360() const { return {x, y, t + 1}; }
}; // e258c0
bool operator<(Angle a, Angle b) {
    // add a.dist2() and b.dist2() to also compare distances
    return make_tuple(a.t, a.half(), a.y * (1l)b.x) <
        make_tuple(b.t, b.half(), a.x * (1l)b.y);
} // ce5ed3
```

// Given two points, this calculates the smallest angle between them, i.e., the angle that covers the defined line segment.  
pair<Angle, Angle> segmentAngles(Angle a, Angle b) {  
 if (b < a) swap(a, b);  
 return (b < a.t180() ?

```
    make_pair(a, b) : make_pair(b, a.t360()));
} // 5eac29
Angle operator+(Angle a, Angle b) { // point a + vector b
    Angle r(a.x + b.x, a.y + b.y, a.t);
    if (a.t180() < r) r.t--;
    return r.t180() < a ? r.t360() : r;
} // 3d8073
Angle angleDiff(Angle a, Angle b) { // angle b - angle a
    int tu = b.t - a.t; a.t = b.t;
    return {a.x*b.x + a.y*b.y, a.x*b.y - a.y*b.x, tu - (b < a)};
} // ba3082
```

## 4.2 Circles

### CircleIntersection.h

**Description:** Computes the pair of points at which two circles intersect. Returns false in case of no intersection.  
"Point.h" 84d6d3, 11L, 2m50s

```
typedef Point<double> P;
bool circleInter(P a,P b,double r1,double r2,pair<P, P>* out) {
    if (a == b) { assert(r1 != r2); return false; }
    P vec = b - a;
    double d2 = vec.dist2(), sum = r1+r2, dif = r1-r2,
        p = (d2 + r1*r1 - r2*r2)/(d2*2), h2 = r1*r1 - p*p*d2;
    if (sum*sum < d2 || dif*dif > d2) return false;
    P mid = a + vec*p, per = vec.perp() * sqrt(fmax(0, h2) / d2);
    *out = {mid + per, mid - per};
    return true;
} // c64785
```

### CircleTangents.h

**Description:** Finds the external tangents of two circles, or internal if r2 is negated. Can return 0, 1, or 2 tangents – 0 if one circle contains the other (or overlaps it, in the internal case, or if the circles are the same); 1 if the circles are tangent to each other (in which case .first = .second and the tangent line is perpendicular to the line between the centers). .first and .second give the tangency points at circle 1 and 2 respectively. To find the tangents of a circle with a point set r2 to 0.  
"Point.h" b0153d, 13L, 2m40s

```
template<class P>
vector<pair<P, P>> tangents(P c1, double r1, P c2, double r2) {
    P d = c2 - c1;
    double dr = r1 - r2, d2 = d.dist2(), h2 = d2 - dr * dr;
    if (d2 == 0 || h2 < 0) return {};
    vector<pair<P, P>> out;
    for (double sign : {-1, 1}) {
        P v = (d * dr + d.perp() * sqrt(h2) * sign) / d2;
        out.push_back({c1 + v * r1, c2 + v * r2});
    } // e25263
    if (h2 == 0) out.pop_back();
    return out;
} // 4835b9
```

### CircleLine.h

**Description:** Finds the intersection between a circle and a line. Returns a vector of either 0, 1, or 2 intersection points. P is intended to be Point<double>.  
"Point.h" e0cfba, 9L, 1m50s

```
template<class P>
vector<P> circleLine(P c, double r, P a, P b) {
    P ab = b - a, p = a + ab * (c-a).dot(ab) / ab.dist2();
    double s = a.cross(b, c), h2 = r*r - s*s / ab.dist2();
    if (h2 < 0) return {};
    if (h2 == 0) return {p};
    P h = ab.unit() * sqrt(h2);
    return {p - h, p + h};
} // 59aded
```



### CirclePolygonIntersection.h

**Description:** Returns the area of the intersection of a circle with a ccw polygon.

**Time:**  $\mathcal{O}(n)$


|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                    |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|
| "../content/geometry/Point.h"                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 19add1, 19L, 4m10s |
| <pre> <b>typedef</b> Point&lt;<b>double</b>&gt; P; <b>#define</b> arg(p, q) atan2(p.cross(q), p.dot(q)) <b>double</b> circlePoly(P c, <b>double</b> r, vector&lt;P&gt; ps) {     <b>auto</b> tri = [&amp;](P p, P q) {         <b>auto</b> r2 = r * r / 2;         P d = q - p;         <b>auto</b> a = d.dot(p)/d.dist2(), b = (p.dist2()-r*r)/d.dist2();         <b>auto</b> det = a * a - b;         <b>if</b> (det &lt;= 0) <b>return</b> arg(p, q) * r2;         <b>auto</b> s = max(0., -a-sqrt(det)), t = min(1., -a+sqrt(det));         <b>if</b> (t &lt; 0    1 &lt;= s) <b>return</b> arg(p, q) * r2;         P u = p + d * s, v = q + d * (t-1);         <b>return</b> arg(p,u) * r2 + u.cross(v)/2 + arg(v,q) * r2;     }; // a526fe     <b>auto</b> sum = 0.0;     rep(i,0,sz(ps))         sum += tri(ps[i] - c, ps[(i + 1) % sz(ps)] - c);     <b>return</b> sum; } // f082e0 </pre> |                    |

### circumcircle.h

**Description:**

The circumcirle of a triangle is the circle intersecting all three vertices. ccRadius returns the radius of the circle going through points A, B and C and ccCenter returns the center of the same circle.

|                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                   |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|
| "Point.h"                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 1caa3a, 9L, 1m50s |
| <pre> <b>typedef</b> Point&lt;<b>double</b>&gt; P; <b>double</b> ccRadius(<b>const</b> P&amp; A, <b>const</b> P&amp; B, <b>const</b> P&amp; C) {     <b>return</b> (B-A).dist()**(C-B).dist()**(A-C).dist()/         abs((B-A).cross(C-A))/2; } // 607d98 P ccCenter(<b>const</b> P&amp; A, <b>const</b> P&amp; B, <b>const</b> P&amp; C) {     P b = C-A, c = B-A;     <b>return</b> A + (b*c.dist2()-c*b.dist2()).perp()/b.cross(c)/2; } // 79372e </pre> |                   |



### MinimumEnclosingCircle.h

**Description:** Computes the minimum circle that encloses a set of points.

**Time:** expected  $\mathcal{O}(n)$

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                 |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| "circumcircle.h"                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 09dd0a, 17L, 3m |
| <pre> pair&lt;P, <b>double</b>&gt; mec(vector&lt;P&gt; ps) {     shuffle(all(ps), mt19937(time(0)));     P o = ps[0];     <b>double</b> r = 0, EPS = 1 + 1e-8;     rep(i,0,sz(ps)) <b>if</b> ((o - ps[i]).dist() &gt; r * EPS) {         o = ps[i], r = 0;         rep(j,0,i) <b>if</b> ((o - ps[j]).dist() &gt; r * EPS) {             o = (ps[i] + ps[j]) / 2;             r = (o - ps[i]).dist();             rep(k,0,j) <b>if</b> ((o - ps[k]).dist() &gt; r * EPS) {                 o = ccCenter(ps[i], ps[j], ps[k]);                 r = (o - ps[i]).dist();             } // 64802f         } // 7b0ecf     } // dcfdf0e     <b>return</b> {o, r}; } // 09dd0a </pre> |                 |

## 4.3 Polygons

### InsidePolygon.h

**Description:** Returns true if p lies within the polygon. If strict is true, it returns false for points on the boundary. The algorithm uses products in intermediate steps so watch out for overflow.

**Usage:** vector<P> v = {P{4,4}, P{1,2}, P{2,1}};

bool in = inPolygon(v, P{3, 3}, false);

**Time:**  $\mathcal{O}(n)$

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                    |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|
| "Point.h", "OnSegment.h", "SegmentDistance.h"                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 2bf504, 11L, 2m10s |
| <pre> <b>template</b>&lt;<b>class</b> P&gt; <b>bool</b> inPolygon(vector&lt;P&gt; &amp;p, P a, <b>bool</b> strict = <b>true</b>) {     <b>int</b> cnt = 0, n = sz(p);     rep(i,0,n) {         P q = p[(i + 1) % n];         <b>if</b> (onSegment(p[i], q, a)) <b>return</b> !strict;         //or: <i>if (segDist(p[i], q, a) &lt;= eps) return !strict;</i>         cnt ^= ((a.y&lt;p[i].y) - (a.y&lt;q.y)) * a.cross(p[i], q) &gt; 0;     } // 1b9961     <b>return</b> cnt; } // c7225e </pre> |                    |

### PolygonCenter.h

**Description:** Returns the center of mass for a polygon.

**Time:**  $\mathcal{O}(n)$

|                                                                                                                                                                                                                                                                                                                                                                                  |                   |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|
| "Point.h"                                                                                                                                                                                                                                                                                                                                                                        | 9706dc, 9L, 1m40s |
| <pre> <b>typedef</b> Point&lt;<b>double</b>&gt; P; P polygonCenter(<b>const</b> vector&lt;P&gt;&amp; v) {     P res(0, 0); <b>double</b> A = 0;     <b>for</b> (<b>int</b> i = 0, j = sz(v) - 1; i &lt; sz(v); j = i++) {         res = res + (v[i] + v[j]) * v[j].cross(v[i]);         A += v[j].cross(v[i]);     } // 307102     <b>return</b> res / A / 3; } // 0d0d84 </pre> |                   |

### PolygonCut.h

**Description:**

Returns a vector with the vertices of a polygon with everything to the left of the line going from s to e cut away.

**Usage:** vector<P> p = ...;

p = polygonCut(p, P(0,0), P(1,0));

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                    |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|
| "Point.h"                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | d07181, 13L, 2m20s |
| <pre> <b>typedef</b> Point&lt;<b>double</b>&gt; P; vector&lt;P&gt; polygonCut(<b>const</b> vector&lt;P&gt;&amp; poly, P s, P e) {     vector&lt;P&gt; res;     rep(i,0,sz(poly)) {         P cur = poly[i], prev = i ? poly[i-1] : poly.back();         <b>auto</b> a = s.cross(e, cur), b = s.cross(e, prev);         <b>if</b> ((a &lt; 0) != (b &lt; 0))             res.push_back(cur + (prev - cur) * (a / (a - b)));         <b>if</b> (a &lt; 0)             res.push_back(cur);     } // 757c0d     <b>return</b> res; } // 42c993 </pre> |                    |

### PolygonUnion.h

**Description:** Calculates the area of the union of  $n$  polygons (not necessarily convex). The points within each polygon must be given in CCW order. (Epsilon checks may optionally be added to sideOf/sgn, but shouldn't be needed.)

**Time:**  $\mathcal{O}(N^2)$ , where  $N$  is the total number of points

|                                                                                                                                                                                                                                     |                    |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|
| "Point.h", "sideOf.h"                                                                                                                                                                                                               | 3931c6, 33L, 7m10s |
| <pre> <b>typedef</b> Point&lt;<b>double</b>&gt; P; <b>double</b> rat(P a, P b) { <b>return</b> sgn(b.x) ? a.x/b.x : a.y/b.y; } <b>double</b> polyUnion(vector&lt;vector&lt;P&gt;&gt;&amp; poly) {     <b>double</b> ret = 0; </pre> |                    |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |  |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| <pre> rep(i,0,sz(poly)) rep(v,0,sz(poly[i])) {     P A = poly[i][v], B = poly[i][(v + 1) % sz(poly[i])];     vector&lt;pair&lt;<b>double</b>, <b>int</b>&gt;&gt; segs = {{0, 0}, {1, 0}};     rep(j,0,sz(poly)) <b>if</b> (i != j) {         rep(u,0,sz(poly[j])) {             P C = poly[j][u], D = poly[j][(u + 1) % sz(poly[j])];             <b>int</b> sc = sideOf(A, B, C), sd = sideOf(A, B, D);             <b>if</b> (sc != sd) {                 <b>double</b> sa = C.cross(D, A), sb = C.cross(D, B);                 <b>if</b> (min(sc, sd) &lt; 0)                     segs.emplace_back(sa / (sa - sb), sgn(sc - sd));             } <b>else if</b> (!sc &amp;&amp; !sd &amp;&amp; j&lt;i &amp;&amp; sgn((B-A).dot(D-C))&gt;0) {                 // cf73dd                 segs.emplace_back(rat(C - A, B - A), 1);                 segs.emplace_back(rat(D - A, B - A), -1);             } // 313ead         } // 0d1e2c     } // fdc855     sort(all(segs));     <b>for</b> (<b>auto</b>&amp; s : segs) s.first = min(max(s.first, 0.0), 1.0);     <b>double</b> sum = 0;     <b>int</b> cnt = segs[0].second;     rep(j,1,sz(segs)) {         <b>if</b> (!cnt) sum += segs[j].first - segs[j - 1].first;         cnt += segs[j].second;     } // f5884f     ret += A.cross(B) * sum; } // 19180c <b>return</b> ret / 2; } // 6e88cf </pre> |  |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|

### ConvexHull.h

**Description:**

Returns a vector of the points of the convex hull in counter-clockwise order. Points on the edge of the hull between two other points are not considered part of the hull. To include these "borders", follow the code comments.

**Time:**  $\mathcal{O}(n \log n)$

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                    |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|
| "Point.h"                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 310954, 13L, 2m50s |
| <pre> <b>typedef</b> Point&lt;ll&gt; P; vector&lt;P&gt; convexHull(vector&lt;P&gt; pts) {     <b>if</b> (sz(pts) &lt;= 1) <b>return</b> pts;     sort(all(pts));     vector&lt;P&gt; h(sz(pts)+1); // 2*sz(pts) to include borders     <b>int</b> s = 0, t = 0;     <b>for</b> (<b>int</b> it = 2; it--; s = --t, reverse(all(pts)))         <b>for</b> (P p : pts) {             <b>while</b> (t &gt;= s + 2 &amp;&amp; h[t-2].cross(h[t-1], p) &lt;= 0) t--;             h[t++] = p; // &lt; above to include borders         } // bf0344     <b>return</b> {h.begin(), h.begin() + t - (t == 2 &amp;&amp; h[0] == h[1])}; } // ec85f8 </pre> |                    |



### HullDiameter.h

**Description:** Returns the two points with max distance on a convex hull (ccw, no duplicate/collinear points).

**Time:**  $\mathcal{O}(n)$

|                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                    |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|
| "Point.h"                                                                                                                                                                                                                                                                                                                                                                                                                                               | c571b8, 12L, 2m20s |
| <pre> <b>typedef</b> Point&lt;ll&gt; P; array&lt;P, 2&gt; hullDiameter(vector&lt;P&gt; S) {     <b>int</b> n = sz(S), j = n &lt; 2 ? 0 : 1;     pair&lt;ll, array&lt;P, 2&gt;&gt; res({0, {S[0], S[0]}});     rep(i,0,j)         <b>for</b> (; j = (j + 1) % n) {             res = max(res, {{S[i] - S[j]].dist2(), {S[i], S[j]}});             <b>if</b> ((S[i + 1] % n] - S[j]).cross(S[i + 1] - S[i]) &gt;= 0)                 <b>break</b>; </pre> |                    |

```
    } // 56cc40
    return res.second;
} // 5f726b
```

PointInsideHull.h

**Description:** Determine whether a point t lies inside a convex hull (CCW order, with no collinear points). Returns true if point lies within the hull. If strict is true, points on the boundary aren't included.

**Time:**  $\mathcal{O}(\log N)$

|                                      |                 |
|--------------------------------------|-----------------|
| "Point.h", "sideOf.h", "OnSegment.h" | 71446b, 14L, 3m |
| <b>typedef</b> Point<ll> P;          |                 |

```
bool inHull(const vector<P>& l, P p, bool strict = true) {
    int a = 1, b = sz(l) - 1, r = !strict;
    if (sz(l) < 3) return r && onSegment(l[0], l.back(), p);
    if (sideOf(l[0], l[a], l[b]) > 0) swap(a, b);
    if (sideOf(l[0], l[a], p) >= r || sideOf(l[0], l[b], p) <= -r)
        return false;
    while (abs(a - b) > 1) {
        int c = (a + b) / 2;
        (sideOf(l[0], l[c], p) > 0 ? b : a) = c;
    } // b265ab
    return sgn(l[a].cross(l[b], p)) < r;
} // c74639
```

LineHullIntersection.h

**Description:** Line-convex polygon intersection. The polygon must be ccw and have no collinear points. lineHull(line, poly) returns a pair describing the intersection of a line with the polygon:  $\bullet(-1, -1)$  if no collision,  $\bullet(i, -1)$  if touching the corner  $i$ ,  $\bullet(i, i)$  if along side  $(i, i+1)$ ,  $\bullet(i, j)$  if crossing sides  $(i, i+1)$  and  $(j, j+1)$ . In the last case, if a corner  $i$  is crossed, this is treated as happening on side  $(i, i+1)$ . The points are returned in the same order as the line hits the polygon. extrVertex returns the point of a hull with the max projection onto a line.

**Time:**  $\mathcal{O}(\log n)$

```
"Point.h" 7cf45b, 38L, 8m
#define cmp(i, j) sgn(dir.perp().cross(poly[(i)%n]-poly[(j)%n]))
#define extr(i) cmp(i + 1, i) >= 0 && cmp(i, i - 1 + n) < 0
template <class P> int extrVertex(vector<P>& poly, P dir) {
    int n = sz(poly), lo = 0, hi = n;
    if (extr(0)) return 0;
    while (lo + 1 < hi) {
        int m = (lo + hi) / 2;
        if (extr(m)) return m;
        int ls = cmp(lo + 1, lo), ms = cmp(m + 1, m);
        (ls < ms || (ls == ms && ls == cmp(lo, m)) ? hi : lo) = m;
    } // 68a24c
    return lo;
} // 7f0477
#define cmpL(i) sgn(a.cross(poly[i], b))
template <class P>
array<int, 2> lineHull(P a, P b, vector<P>& poly) {
    int endA = extrVertex(poly, (a - b).perp());
    int endB = extrVertex(poly, (b - a).perp());
    if (cmpL(endA) < 0 || cmpL(endB) > 0)
        return {-1, -1};
    array<int, 2> res;
    rep(i, 0, 2) {
        int lo = endB, hi = endA, n = sz(poly);
        while ((lo + 1) % n != hi) {
            int m = ((lo + hi + (lo < hi ? 0 : n)) / 2) % n;
            (cmpL(m) == cmpL(endB) ? lo : hi) = m;
        } // 52528c
        res[i] = (lo + !cmpL(hi)) % n;
        swap(endA, endB);
    } // c05c70
    if (res[0] == res[1]) return {res[0], -1};
```

```
    if (!cmpL(res[0]) && !cmpL(res[1]))
        switch ((res[0] - res[1] + sz(poly) + 1) % sz(poly)) {
            case 0: return {res[0], res[0]};
            case 2: return {res[1], res[1]};
        } // 8fa383
    return res;
} // 36fc8e
```

PolygonContainmentTree.h

**Description:** building tree of polygon containment

**Memory:**  $\mathcal{O}(N)$

**Time:**  $\mathcal{O}(N \log N)$

|                    |
|--------------------|
| 14c82a, 44L, 8m40s |
|--------------------|

```
struct P { ll x, y; };

int current_x;
struct Segment {
    int idx; P pl, p2; bool is_upper;
    Segment(P p, P q, int i): idx(i), pl(p), p2(q), is_upper(p2.x
        < pl.x) { if (is_upper)swap(pl, p2); }
    ld get_y(ll x) const { return (ld) (p2.y - pl.y) / (p2.x - pl
        .x) * (x - pl.x) + pl.y; }
    tuple<ld, bool, int> get_comp() const { return {get_y(
        current_x), is_upper, p2.x}; }
    bool operator<(const Segment & o) const { return get_comp() <
        o.get_comp(); }
}; // fc8b4f
```

```
vector<int> build(vector<vector<P>>& polygons) {
    int n = sz(polygons);
    vector<tuple<int, int, int, Segment>> edges; // polygon edges
    rep(idx, 0, n) {
        const auto & v = polygons[idx];
        rep(i, 0, sz(v)) {
            int j = (i + 1) % sz(v);
            if (v[i].x == v[j].x)continue; // ignores vertical edges
            Segment seg = Segment(v[i], v[j], idx);
            edges.eb(seg.pl.x, 0, -seg.pl.y, seg);
            edges.eb(seg.p2.x, 1, -seg.p2.y, seg);
        } // b28b76
    } // 2603da
    sort(edges.begin(), edges.end());
    set<Segment> s;
    vector pai(n+1, n), vis(n, 0);
    for (auto [l, t, y, seg]: edges) {
        current_x = l;
        int i = seg.idx;
        if (t == 0) {
            if (not vis[i]) {
                vis[i] = true;
                auto it = s.upper_bound(seg);
                if (it == s.end())pai[i] = n;
                else if (it->is_upper)pai[i] = it->idx;
                else pai[i] = pai[it->idx];
            } // 17d107
            s.insert(seg);
        } // aff5b0
        else s.erase(seg);
    } // 3514ff
    return pai;
} // 0b7cbd
```

Minkowski.h

**Description:** Calculates the Minkowski sum of two Polygons in ccw order

**Time:**  $\mathcal{O}(N + M)$

|           |                    |
|-----------|--------------------|
| "Point.h" | e510cd, 19L, 4m10s |
|-----------|--------------------|

```
template<typename P>
vector<P> minkowski(vector<P> p, vector<P> q) {
```

```
    auto comp = [](auto a, auto b) {
        return make_pair(a.y, a.x) < make_pair(b.y, b.x);
    }; // 278e98
    rotate(p.begin(), min_element(all(p), comp), p.end());
    rotate(q.begin(), min_element(all(q), comp), q.end());
    p.pb(p[0]); p.pb(p[1]);
    q.pb(q[0]); q.pb(q[1]);
    vector<P> result;
    int i = 0, j = 0;
    while(i < sz(p) - 2 || j < sz(q) - 2){
        result.pb(p[i] + q[j]);
        auto cross = (p[i + 1] - p[i]).cross(q[j + 1] - q[j]);
        if(cross >= 0 && i < sz(p) - 2) i++;
        if(cross <= 0 && j < sz(q) - 2) j++;
    } // 57f2d7
    return result;
} // a99371
```

HalfPlane.h

**Description:** Calculates the halfplane intersection of Halfplanes, Halfplanes allow everything to the left. Cuidado com a precisao

**Time:**  $\mathcal{O}(N \log N)$

|           |                     |
|-----------|---------------------|
| "Point.h" | 9cf69d, 50L, 10m40s |
|-----------|---------------------|

```
const ld EPS = 1e-9, INF = 1e9;
typedef Point<ld> P;
struct HP {
    P p, pq;
    ld angle;
    HP() {}
    HP(P a, P b) : p(a), pq(b - a), angle(atan2(pq.y, pq.x)) {}

    bool out(const P & r) { return pq.cross(r - p) < -EPS; }
    bool operator<(const HP & e) const { return angle < e.angle
        ; }
    friend P inter(const HP & s, const HP & t) {
        ld alpha = (t.p - s.p).cross(t.pq) / s.pq.cross(t.pq);
        return s.p + (s.pq * alpha);
    } // 946b1a
}; // 782415
vector<P> hp_intersect(vector<HP>& &H) {
    P box[4] = {
        P(INF, INF),
        P(-INF, INF),
        P(-INF, -INF),
        P(INF, -INF)
    }; // 63b3ab
    for(int i = 0; i < 4; i++) H.eb(box[i], box[(i+1) % 4]);
    sort(H.begin(), H.end());
    deque<HP> dq;
    int len = 0;
    rep(i, 0, sz(H)) {
        while (len > 1 && H[i].out(inter(dq[len-1], dq[len-2]))
            )
            dq.pop_back(), len--;
        while (len > 1 && H[i].out(inter(dq[0], dq[1])))
            dq.pop_front(), len--;
        // Special case check: Parallel half planes
        if (len > 0 && fabs1(H[i].pq.cross(dq[len-1].pq)) < EPS
            ) {
            if (H[i].pq.dot(dq[len-1].pq) < 0.0) return {};
            if (H[i].out(dq[len-1].p))
                dq.pop_back(), len--;
            else continue;
        } // 6ef632
        dq.push_back(H[i]); len++;
    } // 82e81e
    while (len > 2 && dq[0].out(inter(dq[len-1], dq[len-2])))
        dq.pop_back(), len--;
```

```
while (len > 2 && dq[len-1].out(inter(dq[0], dq[1])))
dq.pop_front(), len--;
if (len < 3) return {};
vector<P> ret(len);
rep(i, 0, len-1) ret[i] = inter(dq[i], dq[i+1]);
ret.back() = inter(dq[len-1], dq[0]);
return ret;
} // 586596
```

4.4 Misc. Point Set Problems

**ClosestPair.h**  
**Description:** Finds the closest pair of points.  
**Time:**  $\mathcal{O}(n \log n)$

|           |                    |
|-----------|--------------------|
| "Point.h" | ac41a6, 17L, 3m10s |
|-----------|--------------------|

```
typedef Point<ll> P;
pair<P, P> closest(vector<P> v) {
assert(sz(v) > 1);
set<P> S;
sort(all(v), [](P a, P b) { return a.y < b.y; });
pair<ll, pair<P, P>> ret{LLONG_MAX, {P(), P()}};
int j = 0;
for (P p : v) {
P d{1 + (ll)sqrt(ret.first), 0};
while (v[j].y <= p.y - d.x) S.erase(v[j++]);
auto lo = S.lower_bound(p - d), hi = S.upper_bound(p + d);
for (; lo != hi; ++lo)
ret = min(ret, {(lo - p).dist2(), {lo, p}});
S.insert(p);
} // 5b096c
return ret.second;
} // bf22c6
```

**ManhattanMST.h**  
**Description:** Given N points, returns up to 4\*N edges, which are guaranteed to contain a minimum spanning tree for the graph with edge weights  $w(p, q) = -p.x - q.x + -p.y - q.y$ . Edges are in the form (distance, src, dst). Use a standard MST algorithm on the result to find the final MST.  
**Time:**  $\mathcal{O}(N \log N)$

|           |                 |
|-----------|-----------------|
| "Point.h" | df6f59, 23L, 4m |
|-----------|-----------------|

```
typedef Point<int> P;
vector<array<int, 3>> manhattanMST(vector<P> ps) {
vi id(sz(ps));
iota(all(id), 0);
vector<array<int, 3>> edges;
rep(k,0,4) {
sort(all(id), [&](int i, int j) {
return (ps[i]-ps[j]).x < (ps[j]-ps[i]).y;}); // 02bd87
map<int, int> sweep;
for (int i : id) {
for (auto it = sweep.lower_bound(-ps[i].y);
it != sweep.end(); sweep.erase(it++)) {
int j = it->second;
P d = ps[i] - ps[j];
if (d.y > d.x) break;
edges.push_back({d.y + d.x, i, j});
} // 271a42
sweep[-ps[i].y] = i;
} // e692f6
for (P& p : ps) if (k & 1) p.x = -p.x; else swap(p.x, p.y);
} // a110e0
return edges;
} // a1195f
```

**FastDelaunay.h**  
**Description:** Fast Delaunay triangulation. Each circumcircle contains none of the input points. There must be no duplicate points. If all points are on a line, no triangles will be returned. Should work for doubles as well, though there may be precision issues in 'circ'. Returns triangles in order {t[0][0], t[0][1], t[0][2], t[1][0], ...}, all counter-clockwise.  
**Time:**  $\mathcal{O}(n \log n)$

|           |                    |
|-----------|--------------------|
| "Point.h" | cefd5, 82L, 17m10s |
|-----------|--------------------|

```
typedef Point<ll> P;
typedef struct Quad* Q;
typedef __int128_t ll1; // (can be ll if coords are < 2e4)
P arb(LLONG_MAX, LLONG_MAX); // not equal to any other point
struct Quad {
Q rot, o; P p = arb; bool mark;
P& F() { return r()->p; }
Q& r() { return rot->rot; }
Q prev() { return rot->o->rot; }
Q next() { return r()->prev(); }
} *H; // 18059e
bool circ(P p, P a, P b, P c) { // is p in the circumcircle?
ll1 p2 = p.dist2(), A = a.dist2()-p2,
B = b.dist2()-p2, C = c.dist2()-p2;
return p.cross(a,b)*C + p.cross(b,c)*A + p.cross(c,a)*B > 0;
} // 6aff7b
Q makeEdge(P orig, P dest) {
Q r = H ? H : new Quad{new Quad{new Quad{0}}}};
H = r->o; r->r()->r() = r;
rep(i,0,4) r = r->rot, r->p = arb, r->o = i & 1 ? r : r->r();
r->p = orig; r->F() = dest;
return r;
} // b3b5b1
void splice(Q a, Q b) {
swap(a->o->rot->o, b->o->rot->o); swap(a->o, b->o);
} // 86ce01
Q connect(Q a, Q b) {
Q q = makeEdge(a->F(), b->p);
splice(q, a->next());
splice(q->r(), b);
return q;
} // 4a4fc2
pair<Q,Q> rec(const vector<P>& s) {
if (sz(s) <= 3) {
Q a = makeEdge(s[0], s[1]), b = makeEdge(s[1], s.back());
if (sz(s) == 2) return { a, a->r() };
splice(a->r(), b);
auto side = s[0].cross(s[1], s[2]);
Q c = side ? connect(b, a) : 0;
return {side < 0 ? c->r() : a, side < 0 ? c : b->r() };
} // c9e598
#define H(e) e->F(), e->p
#define valid(e) (e->F().cross(H(base)) > 0)
Q A, B, ra, rb;
int half = sz(s) / 2;
tie(ra, A) = rec({all(s) - half});
tie(B, rb) = rec({sz(s) - half + all(s)});
while ((B->p.cross(H(A)) < 0 && (A = A->next())) ||
(A->p.cross(H(B)) > 0 && (B = B->r()->o)));
Q base = connect(B->r(), A);
if (A->p == ra->p) ra = base->r();
if (B->p == rb->p) rb = base;
#define DEL(e, init, dir) Q e = init->dir; if (valid(e)) \
while (circ(e->dir->F(), H(base), e->F())) { \
Q t = e->dir; \
splice(e, e->prev()); \
splice(e->r(), e->r()->prev()); \
e->o = H; H = e; e = t; \
} // a2e9b5
for (;;) {
DEL(LC, base->r(), o); DEL(RC, base, prev());
```

```
if (!valid(LC) && !valid(RC)) break;
if (!valid(LC) || (valid(RC) && circ(H(RC), H(LC))))
base = connect(RC, base->r());
else
base = connect(base->r(), LC->r());
} // fcf7ef
return { ra, rb };
} // 7cf639
vector<P> triangulate(vector<P> pts) {
sort(all(pts)); assert(unique(all(pts)) == pts.end());
if (sz(pts) < 2) return {};
Q e = rec(pts).first;
vector<Q> q = {e};
int qi = 0;
while (e->o->F().cross(e->F(), e->p) < 0) e = e->o;
#define ADD { Q c = e; do { c->mark = 1; pts.push_back(c->p); \
q.push_back(c->r()); c = c->next(); } while (c != e); } // 43e195 // 43e195
ADD; pts.clear();
while (qi < sz(q)) if (!(e = q[qi++])->mark) ADD;
return pts;
} // a02307
```

4.5 3D

**PolyhedronVolume.h**  
**Description:** Magic formula for the volume of a polyhedron. Faces should point outwards.

|  |                   |
|--|-------------------|
|  | 3058c3, 6L, 1m10s |
|--|-------------------|

```
template<class V, class L>
double signedPolyVolume(const V& p, const L& trilst) {
double v = 0;
for (auto i : trilst) v += p[i.a].cross(p[i.b]).dot(p[i.c]);
return v / 6;
} // fca9df
```

**Point3D.h**  
**Description:** Class to handle points in 3D space. T can be e.g. double or long long.

|  |                 |
|--|-----------------|
|  | 8058ae, 32L, 9m |
|--|-----------------|

```
template<class T> struct Point3D {
typedef Point3D P;
typedef const P& R;
T x, y, z;
explicit Point3D(T x=0, T y=0, T z=0) : x(x), y(y), z(z) {}
bool operator<(R p) const {
return tie(x, y, z) < tie(p.x, p.y, p.z); } // 8eef6b
bool operator==(R p) const {
return tie(x, y, z) == tie(p.x, p.y, p.z); } // bd6a08
P operator+(R p) const { return P(x+p.x, y+p.y, z+p.z); }
P operator-(R p) const { return P(x-p.x, y-p.y, z-p.z); }
P operator*(T d) const { return P(x*d, y*d, z*d); }
P operator/(T d) const { return P(x/d, y/d, z/d); }
T dot(R p) const { return x*p.x + y*p.y + z*p.z; }
P cross(R p) const {
return P(y*p.z - z*p.y, z*p.x - x*p.z, x*p.y - y*p.x);
} // a77b7e
T dist2() const { return x*x + y*y + z*z; }
double dist() const { return sqrt((double)dist2()); }
//Azimuthal angle (longitude) to x-axis in interval [-pi, pi]
double phi() const { return atan2(y, x); }
//Zenith angle (latitude) to the z-axis in interval [0, pi]
double theta() const { return atan2(sqrt(x*x+y*y), z); }
P unit() const { return *this/(T)dist(); } //makes dist()=1
//returns unit vector normal to *this and p
P normal(P p) const { return cross(p).unit(); }
//returns point rotated 'angle' radians ccw around axis
P rotate(double angle, P axis) const {
double s = sin(angle), c = cos(angle); P u = axis.unit();
```

```
        return u*dot(u)*(1-c) + (*this)*c - cross(u)*s;
    } // 73af70
}; // 8058ae
```

**3dHull.h**  
**Description:** Computes all faces of the 3-dimension hull of a point set. \*No four points must be coplanar\*, or else random results will be returned. All faces will point outwards.  
**Time:**  $\mathcal{O}(n^2)$

|             |                    |
|-------------|--------------------|
| "Point3D.h" | 5b45fc, 46L, 7m50s |
|-------------|--------------------|

```
typedef Point3D<double> P3;
struct PR {
    void ins(int x) { (a == -1 ? a : b) = x; }
    void rem(int x) { (a == x ? a : b) = -1; }
    int cnt() { return (a != -1) + (b != -1); }
    int a, b;
}; // cf7c9e
struct F { P3 q; int a, b, c; };
vector<F> hull3d(const vector<P3>& A) {
    assert(sz(A) >= 4);
    vector<vector<PR>> E(sz(A), vector<PR>(sz(A), {-1, -1}));
#define E(x,y) E[f.x][f.y]
    vector<F> FS;
    auto mf = [&](int i, int j, int k, int l) {
        P3 q = (A[j] - A[i]).cross((A[k] - A[i]));
        if (q.dot(A[l]) > q.dot(A[i]))
            q = q * -1;
        F f{q, i, j, k};
        E(a,b).ins(k); E(a,c).ins(j); E(b,c).ins(i);
        FS.push_back(f);
    }; // d73a06
    rep(i,0,4) rep(j,i+1,4) rep(k,j+1,4)
        mf(i, j, k, 6 - i - j - k);

    rep(i,4,sz(A)) {
        rep(j,0,sz(FS)) {
            F f = FS[j];
            if(f.q.dot(A[i]) > f.q.dot(A[f.a])) {
                E(a,b).rem(f.c);
                E(a,c).rem(f.b);
                E(b,c).rem(f.a);
                swap(FS[j--], FS.back());
                FS.pop_back();
            } // 5cd5dc
        } // 220067
        int nw = sz(FS);
        rep(j,0,nw) {
            F f = FS[j];
#define C(a, b, c) if (E(a,b).cnt() != 2) mf(f.a, f.b, i, f.c);
            C(a, b, c); C(a, c, b); C(b, c, a);
        } // 248ed4
    } // 47289c
    for (F& it : FS) if ((A[it.b] - A[it.a]).cross(
        A[it.c] - A[it.a]).dot(it.q) <= 0) swap(it.c, it.b);
    return FS;
}; // be2ca2
```

**sphericalDistance.h**  
**Description:** Returns the shortest distance on the sphere with radius *radius* between the points with azimuthal angles (longitude) *f1* ( $\phi_1$ ) and *f2* ( $\phi_2$ ) from *x* axis and zenith angles (latitude) *t1* ( $\theta_1$ ) and *t2* ( $\theta_2$ ) from *z* axis (0 = north pole). All angles measured in radians. The algorithm starts by converting the spherical coordinates to cartesian coordinates so if that is what you have you can use only the two last rows. *dx*\**radius* is then the difference between the two points in the *x* direction and *d*\**radius* is the total distance between the points.

|                                                |                   |
|------------------------------------------------|-------------------|
| double sphericalDistance(double f1, double t1, | 611f07, 8L, 1m50s |
|------------------------------------------------|-------------------|

```
        double f2, double t2, double radius) {
    double dx = sin(t2)*cos(f2) - sin(t1)*cos(f1);
    double dy = sin(t2)*sin(f2) - sin(t1)*sin(f1);
    double dz = cos(t2) - cos(t1);
    double d = sqrt(dx*dx + dy*dy + dz*dz);
    return radius*2*asin(d/2);
} // 4fa19e
```

## Graph (5)

### 5.1 Fundamentals

**BellmanFord.h**  
**Description:** Calculates shortest paths from *s* in a graph that might have negative edge weights. Unreachable nodes get *dist* = *inf*; nodes reachable through negative-weight cycles get *dist* = -*inf*. Assumes  $V^2 \max |w_i| < \sim 2^{63}$ .  
**Time:**  $\mathcal{O}(VE)$

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                    |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|
| const ll inf = LLONG_MAX; struct Ed { int a, b, w, s() { return a < b ? a : -a; }}; struct Node { ll dist = inf; int prev = -1; }; void bellmanFord(vector<Node>& nodes, vector<Ed>& eds, int s) {     nodes[s].dist = 0;     sort(all(eds), [](Ed a, Ed b) { return a.s() < b.s(); });     int lim = sz(nodes) / 2 + 2; // /3+100 with shuffled vertices     rep(i,0,lim) for (Ed ed : eds) {         Node cur = nodes[ed.a], &dest = nodes[ed.b];         if (abs(cur.dist) == inf) continue;         ll d = cur.dist + ed.w;         if (d < dest.dist) {             dest.prev = ed.a;             dest.dist = (i < lim-1 ? d : -inf);         } // 452019     } // 75a370     rep(i,0,lim) for (Ed e : eds) {         if (nodes[e.a].dist == -inf)             nodes[e.b].dist = -inf;     } // 1d7315 } // fa39de | 830a8f, 21L, 4m30s |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|

**FunctGraph.h**  
**Description:** Functional Graph  
**Memory:**  $\mathcal{O}(n)$   
**Time:**  $\mathcal{O}(n)$

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                 |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| struct FunctGraph{     int n;     vi head, comp;     vector<vi> gr, cycles;     FunctGraph(vi& fn):         n(sz(fn)), head(n, -1), comp(n), gr(n) {         rep(i, 0, n)gr[fn[i]].pb(i);         vi visited(n, 0);         auto dfs = [&](auto rec, int v, int c) -> void {             head[v] = c; visited[v] = 1;             for(int f : gr[v])if (head[f]!=f)rec(rec, f, c);         }; // e1fa06         rep(i, 0, n){             if (visited[i])continue;             int l=fn[i], r=fn[fn[i]];             while(l!=r) l=fn[l], r=fn[fn[r]];             vi cur = {r};             for(l=fn[l]; l!=r; l=fn[l]) cur.pb(l);             for(int x : cur) head[x] = x, comp[x] = sz(cycles);             cycles.pb(cur);             for(int x : cur) dfs(dfs, x, x);         } // 01a153     } // 0a2937 | 152fc5, 24L, 4m |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|

```
}; // 152fc5
```

### 5.2 Flow

**Dinic.h**  
**Description:** Flow algorithm with complexity  $\mathcal{O}(VE \log U)$  where  $U = \max |cap|$ .  $\mathcal{O}(\min(E^{1/2}, V^{2/3})E)$  if  $U = 1$ ;  $\mathcal{O}(\sqrt{V}E)$  for bipartite matching.

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                    |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|
| struct Dinic {     struct Edge {         int to, rev;         ll c, oc;         ll flow() { return max(oc - c, 0LL); } // if you need flows     }; // d46531     vi lvl, ptr, q;     vector<vector<Edge>> adj;     Dinic(int n) : lvl(n), ptr(n), q(n), adj(n) {}     void addEdge(int a, int b, ll c, ll rcap = 0) {         adj[a].push_back({b, sz(adj[b]), c, c});         adj[b].push_back({a, sz(adj[a]) - 1, rcap, rcap});     } // 01ad91     ll dfs(int v, int t, ll f) {         if (v == t    !f) return f;         for (int& i = ptr[v]; i < sz(adj[v]); i++) {             Edge& e = adj[v][i];             if (lvl[e.to] == lvl[v] + 1)                 if (ll p = dfs(e.to, t, min(f, e.c))) {                     e.c -= p, adj[e.to][e.rev].c += p;                     return p;                 } // 494522         } // f73941         return 0;     } // 0922b8     ll calc(int s, int t) {         ll flow = 0; q[0] = s;         rep(L,0,31) do { // 'int L=30' maybe faster for random data             lvl = ptr = vi(sz(q));             int qi = 0, qe = lvl[s] = 1;             while (qi < qe && !lvl[t]) {                 int v = q[qi++];                 for (Edge e : adj[v])                     if (!lvl[e.to] && e.c >> (30 - L))                         q[qe++] = e.to, lvl[e.to] = lvl[v] + 1;             } // 80ef52             while (ll p = dfs(s, t, LLONG_MAX)) flow += p;         } while (lvl[t]); // 96458d         return flow;     } // 3eb6d1     bool leftOfMinCut(int a) { return lvl[a] != 0; } }; // d7f0f1 | d7f0f1, 42L, 7m30s |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|

**MinCostMaxFlow.h**  
**Description:** Min-cost max-flow. If costs can be negative, call *setpi* before *maxflow*, but note that negative cost cycles are not supported. To obtain the actual flow, look at positive values only.  
**Time:**  $\mathcal{O}(FE \log(V))$  where *F* is max flow.  $\mathcal{O}(VE)$  for *setpi*.

|                                                                                                                                                                                                                                                     |                  |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|
| <bits/extc++.h> const ll INF = numeric_limits<ll>::max() / 4; struct MCMF {     struct edge {         int from, to, rev;         ll cap, cost, flow;     }; // 092ff8     int N;     vector<vector<edge>> ed;     vi seen;     vector<ll> dist, pi; | 135b73, 69L, 13m |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|

```
vector<edge*> par;
MCMF(int N) : N(N), ed(N), seen(N), dist(N), pi(N), par(N) {}
void addEdge(int from, int to, ll cap, ll cost) {
    if (from == to) return;
    ed[from].push_back(edge{ from,to,sz(ed[to]),cap,cost,0 });
    ed[to].push_back(edge{ to,from,sz(ed[from])-1,0,-cost,0 });
} // c71528
void path(int s) {
    fill(all(seen), 0);
    fill(all(dist), INF);
    dist[s] = 0; ll di;
    __gnu_pbds::priority_queue<pair<ll, int>> q;
    vector<decltype(q)::point_iterator> its(N);
    q.push({ 0, s });
    while (!q.empty()) {
        s = q.top().second; q.pop();
        seen[s] = 1; di = dist[s] + pi[s];
        for (edge& e : ed[s]) if (!seen[e.to]) {
            ll val = di - pi[e.to] + e.cost;
            if (e.cap - e.flow > 0 && val < dist[e.to]) {
                dist[e.to] = val;
                par[e.to] = &e;
                if (its[e.to] == q.end())
                    its[e.to] = q.push({ -dist[e.to], e.to });
            } else
                q.modify(its[e.to], { -dist[e.to], e.to });
        } // ca07f4
    } // 4cd18f
} // 062b8f
rep(i,0,N) pi[i] = min(pi[i] + dist[i], INF);
} // 7e4cbe
pair<ll, ll> maxflow(int s, int t) {
    ll totflow = 0, totcost = 0;
    while (path(s), seen[t]) {
        ll fl = INF;
        for (edge* x = par[t]; x; x = par[x->from])
            fl = min(fl, x->cap - x->flow);
        totflow += fl;
        for (edge* x = par[t]; x; x = par[x->from]) {
            x->flow += fl;
            ed[x->to][x->rev].flow -= fl;
        } // 3bfaf3
    } // 8d9a6a
    rep(i,0,N) for(edge& e : ed[i]) totcost += e.cost * e.flow;
    return {totflow, totcost/2};
} // 24f5a0
// If some costs can be negative, call this before maxflow:
void setpi(int s) { // (otherwise, leave this out)
    fill(all(pi), INF); pi[s] = 0;
    int it = N, ch = 1; ll v;
    while (ch-- && it--)
        rep(i,0,N) if (pi[i] != INF)
            for (edge& e : ed[i]) if (e.cap)
                if ((v = pi[i] + e.cost) < pi[e.to])
                    pi[e.to] = v, ch = 1;
    assert(it >= 0); // negative cost cycle
} // 6847d8
}; // b3692f
```

**GlobalMinCut.h**  
Description: Find a global minimum cut in an undirected graph, as represented by an adjacency matrix.  
Time:  $\mathcal{O}(V^3)$

```
pair<int, vi> globalMinCut(vector<vi> mat) {
    pair<int, vi> best = {INT_MAX, {}};
    int n = sz(mat);
    vector<vi> co(n);
```

```
rep(i,0,n) co[i] = {i};
rep(ph,1,n) {
    vi w = mat[0];
    size_t s = 0, t = 0;
    rep(it,0,n-ph) { //  $\mathcal{O}(V^2) \rightarrow \mathcal{O}(E \log V)$  with prio. queue
        w[t] = INT_MIN;
        s = t, t = max_element(all(w)) - w.begin();
        rep(i,0,n) w[i] += mat[t][i];
    } // ec93df
    best = min(best, {w[t] - mat[t][t], co[t]});
    co[s].insert(co[s].end(), all(co[t]));
    rep(i,0,n) mat[s][i] += mat[t][i];
    rep(i,0,n) mat[i][s] = mat[s][i];
    mat[0][t] = INT_MIN;
    } // ca0062
    return best;
} // 8b0e19
```

**GomoryHu.h**  
Description: Given a list of edges representing an undirected flow graph, returns edges of the Gomory-Hu tree. The max flow between any pair of vertices is given by minimum edge weight along the Gomory-Hu tree path.  
Time:  $\mathcal{O}(V)$  Flow Computations  
"Dinic.h" e2b333, 13L, 2m20s

```
typedef array<ll, 3> Edge;
vector<Edge> gomoryHu(int N, vector<Edge> ed) {
    vector<Edge> tree;
    vi par(N);
    rep(i,1,N) {
        Dinic D(N); // Dinic also works
        for (Edge t : ed) D.addEdge(t[0], t[1], t[2], t[2]);
        tree.push_back({i, par[i], D.calc(i, par[i])});
        rep(j,i+1,N)
            if (par[j] == par[i] && D.leftOfMinCut(j)) par[j] = i;
    } // 42d832
    return tree;
} // 4edcec
```

5.3 Matching

**HopcroftKarp.h**  
Description: Fast bipartite matching algorithm. Graph  $g$  should be a list of neighbors of the left partition, and  $r$  should be a vector full of  $-1$ 's of the same size as the right partition. Returns the size of the matching.  $r[i]$  will be the match for vertex  $i$  on the right side, or  $-1$  if it's not matched.  
Time:  $\mathcal{O}(E\sqrt{V})$

```
int hopcroftKarp(vector<vi>& g, vi& r) {
    int n = sz(g), res = 0;
    vi l(n, -1), q(n), d(n);
    auto dfs = [&](auto f, int u) -> bool {
        int t = exchange(d[u], 0) + 1;
        for (int v : g[u])
            if (r[v] == -1 || (d[r[v]] == t && f(f, r[v])))
                return l[u] = v, r[v] = u, 1;
        return 0;
    }; // a95e38
    for (int t = 0, f = 0;; t = f = 0, d.assign(n, 0)) {
        rep(i,0,n) if (l[i] == -1) q[t++] = i, d[i] = 1;
        rep(i,0,t) for (int v : g[q[i]]) {
            if (r[v] == -1) f = 1;
            else if (!d[r[v]]) d[r[v]] = d[q[i]] + 1, q[t++] = r[v];
        } // 64af74
        if (!f) return res;
        rep(i,0,n) if (l[i] == -1) res += dfs(dfs, i);
    } // cdf3b2
} // 731cfb
```

**MinimumVertexCover.h**  
Description: Finds a minimum vertex cover in a bipartite graph. The size is the same as the size of a maximum matching, and the complement is a maximum independent set.

```
"HopcroftKarp.h" bfb654, 20L, 3m50s
vi cover(vector<vi>& g, int n, int m) {
    vi match(m, -1);
    int res = hopcroftKarp(g, match);
    vector<bool> lfound(n, true), seen(m);
    for (int it : match) if (it != -1) lfound[it] = false;
    vi q, cover;
    rep(i,0,n) if (lfound[i]) q.push_back(i);
    while (!q.empty()) {
        int i = q.back(); q.pop_back();
        lfound[i] = 1;
        for (int e : g[i]) if (!seen[e] && match[e] != -1) {
            seen[e] = true;
            q.push_back(match[e]);
        } // 46e035
    } // 069994
    rep(i,0,n) if (!lfound[i]) cover.push_back(i);
    rep(i,0,m) if (seen[i]) cover.push_back(n+i);
    assert(sz(cover) == res);
    return cover;
} // bfb654
```

**GeneralMatching.h**  
Description: Matching for general graphs. 1-indexed vertices.  
Memory:  $\mathcal{O}(n+m)$   
Time:  $\mathcal{O}(\sqrt{nm} \log_{\max\{2,1+m/n\}} n)$

```
class MaximumMatching {
public:
    struct Edge {int from, to;};
    static constexpr int Inf = 1 << 30;
private:
    enum Label {
        kInner = -1, // should be < 0
        kFree = 0 // should be 0
    }; // c09e7e
    struct Link {int from, to;};
    struct Log {int v, par;};
    struct LinkedList {
        LinkedList() {}
        LinkedList(int N, int M) : N(N), next(M) { clear(); }
        void clear() { head.assign(N, -1); }
        void push(int h, int u) { next[u] = head[h], head[h] = u; }
        int N; vector<int> head, next;
    }; // 1a51c7
    template <typename T> struct Queue {
        Queue() {}
        Queue(int N) : qh(0), qt(0), data(N) {}
        T operator[] (int i) const { return data[i]; }
        void enqueue(int u) { data[qt++] = u; }
        int dequeue() { return data[qh++]; }
        bool empty() const { return qh == qt; }
        void clear() { qh = qt = 0; }
        int size() const { return qt; }
        int qh, qt; vector<T> data;
    }; // 4bfceb
    struct DisjointSetUnion {
        DisjointSetUnion() {}
        DisjointSetUnion(int N) : par(N) { for (int i = 0; i < N; ++i) par[i] = i; }
        int find(int u) { return par[u] == u ? u : (par[u] = find(par[u])); }
        void unite(int u, int v) {
```

```

    u = find(u), v = find(v);
    if (u != v) par[v] = u;
} // 461e55
vector<int> par;
}; // a21f68
public:
MaximumMatching(int N, const vector<Edge> &in)
: N(N), NH(N >> 1), ofs(N + 2, 0), edges(in.size() * 2)
{
    for (auto &e : in) ofs[e.from + 1] += 1, ofs[e.to + 1]
        += 1;
    for (int i = 1; i <= N + 1; ++i) ofs[i] += ofs[i - 1];
    for (auto &e : in) {
        edges[ofs[e.from]++] = e;
        edges[ofs[e.to]++] = {e.to, e.from};
    } // 36bba8
    for (int i = N + 1; i > 0; --i) ofs[i] = ofs[i - 1];
    ofs[0] = 0;
} // a78156
int maximum_matching() {
    initialize(); int match = 0;
    while (match * 2 + 1 < N) {
        reset_count();
        bool has_augmenting_path = do_edmonds_search();
        if (!has_augmenting_path) break;
        match += find_maximal();
        clear();
    } // 8c0a2c
    return match;
} // da7b99
vector<Edge> get_edges() {
    vector<Edge> ans;
    for (int i = 1; i <= N; ++i) if (mate[i] > i) ans.
        push_back(Edge{i, mate[i]});
    return ans;
} // f8586b
private:
void reset_count() {
    time_current_ = 0;
    time_augment_ = Inf;
    contract_count_ = 0;
    outer_id_ = 1;
    dsu_changelog_size_ = dsu_changelog_last_ = 0;
} // 6c73d5
void clear() {
    que.clear();
    for (int u = 1; u <= N; ++u) potential[u] = 1;
    for (int u = 1; u <= N; ++u) dsu.par[u] = u;
    for (int t = time_current_; t <= N / 2; ++t) list.head[
        t] = -1;
    for (int u = 1; u <= N; ++u) blossom.head[u] = -1;
} // 6e020f
inline void grow(int x, int y, int z) {
    label[y] = kInner;
    potential[y] = time_current_; // visited time
    link[z] = {x, y};
    label[z] = label[x];
    potential[z] = time_current_ + 1;
    que.enqueue(z);
} // 5a596b
void contract(int x, int y) {
    int bx = dsu.find(x), by = dsu.find(y);
    const int h = -(++contract_count_) + kInner;
    label[mate[bx]] = label[mate[by]] = h;
    int lca = -1;
    while (1) {
        if (mate[by] != 0) swap(bx, by);
        bx = lca = dsu.find(link[bx].from);
        if (label[mate[bx]] == h) break;

```

```

        label[mate[bx]] = h;
    } // d03cf2
    for (auto bv : {dsu.par[x], dsu.par[y]}) {
        for (; bv != lca; bv = dsu.par[link[bv].from]) {
            int mv = mate[bv];
            link[mv] = {x, y};
            label[mv] = label[x];
            potential[mv] =
                1 + (time_current_ - potential[mv]) +
                time_current_;
            que.enqueue(mv);
            dsu.par[bv] = dsu.par[mv] = lca;
            dsu_changelog[dsu_changelog_last_++] = {bv, lca
            };
            dsu_changelog[dsu_changelog_last_++] = {mv, lca
            };
        } // 8fef02
    } // 2b0c42
} // a9547e
bool find_augmenting_path() {
    while (!que.empty()) {
        int x = que.dequeue(), lx = label[x], px =
            potential[x],
            bx = dsu.find(x);
        for (int eid = ofs[x]; eid < ofs[x + 1]; ++eid) {
            int y = edges[eid].to;
            if (label[y] > 0) { // outer blossom/vertex
                int time_next = (px + potential[y]) >> 1;
                if (lx != label[y]) {
                    if (time_next == time_current_) return
                        true;
                    time_augment_ = min(time_next,
                        time_augment_);
                } else { // a6d4c5
                    if (bx == dsu.find(y)) continue;
                    if (time_next == time_current_) {
                        contract(x, y);
                        bx = dsu.find(x);
                    } else if (time_next <= NH) // 1efde3
                        list.push(time_next, eid);
                } // 1666ad
            } else if (label[y] == kFree) { // free vertex
                // c17e44
                int time_next = px + 1;
                if (time_next == time_current_)
                    grow(x, y, mate[y]);
                else if (time_next <= NH)
                    list.push(time_next, eid);
            } // 48780d
        } // 30c821
    } // 1f7dd0
    return false;
} // 5f1707
bool adjust_dual_variables() {
    const int time_lim = min(NH + 1, time_augment_);
    for (++time_current_; time_current_ <= time_lim; ++
        time_current_) {
        dsu_changelog_size_ = dsu_changelog_last_;
        if (time_current_ == time_lim) break;
        bool updated = false;
        for (int h = list.head[time_current_]; h >= 0; h =
            list.next[h]) {
            auto &e = edges[h];
            int x = e.from, y = e.to;
            if (label[y] > 0) {
                if (potential[x] + potential[y] != (
                    time_current_ << 1))
                    continue;
                if (dsu.find(x) == dsu.find(y)) continue;

```

```

                if (label[x] != label[y]) {
                    time_augment_ = time_current_;
                    return false;
                } // e7c864
                contract(x, y);
                updated = true;
            } else if (label[y] == kFree) { // 1a7dca
                grow(x, y, mate[y]);
                updated = true;
            } // ebac0d
        } // 7bf910
        list.head[time_current_] = -1;
        if (updated) return false;
    } // a2963f
    return time_current_ > NH;
} // 361891
bool do_edmonds_search() {
    label[0] = kFree;
    for (int u = 1; u <= N; ++u) {
        if (mate[u] == 0) {
            que.enqueue(u);
            label[u] = u; // component id
        } else // 52e61c
            label[u] = kFree;
    } // 585bc4
    while (1) {
        if (find_augmenting_path()) break;
        bool maximum = adjust_dual_variables();
        if (maximum) return false;
        if (time_current_ == time_augment_) break;
    } // 3b82c1
    for (int u = 1; u <= N; ++u) {
        if (label[u] > 0)
            potential[u] -= time_current_;
        else if (label[u] < 0)
            potential[u] = 1 + (time_current_ - potential[u
            ]);
    } // c77cf7
    return true;
} // e1fc96
void rematch(int v, int w) {
    int t = mate[v];
    mate[v] = w;
    if (mate[t] != v) return;
    if (link[v].to == dsu.find(link[v].to)) {
        mate[t] = link[v].from;
        rematch(mate[t], t);
    } else { // 45eff2
        int x = link[v].from, y = link[v].to;
        rematch(x, y);
        rematch(y, x);
    } // 4a404f
} // c4e2e9
bool dfs_augment(int x, int bx) {
    int px = potential[x], lx = label[bx];
    for (int eid = ofs[x]; eid < ofs[x + 1]; ++eid) {
        int y = edges[eid].to;
        if (px + potential[y] != 0) continue;
        int by = dsu.find(y), ly = label[by];
        if (ly > 0) { // outer
            if (lx >= ly) continue;
            int stack_beg = stack_last_;
            for (int bv = by; bv != bx; bv = dsu.find(link[
                bv].from)) {
                int bw = dsu.find(mate[bv]);
                stack[stack_last_++] = bw;
                link[bw] = {x, y};
                dsu.par[bv] = dsu.par[bw] = bx;
            } // 211d3e

```

```

    while (stack_last_ > stack_beg) {
        int bv = stack[--stack_last_];
        for (int v = blossom.head[bv]; v >= 0;
            v = blossom.next[v]) {
            if (!dfs_augment(v, bv)) continue;
            stack_last_ = stack_beg;
            return true;
        } // 9ded5e
    } // 476c04
} else if (ly == kFree) { // e5357f
    label[by] = kInner;
    int z = mate[by];
    if (z == 0) {
        rematch(x, y);
        rematch(y, x);
        return true;
    } // 781371
    int bz = dsu.find(z);
    link[bz] = {x, y};
    label[bz] = outer_id++;
    for (int v = blossom.head[bz]; v >= 0; v =
        blossom.next[v]) {
        if (dfs_augment(v, bz)) return true;
    } // 5ea9e4
    } // 1c508f
} // 7f2ab3
return false;
} // 44c41a
int find_maximal() {
    for (int u = 1; u <= N; ++u) dsu.par[u] = u;
    for (int i = 0; i < dsu_changelog_size_; ++i) {
        dsu.par[dsu_changelog[i].v] = dsu_changelog[i].par;
    } // 384510
    for (int u = 1; u <= N; ++u) {
        label[u] = kFree;
        blossom.push(dsu.find(u), u);
    } // 2a02fd
    int ret = 0;
    for (int u = 1; u <= N; ++u)
        if (!mate[u]) {
            int bu = dsu.par[u];
            if (label[bu] != kFree) continue;
            label[bu] = outer_id++;
            for (int v = blossom.head[bu]; v >= 0; v =
                blossom.next[v]) {
                if (!dfs_augment(v, bu)) continue;
                ret += 1;
                break;
            } // e4fb6a
        } // 4db9e3
    assert(ret >= 1); return ret;
} // 500171
void initialize() {
    que = Queue<int>(N);
    mate.assign(N + 1, 0);
    potential.assign(N + 1, 1);
    label.assign(N + 1, kFree);
    link.assign(N + 1, {0, 0});
    dsu_changelog.resize(N);
    dsu = DisjointSetUnion(N + 1);
    list = LinkedList(NH + 1, edges.size());
    blossom = LinkedList(N + 1, N + 1);
    stack.resize(N);
    stack_last_ = 0;
} // be011c
private:
const int N, NH;
vector<int> ofs;
vector<Edge> edges;

```

```

Queue<int> que;
vector<int> mate, potential;
vector<int> label;
vector<Link> link;
vector<Log> dsu_changelog;
int dsu_changelog_last_, dsu_changelog_size_;
DisjointSetUnion dsu;
LinkedList list, blossom;
vector<int> stack;
int stack_last_;
int time_current_, time_augment_;
int contract_count_, outer_id_;
}; // b7724d
using Edge = MaximumMatching::Edge;
void example() { // Graph of Love problem
    int n; cin >> n;
    vector<Edge> edges(n, {0, 0});
    for (int i = 1, j; i <= n; i++) cin >> j, edges[i-1] = {i, j
        };
    auto M = MaximumMatching(n, edges);
    cout << M.maximum_matching() << '\n';
} // 0523ec

```

### OnlineMatching.h

**Description:** Modified khun developed for specific question able to run  $2 * 10^6$  queries, in  $2 * 10^6 \times 10^6$  graph in 3 seconds codeforces  
**Time:**  $\mathcal{O}(\text{confia})$

6ac539, 36L, 5m20s

```

struct OnlineMatching {
    int n = 0, m = 0;
    vector<int> vis, match, dist;
    vector<vector<int>> g;
    vector<int> last;
    int t = 0;
    OnlineMatching(int n_, int m_) : n(n_), m(m_), vis(n, 0),
        match(m, -1), dist(n, n+1), g(n), last(n, -1) {}
    void add(int a, int b) { g[a].pb(b); }
    bool kuhn(int a) {
        vis[a] = t;
        for(int b: g[a]) {
            int c = match[b];
            if (c == -1) {
                match[b] = a;
                return true;
            } // 38b210
            if (last[c] != t || (dist[a] + 1 < dist[c]))
                dist[c] = dist[a] + 1, last[c] = t;
        } // d30675
        for (int b: g[a]) {
            int c = match[b];
            if (dist[a] + 1 == dist[c] && vis[c] != t && kuhn(c)) {
                match[b] = a;
                return true;
            } // 2dac75
        } // e58bd5
        return false;
    } // b533ee
    bool can_match(int a) {
        t++;
        last[a] = t;
        dist[a] = 0;
        return kuhn(a);
    } // 32302b
}; // 6ac539

```

## 5.4 DFS algorithms

### SCC.h

**Description:** Finds strongly connected components in a directed graph. If vertices  $u, v$  belong to the same component, we can reach  $u$  from  $v$  and vice versa.

**Usage:** scc(graph, [&](vi& v) { ... }) visits all components in reverse topological order. comp[i] holds the component index of a node (a component only has edges to components with lower index). ncomps will contain the number of components.

**Time:**  $\mathcal{O}(E + V)$

76b5c9, 24L, 3m50s

```

vi val, comp, z, cont;
int Time, ncomps;
template<class G, class F> int dfs(int j, G& g, F& f) {
    int low = val[j] = ++Time, x; z.push_back(j);
    for (auto e : g[j]) if (comp[e] < 0)
        low = min(low, val[e] ? dfs(e, g, f));

    if (low == val[j]) {
        do {
            x = z.back(); z.pop_back();
            comp[x] = ncomps;
            cont.push_back(x);
        } while (x != j); // ae85bd
        f(cont); cont.clear();
        ncomps++;
    } // 64c1b9
    return val[j] = low;
} // 3513bd
template<class G, class F> void scc(G& g, F f) {
    int n = sz(g);
    val.assign(n, 0); comp.assign(n, -1);
    Time = ncomps = 0;
    rep(i, 0, n) if (comp[i] < 0) dfs(i, g, f);
} // 56b050

```

### BiconnectedComponents.h

**Description:** Finds all biconnected components in an undirected graph. In a biconnected component there are at least two internally disjoint paths between any two nodes a cycle exists through them. Note that a node can be in several components. Every edge is in a single component. Nodes without edges will not be in any components

**Time:**  $\mathcal{O}(E + V)$

61b438, 50L, 8m

```

vector<pair<int, int>> edges; // edges
vector<vector<pair<int, int>>> g; // [b, edge idx]
vi tin, st, art;
int dfstime = 0;
vector<vi> bcc;
int dfs(int a, int p) {
    int top = tin[a] = ++dfstime;
    bool child = (p != -1);
    for (auto [b, e]: g[a]) {
        if (tin[b]) {
            top = min(top, tin[b]);
            if (tin[b] < tin[a]) st.pb(e);
        } // 0df373
        else {
            int si = sz(st);
            int up = dfs(b, e);
            top = min(top, up);
            if (up > tin[a]) { /*e is a bridge */
                if (up >= tin[a]) {
                    st.pb(e);
                    bcc.pb(st.begin() + si, st.end());
                    st.resize(si);
                    art[a] += child;
                    child = true;
                } // 46103a
            } else if (up < tin[a]) st.pb(e);
        }
    }
}

```

```
    } // 38ea8a
  } // 53a60e
  return top;
} // 17df2f
void bicomps() {
  int n = sz(g);
  tin.assign(n, 0), art.assign(n, 0);
  rep(i,0,n) if (!tin[i]) dfs(i, -1);
} // 600614
vi comp;
vector<vi> tree;
void build_tree() { // Optional
  int n = sz(g);
  comp.resize(n), tree.resize(n + sz(bcc));
  rep(i, 0, sz(bcc)) {
    for (int eid: bcc[i]) {
      auto [a, b] = edges[eid];
      if (art[a] && (empty(tree[a]) || tree[a].back() != n+i))
        tree[a].pb(n+i), tree[n+i].pb(a);
      if (art[b] && (empty(tree[b]) || tree[b].back() != n+i))
        tree[b].pb(n+i), tree[n+i].pb(b);
      comp[a] = comp[b] = n + i;
    } // 2e7ad5
  } // 8e4c66
  rep(i, 0, n) if (art[i]) comp[i] = i;
} // b645e9
```

TwoCC.h

Description: Finds all two edge connected components in an undirected graph.

Time:  $\mathcal{O}(E + V)$

af5478, 41L, 6m

```
vector<vector<pair<int, int>>> g;
vector<pair<int, int>>> edges;
vi tin, st, bridges;
int dfstime = 0;
vector<vi> twocc;
int dfs(int a, int p) {
  int top = tin[a] = ++dfstime;
  int si = st.size();
  st.pb(a);
  for (auto [b, e]: g[a]) if (e != p) {
    if (tin[b]) top = min(top, tin[b]);
    else {
      int up = dfs(b, e);
      top = min(top, up);
      if (up > tin[a]) bridges.pb(e);
    } // 1dd281
  } // ada038
  if (top == tin[a]) {
    twocc.eb(st.begin() + si, st.end());
    st.resize(si);
  } // 0f03f3
  return top;
} // 55bb17
void twocomps() {
  int n = sz(g);
  tin.assign(n, 0);
  rep(i, 0, n) if (!tin[i]) dfs(i, -1);
} // 9a2d22
vi comp;
vector<vi> tree;
void build_tree() { // Optional
  int n = sz(g);
  tree.resize(sz(twocc)); comp.resize(n);
  rep(i, 0, sz(twocc))
    for (int a: twocc[i]) comp[a] = i;

  for (int eid: bridges) {
```

```
    auto [a, b] = edges[eid];
    tree[comp[a]].pb(comp[b]), tree[comp[b]].pb(comp[a]);
  } // 1a7e1f
} // c306f0
```

2sat.h

Description: Calculates a valid assignment to boolean variables a, b, c,... to a 2-SAT problem, so that an expression of the type (a||b)&&(!a||c)&&(d||b)&&... becomes true, or reports that it is unsatisfiable. Negated variables are represented by bit-inversions (~x).

Usage: TwoSat ts(number of boolean variables);

ts.either(0, ~3); // Var 0 is true or var 3 is false

ts.setValue(2); // Var 2 is true

ts.atMostOne({0,~1,2}); // <= 1 of vars 0, ~1 and 2 are true

ts.solve(); // Returns true iff it is solvable

ts.values[0..N-1] holds the assigned values to the vars

Time:  $\mathcal{O}(N + E)$ , where N is the number of boolean variables, and E is the number of clauses.

8e1208, 48L, 7m40s

```
struct TwoSat {
  int N; vector<vi> gr; vi values; // 0 = false, 1 = true
  TwoSat(int n = 0) : N(n), gr(2*n) {}
  void either(int f, int j) {
    f = max(2*f, -1-2*f);
    j = max(2*j, -1-2*j);
    gr[f].push_back(j^1);
    gr[j].push_back(f^1);
  } // 516db0
  void setValue(int x) { either(x, x); }
  int addVar() { // (optional)
    gr.emplace_back();
    gr.emplace_back();
    return N++;
  } // 7b5f84
  void atMostOne(const vi& li) { // (optional)
    if (sz(li) <= 1) return;
    int cur = ~li[0];
    rep(i,2,sz(li)) {
      int next = addVar();
      either(cur, ~li[i]);
      either(cur, next);
      either(~li[i], next);
      cur = ~next;
    } // 8d3782
    either(cur, ~li[1]);
  } // 10f2ea
  vi val, comp, z; int time = 0;
  int dfs(int i) {
    int low = val[i] = ++time, x; z.push_back(i);
    for(int e : gr[i]) if (!comp[e])
      low = min(low, val[e] ? : dfs(e));
    if (low == val[i]) do {
      x = z.back(); z.pop_back();
      comp[x] = low;
      if (values[x>>1] == -1)
        values[x>>1] = x&1;
    } while (x != i); // b15351
    return val[i] = low;
  } // ef583a
  bool solve() {
    values.assign(N, -1);
    val.assign(2*N, 0); comp = val;
    rep(i,0,2*N) if (!comp[i]) dfs(i);
    rep(i,0,N) if (comp[2*i] == comp[2*i+1]) return 0;
    return 1;
  } // 2bb76d
}; // 8e1208
```

EulerWalk.h

Description: Eulerian undirected/directed path/cycle algorithm. Input should be a vector of (dest, global edge index), where for undirected graphs, forward/backward edges have the same index. Returns a list of nodes in the Eulerian path/cycle with src at both start and end, or empty list if no cycle/path exists. To get edge indices back, add .second to s and ret.

Time:  $\mathcal{O}(V + E)$

780b64, 15L, 3m30s

```
vi eulerWalk(vector<vector<pii>>& gr, int nedges, int src=0) {
  int n = sz(gr);
  vi D(n), its(n), eu(nedges), ret, s = {src};
  D[src]++; // to allow Euler paths, not just cycles
  while (!s.empty()) {
    int x = s.back(), y, e, &it = its[x], end = sz(gr[x]);
    if (it == end){ ret.push_back(x); s.pop_back(); continue; }
    tie(y, e) = gr[x][it++];
    if (!eu[e]) {
      D[x]--, D[y]++;
      eu[e] = 1; s.push_back(y);
    } // 22a87a // 94de26
  }
  for (int x : D) if (x < 0 || sz(ret) != nedges+1) return {};
  return {ret.rbegin(), ret.rend()};
} // 780b64
```

DominatorTree.h

Description: Dominator Tree, creates the graph tree, where all ancestors of a u in the tree are necessary in the path from the root to u

Memory:  $\mathcal{O}(n)$

Time:  $\mathcal{O}((n + m)log(n))$  build

d7c79f, 54L, 9m10s

```
struct DominatorTree {
  int n, dfstime;
  vector<vector<int>> g, gt, tree, bucket, down;
  vector<int> S, dsu, label, sdом, idом, id;

  DominatorTree(vector<vector<int>> &_g, int root)
    : n(sz(_g)), dfstime(0), g(_g), gt(n), tree(n), bucket(n),
      down(n),
      S(n), dsu(n), label(n), sdом(n), idом(n), id(n) {
    prep(root); reverse(S.begin(), S.begin() + dfstime);
    for(int u : S) {
      for(int v : gt[u]) {
        int w = fnd(v);
        if(id[ sdом[w] ] < id[ sdом[u] ])
          sdом[u] = sdом[w];
      } // e059b2
      gt[u].clear();
      if(u != root) bucket[ sdом[u] ].push_back(u);
      for(int v : bucket[u]) {
        int w = fnd(v);
        if(sdom[w] == sdom[v]) idом[v] = sdom[v];
        else idом[v] = w;
      } // 72077b
      bucket[u].clear();
      for(int v : down[u]) dsu[v] = u;
      down[u].clear();
    } // 3197c4
    reverse(S.begin(), S.begin() + dfstime);
    for(int u : S) if(u != root) {
      if(idом[u] != sdom[u]) idом[u] = idом[ idом[u] ];
      tree[ idом[u] ].push_back(u);
    } // 96e582
    idом[root] = root;
  } // b239ba
  void prep(int u){
    S[dfstime] = u;
    id[u] = ++dfstime;
    label[u] = sdom[u] = dsu[u] = u;
```



```
for(int v : g[u]){
    if(!id[v])
        prep(v), down[u].push_back(v);
    gt[v].push_back(u);
} // 4d7944
} // 4351b9
int fnd(int u, int flag = 0){
    if(u == dsu[u]) return u;
    int v = fnd(dsu[u], 1), b = label[ dsu[u] ];
    if(id[ sdом[b] ] < id[ sdом[ label[u] ] ]){
        label[u] = b;
        dsu[u] = v;
        return flag ? v : label[u];
    } // d64927
}; // d7c79f
```

5.5 Cliques

MaximalCliques.h

**Description:** Runs a callback for all maximal cliques in a graph (given as a symmetric bitset matrix; self-edges not allowed). Callback is given a bitset representing the maximal clique.

**Time:**  $\mathcal{O}\left(3^{n/3}\right)$ , much faster for sparse graphs

b0d5b1, 12L, 2m10s

```
typedef bitset<128> B;
template<class F>
void cliques(vector<B>& eds, F f, B P = ~B(), B X={}, B R={}) {
    if (!P.any()) { if (!X.any()) f(R); return; }
    auto q = (P | X)._Find_first();
    auto cands = P & ~eds[q];
    rep(i,0,sz(eds)) if (cands[i]) {
        R[i] = 1;
        cliques(eds, f, P & eds[i], X & eds[i], R);
        R[i] = P[i] = 0; X[i] = 1;
    } // 181f8f
} // c9dc5f
```

MaximumClique.h

**Description:** Quickly finds a maximum clique of a graph (given as symmetric bitset matrix; self-edges not allowed). Can be used to find a maximum independent set by finding a clique of the complement graph.

**Time:** Runs in about 1s for n=155 and worst case random graphs (p=.90). Runs faster for sparse graphs.

f7c0bc, 49L, 9m30s

```
typedef vector<bitset<200>> vb;
struct Maxclique {
    double limit=0.025, pk=0;
    struct Vertex { int i, d=0; };
    typedef vector<Vertex> vv;
    vb e;
    vv V;
    vector<vi> C;
    vi qmax, q, S, old;
    void init(vv& r) {
        for (auto& v : r) v.d = 0;
        for (auto& v : r) for (auto j : r) v.d += e[v.i][j.i];
        sort(all(r), [](auto a, auto b) { return a.d > b.d; });
        int mxD = r[0].d;
        rep(i,0,sz(r)) r[i].d = min(i, mxD) + 1;
    } // 7c428e
    void expand(vv& R, int lev = 1) {
        S[lev] += S[lev - 1] - old[lev];
        old[lev] = S[lev - 1];
        while (sz(R)) {
            if (sz(q) + R.back().d <= sz(qmax)) return;
            q.push_back(R.back().i);
            vv T;
            for(auto v:R) if (e[R.back().i][v.i]) T.push_back({v.i});
```

```
if (sz(T)) {
    if (S[lev]++ / ++pk < limit) init(T);
    int j = 0, mxk = 1, mnk = max(sz(qmax) - sz(q) + 1, 1);
    C[1].clear(), C[2].clear();
    for (auto v : T) {
        int k = 1;
        auto f = [&](int i) { return e[v.i][i]; };
        while (any_of(all(C[k]), f)) k++;
        if (k > mxk) mxk = k, C[mxk + 1].clear();
        if (k < mnk) T[j++] .i = v.i;
        C[k].push_back(v.i);
    } // 3221ac
    if (j > 0) T[j - 1].d = 0;
    rep(k,mnk,mxk + 1) for (int i : C[k])
        T[j].i = i, T[j++] .d = k;
    expand(T, lev + 1);
    } else if (sz(q) > sz(qmax)) qmax = q; // 2a0537
    q.pop_back(), R.pop_back();
    } // 87639b
    } // f0a49d
    vi maxClique() { init(V), expand(V); return qmax; }
    Maxclique(vb conn) : e(conn), C(sz(e)+1), S(sz(C)), old(S) {
        rep(i,0,sz(e)) V.push_back({i});
    } // 36accb
}; // b63641
```

5.6 Trees

CompressTree.h

**Description:** Given a rooted tree and a subset S of nodes, compute the minimal subtree that contains all the nodes by adding all (at most  $|S| - 1$ ) pairwise LCA's and compressing edges. Returns a list of (par, orig\_index) representing a tree rooted at 0. The root points to itself.

**Time:**  $\mathcal{O}(|S| \log |S|)$

7347c3, 26L, 4m10s

```
struct LCA {
    vi time;
    int lca(int a, int b) { return -1; }
}; // 32d408
```

```
typedef vector<pair<int, int>> vpi;
vpi compressTree(LCA& lca, const vi& subset) {
    static vi rev; rev.resize(sz(lca.time));
    vi li = subset, &T = lca.time;
    auto cmp = [&](int a, int b) { return T[a] < T[b]; };
    sort(all(li), cmp);
    int m = sz(li)-1;
    rep(i,0,m){
        int a = li[i], b = li[i+1];
        li.push_back(lca.lca(a, b));
    } // 677c62
    sort(all(li), cmp);
    li.erase(unique(all(li)), li.end());
    rep(i,0,sz(li)) rev[li[i]] = i;
    vpi ret = {pii(0, li[0])};
    rep(i,0,sz(li)-1) {
        int a = li[i], b = li[i+1];
        ret.emplace_back(rev[lca.lca(a, b)], b);
    } // 5efe90
    return ret;
} // 83c9a2
```

HLD.h

**Description:** Does the same thing as a LazySegment tree, but on a tree and with an extra log factor to the complexity. VAL\_EDGES determines if the values are stored in edges. If so, store the value of each edge on its child vertex.

**Time:**  $\mathcal{O}\left((\log N)^2\right)$  for range operations,  $\mathcal{O}(\log(n))$  for point operations

"../data-structures/LazySegmentTree.h" b7947a, 53L, 9m40s

```
template<class S, bool VAL_EDGES>
struct HLD {
    using T = typename S::T; using L = typename S::L;
    int n,tim=0;
    vector<vi> g;
    vi p,siz,hd,ti;
    SegBeats<S> seg, segi;
    HLD(vector<vi> ag) : n(sz(ag)), g(ag), p(n), siz(n,1), hd(n),
        ti(n),
        seg(n), segi(n) { dfs(0); dfs2(0); }
    #warning fix n to be a power of two
    void dfs(int v) {
        for (int& u : g[v]) {
            g[u].erase(find(all(g[u]), v));
            p[u]=v;
            dfs(u);
            siz[v] += siz[u];
            if (siz[u] > siz[g[v][0]]) swap(u, g[v][0]);
        } // 7b54be
    } // a86bcf
    void dfs2(int v) {
        ti[v]=tim++;
        for (int u : g[v]) {
            hd[u] = (u == g[v][0] ? hd[v] : u);
            dfs2(u);
        } // 79707a
    } // 816069
    template <class B, class C> // ops are [l, r)
    void process(int u, int v, B opl, C op2) {
        for (;;) {
            if (hd[u] == hd[v]) break;
            if (ti[u] < ti[v]) op2(ti[hd[v]], ti[v]+1, v=p[hd[v]]);
            else opl(ti[hd[u]], ti[u]+1, u=p[hd[u]]);
        } // 1cb33f
        if (ti[u] < ti[v]) op2(ti[u]+VAL_EDGES, ti[v]+1);
        else opl(ti[v]+VAL_EDGES, ti[u]+1);
    } // 6a6a62
    T query(int u, int v) { // inclusive on both ends
        T vu = S::id, vv = S::id;
        process(u,v,
            [&](int l, int r){ vu = S::op(vu, segi.query(n-r,n-1)); },
            [&](int l, int r){ vv = S::op(seg.query(l,r), vv); } );
        return S::op(vu,vv);
    } // 04b81f
    void update(L val, int u, int v) {
        process(u,v,
            [&](int l, int r){ segi.update(val,n-r,n-1); },
            [&](int l, int r){ seg.update(val,l,r); });
    } // 8e0c4e
    void update(L val, int u) {
        seg.update(val,ti[u], ti[u]+1);
        segi.update(val,n-ti[u]-1, n-ti[u]);
    } // 6fea94
}; // 14746f
```

LinkCutTree.h

**Description:** Represents a forest of unrooted trees. You can add and remove edges (as long as the result is still a forest), and check whether two nodes are in the same tree.

**Time:** All operations take amortized  $\mathcal{O}(\log N)$ .

0fb462, 88L, 13m30s

```
struct Node { // Splay tree. Root's pp contains tree's parent.
    Node *p = 0, *pp = 0, *c[2];
    bool flip = 0;
    Node() { c[0] = c[1] = 0; fix(); }
    void fix() {
        if (c[0]) c[0]->p = this;
```

```

    if (c[l]) c[l]->p = this;
    // (+ update sum of subtree elements etc. if wanted)
} // 454758
void pushFlip() {
    if (!flip) return;
    flip = 0; swap(c[0], c[l]);
    if (c[0]) c[0]->flip ^= 1;
    if (c[l]) c[l]->flip ^= 1;
} // 0cc949
int up() { return p ? p->c[l] == this : -1; }
void rot(int i, int b) {
    int h = i ^ b;
    Node *x = c[i], *y = b == 2 ? x : x->c[h], *z = b ? y : x;
    if ((y->p == p)) p->c[up()] = y;
    c[i] = z->c[i ^ 1];
    if (b < 2) {
        x->c[h] = y->c[h ^ 1];
        y->c[h ^ 1] = x;
    } // 1a82cf
    z->c[i ^ 1] = this;
    fix(); x->fix(); y->fix();
    if (p) p->fix();
    swap(pp, y->pp);
} // 1cf643
void splay() {
    for (pushFlip(); p; ) {
        if (p->p) p->p->pushFlip();
        p->pushFlip(); pushFlip();
        int c1 = up(), c2 = p->up();
        if (c2 == -1) p->rot(c1, 2);
        else p->p->rot(c2, c1 != c2);
    } // e639f4
} // bfb1f7
Node* first() {
    pushFlip();
    return c[0] ? c[0]->first() : (splay(), this);
} // 67f9a1
}; // 225109
struct LinkCut {
    vector<Node> node;
    LinkCut(int N) : node(N) {}
    void link(int u, int v) { // add an edge (u, v)
        assert (!connected(u, v));
        makeRoot (&node[u]);
        node[u].pp = &node[v];
    } // 60799e
    void cut(int u, int v) { // remove an edge (u, v)
        Node *x = &node[u], *top = &node[v];
        makeRoot (top); x->splay();
        assert (top == (x->pp ? x->c[0]));
        if (x->pp) x->pp = 0;
        else {
            x->c[0] = top->p = 0;
            x->fix();
        } // 8acbe8
    } // a58ec7
    bool connected(int u, int v) { // are u, v in the same tree?
        Node* nu = access(&node[u])->first();
        return nu == access(&node[v])->first();
    } // b80a22
    void makeRoot (Node* u) {
        access(u);
        u->splay();
        if (u->c[0]) {
            u->c[0]->p = 0;
            u->c[0]->flip ^= 1;
            u->c[0]->pp = u;
            u->c[0] = 0;
            u->fix();
        }
    }
};
```

```

    } // 586a65
} // 74c908
Node* access(Node* u) {
    u->splay();
    while (Node* pp = u->pp) {
        pp->splay(); u->pp = 0;
        if (pp->c[l]) {
            pp->c[l]->p = 0; pp->c[l]->pp = pp; } // 1ccdfe
        pp->c[l] = u; pp->fix(); u = pp;
    } // b10f33
    return u;
} // 4ac291
}; // ceab83
```

**DirectedMST.h**  
**Description:** Finds a minimum spanning tree/arborescence of a directed graph, given a root node. If no MST exists, returns -1.  
**Time:**  $\mathcal{O}(E \log V)$

|                                          |                     |
|------------------------------------------|---------------------|
| "../data-structures/UnionFindRollback.h" | 39e620, 58L, 10m20s |
|------------------------------------------|---------------------|

```

struct Edge { int a, b; ll w; };
struct Node {
    Edge key;
    Node *l, *r;
    ll delta;
    void prop() {
        key.w += delta;
        if (l) l->delta += delta;
        if (r) r->delta += delta;
        delta = 0;
    } // 0d348f
    Edge top() { prop(); return key; }
}; // ab4902
Node *merge(Node *a, Node *b) {
    if (!a || !b) return a ? b;
    a->prop(), b->prop();
    if (a->key.w > b->key.w) swap(a, b);
    swap(a->l, (a->r = merge(b, a->r)));
    return a;
} // c5109e
void pop(Node*& a) { a->prop(); a = merge(a->l, a->r); }
pair<ll, vi> dmst(int n, int r, vector<Edge>& g) {
    RollbackUF uf(n);
    vector<Node*> heap(n);
    for (Edge e : g) heap[e.b] = merge(heap[e.b], new Node{e});
    ll res = 0;
    vi seen(n, -1), path(n, par(n);
    seen[r] = r;
    vector<Edge> Q(n), in(n, {-1,-1}), comp;
    deque<tuple<int, int, vector<Edge>>> cys;
    rep(s,0,n) {
        int u = s, qi = 0, w;
        while (seen[u] < 0) {
            if (!heap[u]) return {-1,{} };
            Edge e = heap[u]->top();
            heap[u]->delta -= e.w, pop(heap[u]);
            Q[qi] = e, path[qi++] = u, seen[u] = s;
            res += e.w, u = uf.find(e.a);
            if (seen[u] == s) {
                Node* cyc = 0;
                int end = qi, time = uf.time();
                do cyc = merge(cyc, heap[w = path[--qi]]);
                while (uf.join(u, w));
                u = uf.find(u), heap[u] = cyc, seen[u] = -1;
                cys.push_front({u, time, {&Q[qi], &Q[end]}});
            } // 00a339
        } // c8f0da
        rep(i,0,qi) in[uf.find(Q[i].b)] = Q[i];
    } // fa3c2c
};
```

```

for (auto& [u,t,comp] : cys) { // restore sol (optional)
    uf.rollback(t);
    Edge inEdge = in[u];
    for (auto& e : comp) in[uf.find(e.b)] = e;
    in[uf.find(inEdge.b)] = inEdge;
} // 4f9b56
rep(i,0,n) par[i] = in[i].a;
return {res, par};
} // efa3a4
```

**SmallToLarge.h**  
**Description:** good small to large  
**Time:**  $\mathcal{O}(N \log N)$

|  |                    |
|--|--------------------|
|  | 19475e, 26L, 5m30s |
|--|--------------------|

```

void small_to_large(vector<vector<int>> & g){
    int n = sz(g);
    int cans = 0;
    auto add = [&](int v){ cans += v; };
    auto del = [&](int v){ cans -= v; };
    vector ans(n, 0), big(n, -1), sub(n, 1), pos(n, 0), pre(0, 0)
        ;
    auto dfspre = [&](auto&& rec, int v, int p)->void {
        pos[v] = sz(pre); pre.push_back(v);
        for(int f : g[v])if (f != p){
            rec(rec, f, v);
            sub[v] += sub[f];
            if (big[v] == -1 or sub[f] > sub[big[v]])big[v] = f;
        } // 2f5782
    }; // 125df2
    dfspre(dfspre, 0, 0);
    auto dfs = [&](auto&& rec, int v, int p, int keep)->void {
        int b = big[v];
        for(int f : g[v])if (f != p and f != b)rec(rec, f, v, 0);
        if (b != -1)rec(rec, b, v, 1);
        add(v);
        for(int f : g[v])if (f != p and f != b)rep(i,pos[f],pos[f]+
            sub[f])add(pre[i]);
        ans[v] = cans;
        if (not keep)rep(i,pos[v],pos[v]+sub[v])del(pre[i]);
    }; // 022003
    dfs(dfs, 0, 0, 1);
} // 19475e
```

## Data structures (6)

### 6.1 General

**HashMap.h**  
**Description:** Hash map with mostly the same API as unordered\_map, but ~3x faster. Uses 1.5x memory. Initial capacity must be a power of 2 (if provided).

|  |                |
|--|----------------|
|  | d77092, 7L, 2m |
|--|----------------|

```

#include <bits/extc++.h>
// To use most bits rather than just the lowest ones:
struct chash { // large odd number for C
    const uint64_t C = 1l(4e18 * acos(0)) | 7l;
    ll operator()(ll x) const { return __builtin_bswap64(x*C); }
}; // cdd37e
__gnu_pbds::gp_hash_table<ll,int,chash> h({}, {}, {}, {}, {1<16});
```

**OrderedSet.h**  
**Description:** ordered/indexed set and multiset Bad constant factor, works only in Linux  
**Memory:**  $\mathcal{O}(N)$   
**Time:**  $\mathcal{O}(\log N)$  operations

|                                                 |                    |
|-------------------------------------------------|--------------------|
| <bits/extc++.h> //include it before any defines | b8c30a, 15L, 4m20s |
|-------------------------------------------------|--------------------|

```

using namespace __gnu_pbds;
```

```
template<class T, class B = null_type> using ordered_set = tree
<T, B, less<T>, rb_tree_tag,
tree_order_statistics_node_update>;

template<class T>
struct ordered_multiset{
ordered_set<pair<T, int>> o; int c;
ordered_multiset():c(0){}
unsigned order_of_key(T x){return o.order_of_key({x, -1});}
const T* find_by_order(int p){return &(*o.find_by_order(p)).
first;}
void insert(T x){o.insert({x, c++});}
void erase(T x){o.erase(o.lower_bound({x, 0}));}
unsigned size(){return o.size();}
const T* lower_bound(T x){return &(*o.lower_bound({x, 0})).
first;}
const T* upper_bound(T x){return &(*o.upper_bound({x, c})).
first;}
}; // d4e54f
```

UnionFindRollback.h

Description: Disjoint-set data structure with undo. If undo is not needed, skip st.time() and rollback(). Usage: int t = uf.time(); ...; uf.rollback(t); Time:  $\mathcal{O}(\log(N))$

```
struct RollbackUF {
vi e; vector<pii> st;
RollbackUF(int n) : e(n, -1) {}
int size(int x) { return -e[find(x)]; }
int find(int x) { return e[x] < 0 ? x : find(e[x]); }
int time() { return sz(st); }
void rollback(int t) {
for (int i = time(); i --> t;)
e[st[i].first] = st[i].second;
st.resize(t);
} // 30bb61
bool join(int a, int b) {
a = find(a), b = find(b);
if (a == b) return false;
if (e[a] > e[b]) swap(a, b);
st.push_back({a, e[a]});
st.push_back({b, e[b]});
e[a] += e[b]; e[b] = a;
return true;
} // 6c709f
}; // de4ad0
```

StaticCHT.h

Description: static CHT - add must be ordered by slope (a), queries by x. Time: amortized  $\mathcal{O}(1)$ .

```
struct CHT {
int it; vector<ll> a, b;
CHT():it(0){}
ll eval(int i, ll x){return a[i]*x + b[i];}
bool useless(){
int sz = a.size();
int r = sz-1, m = sz-2, l = sz-3;
#warning careful with overflow!
return (b[l] - b[r])*(a[m] - a[l]) <
(b[l] - b[m])*(a[r] - a[l]);
} // c37135
void add(ll A, ll B){
a.push_back(A); b.push_back(B);
while (!a.empty()){
if ((a.size() < 3) || !useless()) break;
a.erase(a.end() - 2);
```

```
b.erase(b.end() - 2);
} // b21fc8
it = min(it, int(a.size()) - 1);
} // 6df532
ll get(ll x){
while (it+1 < a.size()){
if (eval(it+1, x) > eval(it, x)) it++;
else break;
} // fe9dba
return eval(it, x);
} // b44949
}; // da7e40
```

LineContainer.h

Description: Container where you can add lines of the form  $kx+m$ , and query maximum values at points  $x$ . Useful for dynamic programming (“convex hull trick”). Time:  $\mathcal{O}(\log N)$

```
struct Line {
mutable ll k, m, p;
bool operator<(const Line& o) const { return k < o.k; }
bool operator<(ll x) const { return p < x; }
}; // 7e3ecf
struct LineContainer : multiset<Line, less<>> {
// (for doubles, use inf = 1/.0, div(a,b) = a/b)
static const ll inf = LLONG_MAX;
ll div(ll a, ll b) { // floored division
return a / b - ((a ^ b) < 0 && a % b); } // 10f081
bool isect(iterator x, iterator y) {
if (y == end()) return x->p = inf, 0;
if (x->k == y->k) x->p = x->m > y->m ? inf : -inf;
else x->p = div(y->m - x->m, x->k - y->k);
return x->p >= y->p;
} // 2fac86
void add(ll k, ll m) {
auto z = insert({k, m, 0}), y = z++, x = y;
while (isect(y, z)) z = erase(z);
if (x != begin() && isect(--x, y)) isect(x, y = erase(y));
while ((y = x) != begin() && (--x)->p >= y->p)
isect(x, erase(y));
} // 08625f
ll query(ll x) {
assert(!empty());
auto l = *lower_bound(x);
return l.k * x + l.m;
} // d21e2f
}; // 5771f0
```

6.2 Range Queries

Spec.h

Description: Spec for Seg Beats. It’s similar to other data structures. Time: varies

```
struct node{int max1,max2,maxc; ll sum;};
struct BeatsSpec{ //chmin sum
using T = node; using L = int;
static constexpr T id = node{-oo,-oo,0,0};
static T op(T a, T b){
node n;
if (a.max1 > b.max1){
n.max1 = a.max1;
n.max2 = max(a.max2, b.max1);
n.maxc = a.maxc;
} // 60044a
else if (a.max1 == b.max1){
n.max1 = a.max1;
n.max2 = max(a.max2, b.max2);
```

```
n.maxc = a.maxc+b.maxc;
} // 89a062
else{
n.max1 = b.max1;
n.max2 = max(b.max2, a.max1);
n.maxc = b.maxc;
} // dbf86a
n.sum=a.sum+b.sum;
return n;
} // 7211b8
static T ch(T a, L b, int l, int r){
if (a.max2 <= b)a.sum -= (ll)(a.max1-b)*a.maxc, a.max1 = b;
return a;
} // 6f5ec4
static L cmp(L a, L b){return min(a,b);}
static bool brk(L a, T b){return b.max1 <= a;}
static bool tag(L a, T b){return b.max2 < a;}
}; // 0a5678
```

Treap.h

Description: Lazy treap. Its Spec is the same as LazySpec, except that update has the signature update(K f, int n, S a), where n represents the range size. Time:  $\mathcal{O}(\log N)$

```
#define TT template<typename S>
#define NN node<S>*
mt19937 rng(chrono::steady_clock::now().time_since_epoch().
count());
TT struct node {
node *l=0, *r=0;
int y, c=1;
typename S::S val, acc;
typename S::K lz;
bool hlz=0;
node(typename S::S aval) : y(uniform_int_distribution<int>
>(0,(int)1e9)(rng)), val(aval), acc(aval) {}
void rc();
}; // 2469fa
TT int cnt(S n) {return n ? n->c : 0;}
TT void prop(NN t) {
if (!t or !t->hlz) return;
t->hlz=0;
t->val = S::update(t->lz, 1, t->val);
t->acc = S::update(t->lz, t->c, t->acc);
if (t->l) t->l->lz = t->l->hlz ? S::compose(t->l->lz, t->lz)
: t->lz, t->l->hlz=1;
if (t->r) t->r->lz = t->r->hlz ? S::compose(t->r->lz, t->lz)
: t->lz, t->r->hlz=1;
} // 2a8212
TT void node<S>::rc() {
c = cnt(l) + cnt(r) + 1;
prop(l); prop(r);
acc = S::op(S::op(l ? l->acc : S::id(), val), r ? r->acc : S
::id());
} // 25313c
TT pair<NN,NN> split(NN t, int k) {
if (k == 0) return {0, t};
if (cnt(t->l) >= k) {
prop(t->l);
auto [l, r] = split(t->l, k);
t->l = r;
t->rc();
return {l, t};
} // b8bc7b
prop(t->r);
auto [l,r] = split(t->r, k - cnt(t->l) - 1);
t->r = l;
t->rc();
```

```
    return {t, r};
} // 480f11
TT auto merge(NN l, NN r) {
    if (!l) return r;
    if (!r) return l;
    if (l->y < r->y) return prop(l->r, l->r = merge(l->r, r), l->rc(), l);
    return prop(r->l, r->l = merge(l, r->l), r->rc(), r);
} // 902057
```

FenwickTree.h

**Description:** Computes partial sums  $a[0] + a[1] + \dots + a[\text{pos} - 1]$ , and updates single elements  $a[i]$ , taking the difference between the old and new value.

**Time:** Both operations are  $\mathcal{O}(\log N)$ .

e62fac, 22L, 4m

```
struct FT {
    vector<ll> s;
    FT(int n) : s(n) {}
    void update(int pos, ll dif) { // a[pos] += dif
        for (; pos < sz(s); pos |= pos + 1) s[pos] += dif;
    } // a388f1
    ll query(int pos) { // sum of values in [0, pos)
        ll res = 0;
        for (; pos > 0; pos &= pos - 1) res += s[pos-1];
        return res;
    } // 6defa0
    int lower_bound(ll sum) { // min pos st sum of [0, pos] >= sum
        // Returns n if no sum is >= sum, or -1 if empty sum is.
        if (sum <= 0) return -1;
        int pos = 0;
        for (int pw = 1 << 25; pw; pw >= 1) {
            if (pos + pw <= sz(s) && s[pos + pw-1] < sum)
                pos += pw, sum -= s[pos-1];
        } // 63f005
        return pos;
    } // ea70d8
}; // e62fac
```

FenwickTree2d.h

**Description:** Computes sums  $a[i,j]$  for all  $i < I, j < J$ , and increases single elements  $a[i,j]$ . Requires that the elements to be updated are known in advance (call fakeUpdate() before init()).

**Time:**  $\mathcal{O}(\log^2 N)$ . (Use persistent segment trees for  $\mathcal{O}(\log N)$ .)

"FenwickTree.h" 157f07, 22L, 3m40s

```
struct FT2 {
    vector<vi> ys; vector<FT> ft;
    FT2(int limx) : ys(limx) {}
    void fakeUpdate(int x, int y) {
        for (; x < sz(ys); x |= x + 1) ys[x].push_back(y);
    } // 01fc7b
    void init() {
        for (vi& v : ys) sort(all(v)), ft.emplace_back(sz(v));
    } // d5ca1f
    int ind(int x, int y) {
        return (int)(lower_bound(all(ys[x]), y) - ys[x].begin()); }
        // aee02d
    void update(int x, int y, ll dif) {
        for (; x < sz(ys); x |= x + 1)
            ft[x].update(ind(x, y), dif);
    } // bb1454
    ll query(int x, int y) {
        ll sum = 0;
        for (; x; x &= x - 1)
            sum += ft[x-1].query(ind(x-1, y));
        return sum;
    } // 8334c3
}; // 157f07
```

MoQueries.h

**Description:** Answer interval or tree path queries. Includes interval version without deletion. If values are on tree edges, change step to add/remove the edge  $(a,c)$  and remove the initial add call (but keep in).

**Time:**  $\mathcal{O}(N\sqrt{Q})$

d5377e, 76L, 15m30s

```
void add(int ind, int end) { ... } // add a[ind] (end = 0 or 1)
void del(int ind, int end) { ... } // remove a[ind]
int calc() { ... } // compute current answer
```

```
vi mo(vector<pii> Q) {
    int L = 0, R = 0, blk = 350; // ~N/sqrt(Q)
    vi s(sz(Q)), res = s;
    #define K(x) pii(x.first/blk, x.second ^ -(x.first/blk & 1))
    iota(all(s), 0);
    sort(all(s), [&](int s, int t){ return K(Q[s]) < K(Q[t]); });
    for (int qi : s) {
        pii q = Q[qi];
        while (L > q.first) add(--L, 0);
        while (R < q.second) add(R++, 1);
        while (L < q.first) del(L++, 0);
        while (R > q.second) del(--R, 1);
        res[qi] = calc();
    } // 0f7fae
    return res;
} // e3731f
```

```
vi moTree(vector<array<int, 2>> Q, vector<vi>& ed, int root=0){
    int N = sz(ed), pos[2] = {}, blk = 350; // ~N/sqrt(Q)
    vi s(sz(Q)), res = s, I(N), L(N), R(N), in(N), par(N);
    add(0, 0), in[0] = 1;
    auto dfs = [&](int x, int p, int dep, auto& f) -> void {
        par[x] = p;
        L[x] = N;
        if (dep) I[x] = N++;
        for (int y : ed[x]) if (y != p) f(y, x, !dep, f);
        if (!dep) I[x] = N++;
        R[x] = N;
    }; // 329c88
    dfs(root, -1, 0, dfs);
    #define K(x) pii(I[x[0]] / blk, I[x[1]] ^ -(I[x[0]] / blk & 1))
    iota(all(s), 0);
    sort(all(s), [&](int s, int t){ return K(Q[s]) < K(Q[t]); });
    for (int qi : s) rep(end,0,2) {
        int &a = pos[end], b = Q[qi][end], i = 0;
    #define step(c) { if (in[c]) { del(a, end); in[a] = 0; } \
                    else { add(c, end); in[c] = 1; } a = c; } //
        3839ba
        while (!(L[b] <= L[a] && R[a] <= R[b]))
            I[i++] = b, b = par[b];
        while (a != b) step(par[a]);
        while (i--) step(I[i]);
        if (end) res[qi] = calc();
    } // c880be
    return res;
} // ce9c1e
```

```
vector mo_no_deletion(vector<pii>& qs, int n){
    int q = sz(qs), sq = (int)sqrt(q)+1, blk = (n+sq+1)/sq;
    vector<vi> o((n+blk-1)/blk);
    rep(i,0,q)o[qs[i].first/blk].pb(i);
    for(auto& vq : o)sort(all(vq), [&](int i, int j){return qs[i].second < qs[j].second;});
    vector<int> ans(q);
    rep(i,0,sz(o)){
        auto& vq = o[i];
        int l = blk*i + blk, r = l-1;
        // prepare to answer queries
        for(int qi : vq){
            auto [ql, qr] = qs[qi];
```

```
        if (qr <= l){ //if it does not extrapolate
            rep(j,ql,qr+1)add(j, 1); //solving manually
            continue;
        } // b94913
        while(r < qr)add(++r, 1);
        int ml = 1; //we will move l manually
        // prepare checkpoint
        while(ml > ql)add(--ml, 0);
        ans[qi] = calc(i);
        // revert checkpoint: discard changes made by moving l
    } // 6569ca
} // 09ff2d
return ans;
} // fe1e74
```

MergeSortTree.h

**Description:** Merge Sort Tree

**Memory:**  $\mathcal{O}(N \log N)$

**Time:**  $\mathcal{O}(\log^2 N)$

7c1cf9, 38L, 6m50s

```
template<class T> struct MGST{
    int n, h; vector<vector<T>> t;
    int lg(int x){return __builtin_clz(1)-__builtin_clz(x);}
    MGST(vector<T> v) : n(sz(v)), h(lg(n)) {
        if (n != (1<<h))n = 1<<(++h);
        t.assign(h, vector<T>(n));
        rep(i,0,sz(v))t[0][i] = v[i];
        rep(i,sz(v),n)t[0][i] = oo; //non-existent
        rep(k,0,h)for(int i = 0, s = 1<<k; i < n; i += 2*s){
            int p1=0, p2=0;
            rep(p,i,i+2*s){
                if (p1==s)t[k+1][p] = t[k][i+s+p2], p2++;
                else if (p2==s)t[k+1][p] = t[k][i+p1], p1++;
                else if (t[k][i+p1] < t[k][i+s+p2])t[k+1][p] = t[k][i+p1], p1++;
                else t[k+1][p] = t[k][i+s+p2], p2++;
            } // 690730
        } // eb4c11
    } // b7e287
    T query_helper(T x, int k, int l){
        auto it = upper_bound(t[k+1, t[k]+1+(1<<k), x);
        if (it == t[k+1])return 0;
        else return *prev(it);
    } // ef2397
    T lb(T x, int l, int r){ //biggest <= x in [l, r)
        T ans = 0; r++;
        for(int k = 0; l < r; k++){
            if ((1>>k)&1){
                ans = max(ans, query_helper(x, k, l));
                l += 1<<k;
            } // 1bf09f
            if ((r>>k)&1){
                r -= 1<<k;
                ans = max(ans, query_helper(x, k, r));
            } // aa3bad
        } // b63c49
        return ans;
    } // 8e4027
}; // 7c1cf9
```

MPsum.h

**Description:** Multidimensional Psum Requires Abelian Group (op, inv, id)

**Memory:**  $\mathcal{O}(N^D)$

**Time:**  $\mathcal{O}(2^D)$

3c2845, 20L, 4m30s

```
#define MAs template<class... As> //multiple arguments
template<int D, class S> struct Psum{
```

```
using T = typename S::T;
int n; vector<Psum<D-1, S>> v;
MAS Psum(int s, As... ds):n(s+1),v(n,Psum<D-1, S>(ds...)){
MAS void set(T x, int p, As... ps){v[p+1].set(x, ps...);}
void push(Psum& p){rep(i, 1, n)v[i].push(p.v[i]);}
void init(){rep(i, 1, n)v[i].init(),v[i].push(v[i-1]);}
MAS T query(int l, int r, As... ps){
    return S::op(v[r+1].query(ps...),S::inv(v[l].query(ps...)))
        ;
} // eac6a8
}; // 4f6c04
template<class S> struct Psum<0, S>{
using T = typename S::T;
T val=S::id;
void set(T x){val=x;}
void push(Psum& a){val=S::op(a.val,val);}
void init(){
    T query(){return val;}
}; // 713694
```

**Dist.h**  
**Description:** Disjoint Sparse Table Requires Monoid (op, id)  
**Memory:**  $\mathcal{O}(N \log N)$   
**Time:**  $\mathcal{O}(\log N)$

2f4715, 21L, 4m30s

```
#define repinv(i, a, b) for(int i = (a); i >= (b); i--)
template<class S> struct DIST{
using T = typename S::T;
int n, h; vector<vector<T>> t;
int lg(signed x){return __builtin_clz(1)-__builtin_clz(x);}
DiST(vector<T> v): n(sz(v)), h(lg(n)){
    if (n != (1<<h))n = 1<<(+h);
    t.assign(h, vector<T>(n)); v.resize(n, S::id);
    for(int d = 0, s = 1; d < h; d++, s *= 2)
        for(int m = s; m < n; m += 2*s){
            t[d][m] = v[m]; t[d][m-1] = v[m-1];
            rep(i, m+1, m+s)t[d][i] = S::op(t[d][i-1], v[i]);
            repinv(i, m-2, m-s)t[d][i] = S::op(v[i], t[d][i+1]);
        } // 3b44fe
    } // 1c2aa0
T query(int l, int r){
    if (l==r)return t[0][l];
    int k = lg(l^r);
    return S::op(t[k][l], t[k][r]);
} // 07c10a
}; // 612c6a
```

**SparseTable.h**  
**Description:** Sparse Table Requires Idempotent Monoid S (op, inv, id)  
**Memory:**  $\mathcal{O}(n \log n)$   
**Time:**  $\mathcal{O}(1)$  query,  $\mathcal{O}(n \log n)$  build

276609, 14L, 2m50s

```
template<class S> struct SpTable{
using T = typename S::T;
int n; vector<vector<T>> tab;
int lg(signed x){return __builtin_clz(1)-__builtin_clz(x);}
SpTable(vector<T> v):n(sz(v)),tab(1+lg(n),vector<T>(n,S::id)){
    {
        rep(i,0,n)tab[0][i] = v[i];
        rep(i,0,lg(n))rep(j,0,n-(1<<i))
            tab[i+1][j] = S::op(tab[i][j], tab[i][j+(1<<i)]);
    } // c105d7
T query(int l, int r){
    int k = lg(++r-1);
    return S::op(tab[k][l], tab[k][r-(1<<k)]);
} // e06689
}; // 276609
```

**SqrtDecomp.h**  
**Description:** Sqrt Decompostion  
**Memory:**  $\mathcal{O}(n)$   
**Time:**  $\mathcal{O}(n)$  build,  $\mathcal{O}(\sqrt{n})$  queries

f45235, 41L, 7m40s

```
struct SqrtDecomp {
using K = ll; // single element information
using T = ll; // block information
int n, bsz, n_block;
vector<T> v;
vector<int> id;
vector<K> block;
SqrtDecomp(const vector<T> & x): n(sz(x)), v(x), id(n) {
    bsz = sqrt(n) + 1;
    n_block = (n + bsz - 1) / bsz; // ceil(n, bsz)
    rep(i, 0, n) id[i] = i / bsz;
    // Add information to block
    block = vector<K>(n_block, oo);
    rep(i, 0, n) block[id[i]] = min(block[id[i]], v[i]);
} // 3bc167
void update(int idx, ll x) { // Update set idx to x
    int bid = id[idx];
    block[bid] = oo;
    v[idx] = x;
    rep(i, bid * bsz, min((bid+1)*bsz, n)) block[bid] = min(
        block[bid], v[i]);
} // 7aff89
ll query(int l, int r) { // Query of min in interval [l, r]
    assert(l <= r); // Or return id;
    ll ans = oo;
    auto sbkl = [&](int bid, int flag) { // flag [left, right, both]
        rep(i, max(l, bid*bsz), min((bid+1)*bsz, r+1)) ans = min(
            ans, v[i]);
    }; // f49504
    auto allblk = [&](int bid) { // Solve entire block
        ans = min(ans, block[bid]);
    }; // 3566fc
    if (id[l] == id[r]) {
        sbkl(id[l], 2);
    } // 340382
    else {
        sbkl(id[l], 0);
        rep(i, id[l]+1, id[r]) allblk(i);
        sbkl(id[r], 1);
    } // e1769a
    return ans;
} // 7a0d23
}; // f45235
```

6.2.1 Segment Tree

**SegmentTree.h**  
**Description:** Half-Open Iterative SegTree  
**Time:**  $\mathcal{O}(\log N)$

0ea399, 17L, 2m50s

```
template<class S> struct SegTree{
using T = typename S::T;
int n; vector<T> seg;
SegTree(int s):n(s),seg(2*n,S::id){}
void update(T x, int i){
    for(seg[i+=n]=x;i/=2;)
        seg[i] = S::op(seg[2*i], seg[2*i+1]);
} // 781838
T query(int l, int r){ // [l, r)
    T vl=S::id, vr=S::id;
    for(l+=n,r+=n;l<r;l/=2,r/=2){
        if (l&1)vl = S::op(vl, seg[l++]);
        if (r&1)vr = S::op(seg[--r], vr);
    } // eabcd5
```

```
    return S::op(vl, vr);
} // 25936a
}; // 0ea399
```

**LazySegmentTree.h**  
**Description:** Lazy Seg (half-open), N must be a power of 2. Can be transformed into Seg Beats by uncommenting conditions.  
**Time:**  $\mathcal{O}(\log N * (ch + cmp))$ .

fa8696, 30L, 8m

```
template<class S> struct SegBeats{ // n MUST be a power of 2
using T = typename S::T; using L = typename S::L;
int n; vector<T> seg; vector<L> lz; vector<bool> ig;
SegBeats(int s):n(s),seg(2*n,S::id),lz(2*n),ig(2*n,1){}
void apply(int p, L v, int l, int r){
    seg[p] = S::ch(seg[p],v,l,r);
    if (r-1>l)lz[p] = ig[p] ? v : S::cmp(lz[p], v), ig[p] = 0;
} // f453ff
void prop(int p, int l, int r){
    if (ig[p])return;
    int m = (l+r)/2; ig[p] = 1;
    apply(2*p, lz[p], l, m);
    apply(2*p+1, lz[p], m, r);
} // f09d8e
void update(L v, int l, int r){return update(v,l,r,1,0,n);}
void update(L v, int lq, int rq, int no, int lx, int rx){
    if (rq <= lx or rx <= lq /*or S::brk(v,seg[no])*/)return;
    if (lq <= lx and rx <= rq /*and S::tag(v,seg[no])*/)return
        apply(no, v, lx, rx);
    int mid = (lx+rx)/2; prop(no,lx,rx);
    update(v,lq,rq,2*no,lx,mid); update(v,lq,rq,2*no+1,mid,rx);
    seg[no] = S::op(seg[2*no],seg[2*no+1]);
} // 04eed2
T query(int l, int r){return query(l,r,1,0,n);}
T query(int lq, int rq, int no, int lx, int rx){
    if (rq <= lx or rx <= lq)return S::id;
    if (lq <= lx and rx <= rq)return seg[no];
    int mid = (lx+rx)/2; prop(no,lx,rx);
    return S::op(query(lq,rq,2*no,lx,mid),query(lq,rq,2*no+1,
        mid,rx));
} // fb0086
}; // fa8696
```

**MSegTree.h**  
**Description:** Multidimensional SegTree Requires Monoid (op, id)  
**Memory:**  $\mathcal{O}(N^D)$   
**Time:**  $\mathcal{O}((\log N)^D)$

e335e5, 26L, 5m40s

```
#define MAS template<class... As> //multiple arguments
template<int D, class S> struct MSegTree{
using T = typename S::T;
int n; vector<MSegTree<D-1, S>> seg;
MAS MSegTree(int s, As... ds):n(s),seg(2*n, MSegTree<D-1, S>(
    ds...)){
MAS T get(int p, As... ps){return seg[p+n].get(ps...);}
MAS void update(T x, int p, As... ps){
    seg[p+=n].update(x, ps...);
    while(p/=2)seg[p].update(S::op(seg[2*p].get(ps...),seg[2*p
        +1].get(ps...)), ps...);
} // 2c8b52
MAS T query(int l, int r, As... ps){
    T lv=S::id,rv=S::id;
    for(l+=n,r+=n+1;l<r;l/=2,r/=2){
        if (l&1)lv = S::op(lv, seg[l++].query(ps...));
        if (r&1)rv = S::op(seg[--r].query(ps...),rv);
    } // 1569b6
    return S::op(lv,rv);
} // bc7474
```

```
}; // da06ff
template<class S> struct MSegTree<0, S>{
    using T = typename S::T;
    T val=S::id;
    T get(){return val;};
    void update(T x){val=x;}; //set update!
    T query(){return val;};
}; // 50402e
```

LazySparseSeg.h

Description: Lazy Sparse Seg (half-open). Lazy can be removed (prop, lz, ig, ch/cmp)  
Time:  $\mathcal{O}(\log N * (ch + cmp))$ .

|  |                    |
|--|--------------------|
|  | fd0af0, 37L, 9m40s |
|--|--------------------|

```
template<class I, class S> struct LazySparseSeg{ //I is index
    type
    using T = typename S::T; //value type
    using L = typename S::L; //update type
    struct Node{int lc, rc; T val; L lz; bool ig;};
    I n; vector<Node> v;
    int new_node(){return v.eb(0,0,S::id,L(),1), sz(v)-1;}
    LazySparseSeg(I s) : n(s){
        //v.reserve(MXN); //faster node creation
        new_node(); new_node(); //blank and root node
    } // c4ba1b
    void apply(int i, L x, I lx, I rx){
        v[i].val = S::ch(v[i].val, x, lx, rx);
        if (rx-lx>1)v[i].lz = v[i].ig ? x : S::cmp(v[i].lz, x), v[i]
            ].ig = 0;
    } // 9ccb90
    void prop(int i, I lx, I rx){
        if (!v[i].lc)v[i].lc = new_node(), v[i].rc = new_node();
        if (v[i].ig)return;
        I mx = (lx+(rx-lx)/2); v[i].ig = 1;
        apply(v[i].lc, v[i].lz, lx, mx); apply(v[i].rc, v[i].lz, mx
            , rx);
    } // a00350
    void update(L x, I l, I r){return update(x, l, r, l, 0, n);}
    void update(L x, I l, I r, int i, I lx, I rx){
        if (r <= lx or rx <= l)return;
        if (l <= lx and rx <= r)return apply(i, x, lx, rx);
        I mx = (lx+(rx-lx)/2); prop(i, lx, rx);
        int lc = v[i].lc, rc = v[i].rc;
        update(x, l, r, lc, lx, mx); update(x, l, r, rc, mx, rx);
        v[i].val = S::op(v[lc].val, v[rc].val);
    } // f721de
    T query(I l, I r){return query(l, r, l, 0, n);}
    T query(I l, I r, int i, I lx, I rx){
        if (r <= lx or rx <= l)return S::id;
        if (l <= lx and rx <= r)return v[i].val;
        I mx = (lx+(rx-lx)/2); prop(i, lx, rx);
        return S::op(query(l, r, v[i].lc, lx, mx), query(l, r, v[i]
            ].rc, mx, rx));
    } // 52a49e
}; // fd0af0
```

LazyPersistentSeg.h

Description: Persistent Lazy Sparse Segment Tree Can be changed by mod-ifying Spec  
Time:  $\mathcal{O}(\log N * (ch + cmp))$

|  |                     |
|--|---------------------|
|  | b43ed0, 39L, 10m40s |
|--|---------------------|

```
template<class I, class S> struct LazyPersistentSeg{ //I is
    index type
    using T = typename S::T; //value type
    using L = typename S::L; //lazy type
    struct Node{int lc, rc; T val; L lz; bool ig;};
    I n; vector<Node> v;
    int new_node(int l=0, int r=0){return v.eb(l,r,S::op(v[l].val
        ,v[r].val),L(),1), sz(v)-1;}
    LazyPersistentSeg(){ //only creates object, should be "init"
        ed to get root
        //v.reserve(MXN); //faster node creation
        v.eb(0,0,S::id,L(),1); //blank node
    } // 00247f
    int init(I s){return n = s, new_node();}
    int lazy_clone(int i, L lz, I lx, I rx){
        int ni = new_node(v[i].lc, v[i].rc);
        v[ni].lz = v[i].ig ? lz : S::cmp(v[i].lz, lz);
        v[ni].ig = 0; v[ni].val = S::ch(v[i].val, lz, lx, rx);
        return ni;
    } // 4c0efb
    void prop(int i, I lx, I rx){
        if (v[i].ig)return;
        int mx = lx + (rx - lx) / 2; v[i].ig = 1;
        if (lx < rx)
            v[i].lc = lazy_clone(v[i].lc, v[i].lz, lx, mx),
            v[i].rc = lazy_clone(v[i].rc, v[i].lz, mx, rx);
    } // 551bde
    int update(L lz, I l, I r, int root){return update(lz, l, r,
        root, 0, n);}
    int update(L lz, I l, I r, int i, I lx, I rx){
        if (r <= lx or rx <= l)return i;
        if (l <= lx and rx <= r)return lazy_clone(i, lz, lx, rx);
        I mx = lx + (rx - lx) / 2; prop(i, lx, rx);
        return new_node(update(lz, l, r, v[i].lc, lx, mx), update(
            lz, l, r, v[i].rc, mx, rx));
    } // ca252e
    T query(I l, I r, int root){return query(l, r, root, 0, n);}
    T query(I l, I r, int i, I lx, I rx){
        if (r <= lx or rx <= l)return S::id;
        if (l <= lx and rx <= r)return v[i].val;
        I mx = lx + (rx - lx) / 2; prop(i, lx, rx);
        return S::op(query(l, r, v[i].lc, lx, mx), query(l, r, v[i]
            ].rc, mx, rx));
    } // 893689
}; // b43ed0
```

Strings (7)

Hashing.h

Description: String hashing (multiple mods and  $2^{32}$ )  
Memory:  $\mathcal{O}(n)$   
Time:  $\mathcal{O}(1)$  query,  $\mathcal{O}(n)$  build

|  |                    |
|--|--------------------|
|  | c40ee3, 23L, 5m40s |
|--|--------------------|

```
typedef uint64_t ull;
template<int M, class B> struct A {
    int x; B b; A(int x=0) : x(x), b(x) {}
    A(int x, B b) : x(x), b(b) {}
    A operator+(A o) const {int y = x+o.x; return{y - (y>=M)*M, b
        +o.b};}
    A operator-(A o) const {int y = x-o.x; return{y + (y< 0)*M, b
        -o.b};}
    A operator*(A o) const { return {(int)((ll)x*o.x % M), b*o.b}
        ; }
```

```
explicit operator ull() const { return x ^ (ull) b << 21; }
}; // e03276
typedef A<10000000007, A<10000000009, unsigned>> H;
static int C; // initialize to a number less than MOD or random
struct HashInterval {
    int n; vector<H> ha, pw;
    template<typename S>
    HashInterval(const S & str) : n(sz(str)), ha(n+1), pw(n+1) {
        pw[0] = 1;
        rep(i,0,n)
            ha[i+1] = ha[i] * C + str[i],
            pw[i+1] = pw[i] * C;
    } // 185a86
    H query(int a, int b) { return ha[b] - ha[a] * pw[b - a]; }
    H queryI(int a, int b) { return query(n - b, n - a); }
}; // 434a8c
```

KMP.h

Description: KMP automaton  
Memory:  $\mathcal{O}(N)$   
Time:  $\mathcal{O}(N)$  build,  $\mathcal{O}(1)$  query (amortized)

|  |                 |
|--|-----------------|
|  | 8f8450, 19L, 4m |
|--|-----------------|

```
struct KMP {
    string P; int n; vector<int> nb;
    KMP(string& p) : P(p), n((int)P.size()), nb(n+1) {
        for(int k = 1; k < n; k++) nb[k+1] = nxt(nb[k], P[k]);
    } // ca6dc8
    int nxt(int i, char c){
        for(; i; i = nb[i])if (i < n and P[i]==c)return i+1;
        return P[0]==c;
    } // 2b99e2
    vector<vector<int>> dfa;
    void build_dfa(){
        dfa.assign(n+1, vector<int>(26));
        dfa[0][P[0]-'a'] = 1; //only way to advance at 0
        for(int k = 1; k <= n; k++)
            for(int c = 0; c < 26; c++)
                if (k < n and P[k] == 'a'+c) dfa[k][c] = k+1;
                else dfa[k][c] = dfa[nb[k]][c];
    } // f47d83
}; // 8f8450
```

Zfunc.h

Description: z[i] computes the length of the longest common prefix of s[i:] and s, except z[0] = 0. (abacaba -> 0010301)  
Time:  $\mathcal{O}(n)$

|  |                   |
|--|-------------------|
|  | ee09e2, 9L, 1m30s |
|--|-------------------|

```
vi Z(const string& S) {
    vi z(sz(S)); int l = -1, r = -1;
    rep(i,1,sz(S)) {
        z[i] = i >= r ? 0 : min(r - i, z[i - l]);
        while (i + z[i] < sz(S) && S[i + z[i]] == S[z[i]]) z[i]++;
        if (i + z[i] > r) l = i, r = i + z[i];
    } // 44be47
    return z;
} // ee09e2
```

Manacher.h

Description: For each position in a string, computes p[0][i] = half length of longest even palindrome around pos i, p[1][i] = longest odd (half rounded down).  
Time:  $\mathcal{O}(N)$

|  |                    |
|--|--------------------|
|  | e7ad79, 11L, 2m10s |
|--|--------------------|

```
array<vi, 2> manacher(const string& s) {
    int n = sz(s); array<vi,2> p = {vi(n+1), vi(n)};
    rep(z,0,2) for (int i=0,l=0,r=0; i < n; i++) {
        int t = r-i+lz;
        if (i<r) p[z][i] = min(t, p[z][l+t]);
```

```
int L = i-p[z][i], R = i+p[z][i]-!z;
while (L>=1 && R+1<n && s[L-1] == s[R+1]) p[z][i]++, L--, R
    ++;
if (R>r) l=L, r=R;
} // a843d3
return p;
} // e7ad79
```

MinRotation.h

**Description:** Finds the lexicographically smallest rotation of a string.  
**Usage:** rotate(v.begin(), v.begin()+minRotation(v), v.end());  
**Time:**  $\mathcal{O}(N)$

d07a42, 8L, 1m20s

```
int minRotation(string s) {
    int a=0, N=sz(s); s += s;
    rep(b,0,N) rep(k,0,N) {
        if (a+k == b || s[a+k] < s[b+k]) {b += max(0, k-1); break;}
        if (s[a+k] > s[b+k]) { a = b; break; }
    } // 9374b1
    return a;
} // d07a42
```

Automaton.h

**Description:** Suffix automaton with parameterized transition table (can be array or map)  
**Memory:**  $\mathcal{O}(n * |G|)$   
**Time:**  $\mathcal{O}(n)$  build

70eb49, 30L, 5m10s

```
template<class C, class G> struct Automaton{
    vector<G> dag;
    vector<int> lnk, len, cnt;
    int last;
    template<class S> Automaton(S& str):
        dag(2),lnk(2,0),len(2,0),cnt(2,0),last(1){
            for(C& c : str)add(c); //can do .reserve(2*n+2)
        } // cd5999
    int new_node(int l, int is_pref){
        dag.pb(G()); lnk.pb(0); len.pb(l); cnt.pb(is_pref);
        return sz(dag)-1;
    } // 0814f6
    void add(C& c){
        int cur = new_node(len[last]+1, 1), p = last;
        while(p and not dag[p][c])dag[p][c] = cur, p = lnk[p];
        if (not p)lnk[cur] = 1;
        else {
            int q = dag[p][c];
            if (len[p]+1 == len[q])lnk[cur] = q;
            else{
                int clone = new_node(len[p]+1, 0);
                dag[clone] = dag[q];
                lnk[clone] = lnk[q];
                lnk[q] = lnk[cur] = clone;
                while(p and dag[p][c] == q)dag[p][c]=clone, p=lnk[p];
            } // 270a8a
        } // 9e6a19
        last = cur;
    } // b1dc88
}; // 70eb49
```

Aho.h

**Description:** Aho-Corasick  
**Memory:**  $\mathcal{O}(n * 26)$   
**Time:**  $\mathcal{O}(n)$  build

ccf3a0, 47L, 6m40s

```
const int K = 26;
struct Vertex {
    int next[K];
    bool output = false;
```

```
int p = -1;
char pch;
int link = -1;
int go[K];

Vertex(int _p=-1, char ch='$') : p(_p), pch(ch) {
    fill(begin(next), end(next), -1);
    fill(begin(go), end(go), -1);
} // 2636d9
}; // 0c589a
```

```
vector<Vertex> t(1);
```

```
void add_string(string const& s) {
    int v = 0;
    for (char ch : s) {
        int c = ch - 'a';
        if (t[v].next[c] == -1) {
            t[v].next[c] = sz(t);
            t.pb(v, ch);
        } // 2abd5c
        v = t[v].next[c];
    } // fc1e0d
    t[v].output = true;
} // 1bb4a6
```

```
int go(int v, char ch);
int get_link(int v) {
    if (t[v].link == -1) {
        if (v == 0 || t[v].p == 0) t[v].link = 0;
        else t[v].link = go(get_link(t[v].p), t[v].pch);
    } // e9856f
    return t[v].link;
} // 1e38ab
```

```
int go(int v, char ch) {
    int c = ch - 'a';
    if (t[v].go[c] == -1) {
        if (t[v].next[c] != -1) t[v].go[c] = t[v].next[c];
        else t[v].go[c] = v == 0 ? 0 : go(get_link(v), ch);
    } // 202af4
    return t[v].go[c];
} // e442d8
```

DP (8)

We don't know DP optimizations yet :/

Various (9)

9.1 Random

RNG.h

**Description:** RNGs  
**Time:**  $\mathcal{O}(1)$

6823af, 18L, 3m50s

```
mt19937 rng(chrono::steady_clock::now().time_since_epoch().
    count()); // mt19937-64
void example(){
    int n; cin >> n;
    uniform_int_distribution<int> distribution(1,n);
    int num = distribution(rng); // num no range [1, n]
    vector<int> vec(n);
    iota(vec.begin(), vec.end(), 1);
    shuffle(vec.begin(), vec.end(), rng); // shuffle
} // a3f379
```

```
using ull = unsigned long long;
ull mix(ull o){
    o+=0x9e3779b97f4a7c15;
    o=(o^(o>>30))*0xbf58476d1ce4e5b9;
    o=(o^(o>>27))*0x94d049bb133111eb;
    return o^(o>>31);
} // bc6211
ull hash(pii a) {return mix(a.first ^ mix(a.second));}
```

9.2 Ternary Search

GoldenSectionSearch.h

**Description:** Finds the argument minimizing the function  $f$  in the interval  $[a, b]$  assuming  $f$  is unimodal on the interval, i.e. has only one local minimum and no local maximum. The maximum error in the result is  $\epsilon$ . Works equally well for maximization with a small change in the code. See TernarySearch.h in for a discrete version.  
**Usage:** double func(double x) { return 4+x+.3\*x\*x; }  
double xmin = gss(-1000,1000,func);  
**Time:**  $\mathcal{O}(\log((b-a)/\epsilon))$

31d45b, 16L, 3m20s

```
// It is important for r to be precise,
// otherwise we don't necessarily maintain the inequality a <
// x1 < x2 < b.
double gss(double a, double b, double (*f)(double)) {
    double r = (sqrt(5)-1)/2, eps = 1e-7;
    double x1 = b - r*(b-a), x2 = a + r*(b-a);
    double f1 = f(x1), f2 = f(x2);
    while (b-a > eps)
        if (f1 < f2) { //change to > to find maximum
            b = x2; x2 = x1; f2 = f1;
            x1 = b - r*(b-a); f1 = f(x1);
        } else { // 4513d0
            a = x1; x1 = x2; f1 = f2;
            x2 = a + r*(b-a); f2 = f(x2);
        } // 2fe74a
    return a;
} // 31d45b
```

TernarySearch.h

**Description:** Find the smallest  $i$  in  $[a, b]$  that maximizes  $f(i)$ , assuming that  $f(a) < \dots < f(i) \geq \dots \geq f(b)$ . To reverse which of the sides allows non-strict inequalities, change the  $<$  marked with (A) to  $\leq$ , and reverse the loop at (B). To minimize  $f$ , change it to  $>$ , also at (B).  
**Usage:** int ind = ternSearch(0,n-1,[&](int i){return a[i];});  
**Time:**  $\mathcal{O}(\log(b-a))$

9155b4, 10L, 1m40s

```
template<class F> int ternSearch(int a, int b, F f) {
    assert(a <= b);
    while (b - a >= 5) {
        int mid = (a + b) / 2;
        if (f(mid) < f(mid+1)) a = mid; // (A)
        else b = mid+1;
    } // ce7859
    rep(i,a+1,b+1) if (f(a) < f(i)) a = i; // (B)
    return a;
} // 9155b4
```

9.3 Optimization tricks

9.3.1 Bit hacks

- $x \& -x$  is the least bit in  $x$ .
- for (int  $x = m; x;$ ) {  $--x \&= m; \dots$  } loops over all subset masks of  $m$  (except  $m$  itself).

- `c = x&-x, r = x+c; (((r^x) >> 2)/c) | r` is the next number after `x` with the same number of bits set.
- `rep(b,0,K) rep(i,0,(1 << K))`  
    `if (i & 1 << b) D[i] += D[i^(1 << b)];`  
    computes all sums of subsets.

### 9.3.2 Pragma

- **#pragma** `GCC optimize ("Ofast")` will make GCC auto-vectorize loops and optimizes floating points better.
- **#pragma** `GCC target ("avx2")` can double performance of vectorized code, but causes crashes on old machines.
- **#pragma** `GCC optimize ("bmi,bmi2,lzcnt,popcnt")` are good for bitsets.