CS21004 - Tutorial 7

11th Mar 2019

Instructions: For the problems with (To submit), please write the answers neatly in loose sheets with your name and roll number. Submit to the TA at the end of the class.

- 1. Show that following languages are not context-free using pumping lemma
 - (a) $L_1 = \{a^n b^j c^k : k > n, k > j\}$
 - (b) $L_2 = \{a^n b^j : n \le j^2\}$ (To submit)
 - (c) $L_3 = \{a^n b^j c^k : k = jn\}$ (Home)
- 2. Covert the following grammars into Chomsky Normal Form.
 - (a) $S \to aXbX$ $X \to aY|bY|\epsilon$ $Y \to X|c$ (To submit)
 - (b) $S \to AACD$ $A \to aAb|\epsilon$ $C \to aC|a$ $D \to aDa|bDb|\epsilon$ (Home)
- 3. Construct the PDA for the following language
 - (a) L1 = $a^i b^j c^k | i, j, k \ge 0$, and i=j or j=k (To submit)
 - (b) $L2 = a^{2m}c^{4n}d^nb^m|m, n > 0$ (To submit)
 - (c) L3= $x\$y|\exists n: x=binary(n) \land y=binary(n+1)$ where binary(n) is the binary encoding of natural number n. For example, this set contains 0\$1,1101\$1100 and 001\$101 but not 1\$1or11\$10. (Home)
- 4. Give CFG for the following languages.
 - (a) Write a rudimentary CFG to parse the roman numerals 1-99(i,ii,iii,iv,v,...,ix,x,...,xl,...,lxxx,...,xc,...,xcix). Consider the terminals c, l, x, v, i where c = 100, l = 50, x = 10, v = 5, i = 1. (Home)
 - (b) Construct a context free grammar for generating regular expressions which has the set of terminals T = a, b, ep, +, *, (,) over a, b, with + meaning the RegExp OR operator, and ep meaning the the ϵ symbol. (Home)