




Hyperledger Fabric

Theory and Applications of Blockchain (CS61065) - Tutorial 4

Public Blockchains

- Anyone can participate.
- Every node can see all the transactions in the network.



Use case

- The class is divided into various groups
- Each group has to collectively write some code
- If any person makes any changes, he only wants his group to see the changes
- No one from outside the class should be able to join without permission.
- Can we use a single Public Blockchain network here?





HYPERLEDGER

Distributed Ledgers



**HYPERLEDGER
BESU**

Java-based
Ethereum client



**HYPERLEDGER
BURROW**

Permissionable smart
contract machine (EVM)



**HYPERLEDGER
FABRIC**

Enterprise-grade DLT
with privacy support



**HYPERLEDGER
INDY**

Decentralized identity



**HYPERLEDGER
IROHA**

Mobile application focus



**HYPERLEDGER
SAWTOOTH**

Permissioned & permissionless
support; EVM transaction family

Libraries



**HYPERLEDGER
ARIES**



**HYPERLEDGER
QUILT**



**HYPERLEDGER
TRANSACTION**



**HYPERLEDGER
URCA**

Tools



**HYPERLEDGER
AVALON**



**HYPERLEDGER
CACTUS**



**HYPERLEDGER
CALIPER**



**HYPERLEDGER
CELLO**



**HYPERLEDGER
EXPLORER**

Domain-Specific



**HYPERLEDGER
GRID**



**HYPERLEDGER
LABS**



HYPERLEDGER

Distributed Ledgers



**HYPERLEDGER
BESU**

Java-based
Ethereum client



**HYPERLEDGER
BURROW**

Permissionable smart
contract machine (EVM)



**HYPERLEDGER
FABRIC**

Enterprise-grade DLT
with privacy support



**HYPERLEDGER
INDY**

Decentralized identity



**HYPERLEDGER
IROHA**

Mobile application focus



**HYPERLEDGER
SAWTOOTH**

Permissioned & permissionless
support; EVM transaction family

Libraries



**HYPERLEDGER
ARIES**



**HYPERLEDGER
QUILT**



**HYPERLEDGER
TRANSACTION**



**HYPERLEDGER
URSA**

Tools



**HYPERLEDGER
AVALON**



**HYPERLEDGER
CACTUS**



**HYPERLEDGER
CALIPER**



**HYPERLEDGER
CELLO**



**HYPERLEDGER
EXPLORER**

Domain-Specific



**HYPERLEDGER
GRID**




**HYPERLEDGER
LABS**

Hyperledger Fabric (Private Blockchain)



- Like other blockchain technologies, it has a ledger, uses smart contracts, and is a system by which participants manage their transactions.
- It is private and permissioned blockchain.
- Rather than an open permissionless system that allows unknown identities to participate in the network, the members of a Hyperledger Fabric network enroll through a trusted **Membership Service Provider (MSP)**.

Hyperledger Fabric Network




Organization



- Membership Service Providers (MSP) : Identity management of members
- Administrators : To manage the members (enroll, remove etc.)
- Users : Typically applications connecting to the blockchain network
- Peers : Hosting the chaincode and storing the ledger
- Orderers (optional) : Ordering of transactions

Each organization has an ID and a network can have multiple participating organizations


Entities Involved



Flow of Transactions



Client sends the transaction proposal to endorser. The endorsers return results with their signatures. The client checks if the endorsement policy is being satisfied. If yes, it sends the transaction to the orderer.



The orderer simply orders the transactions, puts them into blocks and sends it to all the peers to be validated. It does not have to look at the transactions.



The peers validate the transactions. (Check for double spending, enforcement of the endorsement policy etc.)

Practical Use cases



- **Walmart and Food Traceability**
 - <https://lf-hyperledger.atlassian.net/wiki/spaces/LMDWG/pages/18715588/Walmart>
- **Circular -Traceability of a Conflict Mineral (Tantalum)**
 - <https://lf-hyperledger.atlassian.net/wiki/spaces/LMDWG/pages/18716226/Circular+-Traceability+of+a+Conflict+Mineral+Tantalum>

Setup prerequisites



Recommended to set up on a Linux based system

- Git <https://git-scm.com/downloads>
- CURL <https://curl.se/download.html>
- Docker Engine <https://docs.docker.com/engine/install/>
- NodeJS (recommend to use nvm (Node Version Manager))
- Docker Compose

Installing Hyperledger Fabric



Determine a location on your machine where you want to place the fabric-samples repository and enter that directory in a terminal window.

```
>> mkdir fabric
```

```
>> cd fabric
```

```
>> curl -sLO https://raw.githubusercontent.com/hyperledger/fabric/main/scripts/install-fabric.sh &&  
chmod +x install-fabric.sh
```

```
>> ./install-fabric.sh docker samples binary
```

```
>> export PATH=<path to download location>/fabric-samples/bin:$PATH
```

Starting the test network with CAs



```
>> cd fabric-samples/test-network  
>> ./network.sh up -ca
```

The script will start containers for each member of the test-network namely:

- orderer
- peer0.org1.example.com
- peer0.org2.example.com
- ca_org1
- ca_org2
- ca_orderer
- cli

Creating a channel



```
>> ./network.sh createChannel -ca
```

- Creates a channel with name "mychannel"

```
>> ./network.sh createChannel -c <channel name> -ca
```

- To create a channel with a custom name

Deploying chain-code



```
>> ./network.sh deployCC -ccn <chain-code-name> -ccp <path-to-chaincode> -ccl  
<chaincode-language>
```

- To deploy chaincode

Example:

```
>> ./network.sh deployCC -ccn basic -ccp ../asset-transfer-basic/chaincode-javascript -  
ccl javascript
```

Other optional arguments:

- -ccep : To specify the endorsement policy

Running an application to invoke the chaincode



Example: Go to the `asset-transfer-basic/application-javascript` directory

The wallet directory stores the crypto material for a user issued by a CA. The CA is respawned every time we do `./network.sh up`.

Before running `app.js`

- Remove the wallet directory before running `app.js`.
- Run `>> npm install`

To run the `app.js` file : `>> node app.js`

Things to remember



- `asset-transfer-events`

While deploying the chaincode for this example, set the `-ccep` flag to `"OR('Org1MSP.peer', 'Org2MSP.peer')"`

Example - asset transfer basic



- `cd fabric-samples/test-network`
- `./network.sh down`
- `./network.sh up createChannel -ca -s couchdb`
- `./network.sh deployCC -ccn basic -ccp ../asset-transfer-basic/chaincode-javascript/ -ccl javascript`
- `cd ../asset-transfer-basic/application-gateway-javascript/`
- `npm install`
- `npm start`
- `cd ../../test-network`
- `./network.sh down`

Example - asset transfer events



- `cd fabric-samples/test-network`
- `./network.sh down`
- `./network.sh up createChannel -ca -s couchdb`
- `./network.sh deployCC -ccn events -ccp ../asset-transfer-events/chaincode-javascript/ -ccl javascript -ccep "OR('Org1MSP.peer','Org2MSP.peer')"`
- `cd ../asset-transfer-events/application-gateway-typescript/`
- `npm install`
- `npm start`
- `cd ../../test-network`
- `./network.sh down`

References



- [Hyperledger Fabric Documentation](#)
- [Endorsement policies — hyperledger-fabricdocs main documentation](#)
- [Private data — hyperledger-fabricdocs main documentation](#)
- [Private Data — hyperledger-fabricdocs main documentation](#) - Implicit private data
- [Hyperledger Fabric SDK for Node.js Interface: Network](#) - BlockEventListeners
- [Hyperledger Fabric SDK for Node.js Interface: Contract](#) - ContractEventListeners

NPTEL links:

- <https://youtu.be/4ujj5knD3pg?si=joLsrcNJDv1I7EMk> : Fabric Membership and Identity Management
- <https://youtu.be/xjliVltyLRk?si=IRReh8BBsUDSnWm-> : Fabric Components details
- https://youtu.be/nBXr7dLXAbE?si=x4vaXCHnM_nLyOGs : Fabric Transaction flow