Time in Distributed Systems: Clocks and Ordering of Events

Clocks in Distributed Systems

- Needed to
  - Order two or more events happening at same or different nodes (Ex: Consistent ordering of updates at different replicas, debugging from distributed logs, ordering of multicast messages sent in a group)
  - Decide if two events happened between some fixed duration of each other (Ex: Replay of stolen messages in distributed authentication protocols like Kerberos)
  - Start events at different nodes together at the same time (Ex: tracking in sensor networks, sleep/wakeup scheduling)

- Easy if a globally synchronized clock is available, but
  - Perfectly synchronized clocks are impossible to achieve
  - But perfect synchronization may not be needed always; synchronization within bounds may be enough
    - Degree of synchronization needed depends on application
      - Kerberos requires synchronization of the order of minutes
      - Tracking applications may require synchronization of the order of seconds
  - Still not sufficient for ordering events always
    - Suppose each node timestamps events at the node by its local clock
    - Suppose synchronization is accurate within bound ∂
    - May not be able to order events whose timestamps differ by less than ∂

- Two approaches for building clocks
  - **Physical Clocks**
    - Each machine has its own local clock
    - Clock synchronization algorithms run periodically to keep them synchronized with each other within some bounds
    - Useful for giving a consistent view of "current time" across all nodes within some bounds, but cannot order events always
  - **Logical Clocks**
    - Use the notion of **causality** to order events
    - Can what happened in one event affect what happens in another?
      - Because if not, ordering them is not important
    - Useful for ordering events, but not for giving a consistent view of "current time" across all nodes

Physical Clocks

Physical Clocks

- Each node has a local clock used by it to timestamp events at the node
- Local clocks of different nodes may vary
- Need to keep them synchronized (Clock Synchronization Problem)
- Perfect synchronization not possible because of inability to estimate network delays exactly

Clock Synchronization

- Internal Synchronization
  - Requires the clocks of the nodes to be synchronized to within a pre-specified bound
  - However, the clock times may not be synchronized to any external time reference, and can vary arbitrarily from any such reference
- External Synchronization
  - Requires the clocks to be synchronized to within a pre-specified bound of an external reference clock

How Computer Clocks Work

- Computer clocks are based on crystals that oscillate at a certain frequency
- Every H oscillations, the timer chip interrupts once (clock tick)
  - Resolution: time between two interrupts
- The interrupt handler increments a counter that keeps track of no. of ticks from a reference in the past (epoch)
- Knowing no. of ticks per second, we can calculate year, month, day, time of day etc.

Why Clocks Differ: Clock Drift

- Period of crystal oscillation varies slightly due to temperature, humidity, ageing,…
- If it oscillates faster, more ticks per real second, so clock runs faster; similar for slower clocks
- For machine p, when correct reference time is t, let machine clock show time as $C = C_p(t)$
- Ideally, $C_p(t) = t$ for all p, t
- In practice, $1 - \rho \leq dC/dt \leq 1 + \rho$
- ρ = max. clock drift rate, usually around 10^{-5} for cheap oscillators
- Drift results in skew between clocks (difference in clock values of two machines)

Resynchronization

- Periodic resynchronization needed to offset skew
- If two clocks are drifting in opposite directions, max. skew after time t is $2\rho t$
- If application requires that clock skew $< \delta$, then resynchronization period

$$r < \delta / (2\ \rho)$$

- Usually ρ and δ are known
  - ρ given by crystal manufacturer
  - δ specified from application requirement

Cristian's Algorithm

- One node acts as the time server
- All other nodes sends a message periodically (within resync. period r) to the time server asking for current time
- Time server replies with its time to the client node
- Client node sets its clock to the reply
- Problems:
  - How to estimate the delay incurred by the server's reply in reaching the client?
  - What if time server time is less than client's current time?

- Handling message delay: try to estimate the time the message with the timer server's time took to reach the client
  - Measure round trip time and halve it
  - Make multiple measurements of round trip time, discard too high values, take average of rest
  - Make multiple measurements and take minimum
  - Use knowledge of processing time at server if known to eliminate it from delay estimation (How to know?)
- Handling fast clocks
  - Do not set clock backwards; slow it down over a period of time to bring in tune with server's clock
    - Ex: increase the software clock every two interrupts instead of one

- Can be used for external synchronization if the time server is synchronized with external clock reference
  - Requires a special node with a time source
- What if the time server fails?
  - Usually a problem, as it is assumed that the time server is special (synchronized with external clock or at least with a more reliable clock)
- Works well in small LANs, not scalable to large number of nodes over WANs
  - Load on the central server will be high, affecting its processing time, in turn affecting synchronization error
  - Delay variance increases in larger networks

Berkeley Algorithm

- Centralized as in Cristian's, but the time server is active
- Time server asks for time of other nodes at periodic intervals
- Other nodes reply with their time
- Time server averages the times and sends the adjustments (difference from local clock) needed to each machine
  - Adjustments may be different for different machines
  - Why do we send adjustments, and not the new absolute clock value?
- Nodes sets their time (advances immediately or slows down slowly) to the new time

- Time server can handle faulty clocks by eliminating client clock values that are too low or too high
- What if the time server fails?
  - Just elect another node as the time server (Leader Election Problem)
  - Note that the actual time of the central server does not matter, enough for it to tick at around the same rate as other clocks to compute average correctly (why?)
- Cannot be used for external synchronization
- Works well in small LANs only for the same reason as Cristian's

External Synchronization with Real Time

- Put an atomic clock in each node!!
  - Too costly
  - Most often the accuracy is not needed, so the cost is not worth it
- Put a GPS receiver at each node
  - Still costly
  - GPS does not work well indoor
- Can use a Cristian-like algorithm with a time server sync'ed to real time
  - Not scalable for internet-scale synchronization
- Solution: Use a hierarchical approach

NTP : Network Time Protocol

- Protocol for time synchronization in the internet
- Hierarchical architecture
  - Stratum 0: reference clocks (atomic clocks or receivers for time broadcast by national time standards or satellites, ex. GPS)
  - Stratum 1: primary servers with reference clocks
    - Most accurate
  - Stratum 2, 3,… servers synchronize to primary servers in a hierarchical manner (stratum 2 servers sync. with stratum 1, stratum 3 with stratum 2 etc.)
    - Lower stratum no. means more accurate
    - More servers at higher stratum no.

- Different communication modes
  - Multicast (usually within LAN servers)
    - One or more servers periodically multicasts their time to other servers
  - Symmetric (usually within multiple geographically close servers)
    - Two servers directly exchange timing information
  - Client server (to higher stratum servers)
    - Cristian-like algorithm
- Communicates over UDP
- Reliability ensured by synchronizing with redundant servers
- Accuracy ensured by combining and filtering multiple time values from multiple servers
- Sync. possible to within tens of milliseconds for most machines
  - But just a best-effort service, no guarantees

Logical Clocks and Event Ordering

Ordering Events

- Given two events in a distributed system (at same or different nodes), can we say if one happened before another or not?
  - Common requirement, for example, in applying updates to replicas in a replicated system
- Physical clocks can be used with synchronization in many cases
- Fails to order when events happen too fast
- Are physical clocks needed at all for ordering events?

Causality and Ordering

- Can what happened in one event at one node affect what happens in another event in the same or another node?
  - Because if not, ordering them is not important
- Can we capture this notion of **causality** between events and build a local clock around it?
  - Use the causality to synchronize the local clocks
  - No relation to time synchronization as we have seen so far, no real notion of time

Lamport's Ordering

Lamport's ***Happened Before*** relationship:

- For two events x and y, x $\rightarrow$ y (x *happened before* y) if
  - x and y are events in the same process and x occurred before y
  - x is a send event of a message m and y is the corresponding receive event at the destination process
  - x $\rightarrow$ z and z $\rightarrow$ y for some event z

- $x \longrightarrow y$ implies x is a *potential* cause of y
  - x can affect y
  - Does not mean that x must affect y, just that it can
  - But y cannot affect x (i.e. y cannot be a potential cause of x)
- Causal ordering : *potential* dependencies
- "Happened Before" relationship causally orders events
  - If $x \longrightarrow y$, then x causally affects y
  - If $x \not\rightarrow y$ and $y \not\rightarrow x$, then x and y are concurrent ($x \mid\mid y$)

Lamport's Logical Clock

- Each process i keeps a clock C_i
- Each event x in i is timestamped C(x), the value of C_i when x occurred
- C_i is incremented by 1 for each event in i
- In addition, if x is a send of message m from process i to j, then on receive of m,

$$C_j = \max(C_j + 1, C(x)+1)$$

- Increment amount can be any positive number (not necessarily 1)

Some Observations

- If $x \rightarrow y$, then $C(x) < C(y)$
- Total ordering possible by arbitrarily ordering concurrent events by process numbers (assuming process numbers are unique)
- Frequent communication between nodes brings their logical clocks closer (sync'ed)
- Infrequent communication between nodes may make their logical clocks very different
  - Not a problem, as less communication means less chance of events at one node affecting events at another node

Using the Clock

- Given two events x and y at processes i and j:
  - Order x before y if
    - $C(x) < C(y)$, or
    - $C(x) = C(y)$ and $i < j$
  - This may order two concurrent events also, but that's fine as then the order does not matter for causality anyway
  - If $x \rightarrow y$, then y will never be ordered before x

Limitation of Lamport's Clock

- $x \rightarrow y$ implies $C(x) < C(y)$
- but $C(x) < C(y)$ doesn't imply $x \rightarrow y$!!

So not a true clock !!

Though not a big limitation in many applications

Solution: Vector Clocks

- C_i is a vector of size n (no. of processes)
- C(a) is similarly a vector of size n
- Update rules:
  - $C_i[i]$++ for every event at process i
  - if x is send of message m from i to j with vector timestamp t_m, on receive of m:

    $C_j[k] = \max(C_j[k], t_m[k])$ for all k

- For events x and y with vector timestamps t_x and t_y,
  - $t_x = t_y$ iff for all i, $t_x[i] = t_y[i]$
  - $t_x \neq t_y$ iff for some i, $t_x[i] \neq t_y[i]$
  - $t_x \leq t_y$ iff for all i, $t_x[i] \leq t_y[i]$
  - $t_x < t_y$ iff ($t_x \leq t_y$ and $t_x \neq t_y$)
  - $t_x \mid\mid t_y$ iff ($t_x \not< t_y$ and $t_y \not< t_x$)

- $x \longrightarrow y$ if and only if $t_x < t_y$

- Events x and y are causally related if and only if $t_x < t_y$ or $t_y < t_x$, else they are concurrent

Application of Vector Clocks: Causal Ordering of Messages

- Different message delivery orderings
  - Atomic: all message are delivered by all recipient nodes in the same order (any order possible, but same)
  - Causal: For any two messages m_1 and m_2, if send(m_1)$\rightarrow$ send(m_2), then every recipient of m_1 and m_2 must deliver m_1 before m_2 (but messages not causally related can be delivered by different nodes in different order)
  - FIFO Order: For any two messages m_1 and m_2 from the same node, if m_1 is sent before m_2, then every recipient of m_1 and m_2 must deliver m_1 before m_2 (but messages from different nodes can be delivered by different nodes in different order)
  - Atomic Causal (Atomic and Causal), Atomic FIFO (Atomic and FIFO)
- "deliver" – when the message is actually given to the application for processing, not when received by the network

Birman-Schiper-Stephenson Protocol for Causal Order Broadcast (CBCAST)

- To broadcast m from process i, increment $C_i[i]$, and timestamp m with $VT_m = C_i$
- When $j \neq i$ receives m, j delays delivery of m until
  - $C_j[i] = VT_m[i] - 1$ and
  - $C_j[k] \geq VT_m[k]$ for all $k \neq i$
  - Delayed messaged are queued in j sorted by vector time. Concurrent messages are sorted by receive time.
- When m is delivered at j, C_j is updated according to vector clock rule

- First condition says that j has delivered all previous broadcasts sent by i before delivering m
  - This is the set of all messages at i that can causally precede m
- Second condition says j has delivered at least as many (may be more) broadcasts sent by k as delivered by i ($k \neq i, j$) when i sent m
  - This is the set of all messages at nodes $\neq$ i that can causally precede m
- So both conditions true means j has delivered all messages that causally precedes m

Problem with Vector Clock

- Message size increases since each message needs to be tagged with the vector
- Size can be reduced in some cases by only sending values that have changed
- Can also send only a scaler to keep track of direct dependencies only, with indirect dependencies computed when needed
  - Tradeoff between message size and time