

CONNECTOR					ETHERNET				MOUNTING				CHASSIS				POSITION B			
DIGIT: 1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21
0	4	2	1	-	-		-	X	-		X	-				-	-	-	-	X

NOTES:

- IF YOU ARE NOT FAMILIAR WITH MASTER CONFIGURABLE DRAWINGS, PLEASE SEE INSTRUCTIONS LOCATED ON THE SEL WEBSITE IN THE DRAWINGS.
- THIS DRAWING IS FOR THE 421, 4U, VERTICAL ONLY.
- USE LAYERS TO UPDATE VIEWS. SOME COMBINATIONS MAY NOT BE AVAILABLE. VERIFY PART NUMBER USING SEL WEBSITE.
- ONLY SELECT ONE OPTION PER SLOT. CHASSIS 4U, FRONT PANEL W/ (24) TARGET LEDS, (12) OPERATOR CONTROL PUSHBUTTONS & TRI-COLOR LEDS and AUXILIARY TRIP/CLOSE PUSHBUTTON (24) OPTOISOLATED LEVEL-SENSITIVE INPUT, (4) HIGH-CURRENT INTERRUPTING FORM A OUTPUTS ARE COMBINED OPTIONS.
- DRAWINGS ARE UPDATED FREQUENTLY. PLEASE USE CURRENT LINK FROM SEL WEBSITE.
- DASHED SLOTS DO NOT AFFECT PRODUCT GRAPHICS AND ARE NOT SHOWN AS CONFIGURABLE OPTIONS.

