

关于 QML、Obigo、SDL

2014/08/05	Init	Kevin Tang
2014/08/05	1. QT5 Fix Compile Error 2. 字体放大到小四	Kevin Tang

一、关于 QML

很不幸，系统安装的 QT4 没有 qmlscene，QT5 才有...

为了使用 QML，我们自行编译 QT 和 Qt Creator

【当然你也可以安装系统的 QT5】

【系统安装的 QT4 和 QT5 貌似有部分冲突（qt4-default 和 qt5-default）】

【QT4（libqt4-XXX）和 QT5（libqt5XXX）的包名还稍微有点差异】

【索性那就手动编译 QT4 和 QT5 吧，也可以当作练习编译】

由于换座位了，所以我的 IP 变更为：172.26.14.181

（也许你可以通过 ping 或者 traceroute 或者 nslookup 查找下 tangwenkai 的最新 IP 地址）

很不幸由于编译了 apr 和 apr-util 导致我的 apache 挂了，暂时没有时间修复，用 nginx 替换，端口改为 8080。

Apache Fixed! 80 端口恢复。

QT 下载地址

<http://172.26.14.181:8080/nfs/Downloads/qt-everywhere-opensource-src-4.8.3.tar.gz>

<http://172.26.14.181:8080/nfs/Downloads/qt-everywhere-opensource-src-5.3.0.tar.gz>

Qt Creator 下载地址

<http://172.26.14.181:8080/nfs/Downloads/qt-creator-2.8.1-src.tar.gz>

<http://172.26.14.181:8080/nfs/Downloads/qt-creator-opensource-src-3.1.2.tar.gz>

1. 编译 Qt4

```
# mkdir -p /opt/qt4.8
# tar -zxvf qt-everywhere-opensource-src-4.8.3.tar.gz -C /opt/qt4.8
# cd /opt/qt4.8/qt-everywhere-opensource-src-4.8.3

# ./configure -developer-build -opensource -no-qt3support -confirm-license #。#

# make -j4 #。#

# DO NOT MAKE INSTALL
# sudo update-alternatives --install /usr/bin/qmake qmake
/opt/qt4.8/qt-everywhere-opensource-src-4.8.3/bin/qmake 30 #。#

# sudo update-alternatives --config qmake

#ERR Basic XLib functionality test failed!
#FIX sudo apt-get install libX11-dev libXext-dev libXtst-dev
```

* 对应目录自行替换

* 编译 QT4 的话问题不大，自行解决

2. 编译 Qt Creator

```
# tar -zxvf qt-creator-2.8.1-src.tar.gz -C /opt/qt4.8
# cd /opt/qt4.8/qt-creator-2.8.1-src
# qmake -r
# make -j4
# DO NOT MAKE INSTALL
```

* make 过程会有点漫长 -j4 会稍微快一点

* `./configure` 不通过的时候可能需要指定一些参数 【TODO】

3. 编译 QT5

* QT5 是刚入职的时候编译的，也遇到过几个小问题，当时没有记录，抱歉

```
# sudo apt-get install "^libxcb.*" libx11-xcb-dev libglu1-mesa-dev libxrender-dev  
libxi-dev #。 #
```

```
# sudo apt-get install libssl-dev  
# mkdir /opt/qt5.3  
# cd /opt/qt5.3/opt/qt5.3/qt-everywhere-opensource-src-5.3.0  
# ./configure -developer-build -opensource -nomake tests -confirm-license
```

* 以下是我的 `configure` 输出，当然不一定完全和你的一样

Configure summary

Build type: linux-g++ (x86_64, CPU features: mmx sse sse2)

Platform notes:

- Also available for Linux: linux-kcc linux-icc linux-cxx

Build options:

Configuration accessibility accessibility-atspi-bridge alsa audio-backend avx c++11
clock-gettime clock-monotonic compile_examples concurrent dbus debug directfb evdev eventfd
fontconfig full-config getaddrinfo getifaddrs glib iconv icu inotify ipv6ifname large-config
largefile libudev linuxfb medium-config minimal-config mmap nis no-harfbuzz openssl pcre
png posix_fallocate precompile_header private_tests pulseaudio qpa qpa reduce_exports
reduce_relocations rpath shared small-config sse2 sse3 sse4_1 sse4_2 sse3 system-freetype
system-jpeg system-png system-zlib warnings_are_errors xcb xcb-glx xcb-plugin xcb-render
xcb-sm xinput2 xkbcommon-qt xlib xrender

Build parts libs tools examples tests

Mode debug

Using C++11 yes

Using PCH yes

Target compiler supports:

SSE2/SSE3/SSSE3 yes/yes/yes

SSE4.1/SSE4.2 yes/yes

AVX/AVX2 yes/no

Qt modules and options:

Qt D-Bus yes (loading dbus-1 at runtime)
Qt Concurrent yes
Qt GUI yes
Qt Widgets yes
Large File yes
QML debugging yes
Use system proxies no

Support enabled for:

Accessibility yes
ALSA yes
CUPS no
Evdev yes
FontConfig yes
FreeType yes (system library)
Glib yes
GTK theme no
HarfBuzz no
Iconv yes
ICU yes

Image formats:

GIF yes (plugin, using bundled copy)
JPEG yes (plugin, using system library)
PNG yes (in QtGui, using system library)

journald no

mtdev no

Networking:

getaddrinfo yes
getifaddrs yes
IPv6 ifname yes
OpenSSL yes (loading libraries at run-time)

NIS yes

OpenGL / OpenVG:

EGL no
OpenGL no
OpenVG no

PCRE yes (bundled copy)

pkg-config yes

PulseAudio yes

QPA backends:

DirectFB yes
EGLFS no
KMS no

```

LinuxFB ..... yes
XCB ..... yes (system library)
  EGL on X ..... no
  GLX ..... yes
  MIT-SHM ..... yes
  Xcb-Xlib ..... no
  Xcursor ..... yes (loaded at runtime)
  Xfixes ..... yes (loaded at runtime)
  Xi ..... no
  Xi2 ..... yes
  Xinerama ..... yes (loaded at runtime)
  Xrandr ..... yes (loaded at runtime)
  Xrender ..... yes
  XKB ..... no
  XShape ..... yes
  XSync ..... yes
  XVideo ..... yes
Session management ..... yes
SQL drivers:
  DB2 ..... no
  InterBase ..... no
  MySQL ..... yes (plugin)
  OCI ..... no
  ODBC ..... no
  PostgreSQL ..... yes (plugin)
  SQLite 2 ..... no
  SQLite ..... yes (plugin, using bundled copy)
  TDS ..... no
udev ..... yes
xkbcommon ..... yes (bundled copy, XKB config root: /usr/share/X11/xkb)
zlib ..... yes (system library)

```

NOTE: libxkbcommon and libxkbcommon-x11 0.4.1 or higher not found on the system, will use the bundled version from 3rd party directory.

Info: creating super cache file /opt/qt5.3/temp/qt-everywhere-opensource-src-5.3.0/.qmake.super

Qt is now configured for building. Just run 'make'.

Once everything is built, Qt is installed.

You should not run 'make install'.

Prior to reconfiguration, make sure you remove any leftovers from the previous build.

make -j4 #。#还是一个漫长的编译

NO_NEED_TO_INSTALL

sudo update-alternatives --install /usr/bin/qmake qmake

/opt/qt5.3//opt/qt5.3/qt-everywhere-opensource-src-5.3.0/qtbase/bin/qmake 40 #。#

```
tangwenkai@tangwenkai:qt-everywhere-opensource-src-5.3.0$ ls qtbase/bin/
assistant      qcollectiongenerator  qml               qmlviewer
designer         qdbus                 qml1plugindump    qt.conf
findtr          qdbuscpp2xml          qmlbundle         qtdiag
fixqt4headers.pl qdbusviewer           qmlimportscanner  qtpaths
lconvert        qdbusxml2cpp          qmljs              rcc
linguist        qdoc                  qmlmin             syncqt.pl
lrelease        qhelpconverter        qmlplugindump      uic
lupdate         qhelpgenerator        qmlprofiler        xmlpatterns
moc             qlalr                  qmlscene           xmlpatternsvalidator
pixeltool       qmake                 qmltestrunner
```

* /opt/qt5.3/qt-everywhere-opensource-src-5.3.0/qtbase/bin 路径稍微有些不同

#ERR Project ERROR: Unknown module(s) in QT: quick-private

#FIX sudo apt-get install flex bison gperf libicu-dev libxslt-dev ruby

#EXT 因为这些库和 32 位 GL 库有冲突导致你们的编译失败

* 这里也有一篇参考文档 http://qt-project.org/wiki/Building_Qt_5_from_Git

4. 编译 Qt Creator3.1.2

编译 Qt Creator 之前需要选择 QT5 的 qmake

* 后续随时关注 qmake 版本以防出错

sudo update-alternatives --config qmake

qmake

make -j4

5. QtCreator 配置

工具->选项->添加 【Qt4 qmke 的路径:

/opt/qt4.8/qt-everywhere-opensource-src-4.8.3/bin】



名称：自定义

Qt 版本：选择刚刚添加的 Qt 版本



然后打开工程->项目->添加构建套件->选择刚刚添加的构建套件

* 添加 Qt 和构建套件以 4.8.3 为例，QT5 和交叉环境的 qmake 也是如此配置

二、关于 Obgio

之前的项目，使用 SPAC 协议？

项目仓库：

```
repo init -u ssh://git@nutshell.suntec.net/nutshell/develop/platform/manifest.git -b  
nutshell/iAuto_For_SPAC
```

代码路径：packages/NativeApp/AV/SPAC*

SDL 分支代码从此拉出，所以这边就可以略过。

三、关于 SDL

新的项目，使用 SDL 协议？（3.7 #。#）

全称：smartdevicelink

源码仓库：git://git.projects.genivi.org/smartdevicelink.git

项目仓库：

```
repo init -u ssh://git@nutshell.suntec.net/nutshell/develop/platform/manifest.git -b  
nutshell/iAuto_For_SDL -m AppFramework.xml
```

环境依赖：cmake3.0 （cmake 至少 2.8.11）

下载地址：官网

（或者 <http://172.26.14.181:8080/nfs/Downloads/cmake-3.0.1.tar.gz>）

编译 cmake：

```
# ./configure  
# make
```



```
# sudo make install
```

如果需要 GUI

```
# ./configure --qt-gui
```

```
# make
```

```
# make install
```

依赖 APR APR-UTIL

<http://172.26.14.181/nfs/Downloads/apr-1.5.1.tar.gz>

<http://172.26.14.181/nfs/Downloads/apr-util-1.5.3.tar.gz>

编译 APR:

```
# cd /opt/temp/apr-1.5.1
```

```
# ./configure
```

```
# make
```

```
# sudo make install
```

* ./configure 没有指定 PREFIX 的默认安装到/usr/local

* 这里 apr 的话默认安装到了/usr/local/apr 下面

编译 APR-UTIL

```
# cd /opt/temp/apr-util-1.5.3
```

```
# ./configure --with-apr=/usr/local/apr --with-ldap --with-crypto
```

* 之前没有指定这两个参数导致 Apache 挂了

```
# make
```

```
# sudo make install
```

* 由于 so 安装到了 /usr/local/apr/bin 下，需要额外指定软连接（当然拷贝也行）

```
# cd /usr/local/lib
```

```
# sudo ln -s ../apr/bin/*.so* .
```

依赖 log4cxx:

<http://172.26.14.181/nfs/Downloads/apache-log4cxx-0.10.0.tar.gz>

```
# tar -zxvf apache-log4cxx-0.10.0.tar.gz -C /opt/temp
```

```
# cd /opt/temp/apache-log4cxx-0.10.0
```

```
# ./configure
# make
# sudo make install
```

SDL 有几种模式 1. WEB 2. QML 3. QNX

编译 SDL:

1. WEB

```
# git checkout dev/merge_3.6
# mkdir build
# cd build
# cmake -DXTENDED_MEDIA_MODE=ON -DHMI2=ON
-DGSTREAMER_gst_INCLUDE_DIR=/opt/obigo/sdl/src/components/media_manag
er
-DGSTREAMER_gstreamer_LIBRARY=/opt/obigo/sdl/src/components/media_mana
ger ..
# make
# make install
```

* 照理-DXTENDED_MEDIA_MODE=ON -DHMI2=ON 是编译 QML 的 #。#

* 由于没有指定 HMI=qt -#。#

* 可能缺少的依赖

```
vi ../src/components/media_manager/CMakeLists.txt
vi ../src/appMain/CMakeLists.txt
48  /usr/include/gstreamer-0.10
49  /usr/include/libxml2
```

```
vi ../src/appMain/CMakeLists.txt
@LINE 49 gstreamer-0.10
```

* 可能缺少的组建

```
# sudo apt-get install libbluetooth-dev
```

2. QML 探索中

```
# cmake 参数 -DHMI=qt
```

#ERR 未找到 QT

#FIX

export CUSTOM_QT_DIR=/opt/qt5.3

#ERR 提示缺少 log4cxx

#FIX

vi ../src/components/qt_hmi/qml_plugins/dbus_adapter/CMakeLists.txt

vi ../src/components/qt_hmi/qml_plugins/log4cxx/CMakeLists.txt

@LINK_DIRECTORIES(/usr/local/lib)

运行

cd /opt/obigo/sdl/build-3.6/bin

./start_hmi.sh

3. QNX 略

暂不需要 QNX 环境

编译 iAuto_For_SDL

参考 NativeApp 编译

* 重点查看 SDL 中 QML 的实现

* 重点查看 iAuto_For_SDL 中 SPAC 相关的实现代码

*** 先自行编译 QT4 和 QT5

*** 二、三章节待完善

*** 写的有点仓促，错误必定很多，待反馈