




11mm Size Metal Shaft Type EC11 Series

Part number		EC11B15202AA
Structure		Horizontal
Actuator configuration		Flat
Actuator length		20mm
Number of detent		30
Number of pulse		15
Push-on switch		Without
Operating life		15,000 cycles
Operating temperature range		-40°C to +85°C
Electrical performance	Ratings	10mA 5V DC
	Output signal	Two phase A and B
	Max./min. operating current(Resistive load)	10mA/1mA
	Insulation resistance	100M Ω min. 250V DC
	Voltage proof	300V AC for 1 minute or 360V AC for 2s
Mechanical performance	Detent torque	12 \pm 7mN·m
	Push-pull strength	100N
Minimum order unit (pcs.)	Japan	700
	Export	1,400


Photo



Dimensions




Mounting Hole Dimensions




Viewed from mounting side.

Output Wave




Sliding Noise



At R=5k Ω Chattering: 2ms max. Bounce: 2ms max.

Attached Parts



Packing Specifications

Tray

Number of packages (pcs.)	1 case / Japan	700
	1 case / export packing	1,400
Export package measurements (mm)		370×520×201

Soldering Conditions

Reference for Dip Soldering

Preheating	Soldering surfacetemperature	100°C max.
	Heating time	2 min. max.
Dip soldering	Soldering temperature	260±5°C
	Soldering time	5±1s
No. of solders		2 time max.

Reference for Hand Soldering


Tip temperature	350°C max.
Soldering time	3s max.
No. of solders	1 time

Product Varieties

Single-shaft Type

1) Knorled Type

Unit : mm


Style (Shaft diameter : $\phi 6$)

● Detailed dimensions

L_1	L_B	l_1	l_2	S_1
20	7	6	1	7
25	10	10	2	11

2) Flat Type

Unit : mm

Style (Shaft diameter : $\phi 6$)

● Detailed dimensions

	L_1	L_B	l
※1	15	5	7
	15	7	5 (6)
	20	7	10 (12)
※2	25	10	12


※ 1 Does not comply with EC111

※ 2 $L_B=7$ for EC11B.

Values in parentheses apply to products without push-on switch.

3) Slotted Type

Unit : mm

Style (Shaft diameter : $\phi 6$)

● Detailed dimensions

	L_1	L_B
	15	7
	20	7
※	25	10

※ $L_B=7$ for EC11B.

Notes are common to this series/models.

1. This site catalog shows only outline specifications. When using the products, please obtain formal specifications for supply.
2. Please place purchase orders per minimum order unit (integer).
3. Products other than those listed in the above chart are also available. Please contact us for details.
4. This products can be used in vehicles.
Although these products are designed to perform over a wide operating temperature range, please ensure that you receive and read the formal delivery specifications before use.