YORK®

INSTALL CONFIDENCE





## CASSETTE 60HZ R-410A INVERTER

# YKJE(12-55)BZT(V)MCMORX

## Indoor Unit

- Auto Random Restart
- 360° Air outlet
- Low noise
- Super slim design
- Build-in Drain pump
- Washable air filter
- Follow me function
- Fresh air intake
- Easy clean design
- Wired controller (Optional)



## Remote Control

- Operation modes: Auto, Cool, Dry, Fan only
- Multi-speed fan setting: High/Medium/Low/Auto
- 24-hour timer setting
- Turbo cool setting
- Background light LCD display





## Condensing Unit

- Compact size
- More sturdy and durable
- High efficiency compressor
- Low noise
- 3-minute protection
- Valve protection
- Easier installation
- Easier maintenance
- Universal design



COOLING ONLY



HEAT PUMP

The YORK® line of cassette Air conditioners includes a wide range of sizes to give you more flexibility in your product offering. Each model is designed to provide comfort and efficiency, in an easy-to-operate unit and the sleek design fits a variety of spaces, whether it's in a home or office. Models meet the highest energy efficiency ratings, so less energy is consumed without sacrificing comfort and performance. Both the condensing and indoor units are engineered for quiet operation. And comfort control settings are easily changed with the touch of a button on the remote control.

## Features and benefits

### Self Diagnosis
Clearly displayed failure codes allow for quicker troubleshooting and easier maintenance.

### 24-Hour Timer
Allows programmed start times up to 24 hours in advance for flexible and more convenient operation.

### Auto Restart
Unit is automatically returned to previous operating conditions after a power outage, for simplified operation.

### 3-Minute Protection
A 3-minute delay before the compressor will restart helps avoid compressor damage and work time.

### Low Ambient Cooling at -15°C
The AC will run in cooling mode when outdoor temperature is below -15°C to meet special user-requested applications.

### Washable Filter
Washable filter allows for convenient service and maintenance.

### Built-in Drain Pump
Built-in drain pump can pump condensation to a high level, which facilitates draining condensation from indoor unit and makes installation easier.

### Compact Design
Smaller dimensions for easy installation, transportation, and reduced cost.

### Multi-Speed Fan
Multi-speed fan helps satisfy various airflow requirements.

### DC Inverter Compressor
DC inverter compressor provides more comfortable indoor environment, higher performance in partial load and better heating performance in low ambient temperature than fixed compressor.



### Inner Groove Copper Tube

Inner groove copper tubing allows more refrigerant to pass through, improving heat exchange by 30 to 50% when compared to traditional copper tubing, and lowering power consumption while keeping output capacity at the same level.

## Specification

| Set model | | | YKJE12BZTMCMORX | YKJE18BZTMCMORX | YKJE24BZTMCMORX |
|---|---|---|---|---|---|
| Outdoor model | | | YUJE12BYTMCMO-X | YUJE18BYTMCMO-X | YUJE24BYTMCMO-X |
| Indoor model | | | YKJE12BXTMCM-RX | YKJE18BXTMCM-RX | YKJE24BXTMCM-RX |
| Power supply (Indoor ) | | V- Ph-Hz | 220-230V,1Ph,60Hz | 220-230V,1Ph,60Hz | 220-230V,1Ph,60Hz |
| Power supply (Outdoor ) | | V- Ph-Hz | 220-230V,1Ph,60Hz | 220-230V,1Ph,60Hz | 220-230V,1Ph,60Hz |
| Cooling | Capacity | W | 3517 | 5275 | 7034 |
| | Input | W | 1256 | 1884 | 2512 |
| | EER | W/W | 2.80 | 2.80 | 2.80 |
| Max. input consumption | | W | 1750 | 3200 | 3450 |
| Max. current | | A | 8.0 | 14 | 15 |
| Indoor fan motor | Qty | | 1 | 1 | 1 |
| | Type | | DC | DC | DC |
| | Input | W | 45.0 | 45.0 | 58.0 |
| | Capacitor | μF | / | / | / |
| | Speed(Hi/Mi/Lo) | r/min | 680/580/500 | 730/630/570 | 600/520/450 |
| Indoor air flow (Hi/Mi/Lo) | | $m^3/h$ | 644/525/443 | 956/825/746 | 1400/1250/1000 |
| Indoor noise level (Hi/Mi/Lo) | | dB(A) | 41/38.5/33.5 | 41/38.5/33.5 | 48.5/46.5/40.5 |
| Indoor unit | Dimension (WxDxH)(body) | mm | 570x570x260 | 570x570x260 | 840x840x205 |
| | Packing (WxDxH)(body) | mm | 662x662x317 | 662x662x317 | 900x900x225 |
| | Dimension (WxDxH)(panel) | mm | 647x647x50 | 647x647x50 | 950x950x55 |
| | Packing (WxDxH)(panel) | mm | 715x715x123 | 715x715x123 | 1035x1035x90 |
| | Net/Gross weight(body) | kg | 16/18.6 | 16.2/21.3 | 21/24.6 |
| Drainage water pipe dia | | mm | OD Φ25 | OD Φ25 | OD Φ32 |
| Qty'per 20' /40' /40'HQ | | Indoor unit | 186/375/429 | 186/375/429 | 148/312/342 |
| Compressor | Type | | ROTARY | ROTARY | ROTARY |
| | Capacity | W | 2958 | 4055 | 7135 |
| | Input | W | 730 | 1035 | 1970 |
| | Rated current(RLA) | A | 5.08 | 7.32 | 6.95 |
| | Thermal protector position | | NA | NA | NA |
| | Refrigerant oil/oil charge | ml | VG74/340 | VG74/450 | VG74/670 |
| Outdoor fan motor | Qty | | 1 | 1 | 1 |
| | Type | | DC | DC | DC |
| | Input | W | 63.0 | 115.0 | 150.0 |
| | Capacitor | μF | / | / | / |
| | Speed | r/min | 800 | 850 | 850 |
| Outdoor air flow | | $m^3/h$ | 2000 | 2500 | 3800 |
| Outdoor noise level | | dB(A) | 55 | 57.5 | 58.5 |
| Outdoor unit | Dimension(W*D*H) | mm | 800x333x554 | 845x363x702 | 946x410x810 |
| | Packing (W*D*H) | mm | 920x390x625 | 965x395x775 | 1090x500x885 |
| | Net/Gross weight | Kg | 36.5/39.1 | 47.7/51 | 64/69 |
| Refrigerant type | | Kg | R410A/1.15 | R410A/1.95 | R410A/2.35 |
| Design pressure | | MPa | 4.2/1.5 | 4.2/1.5 | 4.2/1.5 |
| Refrigerant piping | Liquid side/ Gas side | mm(inch) | 6.35mm(1/4in)/12.7mm(/1/2in) | 6.35mm(1/4in)/12.7mm(/1/2in) | 9.52mm(3/8in)/15.9mm(5/8in) |
| | Max. refrigerant pipe length | m | 15 | 25 | 25 |
| | Max. difference in level | m | 8 | 15 | 15 |
| Thermostat type | | | RG94 | RG94 | RG94 |
| Operation temperature | | °C | 17~30 | 17~30 | 17~30 |
| Room temperature | Indoor(cooling/ heating) | °C | 17～32/0～30 | 17～32/0～30 | 17～32/0～30 |
| | Outdoor(cooling/heating) | °C | 0～50/-15～24 | 0～50/-15～24 | 0～50/-15～24 |
| Qty'per 20' /40' /40'HQ | | Outdoor unit | 108/219/292 | 102/215/216 | 44/96/138 |



YORK

## Specification

| Set model | | | YKJE36BZTMCMORX | YKJE48BZTMCMORX | YKJE55BZTMCMORX |
|---|---|---|---|---|---|
| Outdoor model | | | YUJE36BYTMCMO-X | YUJE48BYTMCMO-X | YUJE55BYTMCMO-X |
| Indoor model | | | YKJE36BXTMCM-RX | YKJE48BXTMCM-RX | YKJE55BXTMCM-RX |
| Power supply (Indoor ) | | V- Ph-Hz | 220-230V,1Ph,60Hz | 220-230V,1Ph,60Hz | 220-230V,1Ph,60Hz |
| Power supply (Outdoor ) | | V- Ph-Hz | 220-230V,1Ph,60Hz | 220-230V,1Ph,60Hz | 220-230V,1Ph,60Hz |
| Cooling | Capacity | W | 8756 | 10481 | 11949 |
| | Input | W | 3285 | 3894 | 4553 |
| | EER | W/W | 2.823 | 2.826 | 2.756 |
| Max. input consumption | | W | 5150 | 6900 | 7000 |
| Max. current | | A | 22.5 | 30 | 31.0 |
| Indoor fan motor | Qty | | 1 | 1 | 1 |
| | Type | | AC | AC | AC |
| | Input | W | 242.0 | 242.0 | 242.0 |
| | Capacitor | μF | 4.5 | 4.5 | 4.5 |
| | Speed(Hi/Mi/Lo) | r/min | 715/600/550 | 715/600/550 | 715/600/550 |
| Indoor air flow (Hi/Mi/Lo) | | $m^3/h$ | 1927/1437/1309 | 1847/1355/1242 | 1856/1370/1252 |
| Indoor noise level (Hi/Mi/Lo) | | dB(A) | 57/49/47 | 55/49/47.5 | 53.5/49/47 |
| Indoor unit | Dimension (WxDxH)(body) | mm | 840x840x245 | 840x840x287 | 840x840x287 |
| | Packing (WxDxH)(body) | mm | 900x900x265 | 900x900x307 | 900x900x307 |
| | Dimension (WxDxH)(panel) | mm | 950x950x55 | 950x950x55 | 950x950x55 |
| | Packing (WxDxH)(panel) | mm | 1035x1035x90 | 1035x1035x90 | 1035x1035x90 |
| | Net/Gross weight(body) | kg | 25.7/30.8 | 30/35.3 | 30.1/35.4 |
| Drainage water pipe dia | | mm | OD Φ32mm | OD Φ32mm | OD Φ32mm |
| Qty'per 20' /40' /40'HQ | | Indoor unit | 128/268/294 | 100/212/238 | 100/212/238 |
| Compressor | Type | | ROTARY | ROTARY | ROTARY |
| | Capacity | W | 8095 | 13700 | 13700 |
| | Input | W | 2200 | 3700 | 3700 |
| | Rated current(RLA) | A | 10 | 7.02 | 7.02 |
| | Thermal protector position | | EXTERNAL | EXTERNAL | EXTERNAL |
| | Refrigerant oil/oil charge | ml | VG74/670 | VG74/1400 | VG74/1400 |
| Outdoor fan motor | Qty | | 1 | 2 | 2 |
| | Type | | DC | AC | AC |
| | Input | W | 150.0 | 143.0 | 143.0 |
| | Capacitor | μF | / | 5 | 5 |
| | Speed | r/min | 1050 | 860 | 860 |
| Outdoor air flow | | $m^3/h$ | 5100 | 7500 | 7200 |
| Outdoor noise level | | dB(A) | 67 | 63 | 64 |
| Outdoor unit | Dimension(W*D*H) | mm | 946x410x810 | 952x415x1333 | 952x415x1333 |
| | Packing (W*D*H) | mm | 1090x500x885 | 1095x495x1480 | 1095x495x1480 |
| | Net/Gross weight | Kg | 65/70 | 95.3/108.1 | 100/113 |
| Refrigerant type | | Kg | R410A/2.8 | R410A/4 | R410A/4.3 |
| Design pressure | | MPa | 4.2/1.5 | 4.2/1.5 | 4.2/1.5 |
| Refrigerant piping | Liquid side/ Gas side | mm(inch) | 9.52mm(3/8in)/19mm(3/4in) | 9.52mm(3/8in)/19mm(3/4in) | 9.52mm(3/8in)/19mm(3/4in) |
| | Max. refrigerant pipe length | m | 30 | 50 | 50 |
| | Max. difference in level | m | 20 | 30 | 30 |
| Thermostat type | | | RG94 | RG94 | RG94 |
| Operation temperature | | °C | 17~30 | 17~30 | 17~30 |
| Room temperature | Indoor(cooling/ heating) | °C | 17～32/0～30 | 17～32/0～30 | 17～32/0～30 |
| | Outdoor(cooling/heating) | °C | 0～50/-15～24 | 0～50/-15～24 | 0～50/-15～24 |
| Qty'per 20' /40' /40'HQ | | Outdoor unit | 44/96/138 | 22/48/48 | 22/48/48 |

## Specification

| Set model | | | YKJE36BZVMCMORX | YKJE55BZVMCMORX |
|---|---|---|---|---|
| Outdoor model | | | YUJE36BYVMCMO-X | YUJE55BYVMCMO-X |
| Indoor model | | | YKJE36BXTMCM-RX | YKJE55BXTMCM-RX |
| Power supply (Indoor ) | | V- Ph-Hz | 220-230V,1Ph,60Hz | 220-230V,1Ph,60Hz |
| Power supply (Outdoor ) | | V- Ph-Hz | 220V,3Ph,60Hz | 220-230V,3Ph,60Hz |
| Cooling | Capacity | W | 9426 | 13124 |
| | Input | W | 3593 | 4999 |
| | EER | W/W | 2.755 | 2.771 |
| Max. input consumption | | W | 5150 | 7000 |
| Max. current | | A | 13.5 | 20.5 |
| Indoor fan motor | Qty | | 1 | 1 |
| | Type | | AC | AC |
| | Input | W | 242.0 | 242.0 |
| | Capacitor | μF | 4.5 | 4.5 |
| | Speed(Hi/Mi/Lo) | r/min | 715/600/550 | 715/600/550 |
| Indoor air flow (Hi/Mi/Lo) | | $m^3/h$ | 1927/1437/1309 | 1856/1370/1252 |
| Indoor noise level (Hi/Mi/Lo) | | dB(A) | 56/49/47 | 53.5/49/47 |
| Indoor unit | Dimension (WxDxH)(body) | mm | 840x840x245 | 840x840x287 |
| | Packing (WxDxH)(body) | mm | 900x900x265 | 900x900x307 |
| | Dimension (WxDxH)(panel) | mm | 950x950x55 | 950x950x55 |
| | Packing (WxDxH)(panel) | mm | 1035x1035x90 | 1035x1035x90 |
| | Net/Gross weight(body) | kg | 25.7/30.8 | 30.1/35.4 |
| Drainage water pipe dia | | mm | OD Φ 32mm | OD Φ 32mm |
| Qty'per 20' /40' /40'HQ | | Indoor unit | 128/268/294 | 100/212/238 |
| Compressor | Type | | ROTARY | ROTARY |
| | Capacity | W | 8095 | 13700 |
| | Input | W | 2200 | 3700 |
| | Rated current(RLA) | A | 10 | 7.02 |
| | Thermal protector position | | EXTERNAL | EXTERNAL |
| | Refrigerant oil/oil charge | ml | VG74/670 | VG74/1400 |
| Outdoor fan motor | Qty | | 1 | 2 |
| | Type | | DC | AC |
| | Input | W | 150.0 | 143.0 |
| | Capacitor | μF | / | 5 |
| | Speed | r/min | 1050 | 860 |
| Outdoor air flow | | $m^3/h$ | 5100 | 7200 |
| Outdoor noise level | | dB(A) | 64 | 64 |
| Outdoor unit | Dimension(W*D*H) | mm | 946x410x810 | 952x415x1333 |
| | Packing (W*D*H) | mm | 1090x500x885 | 1095x495x1480 |
| | Net/Gross weight | Kg | 66.8/71.5 | 102.6/115.3 |
| Refrigerant type | | Kg | R410A/2.8 | R410A/4.3 |
| Design pressure | | MPa | 4.2/1.5 | 4.2/1.5 |
| Refrigerant piping | Liquid side/ Gas side | mm(inch) | 9.52mm(3/8in)/19mm(3/4in) | 9.52mm(3/8in)/19mm(3/4in) |
| | Max. refrigerant pipe length | m | 30 | 50 |
| | Max. difference in level | m | 20 | 30 |
| Thermostat type | | | RG94 | RG94 |
| Operation temperature | | °C | 17~30 | 17~30 |
| Room temperature | Indoor(cooling/ heating) | °C | 17~32/0~30 | 17~32/0~30 |
| | Outdoor(cooling/heating) | °C | 0~50/-15~24 | 0~50/-15~24 |
| Qty'per 20' /40' /40'HQ | | Outdoor unit | 44/96/138 | 22/48/48 |

Nominal testing conditions:
Cooling - Indoor 80.6°F DB / 66.2°F WB (27°C DB / 19°C WB) & Outdoor 95°F DB / 75.2°F WB (35°C DB / 24°C WB)
Heating - Indoor 68°F DB / 59°F WB (20°C DB / 15°C WB) & Outdoor 44.6°F DB / 42.8°F WB (7°C DB / 6°C WB)

YORK®

INSTALL CONFIDENCE

Johnson Controls, the Johnson Controls logo, YORK are registered trademarks of Johnson Controls, Inc in the United States of America and other countries. Other trademarks used herein may be trademarks or registered trademarks of other companies.

**FOR MORE INFORMATION CONTACT JOHNSONCONTROLS.COM**

© 2019 Johnson Controls, Inc, P.O. Box 423, Milwaukee, WI 53201, All rights reserved worldwide.

SKJEBZTMC-190723(COLUMBIA)