

Lecture 10 File Processing

Objectives

- To understand how to format strings
- To understand the basic text file processing concepts in Python.
- To learn how to read and write text files in Python and string formatting

Revision

```
intlist = []
for i in range(6) :
    if i % 2 == 0 :
        intlist.append(i)
    else:
        intlist[-1] += 1
print(intlist)
```

What is printed when the code is executed

String Formatting

```
>>> amount = 1.50
>>> print(amount)
1.5
```

- If the code about is meant to represent an amount in dollars and cents, we conventionally do not use fractional dollars but rather dollars with 2 digits for cents
- Use the format method

```
>>> print("${0:0.2f} change".format(amount))
$1.50 change
```

• The first part is the string to be printed, called the template string. The part between {} is the format specifier (where the value is to be inserted and how it should look).

String Formatting

```
"${0:0.2f} change".format(amount)
```

- The template contains a single specifier slot with the description: 0:0.2f
- Form of description:<index>:<format-specifier>
- Index tells which parameter to insert into the slot (there can be more than one). In this case, amount (numbered from 0!)

String Formatting

Looking at 0.2f

- The formatting specifier has the form: <width>.<micli><type>
- f means "fixed point" number
- <width> tells us how many spaces to use to display the value. 0 means to use as much space as necessary.
- cision> is the number of decimal places.

```
>>> "Compare {0} and {0:0.20f}".format(3.14)
'Compare 3.14 and 3.140000000000001243'
```

String Formatting Example

```
# Print out a child's multiplication table 0..10
def multiplication table() :
  for i in range (11):
       for j in range(11):
           print("\{0:0d\} x \{1:0d\} = \{2:0d\}".format(i, j, i*j))
      print()
  >>> %Run multiplication table.py
                                             A basic child's
    0 \times 0 = 0
    0 \times 1 = 0
                                             multiplication table to
     0 \times 2 = 0
                                             illustrate string
     0 \times 3 = 0
     0 \times 4 = 0
                                             formatting.
     0 \times 5 = 0
    0 \times 6 = 0
    0 \times 7 = 0
     0 \times 8 = 0
                                             Needs modification to
    0 \times 9 = 0
     0 \times 10 = 0
                                             properly resemble table,
                                             e.g. numbers along top
     1 \times 0 = 0
     1 \times 1 = 1
                                             and down left hand side
     1 \times 2 = 2
     1 \times 3 = 3
```

Multiline Strings

- You sometimes need strings that span more than one line. Two ways to do this:
- Embedded '\n' in single string
 - "Twas brillig, and the slithy toves \n Did gyre and gimble in the wabe \n All mimsy were the borogoves \n And the mome raths outgrabe."

Multiline string:

```
"""Beware the Jabberwock, my son!
The jaws that bite, the claws that catch!
Beware the Jubjub bird, and shun
The frumious Bandersnatch!"""
```

- """ also available
- "hello\tworld"
- '\t' is the tab character

Files: Multi-line Strings

- A file is a sequence of data that is stored in secondary memory (disk drive).
 - Files don't disappear when program ends
- Files can contain any data type, but the easiest to work with are text.
- A file usually contains more than one line of text.
- Python uses the standard newline character (\n) to mark line breaks.

- The process of *opening* a file involves associating a file on disk with variable in memory.
- We can manipulate the file by manipulating this variable.
 - Read from the file
 - Write to the file

- When you've finished working with the file, it needs to be closed.
 - Closing the file causes any outstanding operations and other bookkeeping for the file to be completed.
- In some cases, not properly closing a file could result in data loss.
 - Think of safely ejecting your memory stick

File Processing - Reading

- Reading a file into a program, e.g. word processor
 - File opened
 - Contents read into RAM
 - File closed
 - Changes to the file are made to the copy stored in memory, not on the disk.

File Processing - Writing

- Saving a file, i.e. data in RAM onto file
 - The original file on the disk is reopened in a mode that will allow writing (this actually erases the old contents unless specifically appending)
 - File writing operations copy the version of the document in memory to the disk
 - The file is closed

File Processing in Python

- Working with text files in Python
 - Associate a disk file with a file object using the open function

```
<filevar> = open (<name>, <mode>)
```

- <name> is a string with the actual file name on the disk. The <mode> is either `r' or `w' depending on whether we are reading or writing the file.
- infile = open("numbers.dat", "r")

File Methods

- <file>.read() returns the entire remaining contents of the file as a single (possibly large, multiline) string. Watch out for final \n
- <file>.readline() returns the next line of the file. This is all text up to *and including* the next newline character
- <file>.readlines() returns a list of the remaining lines in the file. Each list item is a single line including the newline characters.

```
# printfile.py
# Prints a file to the screen.

def main():
    fname = input("Enter filename: ")
    infile = open(fname, 'r')
    data = infile.read()
    infile.close()
    print(data)
```

- First, prompt the user for a file name
- Open the file for reading
- The file is read as one string and stored in the variable data

• readline can be used to read the next line from a file, including the trailing newline character

```
infile = open(someFile, "r")
for i in range(5):
   line = infile.readline()
   print(line[:-1])
```

- This reads the first 5 lines of a file
- Slicing is used to strip out the newline characters at the ends of the lines

File Processing Loop

• Python treats the file itself as a sequence of lines!

```
infile = open(someFile, "r")
for line in infile:
    # process the line here
infile.close()
```

- Most efficient way to read through (and process) file
 - Multiple calls to readline() is inefficient

- Opening a file for writing prepares the file to receive data
- If you open an existing file for writing, you wipe out the file's contents. If the named file does not exist, a new one is created.

```
outfile = open("mydata.out", "w")
outlife.write(<string>)
```

May use writelines() for writing sequence (list) of strings

- Batch mode processing is where program input and output are done through files (the program is not designed to be interactive)
 - Real strength of Python of many applications.

 GUI is fine for small number of cases, but need automation for larger number.
- Let's create usernames for a computer system where the first and last names come from an input file.

```
# userfile.py
#
     Program to create a file of usernames in batch mode.
def main():
    print ("This program creates a file of usernames from")
    print ("a file of names.")
    # get the file names
    infileName = input("Which file are the names in? ")
    outfileName = input ("Where should the usernames go? ")
    # open the files
    infile = open(infileName, 'r')
    outfile = open(outfileName, 'w')
```

```
# process each line of the input file
 for line in infile:
     # get the first and last names from line
     first, last = line.split()
     # create a username
     uname = (first[0]+last[:7]).lower()
     # write it to the output file
     outfile.write(uname)
 # close both files
 infile.close()
 outfile.close()
 print ("Usernames written to", outfileName)
```

• Things to note:

- It's not unusual for programs to have multiple files open for reading and writing at the same time. However, if a file is no longer needed, close it as there is a limit to number of open files.
- The lower method is used to convert the names into all lower case, in the event the names are mixed upper and lower case, e.g de Witt.

Summary

- We learned how to format a string for output that is more readable and looks nice
- We learned how to read files
 - All at once
 - Single lines
 - All the lines, line-by-line
- We learned how to write into files