

GRINDING PRODUCTS

ZENESIS™ ZFBS

Finger Bit



APPLICATION SNAPSHOT

The ZENESIS™ 4 AND 7 SEGMENT FINGER BITS provide top CNC performance on all stone

materials. They deliver precise, quiet and chip-free cutting at faster speeds and can be used

on soft to medium-hard materials (4 segments) or medium to hard materials (7 segments).

The enhanced design utilizes our most advanced diamond pattern to date, which increases

durability and prevents premature wear to ensure long tool life.

CONFIGURATIONS & TECHNICAL DETAILS

1/2" gas thread	Cuts granite and engineered stone (without the full stop)
Recommended RPM ranges from 4,200 in hard material to 5,500 in	softer material with a feed rate of 12"~16" per minute
Wet use only	Part No. Description
ZFBS02040A4 20mm x 1-5/8" x 1/2" Gas, 4 seg (40L-7W-3.5T)	ZFBS02250A4 22mm x 2" x 1/2" Gas, 4 seg (50L-7W-3.5T)
ZFBS02040A7 20mm x 1-5/8" x 1/2" Gas, 7 seg (40L-3W-4.0T)	ZFBS02250A7 22mm x 2" x 1/2" Gas, 7 seg (50L-7W-4.0T)
FINGER BITS	Granite
Engineered Stone	4 Seg 7 Seg

MATCH IT TO THE JOB

For the right bond and configuration, have the saw, material, aggregate hardness, cut depth, wet/dry requirement, and daily production target ready.

Technical data reformatted for Titan Diamond USA from the OEM product sheet. Verify availability and current specifications with Titan before ordering.