

POLISHING PRODUCTS

ASFM

Snail Lock Pad



APPLICATION SNAPSHOT

5" and 6" snail lock backed pads for ■at polishing of engineered and natural stone on automated polishing machines.

Soft bond requires minimum pressure to achieve perfect shine.

White resin will not bleed or stain stone.

Polishes all engineered stones in a single pass, light or dark.

CONFIGURATIONS & TECHNICAL DETAILS

Unique resin pattern evenly distributes water to prevent burning.	Extra thick pad gives very long life.
Available in 50, 100, 200, 400, 800, 1500 and 3000 grit.	SIZE GRIT PART NUMBER
5" 50 Grit ASFM050050S	5" 100 Grit ASFM050100S
5" 200 Grit ASFM050200S	5" 400 Grit ASFM050400S
5" 800 Grit ASFM050800S	5" 1500 Grit ASFM051500S
5" 3000 Grit ASFM053000S	6" 50 Grit ASFM060050S
6" 100 Grit ASFM060100S	6" 200 Grit ASFM060200S
6" 400 Grit ASFM060400S	6" 800 Grit ASFM060800S
6" 1500 Grit ASFM061500S	6" 3000 Grit ASFM063000S
INTRODUCING	

MATCH IT TO THE JOB

For the right bond and configuration, have the saw, material, aggregate hardness, cut depth, wet/dry requirement, and daily production target ready.

Technical data reformatted for Titan Diamond USA from the OEM product sheet. Verify availability and current specifications with Titan before ordering.