

Matter Surfaces Technical Data

Slip Not 2000 Tile

I. Product Description

Material	100% solution-dyed UV stabilized polypropylene fibers
Backing	Bitumen
Tile Size	19-11/16" x 19-11/16" (50 cm x 50 cm) - approximately 2.7 sq ft per tile
Case Pack	12 tiles per case - 32.4 sq ft per case

II. Technical Specifications

	Test	Requirement	Slip Not 2000 Tile
Product Dimensions			
Pile height	ISO 1776	In inches	3/16"
Total height	ISO 1776	In inches	1/2"
Pile weight	ISO 8543	In ounces per square yard	54.56 oz/sq yd
Total weight	ISO 8543	In ounces per square yard	152.18 oz/sq yd
Safety			
Surface flammability	ASTM D2859 CPSC FF 1-70	Test specimen must be greater than 1" in at least 7 of 8 specimens tested	Passes
III. Performance			
Static electrical propensity	EN 1815	Antistatic: less than 2 kilovolts (kV)	< 2 kV
Static coefficient of friction	ASTM C1028	Slip coefficient: OSHA min. 0.5; ADA (guideline) min. 0.6	Wet: 0.6; dry: 0.61
Color Fastness			
To light	ISO 105 B02	1 = considerable change; 6 = negligible or no change	5

To water	ISO 105 E01	1 = considerable change; 6 = negligible or no change	5
To shampoo	BS 1006	1 = considerable change; 6 = negligible or no change	5
To rubbing wet and dry	ISO 105 x 12	1 = considerable change; 6 = negligible or no change	Wet: 4; Dry: 4
IV. LEED			
IEQ Credit 4.1	LEED-NC v. 4	For 1 point: low-emitting adhesive with a VOC of 50 g/L or less for indoor carpet adhesive	MI 1000 VOC: 0 g/L
IEQ Credit 4.3	LEED-NC v.	For 1 point: low-emitting flooring per GreenLabelPlus or FloorScore™	GreenLabelPlus certified
IEQ Credit 5	LEED-NC v. 4	For 1 point: semi-permanently installed entrance system at least ten feet in length and maintained on a weekly basis by a contracted service organization	Slip Not 2000 Tile is designed for semi-permanent installation.