




3. Network Services Involved in the Deployment of a Web Application

Miquel Àngel París i Peñaranda

Web Application Deployment

2nd C-VET Web Application Development



Index

DNS Practice	3
--------------	---

DNS Practice

Environment we will simulate:

The enterprise Equipamientos Industriales Homero S.A. (EIHSA) has acquired a .com domain and has commissioned you to install and configure the primary and secondary servers of the domain authority.

For the simulation, use the following relationship between machine names and IPs:

Name	IP	Description
router	192.168.x.1	Gateway
NS1	NS1 virtual Machine IP	Name Server 1 (Primary DNS Server)
NS2	NS2 virtual Machine IP	Name Server 2 (Secondary DNS Server)
www	192.168.x.252	Web server
FTP	192.168.x.252	FTP server (located on the same www machine) alias
mail	192.168.x.251	Mail Server
management	192.168.x.2	Management computer
Inf	192.168.x.3	Computer IT department

A. Installation planning

A.1. With the DIA or similar software, you make a physical and logical diagram of the network where the different equipment and devices are shown, as well as their IPs and DNS names.

Insert physical/logical schematic of the network.

A.2. Indicate which registers will be required to configure the direct resolution zone and the values of the configuration parameters for each register.

Indicate the required registers and the value of the different configuration parameters


A.3. Indicate which registers will be required to configure the reverse resolution zone and the values of the configuration parameters for each register.

Indicate the required registers and the value of the different configuration parameters

B. DNS Server Installation and Forwarder Operation

B.1. Assign a static network configuration to the NS1 server according to the IP that corresponds to your virtual machine

Insert screenshot

A screenshot of a terminal window with a dark background. The title bar at the top shows 'GNU nano 6.2' on the left and '00-installer-config.yaml *' on the right. The terminal content shows a YAML configuration for a network interface. It starts with a comment line '# This is the network config written by 'subiquity'', followed by the 'network:' key. Under 'network:', there is an 'ethernets:' key. Under 'ethernets:', there are two entries: 'enp0s3' and 'enp0s8'. 'enp0s3' has 'dhcp4: true'. 'enp0s8' has 'addresses: [192.168.18.254/24]', 'gateway4: 192.168.18.1', and 'nameservers:'. Under 'nameservers:', there is a 'search: [eihsa]' and 'addresses: [192.168.18.254]'. The file ends with 'version: 2'.

```
GNU nano 6.2                                00-installer-config.yaml *
# This is the network config written by 'subiquity'
network:
  ethernets:
    enp0s3:
      dhcp4: true
    enp0s8:
      addresses: [192.168.18.254/24]
      gateway4: 192.168.18.1
      nameservers:
        search: [eihsa]
        addresses: [192.168.18.254]
  version: 2
```

B.2. Install the bind9 DNS server software.

Insert screenshot and answer, if applicable, the question

Unit 3. Network Services Involved in the Deployment of a Web Application

```
root@server:/etc/netplan# dpkg -l | grep bind9
ii bind9 1:9.18.28-0ubuntu0.22.04.1 amd64 Internet Domain Name Ser
ii bind9-dnsutils 1:9.18.28-0ubuntu0.22.04.1 amd64 Clients provided with B
ii bind9-doc 1:9.18.28-0ubuntu0.22.04.1 all Documentation for BIND 9
ii bind9-host 1:9.18.28-0ubuntu0.22.04.1 amd64 DNS Lookup Utility
ii bind9-libs:amd64 1:9.18.28-0ubuntu0.22.04.1 amd64 Shared Libraries used by
ii bind9-utils 1:9.18.28-0ubuntu0.22.04.1 amd64 Utilities for BIND 9
ii dnsutils 1:9.18.28-0ubuntu0.22.04.1 all Transitional package for
nsutils
root@server:/etc/netplan# systemctl status bind9.service
• named.service - BIND Domain Name Server
  Loaded: loaded (/lib/systemd/system/named.service; enabled; vendor preset: enabled)
  Active: active (running) since Mon 2024-09-23 13:51:36 UTC; 42min ago
    Docs: man:named(8)
  Main PID: 1745 (named)
    Tasks: 5 (limit: 2204)
  Memory: 5.6M
    CPU: 163ms
  CGroup: /system.slice/named.service
          └─1745 /usr/sbin/named -u bind

Sep 23 13:51:36 server named[1745]: FORMERR resolving './NS/IN': 202.12.27.33#53
Sep 23 13:51:36 server named[1745]: resolver priming query complete: failure
Sep 23 14:28:23 server named[1745]: no longer listening on 10.0.2.15#53
Sep 23 14:28:23 server named[1745]: no longer listening on 192.168.18.254#53
Sep 23 14:28:23 server named[1745]: listening on IPv4 interface enp0s3, 10.0.2.15#53
Sep 23 14:28:23 server named[1745]: listening on IPv4 interface enp0s8, 192.168.18.254#53
Sep 23 14:28:23 server named[1745]: no longer listening on 192.168.18.254#53
Sep 23 14:28:23 server named[1745]: no longer listening on 10.0.2.15#53
Sep 23 14:28:23 server named[1745]: listening on IPv4 interface enp0s8, 192.168.18.254#53
Sep 23 14:28:23 server named[1745]: listening on IPv4 interface enp0s3, 10.0.2.15#53
root@server:/etc/netplan# _
```

B.3. Show the contents of the configuration file `/etc/bind/named.conf`. What is the use of the include directive? What files are included?

Insert screenshot and answer the questions

```
GNU nano 6.2 named.conf
// This is the primary configuration file for the BIND DNS server named.
//
// Please read /usr/share/doc/bind9/README.Debian.gz for information on the
// structure of BIND configuration files in Debian, *BEFORE* you customize
// this configuration file.
//
// If you are just adding zones, please do that in /etc/bind/named.conf.local

include "/etc/bind/named.conf.options";
include "/etc/bind/named.conf.local";
include "/etc/bind/named.conf.default-zones";
```

B.4. Look for which file, within the configuration directory `/etc/bind/` you find the IP addresses of the root servers and show their content.

Insert screenshot

```
GNU nano 6.2                                named.conf.default-zones
// prime the server with knowledge of the root servers
zone "." {
    type hint;
    file "/usr/share/dns/root.hints";
};

// be authoritative for the localhost forward and reverse zones, and for
// broadcast zones as per RFC 1912

zone "localhost" {
    type master;
    file "/etc/bind/db.local";
};

zone "127.in-addr.arpa" {
    type master;
    file "/etc/bind/db.127";
};

zone "0.in-addr.arpa" {
    type master;
    file "/etc/bind/db.0";
};

zone "255.in-addr.arpa" {
    type master;
    file "/etc/bind/db.255";
};
```

B.5. Configure forwarders to the `named.conf.options` file.

Insert screenshot

```
GNU nano 6.2                                named.conf.options
options {
    directory "/var/cache/bind";

    // If there is a firewall between you and nameservers you want
    // to talk to, you may need to fix the firewall to allow multiple
    // ports to talk.  See http://www.kb.cert.org/vuls/id/800113

    // If your ISP provided one or more IP addresses for stable
    // nameservers, you probably want to use them as forwarders.
    // Uncomment the following block, and insert the addresses replacing
    // the all-0's placeholder.

    forwarders {
        8.8.8.8;
    };

    //=====
    // If BIND logs error messages about the root key being expired,
    // you will need to update your keys.  See https://www.isc.org/bind-keys
    //=====
    dnssec-validation auto;

    listen-on-v6 { any; };
};
```

B.6. Configure your server and a client so that they have the DNS server you are configuring. Check the result of the `resolve status` command to check the configuration of the Name Resolution System (DNS).

Insert screenshot

```
root@user-virtualbox:/etc/netplan# resolvectl status
Global
    Protocols: -LLMNR -mDNS -DNSOverTLS DNSSEC=no/unsupported
resolv.conf mode: stub

Link 2 (enp0s3)
    Current Scopes: DNS
        Protocols: +DefaultRoute +LLMNR -mDNS -DNSOverTLS
                  DNSSEC=no/unsupported
Current DNS Server: 192.168.18.254
    DNS Servers: 192.168.18.254
    DNS Domain: eihsa
root@user-virtualbox:/etc/netplan#
```

B.7. Install the `dnsutils` package and check that your server performs the catching correctly by testing `dig`, `nslookup` and `host` requests

Insert screenshot

```
root@server:/etc# dig eihsa

; <>> DiG 9.18.28-0ubuntu0.22.04.1-Ubuntu <>> eihsa
;; global options: +cmd
;; Got answer:
;; ->>HEADER<<- opcode: QUERY, status: NOERROR, id: 63038
;; flags: qr aa rd ra ad; QUERY: 1, ANSWER: 1, AUTHORITY: 0, ADDITIONAL: 1

;; OPT PSEUDOSECTION:
; EDNS: version: 0, flags:; udp: 65494
;; QUESTION SECTION:
;eihsa.                IN      A

;; ANSWER SECTION:
eihsa.                0      IN      A      192.168.18.254

;; Query time: 0 msec
;; SERVER: 127.0.0.53#53(127.0.0.53) (UDP)
;; WHEN: Wed Sep 25 15:26:08 UTC 2024
;; MSG SIZE rcvd: 50

root@server:/etc# nslookup eihsa
Server:          127.0.0.53
Address:         127.0.0.53#53


Name:   eihsa
Address: 192.168.18.254

root@server:/etc# host eihsa
eihsa has address 192.168.18.254
Host eihsa not found: 3(NXDOMAIN)
root@server:/etc# _
```


C. Direct Zone Configuration

C.1. Create a new direct zone for the domain *eihsa.com* to the `/etc/bind/named.conf.local` file. The file where the database of the zone will be saved will be the `/etc/bind/db.eihsa.com`

Insert screenshot




```
GNU nano 6.2                                named.conf.local
//
// Do any local configuration here
//
// Consider adding the 1918 zones here, if they are not used in your
// organization
//include "/etc/bind/zones.rfc1918";

zone "eihsa.com" {
    type master;
    file "/etc/bind/db.eihsa.com";
    allow-query{ any; };
    allow-transfer { none; };
};
```

C.2. Create a new file called `/etc/bind/db.eihsa.com` and configure it taking into account the requirements of the statement for the direct zone.

Insert screenshot



```
root@server:/etc/bind# systemctl restart bind9
Job for named.service failed because the control process exited with error code.
See "systemctl status named.service" and "journalctl -xeu named.service" for details.
root@server:/etc/bind#
```

C.3. Restart the service with the `$ sudo systemctl restart bind9.service` command for the changes to take effect.

Insert screenshot

```
GNU nano 6.2 db.eihsa.com
;
; BIND data file for broadcast zone
;
$TTL      604800
@         IN      SOA      eihsa. root.eihsa. (
                        2      ; Serial
                        604800 ; Refresh
                        86400  ; Retry
                        2419200 ; Expire
                        604800 ) ; Negative Cache TTL
;
@         IN      NS       ns1.eihsa.
@         IN      NS       ns2.eihsa.
ns1       IN      A        192.168.18.254
ns2       IN      A        192.168.18.253
www       IN      A        192.168.18.252
ftp       IN      A        192.168.18.252
mail      IN      MX       10      mail.eihsa.com
mail.eihsa.com IN      A        192.168.18.251
management IN      A        192.168.18.2
inf       IN      A        192.168.18.3
```

C.4. Check, using the `named-checkzone` command, that the syntax of the `/etc/bind/db.eihsa.com` file is correct. You can use the `$ man named-checkzone` command to check how the order works. If you have any syntax errors, correct them until the zone is correctly configured. Don't forget to restart the service and update the serial of the SOA record. Insert screenshot

```
root@server:/etc/bind# named-checkzone eihsa.com /etc/bind/db.eihsa.com
zone eihsa.com/IN: loaded serial 2
OK
root@server:/etc/bind# _
```

C.5. Using the `nslookup`, `dig` and `host` commands, verify that your DNS server has the direct zone correctly configured.

Insert screenshot

```
root@server:/etc/bind# nslookup eihsa
Server:      127.0.0.53
Address:     127.0.0.53#53

Name:   eihsa
Address: 192.168.18.254

root@server:/etc/bind# dig eihsa

; <>> DiG 9.18.28-0ubuntu0.22.04.1-Ubuntu <>> eihsa
;; global options: +cmd
;; Got answer:
;; ->>HEADER<<- opcode: QUERY, status: NOERROR, id: 50258
;; flags: qr aa rd ra ad; QUERY: 1, ANSWER: 1, AUTHORITY: 0, ADDITIONAL: 1

;; OPT PSEUDOSECTION:
; EDNS: version: 0, flags:; udp: 65494
;; QUESTION SECTION:
;eihsa.                IN      A

;; ANSWER SECTION:
eihsa.                  0       IN      A      192.168.18.254

;; Query time: 0 msec
;; SERVER: 127.0.0.53#53(127.0.0.53) (UDP)
;; WHEN: Wed Sep 25 17:01:00 UTC 2024
;; MSG SIZE rcvd: 50

root@server:/etc/bind# host eihsa
eihsa has address 192.168.18.254
Host eihsa not found: 3(NXDOMAIN)
root@server:/etc/bind#
```

D. Reverse Zone Configuration

D.1. Create a new reverse zone for the domain *eihsa.com* to the `/etc/bind/named.conf.local` file. The file where the database of the zone will be saved will be the `/etc/bind/db.x.168.192.in-addr.arpa`.

Insert screenshot

```
GNU nano 6.2                                named.conf.local
//
// Do any local configuration here
//
// Consider adding the 1918 zones here, if they are not used in your
// organization
//include "/etc/bind/zones.rfc1918";

zone "eihsa.com" {
    type master;
    file "/etc/bind/db.eihsa.com";
    allow-query{ any; };
    allow-transfer { none; };
};

zone "18.168.192.in-addr.arpa"{
    type master;
    file "/etc/bind/db.18.168.192.in-addr.arpa";
    allow-query{ any;};
    allow-transfer{ none; };
}
```

D.2. Create a new file called `/etc/bind/db.x.168.192.in-addr.arpa`. Set it up with the requirements of the statement for the inverse zone in mind.

Insert screenshot

Unit 3. Network Services Involved in the Deployment of a Web Application

```
GNU nano 6.2 db.18.168.192.in-addr.arpa
;
; BIND reverse data file for broadcast zone
;
$TTL      604800
@         IN      SOA      eihsa. root.eihsa. (
                        1      ; Serial
                        604800  ; Refresh
                        86400   ; Retry
                        2419200 ; Expire
                        604800 ) ; Negative Cache TTL
;
@         IN      NS       ns1.eihsa.
@         IN      NS       ns2.eihsa.
254       IN      PTR      ns1.eihsa.
253       IN      PTR      ns2.eihsa.
252       IN      PTR      www.eihsa
252       IN      PTR      ftp.eihsa
251       IN      PTR      mail.eihsa.
2         IN      PTR      managment.eihsa.
3         IN      PTR      inf.eihsa.
```

D.3. Restart the service with the `$ sudo systemctl restart bind9` command for the changes to take effect. Insert screenshot

```
root@server:/etc/bind# systemctl status bind9
● named.service - BIND Domain Name Server
   Loaded: loaded (/lib/systemd/system/named.service; enabled; vendor preset: enabled)
   Active: active (running) since Mon 2024-09-30 14:19:51 UTC; 44s ago
     Docs: man:named(8)
  Process: 567 ExecStart=/usr/sbin/named $OPTIONS (code=exited, status=0/SUCCESS)
    Main PID: 635 (named)
      Tasks: 5 (limit: 2204)
     Memory: 13.3M
        CPU: 172ms
    CGroup: /system.slice/named.service
            └─635 /usr/sbin/named -u bind

Sep 30 14:20:16 server named[635]: network unreachable resolving 'api.snapcraft.io/AAAA/IN': 2801:1b8:10::b#53
Sep 30 14:20:17 server named[635]: network unreachable resolving 'api.snapcraft.io/A/IN': 2001:7fd::1#53
Sep 30 14:20:17 server named[635]: network unreachable resolving 'api.snapcraft.io/AAAA/IN': 2001:7fd::1#53
Sep 30 14:20:19 server named[635]: network unreachable resolving './NS/IN': 2001:500:12::d0d#53
Sep 30 14:20:19 server named[635]: network unreachable resolving './NS/IN': 2001:500:1::53#53
Sep 30 14:20:20 server named[635]: network unreachable resolving 'api.snapcraft.io/A/IN': 2001:500:12::d0d#53
Sep 30 14:20:20 server named[635]: network unreachable resolving 'api.snapcraft.io/AAAA/IN': 2001:500:12::d0d#53
Sep 30 14:20:20 server named[635]: network unreachable resolving 'api.snapcraft.io/A/IN': 2001:500:1::53#53
Sep 30 14:20:20 server named[635]: network unreachable resolving 'api.snapcraft.io/AAAA/IN': 2001:500:1::53#53
Sep 30 14:20:23 server named[635]: resolver priming query complete: timed out
root@server:/etc/bind# _
```

D.4. Check, using the `named-checkzone` command, that the syntax of the `/etc/bind/db.x.168.192.in-addr.arpa` file is correct. You can use the `$ man named-checkzone` command to check how the order works. If you have any syntax errors, correct them until the zone is correctly configured. Don't forget to restart the service and update the serial of the SOA record. Insert screenshot

```
root@server:/etc/bind# named-checkzone 192.168.18.254 db.18.168.192.in-addr.arpa
zone 192.168.18.254/IN: loaded serial 1
OK
root@server:/etc/bind# _
```

D.5. Using the `nslookup`, `dig` and `host` commands, verify that your DNS server has the reverse zone correctly configured. Insert screenshot

```
root@server:/etc/bind# nslookup 192.168.18.254
254.18.168.192.in-addr.arpa      name = eihsa.

root@server:/etc/bind# dig -x 192.168.18.254

; <<> DiG 9.18.28-0ubuntu0.22.04.1-Ubuntu <<> -x 192.168.18.254
;; global options: +cmd
;; Got answer:
;; ->>HEADER<<- opcode: QUERY, status: NOERROR, id: 56952
;; flags: qr aa rd ra ad; QUERY: 1, ANSWER: 1, AUTHORITY: 0, ADDITIONAL: 1

;; OPT PSEUDOSECTION:
; EDNS: version: 0, flags:; udp: 65494
;; QUESTION SECTION:
;254.18.168.192.in-addr.arpa.    IN      PTR


;; ANSWER SECTION:
254.18.168.192.in-addr.arpa. 0 IN      PTR      eihsa.

;; Query time: 0 msec
;; SERVER: 127.0.0.53#53(127.0.0.53) (UDP)
;; WHEN: Mon Sep 30 14:22:34 UTC 2024
;; MSG SIZE rcvd: 75

root@server:/etc/bind# host 192.168.18.254
254.18.168.192.in-addr.arpa domain name pointer eihsa.
root@server:/etc/bind#
```

E. Secondary Server Configuration

E.1. Allow the primary server to transfer the zone to the secondary server. Add the corresponding configuration options to the `/etc/bind/named.conf.local` file on the primary server. Don't forget to restart the service for the changes to take effect. Insert screenshot



```
GNU nano 6.2                                named.conf.local
//
// Do any local configuration here
//
// Consider adding the 1918 zones here, if they are not used in your
// organization
//include "/etc/bind/zones.rfc1918";

zone "eihsa.com" {
    type master;
    file "/etc/bind/db.eihsa.com";
    allow-transfer { 192.168.18.253; };
};

zone "18.168.192.in-addr.arpa" {
    type master;
    file "/etc/bind/db.18.168.192.in-addr.arpa";
    allow-transfer { 192.168.18.253; };
};
```

E.2. Configure the `/etc/bind/named.conf.local` file of the secondary server to connect to the primary server and perform the corresponding zone transfer. You need to edit the `/etc/bind/named.conf.local` file. Don't forget to restart the service for the changes to take effect.

Insert screenshot

```
GNU nano 6.2                                named.conf.local
//
// Do any local configuration here
//
// Consider adding the 1918 zones here, if they are not used in your
// organization
//include "/etc/bind/zones.rfc1918";

zone "eihsa.com" {
    type slave;
    file "/var/cache/bind/db.eihsa.com";
    masters { 192.168.18.254; };
};

zone "18.168.192.in-addr.arpa"{
    type slave;
    file "/var/cache/bind/db.18.168.192.in-addr.arpa";
    masters { 192.168.18.254; };
};
```

E.3. Check the `/var/log/syslog` file, both on the primary and secondary servers, that the transfer has been carried out correctly.

Insert screenshots

- primary

```
root@server:/var/log/journal# ls
4d4f462bfe4048c5abfb3747f0445687
root@server:/var/log/journal# cd 4d4f462bfe4048c5abfb3747f0445687/
root@server:/var/log/journal/4d4f462bfe4048c5abfb3747f0445687# ls
system.journal
system@000622f2d6500680-487c1f322d6f6d55.journal~
system@000622f2db8005f9-26d57cedbf3613bc.journal~
system@000623569c085ae2-e52a6fcf08bbd4f9.journal~
system@00062356a89e3249-ff6f79c401b31dd5.journal~
system@00062356e47cd1fd-f77877508d2bd740.journal~
system@00062357ad0b2939-9df0b19a33ce0129.journal~
system@000623679d5348b2-8c946bc2a979a543.journal~
system@00062367d7cfefc5-28ab8bf7c300574e.journal~
system@0006236a92438626-cddce6e1d67c5e93.journal~
system@0006237022f1bfca-e09d1b44b50ca2d2.journal~
system@000623813db8d1d0-a2cae7e617c953ba.journal~
user-1000.journal
user-1000@000622f2ddd09708-ea543751e63960ea.journal~
user-1000@00062356aa857ea9-986f159bf5236b1f.journal~
user-1000@00062356e6b5eb63-25c40b2dcc43f040.journal~
user-1000@0006236a94a98300-dd71beb0fc3d87cc.journal~
user-1000@0006238140ddad77-5c54adcde80e42d1.journal~
root@server:/var/log/journal/4d4f462bfe4048c5abfb3747f0445687# _
```

- secondary


```
root@user2:/home/user2# cd /var/log/journal/
root@user2:/var/log/journal# ls
fc01dc0397fd4e079e2ee52319d9d866
root@user2:/var/log/journal# cd fc01dc0397fd4e079e2ee52319d9d866/
root@user2:/var/log/journal/fc01dc0397fd4e079e2ee52319d9d866# ls
system.journal
system@00062367a9053e35-bc621afb6e8d1a3e.journal~
system@00062367d1009067-93f2474be5632f49.journal~
system@0006236a92ab989d-fb5b9479e91036ce.journal~
system@00062370282f4924-e78ad8eea2802293.journal~
system@000623813db91e49-19283382643d843c.journal~
user-1000.journal
user-1000@0006236a973eae3e-5a7d271d65a6447f.journal~
user-1000@00062381553cdb6c-779d2bfaaf65405d.journal~
root@user2:/var/log/journal/fc01dc0397fd4e079e2ee52319d9d866# _
```

E.4. A zone transfer is performed only if the serial number of the primary server is larger than the serial number of the secondary server. Add the also-notify directive to the /etc/bind/named.conf.local configuration file on the primary server to notify the secondary server of the changes made. Insert screenshot

```
GNU nano 6.2                                named.conf.local
//
// Do any local configuration here
//
// Consider adding the 1918 zones here, if they are not used in your
// organization
//include "/etc/bind/zones.rfc1918";

zone "eihsa.com" {
    type master;
    file "/etc/bind/db.eihsa.com";
    allow-transfer { 192.168.18.253; };
    also-notify { 192.168.18.253; };
};

zone "18.168.192.in-addr.arpa" {
    type master;
    file "/etc/bind/db.18.168.192.in-addr.arpa";
    allow-transfer { 192.168.18.253; };
    also-notify { 192.168.18.253; };
};
```

E.5. Access the files contained in the `/var/cache/bind` folder of the secondary server. What content is saved to this folder? Insert screenshot and answer the question

```
root@user2:/var/cache/bind# ls
db.18.168.192.in-addr.arpa db.eihsa.com managed-keys.bind managed-keys.bind.jnl
```

E.6. Configure a DNS client to connect to the secondary DNS server. Using the `nslookup`, `dig` and `host` commands, verify that your DNS server is correctly configured. Based on the results obtained, indicate whether the responses obtained from the secondary DNS server are authoritative or non-authoritative.

Insert screenshot and answer the question

```
root@user-virtualbox:/etc/netplan# nslookup www.eihsa.com 192.168.18.254
Server:          192.168.18.254
Address:         192.168.18.254#53

Name:   www.eihsa.com
Address: 192.168.18.252

root@user-virtualbox:/etc/netplan# nslookup www.eihsa.com 192.168.18.253
Server:          192.168.18.253
Address:         192.168.18.253#53

Name:   www.eihsa.com
Address: 192.168.18.252

root@user-virtualbox:/etc/netplan# host www.eihsa.com 192.168.18.253
Using domain server:
Name: 192.168.18.253
Address: 192.168.18.253#53
Aliases:

www.eihsa.com has address 192.168.18.252
root@user-virtualbox:/etc/netplan# host www.eihsa.com 192.168.18.254
Using domain server:
Name: 192.168.18.254
Address: 192.168.18.254#53
Aliases:

www.eihsa.com has address 192.168.18.252
root@user-virtualbox:/etc/netplan# █
```

```
root@user-virtualbox:/etc/netplan# dig @192.168.18.254 www.eihsa.com

; <=> DiG 9.18.28-0ubuntu0.22.04.1-Ubuntu <=> @192.168.18.254 www.eihsa.com
; (1 server found)
;; global options: +cmd
;; Got answer:
;; ->>HEADER<<- opcode: QUERY, status: NOERROR, id: 35147
;; flags: qr aa rd ra; QUERY: 1, ANSWER: 1, AUTHORITY: 0, ADDITIONAL: 1
;; OPT PSEUDOSECTION:
; EDNS: version: 0, flags:; udp: 1232
; COOKIE: af531704967f55dd0100000066fdb41ab0ebb3b67cbf87d8 (good)
;; QUESTION SECTION:
;www.eihsa.com.                IN      A
;; ANSWER SECTION:
www.eihsa.com.                604800  IN      A      192.168.18.252
;; Query time: 3 msec
;; SERVER: 192.168.18.254#53(192.168.18.254) (UDP)
;; WHEN: Wed Oct 02 22:59:21 CEST 2024
;; MSG SIZE rcvd: 86

root@user-virtualbox:/etc/netplan# dig @192.168.18.253 www.eihsa.com

; <=> DiG 9.18.28-0ubuntu0.22.04.1-Ubuntu <=> @192.168.18.253 www.eihsa.com
; (1 server found)
;; global options: +cmd
;; Got answer:
;; ->>HEADER<<- opcode: QUERY, status: NOERROR, id: 27103
;; flags: qr aa rd ra; QUERY: 1, ANSWER: 1, AUTHORITY: 0, ADDITIONAL: 1
;; OPT PSEUDOSECTION:
; EDNS: version: 0, flags:; udp: 1232
; COOKIE: d456f445134666e50100000066fdb41d64c964ec641aede7 (good)
;; QUESTION SECTION:
;www.eihsa.com.                IN      A
;; ANSWER SECTION:
www.eihsa.com.                604800  IN      A      192.168.18.252
;; Query time: 4 msec
;; SERVER: 192.168.18.253#53(192.168.18.253) (UDP)
;; WHEN: Wed Oct 02 22:59:24 CEST 2024
;; MSG SIZE rcvd: 86

root@user-virtualbox:/etc/netplan#
```