
Learning to parse developer documentation

Anonymous Author(s)

Affiliation

Address

email

Abstract

Semantic information plays a key role in the code search and synthesis settings. In this work, we propose a regular expression synthesizer for parsing source code and API documentation which incorporates semantic and relational information the surrounding context. We apply our synthesizer to a link prediction task on a corpus of Java code and developer docs, and demonstrate the effectiveness of model-based representation learning for link prediction in the source-to-source and doc-to-doc setting.

1 Introduction

In addition to its syntax, source code contains a rich denotational and operational semantics [Henkel et al., 2018]. To effectively reason about code in semantically similar but syntactically diverse settings requires models which incorporate features from the call graph [Gu et al., 2016, Liu et al., 2019] and surrounding typing context [Allamanis et al., 2017]. Many semantic features, such as data and control flow [Si et al., 2018] can be represented by a directed acyclic graph (DAG), which admits linear-time solutions to many graph problems, including topological sorting, single-source shortest path and reachability queries.

The field of natural language has also developed a rich set of graph-based representations, including Reddy et al. [2016]’s and other typed attribute grammars which can be used to reason about syntactic and semantic relations between natural language entities. The pointer network architecture [Vinyals et al., 2015b,a] can be used to construct permutation-invariant semantic relations between entities, and has important applications in dependency parsing [Ma et al., 2018], named-entity recognition [Lample et al., 2016], and other semantic parsing tasks where sequence-based representations fall short. Li et al. [2017] extend pointer networks with a copy-mechanism to handle out-of-vocabulary code tokens.

Prior work has studied dataflow and datatypes in code [Si et al., 2018, Gu et al., 2018, Liu et al., 2019], as well as document hierarchy [Yang et al., 2016] and link-based [Zhang and Chen, 2018] learning representations. Entity linking in doc-to-doc (D2D) and source-to-source (S2S) is a straightforward application of link prediction [Zhang and Chen, 2018] and code embedding [Gu et al., 2018] techniques, but cross-domain transfer remains challenging. Robillard and Chhetri [2015], Robillard et al. [2017] first explore the task of predicting reference API docs from source code using manual annotation. Prior work also studies the association between comments and code entities [Iyer et al., 2018, Panthaplackel et al., 2020] using machine learning, but only within source code.

Maintainers of widely-used software projects often publish web-based developer docs, typically stored in markup languages like HTML or Markdown [Terrasa et al., 2018]. These files contain a collection of natural language sentences, markup, and hyperlinks to other documents and source code entities. Both the document tree and link graph contain important semantic information: the markup describes the text in relation to the other entities in

the document hierarchy [Yang et al., 2016], while the link graph describes the relationship between the parent document and related documents or source code entities. Documents occasionally contain hyperlinks to source code, but source code rarely contains links to developer documents. To compensate for the sparsity of hyperlinks between code and documentation, new techniques are required.

Unlike natural language where polysemy is common [Ganea et al., 2016], named entities in most programming languages are relatively unique, even across unrelated APIs. Given a single token in source code or documentation, a skilled developer can quickly locate the referent, even without prior familiarity with the API in question, by using some contextual cues. For example, we observe the string `AbstractSingletonProxyFactoryBean` has the following properties:

1. The string is camel-case, indicating it refers to an entity in a camel-case language.
2. The string contains the substring `Bean`, a common token in the Java language.
3. The string begins with a capital letter, indicating it refers to a class or interface.

Developers often use a tool called `grep` to locate files, which accepts queries written in the regular expression (regex) language, a domain specific language for string parsing. Skilled `grep` users are able to rapidly construct a regular expression which retrieves the document with high probability whilst omitting irrelevant results. Assuming the aforementioned entity exists on a filesystem, one might simply execute the following command to locate it:

```
$ grep -r --include .java "class AbstractSingletonProxyFactoryBean" .
```

We hypothesize it is possible to construct a short query which uniquely identifies any named entity (assuming it exists) in a corpus of software documents and furthermore, it is possible to learn a program which synthesizes a query retrieving the canonical entity with high probability, given a named entity reference and its surrounding documentation context.

2 Background

Let $\Sigma = \{A, a, \dots, Z, z, 0, 1, \dots, 9, \$, ^\wedge\}$. Our language $J_<$ has the following productions:

$$\langle exp \rangle ::= \langle exp \rangle \langle exp \rangle \mid \langle exp \rangle \mid \langle exp \rangle \mid \alpha \in \Sigma \mid \langle exp \rangle^* \mid \cdot \quad (1)$$

An expression in $J_<$ is a regular expression, reducible to a non-deterministic finite automaton (NFA) using Glushkov’s algorithm [Glushkov, 1961], independently discovered by McNaughton-Yamada-Thompson, as shown in Figure 1. NFA are reducible to both deterministic finite automata (DFA) using the powerset construction [Rabin and Scott, 1959] and regular expressions using Arden’s Lemma [Arden, 1961]. It is also possible to convert regular expressions directly to DFA using the Berry-Sethi Algorithm [Berry and Sethi, 1986].

Formally, an NFA is a 5-tuple $\langle Q, \Sigma, \Delta, q_0, F \rangle$, where Q is a finite set of states, Σ is the alphabet, $\Delta : Q \times (\Sigma \cup \{\epsilon\}) \rightarrow P(Q)$ is the transition function, $q_0 \in Q$ is the initial state and $F \subseteq Q$ are the terminal states. An NFA can be represented as a directed graph whose adjacency matrix is defined by the transition function, with edge labels representing symbols from the alphabet and binary node labels indicating whether the node is a terminal or nonterminal state.

We pose the problem as a few-shot generative modeling task, where the input is a local graph consisting of the query text and graph context, and the output is an adjacency matrix defining the NFA. Our goal is to synthesize an NFA which accepts the target document and no other documents or as few others as possible from the entire corpus.

3 Method

Let \mathcal{D} be a document graph, constructed by semantically parsing the document’s contents, and neighboring documents from the link graph. Let \mathcal{T} be a code token, corresponding to




Figure 1: NFA corresponding to the regular expression $(a(ab)^*)^*(ba)^*$.

82 a node in a document graph \mathcal{D} . Following prior work in few-shot meta-learning on graphs,
 83 we adapt the training procedure suggested by Bose et al. [2019] to pretrain a meta learner
 84 \mathcal{M} on the following objective:

$$\mathcal{L}_G = \mathbb{E}_{q_\phi}[\log p(A^{train}|Z)] - KL[q_\phi(Z|X, A^{train})||p(z)] \quad (2)$$


85 Our synthesizer is trained on a local context, a semantic graph parsed from the parent doc-
 86 ument and neighboring documents from the link graph. Instead of directly performing link
 87 prediction, we train a generative model to output an NFA, which can be directly translated
 88 to a regular expression to select the candidate documents. Using the pretrained embedding,
 89 we then rank each candidate document using the Weisfeiler-Lehman similarity [Shervashidze
 90 et al., 2011], then select a single document to link. We then compare precision and recall
 91 over the meta-test set.

92 4 Dataset

93 Java, one of the most prolific programming languages on GitHub, is a statically typed lan-
 94 guage with a high volume of API documentation. Offering a variety of tools for source
 95 code [Parr, 2013, Hosseini and Brusilovsky, 2013, Kovalenko et al., 2019] and natural lan-
 96 guage [Manning et al., 2014, Grella and Cangialosi, 2018] parsing, it is a convenient language
 97 for both analysis and implementation. Our dataset consists of Java repositories on GitHub,
 98 and their accompanying developer documents. All projects in our dataset have a collection
 99 of source code files and multiple related repositories on GitHub.

100 We construct two datasets consisting of naturally-occurring links between developer docs
 101 and source code, and a surrogate set of links constructed by matching lexical tokens available
 102 in both domains. Our target is recovery of ground truth links in the test set and surrogate
 103 links in the lexical matching graph. We first add weighted edges between code and docs,
 104 then evaluate our approach by predicting synthetic links between tokens contained in code
 105 fragments and markup entities which refer to the selected token. In addition, we evaluate
 106 our approach on both D2D and C2C link retrieval, as well as precision and recall on the
 107 surrogate link relations.

108 Our data consists of two complementary datasets: abstract syntax trees collected from
 109 Java source code and developer documentation. We use the astminer [Kovalenko et al.,
 110 2019] library to parse Java code, jsoup [Hedley, 2009] to parse HTML and Stanford’s
 111 CoreNLP [Manning et al., 2014] library to parse dependency graphs from developer docs.
 112 Consider the following AST, parsed from the Eclipse Collections Java project:



113 The AST depicted above was generated by parsing the following code snippet:

```
public void lastKey_throws() {
    new ImmutableTreeMap<>(new TreeSortedMap<>()).lastKey();
}
```

114

1
2
3

115 Now consider the following dependency graph, taken from a Javadoc in the same project:




Figure 2: This graph was parsed from the following comment: “The advantages to using this container over a `Map<K, Collection<V>>` is that all of the handling of the value collection can be done automatically. It also allows implementations to further specialize in how duplicate values will be handled. Value collections with list semantics would allow duplicate values for a key, while those implementing set semantics would not. The value collections can never be empty.”

116 Our goal is to connect these two graphs using a common model for source code and natural
 117 language. Absent any explicit `@link` or `@see` annotations, in order to relate these two
 118 graphs, we must somehow infer the shared semantic entities, which we can do for a subset
 119 using a simple lexical matching procedure. Inferring semantically relevant links however
 120 requires a more meaningful representation.

121 5 Preliminary Results

122 We compare precision on our benchmark using top-K rank retrieval with respect to various
 123 baselines. For instance, to compute the count-search baseline, we search our corpus for the

124 hyperlink anchor text, and rank the resulting documents by the frequency of the anchor
125 text. Results are shown in Figure 3.




Figure 3: Preliminary results.

126 6 Discussion

127 Preliminary results indicate 40% of all links in our dataset point to the document in which
128 the anchor text occurs most frequently across the corpus, and 93% of all links refer to
129 documents where the ground truth link occurs in the top-10 results ranked by frequency
130 of the anchor text. In future work, we will compare performance against a neural network
131 using a simple word-embedding approach, trained to minimize cosine distance between the
132 source document and target document’s context, using a set of candidate links returned by
133 the count-search baseline. Finally, we will compare our approach against the count-search
134 baseline.

135 In the weeks, we will need to train a synthesizer using a yet-to-be-determined loss function
136 over the regular expression. Prior literature suggests there may be a way to backpropagate
137 through the regular expression synthesizer using the Brzozowski [1964] derivative. Further-
138 more, we will need to construct the semantic graph embedding over the surrounding context.
139 This will require some additional consideration.

References

- Miltiadis Allamanis, Marc Brockschmidt, and Mahmoud Khademi. Learning to represent programs with graphs. *arXiv preprint arXiv:1711.00740*, 2017. URL <https://arxiv.org/pdf/1711.00740.pdf>.
- Dean N Arden. Delayed-logic and finite-state machines. In *2nd Annual Symposium on Switching Circuit Theory and Logical Design (SWCT 1961)*, pages 133–151. IEEE, 1961.
- Gerard Berry and Ravi Sethi. From regular expressions to deterministic automata. *Theoretical computer science*, 48:117–126, 1986. URL <https://core.ac.uk/reader/82374120>.
- Avishek Joey Bose, Ankit Jain, Piero Molino, and William L Hamilton. Meta-graph: Few shot link prediction via meta learning. *arXiv preprint arXiv:1912.09867*, 2019. URL <https://arxiv.org/pdf/1912.09867.pdf>.
- Janusz A Brzozowski. Derivatives of regular expressions. *Journal of the ACM (JACM)*, 11(4):481–494, 1964. URL http://maveric.uwaterloo.ca/reports/1964_JACM_Brzozowski.pdf.
- Octavian-Eugen Ganea, Marina Ganea, Aurelien Lucchi, Carsten Eickhoff, and Thomas Hofmann. Probabilistic bag-of-hyperlinks model for entity linking. In *Proceedings of the 25th International Conference on World Wide Web*, pages 927–938, 2016. URL <https://arxiv.org/pdf/1509.02301.pdf>.
- Victor Mikhaylovich Glushkov. The abstract theory of automata. *Russian Mathematical Surveys*, 16(5):1, 1961.
- Matteo Grella and Simone Cangialosi. Non-projective dependency parsing via latent heads representation LHR. *arXiv preprint arXiv:1802.02116*, 2018. URL <https://arxiv.org/pdf/1802.02116.pdf>.
- Xiaodong Gu, Hongyu Zhang, Dongmei Zhang, and Sunghun Kim. Deep API learning. In *Proceedings of the 2016 24th ACM SIGSOFT International Symposium on Foundations of Software Engineering*, pages 631–642, 2016. URL <https://arxiv.org/pdf/1605.08535.pdf>.
- Xiaodong Gu, Hongyu Zhang, and Sunghun Kim. Deep code search. In *2018 IEEE/ACM 40th International Conference on Software Engineering (ICSE)*, pages 933–944. IEEE, 2018. URL <https://guxd.github.io/papers/deepcs.pdf>.
- Jonathan Hedley. jsoup: Java HTML parser. 2009. URL <https://jsoup.org>.
- Jordan Henkel, Shuvendu K Lahiri, Ben Liblit, and Thomas Reps. Code vectors: Understanding programs through embedded abstracted symbolic traces. In *Proceedings of the 2018 26th ACM Joint Meeting on European Software Engineering Conference and Symposium on the Foundations of Software Engineering*, pages 163–174, 2018. URL <https://arxiv.org/pdf/1803.06686.pdf>.
- Roya Hosseini and Peter Brusilovsky. JavaParser: A fine-grain concept indexing tool for Java problems. In *CEUR Workshop Proceedings*, volume 1009, pages 60–63. University of Pittsburgh, 2013.
- Srinivasan Iyer, Ioannis Konostas, Alvin Cheung, and Luke Zettlemoyer. Mapping language to code in programmatic context. *arXiv preprint arXiv:1808.09588*, 2018. URL <https://arxiv.org/pdf/1808.09588.pdf>.
- Vladimir Kovalenko, Egor Bogomolov, Timofey Bryksin, and Alberto Bacchelli. PathMiner: a library for mining of path-based representations of code. In *Proceedings of the 16th International Conference on Mining Software Repositories*, pages 13–17. IEEE Press, 2019. URL <https://github.com/JetBrains-Research/astminer>.

187 Guillaume Lample, Miguel Ballesteros, Sandeep Subramanian, Kazuya Kawakami, and
188 Chris Dyer. Neural architectures for named entity recognition. *arXiv preprint*
189 *arXiv:1603.01360*, 2016. URL <https://arxiv.org/pdf/1603.01360.pdf>.

190 Jian Li, Yue Wang, Michael R Lyu, and Irwin King. Code completion with neural attention
191 and pointer networks. *arXiv preprint arXiv:1711.09573*, 2017. URL <https://www.ijcai.org/Proceedings/2018/0578.pdf>.

193 Bohong Liu, Tao Wang, Xunhui Zhang, Qiang Fan, Gang Yin, and Jinsheng Deng. A
194 neural-network based code summarization approach by using source code and its call
195 dependencies. In *Proceedings of the 11th Asia-Pacific Symposium on Internetwork, Inter-*
196 *network '19*, New York, NY, USA, 2019. Association for Computing Machinery. ISBN
197 9781450377010. doi: 10.1145/3361242.3362774. URL [https://doi.org/10.1145/](https://doi.org/10.1145/3361242.3362774)
198 [3361242.3362774](https://doi.org/10.1145/3361242.3362774).

199 Xuezhe Ma, Zecong Hu, Jingzhou Liu, Nanyun Peng, Graham Neubig, and Eduard Hovy.
200 Stack-pointer networks for dependency parsing. *arXiv preprint arXiv:1805.01087*, 2018.
201 URL <https://arxiv.org/pdf/1805.01087.pdf>.

202 Christopher D Manning, Mihai Surdeanu, John Bauer, Jenny Rose Finkel, Steven Bethard,
203 and David McClosky. The stanford coreNLP natural language processing toolkit. In
204 *Proceedings of 52nd annual meeting of the association for computational linguistics: sys-*
205 *tem demonstrations*, pages 55–60, 2014. URL [https://nlp.stanford.edu/pubs/](https://nlp.stanford.edu/pubs/StanfordCoreNlp2014.pdf)
206 [StanfordCoreNlp2014.pdf](https://nlp.stanford.edu/pubs/StanfordCoreNlp2014.pdf).

207 Sheena Panthaplackel, Milos Gligoric, Raymond J. Mooney, and Junyi Jessy Li. Associating
208 natural language comment and source code entities. In *AAAI*, 2020. URL [https://](https://arxiv.org/pdf/1912.06728.pdf)
209 arxiv.org/pdf/1912.06728.pdf.

210 Terence Parr. *The definitive ANTLR 4 reference*. Pragmatic Bookshelf, 2013.

211 Michael O Rabin and Dana Scott. Finite automata and their decision problems. *IBM*
212 *journal of research and development*, 3(2):114–125, 1959.

213 Siva Reddy, Oscar Täckström, Michael Collins, Tom Kwiatkowski, Dipanjan Das, Mark
214 Steedman, and Mirella Lapata. Transforming dependency structures to logical forms
215 for semantic parsing. *Transactions of the Association for Computational Linguistics*, 4:
216 127–140, 2016. URL [https://www.mitpressjournals.org/doi/pdf/10.1162/](https://www.mitpressjournals.org/doi/pdf/10.1162/tac1_a_00088)
217 [tac1_a_00088](https://www.mitpressjournals.org/doi/pdf/10.1162/tac1_a_00088).

218 Martin P Robillard and Yam B Chhetri. Recommending reference API documentation. *Em-*
219 *pirical Software Engineering*, 20(6):1558–1586, 2015. URL [https://www.cs.mcgill.](https://www.cs.mcgill.ca/~martin/papers/cr2014a.pdf)
220 [ca/~martin/papers/cr2014a.pdf](https://www.cs.mcgill.ca/~martin/papers/cr2014a.pdf).

221 Martin P Robillard, Andrian Marcus, Christoph Treude, Gabriele Bavota, Oscar Cha-
222 parro, Neil Ernst, Marco Aurélio Gerosa, Michael Godfrey, Michele Lanza, Mario Linares-
223 Vázquez, et al. On-demand developer documentation. In *2017 IEEE International Con-*
224 *ference on Software Maintenance and Evolution (ICSME)*, pages 479–483. IEEE, 2017.

225 Nino Shervashidze, Pascal Schweitzer, Erik Jan van Leeuwen, Kurt Mehlhorn, and
226 Karsten M Borgwardt. Weisfeiler-Lehman graph kernels. *Journal of Machine Learning*
227 *Research*, 12(Sep):2539–2561, 2011.

228 Xujie Si, Hanjun Dai, Mukund Raghothaman, Mayur Naik, and Le Song. Learning
229 loop invariants for program verification. In *Advances in Neural Information Pro-*
230 *cessing Systems*, pages 7751–7762, 2018. URL [https://papers.nips.cc/paper/](https://papers.nips.cc/paper/8001-learning-loop-invariants-for-program-verification.pdf)
231 [8001-learning-loop-invariants-for-program-verification.pdf](https://papers.nips.cc/paper/8001-learning-loop-invariants-for-program-verification.pdf).

232 Alexandre Terrasa, Jean Privat, and Guy Tremblay. Using natural language processing for
233 documentation assist. In *Workshops at the Thirty-Second AAAI Conference on Artificial*
234 *Intelligence*, 2018.

- 235 Oriol Vinyals, Samy Bengio, and Manjunath Kudlur. Order matters: Sequence to sequence
236 for sets. *arXiv preprint arXiv:1511.06391*, 2015a. URL [https://arxiv.org/pdf/](https://arxiv.org/pdf/1511.06391.pdf)
237 [1511.06391.pdf](https://arxiv.org/pdf/1511.06391.pdf).
- 238 Oriol Vinyals, Meire Fortunato, and Navdeep Jaitly. Pointer networks. In *Advances in*
239 *neural information processing systems*, pages 2692–2700, 2015b. URL [https://arxiv.](https://arxiv.org/pdf/1506.03134.pdf)
240 [org/pdf/1506.03134.pdf](https://arxiv.org/pdf/1506.03134.pdf).
- 241 Zichao Yang, Diyi Yang, Chris Dyer, Xiaodong He, Alex Smola, and Eduard Hovy. Hierarchi-
242 cal attention networks for document classification. In *Proceedings of the 2016 conference*
243 *of the North American chapter of the association for computational linguistics: human*
244 *language technologies*, pages 1480–1489, 2016. URL [https://www.cs.cmu.edu/~.](https://www.cs.cmu.edu/~hovy/papers/16HLT-hierarchical-attention-networks.pdf)
245 [/hovy/papers/16HLT-hierarchical-attention-networks.pdf](https://www.cs.cmu.edu/~hovy/papers/16HLT-hierarchical-attention-networks.pdf).
- 246 Muhan Zhang and Yixin Chen. Link prediction based on graph neu-
247 ral networks. In *Advances in Neural Information Processing Systems*,
248 pages 5165–5175, 2018. URL [https://papers.nips.cc/paper/](https://papers.nips.cc/paper/7763-link-prediction-based-on-graph-neural-networks.pdf)
249 [7763-link-prediction-based-on-graph-neural-networks.pdf](https://papers.nips.cc/paper/7763-link-prediction-based-on-graph-neural-networks.pdf).