
rinoh^{type}

Reference Guide

Release 0.5.6

Contents

5	Chapter 1: rinoh
7	Chapter 2: Sphinx Builder
8	Legacy Configuration Variables
11	Chapter 3: Style Sheets
11	Included Style Sheets
11	Default Matcher
18	Element Style Classes
93	Chapter 4: Standard Document Templates
93	Article
94	Book
99	Chapter 5: API Documentation
99	Attribute (<code>rinoh.attribute</code>)
100	Color (<code>rinoh.color</code>)
100	Dimension (<code>rinoh.dimension</code>)
101	Document (<code>rinoh.document</code>)
103	Drawing Primitives (<code>rinoh.draw</code>)
103	Flowable (<code>rinoh.flowable</code>)
106	Fonts and Typefaces (<code>rinoh.font</code>)
108	Images and Figures (<code>rinoh.image</code>)
110	Index (<code>rinoh.index</code>)
110	Language (<code>rinoh.language</code>)
113	Number (<code>rinoh.number</code>)
114	Paper sizes (<code>rinoh.paper</code>)
115	Paragraph (<code>rinoh.paragraph</code>)
119	Cross-References and Fields (<code>rinoh.reference</code>)
125	Structure (<code>rinoh.structure</code>)
145	Strings (<code>rinoh.strings</code>)
145	Style (<code>rinoh.style</code>)
147	Tables (<code>rinoh.table</code>)

151 Templates (`rinoh.template`)

161 **Python Module Index**

163 **Index**

Render a structured document to PDF.

```
usage: rinoh [-h] [-f FORMAT] [-o OPTION=VALUE] [-t NAME or FILENAME]
             [-s NAME or FILENAME] [-O FILENAME or DIRECTORY] [-p PAPER] [-i]
             [--list-templates] [--list-stylesheets] [--list-fonts]
             [FILENAME]
             [--list-formats] [--list-options FRONTEND] [--version]
             [--versions] [--docs]
             [input]
```

input

the document to render

-h, --help

show this help message and exit

-f <format>, --format <format>

the format of the input file (default: autodetect)

-o <option=value>, --option <option=value>

options to be passed to the input file reader

-t <name or filename>, --template <name or filename>

the document template or template configuration file to use (default: article)

-s <name or filename>, --stylesheet <name or filename>

the style sheet used to style the document elements (default: the template's default)

-O <filename or directory>, --output <filename or directory>

write the PDF output to FILENAME or to an existing DIRECTORY with a filename derived from the input filename (default: the current working directory)

-p <paper>, --paper <paper>

the paper size to render to (default: the template's default)

-i, --install-resources

automatically install missing resources (fonts, templates, style sheets) from PyPI

--list-templates

list the installed document templates and exit

--list-stylesheets

list the installed style sheets and exit

--list-fonts <filename>
list the installed fonts or, if FILENAME is given, write a PDF file displaying all the fonts

--list-formats
list the supported input formats and exit

--list-options <frontend>
list the options supported by the given frontend and exit

--version
show program's version number and exit

--versions
list versions of rinohtype and related software (for inclusion in bug reports)

--docs
open the online documentation in the default browser

`rinoh.frontend.sphinx` is a Sphinx extension module. It provides a Sphinx builder with the name *rinoh*. The builder recognizes the following `conf.py` options. Of these, only `rinoh_documents` (or `latex_documents`) is required.

rinoh_documents

Determines which PDF documents to build. Its format is a list of dictionaries, one for each document to be generated. The supported keys for these dictionaries are listed below. Two of them are required:

doc (required)

String that specifies the name of the master document (typically `index`).

target (required)

The name of the target PDF file without the extension.

The following keys allow overriding the content included on the document's title page and page headers/footers (depending on the template and its configuration). The values for text content can be plain text or `StyledText`.

logo (no default)

Path (absolute or relative to the location of the `conf.py` file) to an image file, typically included on the title page.

title (default: "project documentation")

The title of the document.

subtitle (default: "Release release")

Subtitle of the document.

author (default: "author")

The document's author.

date (default: determined from `today` and `today_fmt`)

The document (build) date.

The remaining keys control what is included in the document and the document template (configuration) to use.

toctree_only (default: `False`)

Must be `True` or `False`. If `true`, the document itself is not included in the output, only the documents referenced by it via TOC trees.

domain_indices (default: `True`)

If `true`, generate domain-specific indices in addition to the general index. It is equivalent to the `html_domain_indices` and `latex_domain_indices` configuration variables.

template (default: `Book`)

Determines the template used to render the document. It takes:

- the filename of a template configuration file,
- a `TemplateConfiguration` instance,

- the name of an installed template (see `rinoh --list-templates`), or
- a `DocumentTemplate` subclass

`rinoh_documents` will also accept other keys than those listed above. These items will be available as document metadata and can be used in a custom document template.

Example:

```
rinoh_documents = [
    dict(doc='index', target='manual', toctree_only=False,
         template='manual.rtt', logo='logo.pdf'),
    dict(doc='ref', target='reference', title='Reference Manual',
         template='reference.rtt', stamp='DRAFT'),
]
```

`rinoh_targets`

Limits rendering to the specified set of targets. This variable accepts either a list of strings or a string containing comma-separated values. The target names should match those set in `rinoh_documents`.

To render only the ‘manual’ target, you can set the following in `conf.py`:

```
rinoh_targets = ['manual']
```

The same can be achieved from the command line using the by using the string form with `sphinx-build -D`:

```
sphinx-build -b rinoh -D rinoh_targets="manual" source build
```

2.1 Legacy Configuration Variables

The configuration variables below are no longer supported. Instead, their functionality can now be configured per document in `rinoh_documents`.

`rinoh_template`

This configuration variable is **no longer supported** since the document template can be specified in `rinoh_documents` entries.

`rinoh_stylesheet`

This configuration variable is **no longer supported** since it is not obvious which style sheet will be used when the template configuration also specifies a style sheet. Please specify the style sheet to use in your template configuration file:

```
[TEMPLATE_CONFIGURATION]
name = My Book
template = book
stylesheet = my_stylesheet.rts
```

`rinoh_paper_size`

This configuration variable is **no longer supported** since it was not obvious which paper size was being used when the template configuration (`rinoh_template`) also specified a paper size. Please specify the `paper_size` to use in your template configuration file:

```
[TEMPLATE_CONFIGURATION]
name = My Book
template = book

[VARIABLES]
```

```
paper_size = A5
```

rinoh_logo

This configuration variable is **no longer supported** since the logo can be specified in the `rinoh_documents` entries.

rinoh_domain_indices

This configuration variable is **no longer supported** since the `domain_indices` can be specified in the `rinoh_documents` entries.

rinoh_metadata

This configuration variable is **no longer supported**. Metadata entries can now be added to `rinoh_documents` entries.

3.1 Included Style Sheets

These style sheets are included with rinohtype:

`rinohtype.stylesheets.sphinx`

Mostly a copy of the LaTeX style included with Sphinx

Entry point name: `sphinx`

`rinohtype.stylesheets.sphinx_article`

The Sphinx stylesheet adjusted for the article template

Entry point name: `sphinx_article`

`rinohtype.stylesheets.sphinx_base14`

The Sphinx stylesheet, but using the fonts from the PDF core set (yielding smaller PDF files)

Entry point name: `sphinx_base14`

Additional style sheets can be installed from PyPI. The installed style sheets can be listed using `rinohtype --list-stylesheets`.

3.2 Default Matcher

The default matcher provides the selectors for the styles used in the standard style sheets.

`rinohtype.stylesheets.matcher`

The default matcher defines the following styles

- title page rule: `HorizontalRuleStyle`
- title page logo: `FlowableStyle`
- title page title: `ParagraphStyle`
- title page subtitle: `ParagraphStyle`
- title page author: `ParagraphStyle`
- title page date: `ParagraphStyle`
- title page extra: `ParagraphStyle`
- front matter section title: `ParagraphStyle`
- body matter chapter label: `ParagraphStyle`
- body matter chapter number: `TextStyle`
- body matter chapter title: `ParagraphStyle`
- fallback: `TextStyle`
- italic: `TextStyle`

- **bold:** TextStyle
- **monospaced:** TextStyle
- **emphasis:** TextStyle
- **strong:** TextStyle
- **literal emphasis:** TextStyle
- **literal strong:** TextStyle
- **inline equation:** EquationStyle
- **inline definition:** TextStyle
- **quote:** TextStyle
- **file path:** TextStyle
- **keystrokes:** TextStyle
- **regular expression:** TextStyle
- **code with variable:** TextStyle
- **mail header:** TextStyle
- **MIME type:** TextStyle
- **newsgroup:** TextStyle
- **command:** TextStyle
- **make variable:** TextStyle
- **program:** TextStyle
- **man page:** TextStyle
- **window title:** TextStyle
- **UI control:** TextStyle
- **UI control accelerator:** TextStyle
- **menu cascade:** TextStyle
- **draft comment:** TextStyle
- **title reference:** TextStyle
- **error:** TextStyle
- **linked reference:** ReferenceStyle
- **external hyperlink:** TextStyle
- **broken hyperlink:** TextStyle
- **glossary inline definition:** TextStyle
- **body:** ParagraphStyle
- **code block:** ParagraphStyle
- **code block caption:** CaptionStyle
- **graphviz code block:** ParagraphStyle
- **attribution:** ParagraphStyle
- **centered:** ParagraphStyle
- **line block:** ParagraphStyle
- **block quote:** GroupedFlowablesStyle
- **math block:** LabeledFlowableStyle
- **math block paragraph:** ParagraphStyle
- **math block equation:** EquationStyle
- **math block label:** EquationLabelStyle
- **chapter:** SectionStyle
- **content chapter:** SectionStyle
- **heading level 1:** HeadingStyle
- **heading level 1 label:** TextStyle
- **unnumbered heading level 1:** HeadingStyle
- **heading level 2:** HeadingStyle
- **heading level 2 label:** TextStyle
- **unnumbered heading level 2:** HeadingStyle
- **heading level 3:** HeadingStyle
- **heading level 3 label:** TextStyle

- unnumbered heading level 3: HeadingStyle
- heading level 4: HeadingStyle
- heading level 4 label: TextStyle
- unnumbered heading level 4: HeadingStyle
- heading level 5: HeadingStyle
- heading level 5 label: TextStyle
- unnumbered heading level 5: HeadingStyle
- other heading levels: HeadingStyle
- appendix: SectionStyle
- appendix heading level 1: HeadingStyle
- appendix heading level 2: HeadingStyle
- appendix heading level 3: HeadingStyle
- appendix heading level 4: HeadingStyle
- appendix heading level 5: HeadingStyle
- title: ParagraphStyle
- prerequisites: GroupedFlowablesStyle
- prerequisites title: ParagraphStyle
- post requirement: GroupedFlowablesStyle
- abstract: GroupedFlowablesStyle
- abstract paragraph: ParagraphStyle
- example: GroupedFlowablesStyle
- example title: ParagraphStyle
- topic: GroupedFlowablesStyle
- topic title: ParagraphStyle
- rubric: ParagraphStyle
- sidebar: GroupedFlowablesStyle
- sidebar title: ParagraphStyle
- sidebar subtitle: ParagraphStyle
- list item label: ListItemLabelStyle
- list item body: GroupedFlowablesStyle
- list item paragraph: ParagraphStyle
- enumerated list: ListStyle
- enumerated list item: LabeledFlowableStyle
- enumerated list item label: ListItemLabelStyle
- nested enumerated list: ListStyle
- (table) enumerated list: ListStyle
- (table) enumerated list item: LabeledFlowableStyle
- (table) enumerated list item label: ListItemLabelStyle
- bulleted list: ListStyle
- compact bulleted list: ListStyle
- bulleted list item: LabeledFlowableStyle
- bulleted list item label: ListItemLabelStyle
- nested bulleted list: ListStyle
- (table) bulleted list: ListStyle
- (table) bulleted list item: LabeledFlowableStyle
- (table) bulleted list item label: ListItemLabelStyle
- steps list: ListStyle
- steps list title: ParagraphStyle
- steps list item: LabeledFlowableStyle
- steps list item label: ListItemLabelStyle
- unordered steps list: ListStyle
- unordered steps list title: ParagraphStyle
- unordered steps list item: LabeledFlowableStyle

- unordered steps list item label: ListItemLabelStyle
- choices list: ListStyle
- choices list item: LabeledFlowableStyle
- choices list item label: ListItemLabelStyle
- definition list: GroupedFlowablesStyle
- definition list item: LabeledFlowableStyle
- definition term: GroupedFlowablesStyle
- definition term paragraph: ParagraphStyle
- definition term classifier: TextStyle
- definition: GroupedFlowablesStyle
- definition paragraph: ParagraphStyle
- related links: GroupedFlowablesStyle
- related links section title: ParagraphStyle
- related links list: ListStyle
- related links list item: LabeledFlowableStyle
- related links list item label: ListItemLabelStyle
- related links list item paragraph: ReferencingParagraphStyle
- related link title reference: ReferenceStyle
- related link page reference: ReferenceStyle
- related link number reference: ReferenceStyle
- related link reference: ReferenceStyle
- versionmodified: AdmonitionStyle
- versionmodified title: ParagraphStyle
- versionmodified inline title: TextStyle
- versionadded: AdmonitionStyle
- versionadded title: ParagraphStyle
- versionadded inline title: TextStyle
- versionremoved: AdmonitionStyle
- versionremoved title: ParagraphStyle
- versionremoved inline title: TextStyle
- versionchanged: AdmonitionStyle
- versionchanged title: ParagraphStyle
- versionchanged inline title: TextStyle
- deprecated: AdmonitionStyle
- deprecated title: ParagraphStyle
- deprecated inline title: TextStyle
- object description: LabeledFlowableStyle
- object signatures: GroupedFlowablesStyle
- object signature: ParagraphStyle
- object name: TextStyle
- additional name part: TextStyle
- object type: TextStyle
- object returns: TextStyle
- object parentheses: TextStyle
- object parameter list: TextStyle
- object parameter: TextStyle
- object parameter (no emphasis): TextStyle
- object signature space: TextStyle
- object signature name: TextStyle
- object signature operator: TextStyle
- object signature punctuation: TextStyle
- object signature keyword: TextStyle
- object signature keyword type: TextStyle

- object signature literal number: TextStyle
- object signature literal string: TextStyle
- object signature literal char: TextStyle
- object brackets: TextStyle
- object optional parameter: TextStyle
- object annotation: TextStyle
- object description content: GroupedFlowablesStyle
- object description content paragraph: ParagraphStyle
- inline signature: TextStyle
- inline signature texpr: TextStyle
- inline signature space: TextStyle
- inline signature name: TextStyle
- inline signature operator: TextStyle
- inline signature punctuation: TextStyle
- inline signature keyword: TextStyle
- inline signature keyword type: TextStyle
- production list: GroupedFlowablesStyle
- production: LabeledFlowableStyle
- token name: ParagraphStyle
- token definition: ParagraphStyle
- field list: GroupedFlowablesStyle
- field list item: LabeledFlowableStyle
- field name: ParagraphStyle
- option list: GroupedFlowablesStyle
- option list item: LabeledFlowableStyle
- option: ParagraphStyle
- option string: TextStyle
- option argument: TextStyle
- admonition: AdmonitionStyle
- admonition label: FlowableStyle
- admonition content: GroupedFlowablesStyle
- admonition title: ParagraphStyle
- admonition title paragraph: ParagraphStyle
- admonition paragraph: ParagraphStyle
- admonition inline title: TextStyle
- attention admonition: AdmonitionStyle
- attention admonition label: FlowableStyle
- attention admonition content: GroupedFlowablesStyle
- attention admonition title: ParagraphStyle
- attention admonition title paragraph: ParagraphStyle
- attention admonition paragraph: ParagraphStyle
- attention admonition inline title: TextStyle
- caution admonition: AdmonitionStyle
- caution admonition label: FlowableStyle
- caution admonition content: GroupedFlowablesStyle
- caution admonition title: ParagraphStyle
- caution admonition title paragraph: ParagraphStyle
- caution admonition paragraph: ParagraphStyle
- caution admonition inline title: TextStyle
- danger admonition: AdmonitionStyle
- danger admonition label: FlowableStyle
- danger admonition content: GroupedFlowablesStyle
- danger admonition title: ParagraphStyle

- danger admonition title paragraph: ParagraphStyle
- danger admonition paragraph: ParagraphStyle
- danger admonition inline title: TextStyle
- error admonition: AdmonitionStyle
- error admonition label: FlowableStyle
- error admonition content: GroupedFlowablesStyle
- error admonition title: ParagraphStyle
- error admonition title paragraph: ParagraphStyle
- error admonition paragraph: ParagraphStyle
- error admonition inline title: TextStyle
- hint admonition: AdmonitionStyle
- hint admonition label: FlowableStyle
- hint admonition content: GroupedFlowablesStyle
- hint admonition title: ParagraphStyle
- hint admonition title paragraph: ParagraphStyle
- hint admonition paragraph: ParagraphStyle
- hint admonition inline title: TextStyle
- important admonition: AdmonitionStyle
- important admonition label: FlowableStyle
- important admonition content: GroupedFlowablesStyle
- important admonition title: ParagraphStyle
- important admonition title paragraph: ParagraphStyle
- important admonition paragraph: ParagraphStyle
- important admonition inline title: TextStyle
- note admonition: AdmonitionStyle
- note admonition label: FlowableStyle
- note admonition content: GroupedFlowablesStyle
- note admonition title: ParagraphStyle
- note admonition title paragraph: ParagraphStyle
- note admonition paragraph: ParagraphStyle
- note admonition inline title: TextStyle
- tip admonition: AdmonitionStyle
- tip admonition label: FlowableStyle
- tip admonition content: GroupedFlowablesStyle
- tip admonition title: ParagraphStyle
- tip admonition title paragraph: ParagraphStyle
- tip admonition paragraph: ParagraphStyle
- tip admonition inline title: TextStyle
- warning admonition: AdmonitionStyle
- warning admonition label: FlowableStyle
- warning admonition content: GroupedFlowablesStyle
- warning admonition title: ParagraphStyle
- warning admonition title paragraph: ParagraphStyle
- warning admonition paragraph: ParagraphStyle
- warning admonition inline title: TextStyle
- seealso admonition: AdmonitionStyle
- seealso admonition label: FlowableStyle
- seealso admonition content: GroupedFlowablesStyle
- seealso admonition title: ParagraphStyle
- seealso admonition title paragraph: ParagraphStyle
- seealso admonition paragraph: ParagraphStyle
- seealso admonition inline title: TextStyle
- header: ParagraphStyle

- footer: ParagraphStyle
- footnote: NoteStyle
- footnote marker: NoteMarkerStyle
- footnote paragraph: ParagraphStyle
- footnote label: ParagraphStyle
- citation: NoteStyle
- citation marker: NoteMarkerStyle
- citation paragraph: ParagraphStyle
- citation label: ParagraphStyle
- image: FlowableStyle
- inline image: InlineFlowableStyle
- figure: FigureStyle
- figure image: FlowableStyle
- figure caption: CaptionStyle
- figure legend: GroupedFlowablesStyle
- figure legend paragraph: ParagraphStyle
- image alt: ParagraphStyle
- table of contents section: SectionStyle
- table of contents title: HeadingStyle
- table of contents: TableOfContentsStyle
- local table of contents: TableOfContentsStyle
- toc level 1: TableOfContentsEntryStyle
- toc level 2: TableOfContentsEntryStyle
- toc level 3: TableOfContentsEntryStyle
- toc level 4: TableOfContentsEntryStyle
- toc level 5: TableOfContentsEntryStyle
- toc level 6: TableOfContentsEntryStyle
- L3 toc level 3: TableOfContentsEntryStyle
- toc entry number reference field: ReferenceStyle
- list of figures section: SectionStyle
- list of figures: ListOfStyle
- list of figures entry: ListOfEntryStyle
- list of tables section: SectionStyle
- list of tables: ListOfStyle
- list of tables entry: ListOfEntryStyle
- table: TableStyle
- table with caption: TableWithCaptionStyle
- table caption: CaptionStyle
- choices table: TableStyle
- table cell: TableCellStyle
- table body cell background on even row: TableCellBackgroundStyle
- table body cell background on odd row: TableCellBackgroundStyle
- table body cell paragraph: ParagraphStyle
- table first column paragraph: ParagraphStyle
- table body cell list item number: ParagraphStyle
- table head cell: TableCellStyle
- table head cell background: TableCellBackgroundStyle
- table head cell paragraph: ParagraphStyle
- table cell left border: TableCellBorderStyle
- table cell top border: TableCellBorderStyle
- table cell right border: TableCellBorderStyle
- table cell bottom border: TableCellBorderStyle
- table top border: TableCellBorderStyle

- table bottom border: TableCellBorderStyle
- table left border: TableCellBorderStyle
- table right border: TableCellBorderStyle
- table head cell left border: TableCellBorderStyle
- table head cell right border: TableCellBorderStyle
- table head bottom border: TableCellBorderStyle
- table head left border: TableCellBorderStyle
- table head right border: TableCellBorderStyle
- table body top border: TableCellBorderStyle
- table body left border: TableCellBorderStyle
- table body right border: TableCellBorderStyle
- horizontal rule: HorizontalRuleStyle
- index: IndexStyle
- index section label: ParagraphStyle
- level 1 index entry: ParagraphStyle
- level 2 index entry: ParagraphStyle
- level 3 index entry: ParagraphStyle
- level 4 index entry: ParagraphStyle
- domain index entry name: TextStyle

3.3 Element Style Classes

These are the style classes corresponding to each type of document element. For each style class, the supported style attributes are listed along with the values that can be assigned to them in a style sheet.

<code>draw.LineStyle</code>	Style class for Line
<code>draw.ShapeStyle</code>	Style class for Shape
<code>flowable.FlowableStyle</code>	Style class for Flowable
<code>flowable.LabeledFlowableStyle</code>	Style class for LabeledFlowable
<code>flowable.GroupedFlowablesStyle</code>	Style class for GroupedFlowables
<code>flowable.FloatStyle</code>	Style class for Float
<code>image.CaptionStyle</code>	Style class for Caption
<code>image.FigureStyle</code>	Style class for Figure
<code>index.IndexStyle</code>	Style class for Index
<code>paragraph.ParagraphStyle</code>	Style class for Paragraph
<code>text.TextStyle</code>	Style class for Text
<code>inline.InlineFlowableStyle</code>	Style class for InlineFlowable
<code>reference.ReferencingParagraphStyle</code>	Style class for ReferencingParagraph
<code>reference.NoteMarkerStyle</code>	Style class for NoteMarker
<code>structure.SectionStyle</code>	Style class for Section
<code>structure.HeadingStyle</code>	Style class for Heading
<code>structure.ListStyle</code>	Style class for List
<code>structure.ListItemLabelStyle</code>	Style class for ListItemLabel
<code>structure.TableOfContentsStyle</code>	Style class for TableOfContents
<code>structure.TableOfContentsEntryStyle</code>	Style class for TableOfContentsEntry
<code>structure.AdmonitionStyle</code>	Style class for Admonition
<code>structure.HorizontalRuleStyle</code>	Style class for HorizontalRule

<code>table.TableStyle</code>	Style class for <code>Table</code>
<code>table.TableCellStyle</code>	Style class for <code>TableCell</code>
<code>table.TableCellBorderStyle</code>	Style class for <code>TableCellBorder</code>
<code>table.TableCellBackgroundStyle</code>	Style class for <code>TableCellBackground</code>

3.3.1 LineStyle

```
class rinoh.draw.LineStyle ( base=None, **attributes )
    Style class for Line

    stroke
        Width and color used to draw the line
        Accepts Stroke: the width (Dimension) and color (Color) of the stroke, separated by
        a comma (,)
        Default: 1pt, #000

    hide
        Suppress rendering this element (inherited from Style)
        Accepts Bool: true or false
        Default: false
```

3.3.2 ShapeStyle

```
class rinoh.draw.ShapeStyle ( base=None, **attributes )
    Style class for Shape

    fill_color
        Color to fill the shape
        Accepts Color: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA,
        #RGB or #RGBA)
        Default: #e5e5e5

    stroke
        Width and color used to draw the line (inherited from LineStyle)
        Accepts Stroke: the width (Dimension) and color (Color) of the stroke, separated by
        a comma (,)
        Default: 1pt, #000

    hide
        Suppress rendering this element (inherited from Style)
        Accepts Bool: true or false
        Default: false
```

3.3.3 FlowableStyle

```
class rinoh.flowable.FlowableStyle ( base=None, **attributes )
    Style class for Flowable

    width
        Width to render the flowable at
        Accepts FlowableWidth: auto, fill or a numeric value followed by a unit (pt, in,
        pc, mm, cm, %, /2, /4)
```

Default: auto

horizontal_align

Horizontal alignment of the flowable

Accepts `HorizontalAlignment`: left, right, center

Default: left

space_above

Vertical space preceding the flowable

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page

Accepts `Bool`: true or false

Default: false

border

Border surrounding the flowable

Accepts Stroke: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable

Accepts Stroke: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable

Accepts Stroke: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable

Accepts Stroke: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable

Accepts Stroke: the width (*Dimension*) and color (*Color*) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders

Accepts Color: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

page_break

Type of page break to insert before rendering this flowable

Accepts Break: none, any, left, right, any restart, left restart, right restart

Default: None

hide

Suppress rendering this element (inherited from *Style*)

Accepts Bool: true or false

Default: false

3.3.4 LabeledFlowableStyle

```
class rinoh.flowable.LabeledFlowableStyle ( base=None, **attributes )
```

Style class for LabeledFlowable

label

Custom label to override the default

Accepts FlowablesList: Python source code that represents a list of *Flowables*

Default: none

label_position

Where to place the label

Accepts `LabelPosition`: left, right

Default: left

label_min_width

Minimum label width

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 12pt

label_max_width

Maximum label width

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 80pt

label_spacing

Spacing between a label and the labeled flowable

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3pt

align_baselines

Line up the baselines of the label and the labeled flowable

Accepts `Bool`: true or false

Default: true

wrap_label

Wrap the label at *label_max_width*

Accepts `Bool`: true or false

Default: false

width

Width to render the flowable at (inherited from `FlowableStyle`)

Accepts `FlowableWidth`: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: auto

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts `HorizontalAlignment`: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts Bool: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by

a comma (,)
Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)
Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)
Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)
Accepts Color: HEX string with optional alpha component (`#RRGGBB`, `#RRGGBBAA`, `#RGB` or `#RGBA`)
Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)
Accepts Break: none, any, left, right, any restart, left restart, right restart
Default: None

hide

Suppress rendering this element (inherited from `Style`)
Accepts Bool: true or false
Default: false

3.3.5 GroupedFlowablesStyle

```
class rinoh.flowable.GroupedFlowablesStyle ( base=None, **attributes )
```

Style class for `GroupedFlowables`

width

Width to render the flowable at (inherited from `FlowableStyle`)
Accepts FlowableWidth: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: fill (overrides `FlowableStyle` default)

title

Title to precede the flowables
Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

flowable_spacing

Spacing between flowables
Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

same_page

Keep all flowables on a single page, if possible.
Accepts Bool: true or false
Default: false

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts `HorizontalAlignment`: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts `Bool`: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts Color: HEX string with optional alpha component (`#RRGGBB`, `#RRGGBBAA`, `#RGB` or `#RGBA`)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts Break: none, any, left, right, any restart, left restart, right restart

Default: None

hide

Suppress rendering this element (inherited from `Style`)

Accepts Bool: true or false

Default: false

3.3.6 FloatStyle

```
class rinoh.flowable.FloatStyle ( base=None, **attributes )
```

Style class for `Float`

float

Float the flowable to the top or bottom of the current page, to a dedicated page, or side-

ways to a dedicated page
Accepts FloatLocation: none, here, sideways
Default: None

width

Width to render the flowable at (inherited from FlowableStyle)
Accepts FlowableWidth: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: auto

horizontal_align

Horizontal alignment of the flowable (inherited from FlowableStyle)
Accepts HorizontalAlignment: left, right, center
Default: left

space_above

Vertical space preceding the flowable (inherited from FlowableStyle)
Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

space_below

Vertical space following the flowable (inherited from FlowableStyle)
Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

margin_left

Left margin (inherited from FlowableStyle)
Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

margin_right

Right margin (inherited from FlowableStyle)
Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding

Padding (inherited from FlowableStyle)
Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_left

Left padding (inherited from FlowableStyle)
Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_right

Right padding (inherited from FlowableStyle)
Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_top

Top padding (inherited from FlowableStyle)
Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_bottom

Bottom padding (inherited from FlowableStyle)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)
Accepts `Bool`: true or false
Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)
Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)
Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)
Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)
Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)
Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)
Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)
Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)
Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)
Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)
Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)
Accepts `Color`: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)
Accepts `Break`: none, any, left, right, any restart, left restart, right restart
Default: None

hide

Suppress rendering this element (inherited from `Style`)
Accepts `Bool`: true or false
Default: false

3.3.7 CaptionStyle

```
class rinoh.image.CaptionStyle ( base=None, **attributes )
```

Style class for Caption

number_format

How numbers are formatted (inherited from ParagraphStyle)

Accepts NumberFormat: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: number (overrides ParagraphStyle default)

numbering_level

At which section level to restart numbering (positive: absolute, negative: relative) (inherited from ParagraphStyle)

Accepts Integer: a natural number (positive integer)

Default: 1 (overrides ParagraphStyle default)

width

Width to render the flowable at (inherited from ParagraphStyle)

Accepts FlowableWidth: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: fill

indent_first

Indentation of the first line of text (inherited from ParagraphStyle)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0pt

line_spacing

Spacing between the baselines of two successive lines of text (inherited from ParagraphStyle)

Accepts LineSpacing: a predefined line spacing type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: <spacing type>(<arg1>, <arg2>, ...)

Default: default

text_align

Alignment of text to the margins (inherited from ParagraphStyle)

Accepts TextAlign: left, right, center, justify

Default: justify

tab_stops

List of tab positions (inherited from ParagraphStyle)

Accepts TabStopList: a comma-separated list of tab stops. A tab stop is specified as <position> [align] [fill string], where position (Dimension) is required and align (TabAlign) and fill string (string enclosed in quotes) are optional.

Default: (no value)

split_minimum_lines

Minimum number of lines to keep together when splitting a paragraph across pages (inherited from ParagraphStyle)

Accepts Integer: a natural number (positive integer)

Default: (no value)

number_separator

Characters inserted between the number label of this element's parent and this element's own number label. If `None`, only show this item's number label. (inherited from `ParagraphStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: ' . '

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts `HorizontalAlignment`: `left`, `right`, `center`

Default: `left`

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts `Bool`: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts `Color`: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts `Break`: none, any, left, right, any restart, left restart, right restart

Default: None

label_prefix

Text to prepend to the label (inherited from `LabelStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

label_suffix

Text to append to the label (inherited from `LabelStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

custom_label

Use a custom label if specified (inherited from `LabelStyle`)

Accepts `Bool`: true or false

Default: false

typeface

Typeface to set the text in (inherited from `TextStyle`)

Accepts `Typeface`: the name of a typeface. See `rinoh --list-fonts` for a list of the available typefaces.

Default: Times

font_weight

Thickness of character outlines relative to their height (inherited from `TextStyle`)

Accepts `FontWeight`: hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black

Default: 500

font_slant

Slope style of the font (inherited from `TextStyle`)

Accepts `FontSlant`: upright, oblique, italic

Default: upright

font_width

Stretch of the characters (inherited from `TextStyle`)

Accepts `FontWidth`: ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded

Default: 5

font_size

Height of characters (inherited from `TextStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 10pt

font_color

Color of the font (inherited from `TextStyle`)

Accepts `Color`: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: #000

font_variant

Variant of the font (inherited from `TextStyle`)

Accepts `FontVariant`: normal, small capital, oldstyle figures

Default: normal

position

Vertical text position (inherited from `TextStyle`)

Accepts `TextPosition`: normal, superscript, subscript

Default: normal

kerning

Improve inter-letter spacing (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

ligatures

Run letters together where possible (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

character_spacing

Additional spacing between characters (inherited from `TextStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0pt

hyphenate

Allow words to be broken over two lines (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

hyphen_chars

Minimum number of characters in a hyphenated part of a word (inherited from `TextStyle`)

Accepts `Integer`: a natural number (positive integer)

Default: 2

hyphen_lang

Language to use for hyphenation. Accepts locale codes such as 'en_US' (inherited from `TextStyle`)

Accepts `Locale`: locale identifier in the <language ID>_<region ID> format

Default: en_US

no_break_after

Prevent a line break after these words (inherited from `TextStyle`)

Accepts `NoBreakAfter`: language-default, or a space-separated list of words

Default: language-default

before

Item to insert before this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

after

Item to insert after this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

hide

Suppress rendering this element (inherited from `Style`)

Accepts `Bool`: true or false

Default: false

3.3.8 FigureStyle

```
class rinoh.image.FigureStyle ( base=None, **attributes )
```

Style class for Figure

float

Float the flowable to the top or bottom of the current page, to a dedicated page, or sideways to a dedicated page (inherited from `FloatStyle`)

Accepts `FloatLocation`: none, here, sideways

Default: None

width

Width to render the flowable at (inherited from `FlowableStyle`)

Accepts `FlowableWidth`: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: auto

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts `HorizontalAlignment`: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts `Bool`: true or false
Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)
Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)
Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)
Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)
Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)
Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts `Color`: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts Break: none, any, left, right, any restart, left restart, right restart

Default: None

hide

Suppress rendering this element (inherited from `Style`)

Accepts Bool: true or false

Default: false

title

Title to precede the flowables (inherited from `GroupedFlowablesStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

flowable_spacing

Spacing between flowables (inherited from `GroupedFlowablesStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

same_page

Keep all flowables on a single page, if possible. (inherited from `GroupedFlowablesStyle`)

Accepts Bool: true or false

Default: false

3.3.9 IndexStyle

```
class rinoh.index.IndexStyle ( base=None, **attributes )
```

Style class for Index

initials

Group index entries based on their first letter

Accepts Bool: true or false

Default: true

width

Width to render the flowable at (inherited from `GroupedFlowablesStyle`)

Accepts `FlowableWidth`: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: fill

title

Title to precede the flowables (inherited from `GroupedFlowablesStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

flowable_spacing

Spacing between flowables (inherited from `GroupedFlowablesStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

same_page

Keep all flowables on a single page, if possible. (inherited from `GroupedFlowablesStyle`)

Accepts `Bool`: true or false

Default: false

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts `HorizontalAlignment`: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts `Bool`: `true` or `false`

Default: `false`

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: `none`

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: `none`

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: `none`

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: `none`

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: `none`

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts `Color`: HEX string with optional alpha component (`#RRGGBB`, `#RRGGBBAA`, `#RGB` or `#RGBA`)

Default: `none`

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts `Break`: `none`, `any`, `left`, `right`, `any restart`, `left restart`, `right restart`

Default: `None`

hide

Suppress rendering this element (inherited from `Style`)

Accepts `Bool`: `true` or `false`

Default: `false`

3.3.10 ParagraphStyle

```
class rinoh.paragraph.ParagraphStyle ( base=None, **attributes )
```

Style class for Paragraph

width

Width to render the flowable at (inherited from FlowableStyle)

Accepts FlowableWidth: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: fill (overrides FlowableStyle default)

indent_first

Indentation of the first line of text

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0pt

line_spacing

Spacing between the baselines of two successive lines of text

Accepts LineSpacing: a predefined line spacing type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: <spacing type>(<arg1>, <arg2>, ...)

Default: default

text_align

Alignment of text to the margins

Accepts TextAlign: left, right, center, justify

Default: justify

tab_stops

List of tab positions

Accepts TabStopList: a comma-separated list of tab stops. A tab stop is specified as <position> [align] [fill string], where position (Dimension) is required and align (TabAlign) and fill string (string enclosed in quotes) are optional.

Default: (no value)

split_minimum_lines

Minimum number of lines to keep together when splitting a paragraph across pages

Accepts Integer: a natural number (positive integer)

Default: (no value)

number_format

How numbers are formatted (inherited from NumberStyle)

Accepts NumberFormat: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: None (overrides NumberStyle default)

number_separator

Characters inserted between the number label of this element's parent and this element's own number label. If None, only show this item's number label.

Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: '.'

numbering_level

At which section level to restart numbering (positive: absolute, negative: relative)

Accepts Integer: a natural number (positive integer)

Default: (no value)

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts HorizontalAlignment: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts `Bool`: `true` or `false`

Default: `false`

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: `none`

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: `none`

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: `none`

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: `none`

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: `none`

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts `Color`: HEX string with optional alpha component (`#RRGGBB`, `#RRGGBBAA`, `#RGB` or `#RGBA`)

Default: `none`

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts `Break`: `none`, `any`, `left`, `right`, `any restart`, `left restart`, `right restart`

Default: `None`

hide

Suppress rendering this element (inherited from `Style`)

Accepts `Bool`: `true` or `false`

Default: `false`

label_prefix

Text to prepend to the label (inherited from `LabelStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text

string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

label_suffix

Text to append to the label (inherited from `LabelStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

custom_label

Use a custom label if specified (inherited from `LabelStyle`)

Accepts `Bool`: true or false

Default: false

typeface

Typeface to set the text in (inherited from `TextStyle`)

Accepts `Typeface`: the name of a typeface. See `rinoh --list-fonts` for a list of the available typefaces.

Default: Times

font_weight

Thickness of character outlines relative to their height (inherited from `TextStyle`)

Accepts `FontWeight`: hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black

Default: 500

font_slant

Slope style of the font (inherited from `TextStyle`)

Accepts `FontSlant`: upright, oblique, italic

Default: upright

font_width

Stretch of the characters (inherited from `TextStyle`)

Accepts `FontWidth`: ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded

Default: 5

font_size

Height of characters (inherited from `TextStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 10pt

font_color

Color of the font (inherited from `TextStyle`)

Accepts `Color`: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: #000

font_variant

Variant of the font (inherited from `TextStyle`)

Accepts `FontVariant`: normal, small capital, oldstyle figures

Default: normal

position

Vertical text position (inherited from `TextStyle`)

Accepts `TextPosition`: normal, superscript, subscript

Default: normal

kerning

Improve inter-letter spacing (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

ligatures

Run letters together where possible (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

character_spacing

Additional spacing between characters (inherited from `TextStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0pt

hyphenate

Allow words to be broken over two lines (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

hyphen_chars

Minimum number of characters in a hyphenated part of a word (inherited from `TextStyle`)

Accepts `Integer`: a natural number (positive integer)

Default: 2

hyphen_lang

Language to use for hyphenation. Accepts locale codes such as 'en_US' (inherited from `TextStyle`)

Accepts `Locale`: locale identifier in the <language ID>_<region ID> format

Default: en_US

no_break_after

Prevent a line break after these words (inherited from `TextStyle`)

Accepts `NoBreakAfter`: language-default, or a space-separated list of words

Default: language-default

before

Item to insert before this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

after

Item to insert after this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

3.3.11 TextStyle

```
class rinoh.text.TextStyle ( base=None, **attributes )
```

Style class for Text

typeface

Typeface to set the text in

Accepts Typeface: the name of a typeface. See `rinoh --list-fonts` for a list of the available typefaces.

Default: Times

font_weight

Thickness of character outlines relative to their height

Accepts FontWeight: hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black

Default: 500

font_slant

Slope style of the font

Accepts FontSlant: upright, oblique, italic

Default: upright

font_width

Stretch of the characters

Accepts FontWidth: ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded

Default: 5

font_size

Height of characters

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 10pt

font_color

Color of the font

Accepts Color: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: #000

font_variant

Variant of the font

Accepts FontVariant: normal, small capital, oldstyle figures

Default: normal

position

Vertical text position

Accepts TextPosition: normal, superscript, subscript

Default: normal

kerning

Improve inter-letter spacing

Accepts Bool: true or false

Default: true

ligatures

Run letters together where possible

Accepts Bool: true or false

Default: true

character_spacing

Additional spacing between characters

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0pt

hyphenate

Allow words to be broken over two lines

Accepts Bool: true or false

Default: true

hyphen_chars

Minimum number of characters in a hyphenated part of a word

Accepts Integer: a natural number (positive integer)

Default: 2

hyphen_lang

Language to use for hyphenation. Accepts locale codes such as 'en_US'

Accepts Locale: locale identifier in the <language ID>_<region ID> format

Default: en_US

no_break_after

Prevent a line break after these words

Accepts NoBreakAfter: language-default, or a space-separated list of words

Default: language-default

before

Item to insert before this one (inherited from `InlineStyle`)

Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

after

Item to insert after this one (inherited from `InlineStyle`)

Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

hide

Suppress rendering this element (inherited from `Style`)

Accepts Bool: true or false

Default: false

3.3.12 `InlineFlowableStyle`

```
class rinoh.inline.InlineFlowableStyle ( base=None, **attributes )
```

Style class for `InlineFlowable`

baseline

The location of the flowable's baseline relative to the bottom edge

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0pt

width

Width to render the flowable at (inherited from `FlowableStyle`)

Accepts FlowableWidth: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: auto

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts HorizontalAlignment: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts `Bool`: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts `Color`: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts `Break`: none, any, left, right, any restart, left restart, right restart

Default: None

hide

Suppress rendering this element (inherited from `Style`)

Accepts `Bool`: true or false

Default: false

before

Item to insert before this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

after

Item to insert after this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

3.3.13 ReferencingParagraphStyle

```
class rinoh.reference.ReferencingParagraphStyle ( base=None, **attributes )
```

Style class for `ReferencingParagraph`

text

The text content of this paragraph

Accepts `ReferenceText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: '{TITLE}'

width

Width to render the flowable at (inherited from `ParagraphStyle`)

Accepts `FlowableWidth`: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: fill

indent_first

Indentation of the first line of text (inherited from `ParagraphStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0pt

line_spacing

Spacing between the baselines of two successive lines of text (inherited from `ParagraphStyle`)

Accepts `LineSpacing`: a predefined line spacing type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: <spacing type>(<arg1>, <arg2>, ...)

Default: default

text_align

Alignment of text to the margins (inherited from `ParagraphStyle`)

Accepts `TextAlign`: left, right, center, justify

Default: justify

tab_stops

List of tab positions (inherited from `ParagraphStyle`)

Accepts `TabStopList`: a comma-separated list of tab stops. A tab stop is specified as <position> [align] [fill string], where position (`Dimension`) is

required and `align` (`TabAlign`) and `fill` `string` (string enclosed in quotes) are optional.

Default: (no value)

split_minimum_lines

Minimum number of lines to keep together when splitting a paragraph across pages (inherited from `ParagraphStyle`)

Accepts Integer: a natural number (positive integer)

Default: (no value)

number_format

How numbers are formatted (inherited from `ParagraphStyle`)

Accepts NumberFormat: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: None

number_separator

Characters inserted between the number label of this element's parent and this element's own number label. If None, only show this item's number label. (inherited from `ParagraphStyle`)

Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: ' . '

numbering_level

At which section level to restart numbering (positive: absolute, negative: relative) (inherited from `ParagraphStyle`)

Accepts Integer: a natural number (positive integer)

Default: (no value)

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts HorizontalAlignment: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts Bool: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts `Color`: HEX string with optional alpha component (`#RRGGBB`, `#RRGGBBAA`, `#RGB` or `#RGBA`)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts `Break`: none, any, left, right, any restart, left restart, right restart

Default: None

label_prefix

Text to prepend to the label (inherited from `LabelStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

label_suffix

Text to append to the label (inherited from `LabelStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

custom_label

Use a custom label if specified (inherited from `LabelStyle`)

Accepts `Bool`: true or false

Default: false

typeface

Typeface to set the text in (inherited from `TextStyle`)

Accepts `Typeface`: the name of a typeface. See `rinoh --list-fonts` for a list of the available typefaces.

Default: Times

font_weight

Thickness of character outlines relative to their height (inherited from `TextStyle`)

Accepts `FontWeight`: hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black

Default: 500

font_slant

Slope style of the font (inherited from `TextStyle`)

Accepts `FontSlant`: upright, oblique, italic

Default: upright

font_width

Stretch of the characters (inherited from `TextStyle`)

Accepts `FontWidth`: ultra-condensed, extra-condensed, condensed,

semi-condensed, normal, medium, semi-expanded, expanded,
extra-expanded, ultra-expanded
Default: 5

font_size

Height of characters (inherited from `TextStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 10pt

font_color

Color of the font (inherited from `TextStyle`)

Accepts `Color`: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: #000

font_variant

Variant of the font (inherited from `TextStyle`)

Accepts `FontVariant`: normal, small capital, oldstyle figures

Default: normal

position

Vertical text position (inherited from `TextStyle`)

Accepts `TextPosition`: normal, superscript, subscript

Default: normal

kerning

Improve inter-letter spacing (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

ligatures

Run letters together where possible (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

character_spacing

Additional spacing between characters (inherited from `TextStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0pt

hyphenate

Allow words to be broken over two lines (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

hyphen_chars

Minimum number of characters in a hyphenated part of a word (inherited from `TextStyle`)

Accepts `Integer`: a natural number (positive integer)

Default: 2

hyphen_lang

Language to use for hyphenation. Accepts locale codes such as 'en_US' (inherited from `TextStyle`)

Accepts `Locale`: locale identifier in the <language ID>_<region ID> format

Default: en_US

no_break_after

Prevent a line break after these words (inherited from `TextStyle`)

Accepts `NoBreakAfter`: language-default, or a space-separated list of words

Default: language-default

before

Item to insert before this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

after

Item to insert after this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

hide

Suppress rendering this element (inherited from `Style`)

Accepts `Bool`: true or false

Default: false

3.3.14 NoteMarkerStyle

class `rinoh.reference.NoteMarkerStyle` (*base=None, **attributes*)

Style class for `NoteMarker`

type

How the reference should be displayed (inherited from `ReferenceStyle`)

Accepts `ReferenceType`: reference, number, title, page, custom

Default: number (overrides `ReferenceStyle` default)

link

Create a hyperlink to the reference target (inherited from `ReferenceStyle`)

Accepts `Bool`: true or false

Default: true

quiet

If the given reference type does not exist for the target, resolve to an empty string instead of making a fuss about it (inherited from `ReferenceStyle`)

Accepts `Bool`: true or false

Default: false

typeface

Typeface to set the text in (inherited from `TextStyle`)

Accepts `Typeface`: the name of a typeface. See `rinoh --list-fonts` for a list of the available typefaces.

Default: Times

font_weight

Thickness of character outlines relative to their height (inherited from `TextStyle`)

Accepts `FontWeight`: hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold,

extra-bold, ultra-bold, black, heavy, extra-black, ultra-black
Default: 500

font_slant

Slope style of the font (inherited from `TextStyle`)
Accepts `FontSlant`: upright, oblique, italic
Default: upright

font_width

Stretch of the characters (inherited from `TextStyle`)
Accepts `FontWidth`: ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded
Default: 5

font_size

Height of characters (inherited from `TextStyle`)
Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 10pt

font_color

Color of the font (inherited from `TextStyle`)
Accepts `Color`: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
Default: #000

font_variant

Variant of the font (inherited from `TextStyle`)
Accepts `FontVariant`: normal, small capital, oldstyle figures
Default: normal

position

Vertical text position (inherited from `TextStyle`)
Accepts `TextPosition`: normal, superscript, subscript
Default: normal

kerning

Improve inter-letter spacing (inherited from `TextStyle`)
Accepts `Bool`: true or false
Default: true

ligatures

Run letters together where possible (inherited from `TextStyle`)
Accepts `Bool`: true or false
Default: true

character_spacing

Additional spacing between characters (inherited from `TextStyle`)
Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0pt

hyphenate

Allow words to be broken over two lines (inherited from `TextStyle`)
Accepts `Bool`: true or false
Default: true

hyphen_chars

Minimum number of characters in a hyphenated part of a word (inherited from `TextStyle`)

Accepts `Integer`: a natural number (positive integer)

Default: 2

hyphen_lang

Language to use for hyphenation. Accepts locale codes such as 'en_US' (inherited from `TextStyle`)

Accepts `Locale`: locale identifier in the <language ID>_<region ID> format

Default: en_US

no_break_after

Prevent a line break after these words (inherited from `TextStyle`)

Accepts `NoBreakAfter`: language-default, or a space-separated list of words

Default: language-default

before

Item to insert before this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

after

Item to insert after this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

number_format

How numbers are formatted (inherited from `NumberStyle`)

Accepts `NumberFormat`: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: number

label_prefix

Text to prepend to the label (inherited from `LabelStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

label_suffix

Text to append to the label (inherited from `LabelStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

custom_label

Use a custom label if specified (inherited from `LabelStyle`)

Accepts `Bool`: true or false

Default: false

hide

Suppress rendering this element (inherited from `Style`)

Accepts `Bool`: true or false

Default: false

3.3.15 SectionStyle

```
class rinoh.structure.SectionStyle ( base=None, **attributes )
```

Style class for Section

show_in_toc

List this section in the table of contents

Accepts `Bool`: true or false

Default: true

width

Width to render the flowable at (inherited from `GroupedFlowablesStyle`)

Accepts `FlowableWidth`: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: fill

title

Title to precede the flowables (inherited from `GroupedFlowablesStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

flowable_spacing

Spacing between flowables (inherited from `GroupedFlowablesStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

same_page

Keep all flowables on a single page, if possible. (inherited from `GroupedFlowablesStyle`)

Accepts `Bool`: true or false

Default: false

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts `HorizontalAlignment`: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts Bool: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts Color: HEX string with optional alpha component (`#RRGGBB`, `#RRGGBBAA`, `#RGB` or `#RGBA`)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts Break: none, any, left, right, any restart, left restart, right restart

Default: None

hide

Suppress rendering this element (inherited from `Style`)

Accepts Bool: true or false

Default: false

3.3.16 HeadingStyle

```
class rinoh.structure.HeadingStyle ( base=None, **attributes )
```

Style class for Heading

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts Bool: true or false

Default: true (overrides `FlowableStyle` default)

numbering_level

At which section level to restart numbering (positive: absolute, negative: relative) (inherited from `ParagraphStyle`)

Accepts Integer: a natural number (positive integer)

Default: -1 (overrides `ParagraphStyle` default)

width

Width to render the flowable at (inherited from `ParagraphStyle`)

Accepts FlowableWidth: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: fill

indent_first

Indentation of the first line of text (inherited from `ParagraphStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0pt

line_spacing

Spacing between the baselines of two successive lines of text (inherited from `ParagraphStyle`)

Accepts `LineSpacing`: a predefined line spacing type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: `<spacing type>(<arg1>, <arg2>, ...)`

Default: default

text_align

Alignment of text to the margins (inherited from `ParagraphStyle`)

Accepts `TextAlign`: left, right, center, justify

Default: justify

tab_stops

List of tab positions (inherited from `ParagraphStyle`)

Accepts `TabStopList`: a comma-separated list of tab stops. A tab stop is specified as `<position> [align] [fill string]`, where `position` (`Dimension`) is required and `align` (`TabAlign`) and `fill string` (string enclosed in quotes) are optional.

Default: (no value)

split_minimum_lines

Minimum number of lines to keep together when splitting a paragraph across pages (inherited from `ParagraphStyle`)

Accepts `Integer`: a natural number (positive integer)

Default: (no value)

number_format

How numbers are formatted (inherited from `ParagraphStyle`)

Accepts `NumberFormat`: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: None

number_separator

Characters inserted between the number label of this element's parent and this element's own number label. If None, only show this item's number label. (inherited from `ParagraphStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: `'text string' (style name)`

Default: ' . '

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts `HorizontalAlignment`: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)
Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)
Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)
Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts Color: HEX string with optional alpha component (`#RRGGBB`, `#RRGGBBAA`, `#RGB` or `#RGBA`)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts Break: none, any, left, right, any restart, left restart, right restart

Default: None

label_prefix

Text to prepend to the label (inherited from `LabelStyle`)

Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

label_suffix

Text to append to the label (inherited from `LabelStyle`)

Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

custom_label

Use a custom label if specified (inherited from `LabelStyle`)

Accepts Bool: true or false

Default: false

typeface

Typeface to set the text in (inherited from `TextStyle`)

Accepts Typeface: the name of a typeface. See `rinoh --list-fonts` for a list of the available typefaces.

Default: Times

font_weight

Thickness of character outlines relative to their height (inherited from `TextStyle`)

Accepts FontWeight: hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black

Default: 500

font_slant

Slope style of the font (inherited from `TextStyle`)

Accepts `FontSlant`: upright, oblique, italic

Default: upright

font_width

Stretch of the characters (inherited from `TextStyle`)

Accepts `FontWidth`: ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded

Default: 5

font_size

Height of characters (inherited from `TextStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 10pt

font_color

Color of the font (inherited from `TextStyle`)

Accepts `Color`: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: #000

font_variant

Variant of the font (inherited from `TextStyle`)

Accepts `FontVariant`: normal, small capital, oldstyle figures

Default: normal

position

Vertical text position (inherited from `TextStyle`)

Accepts `TextPosition`: normal, superscript, subscript

Default: normal

kerning

Improve inter-letter spacing (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

ligatures

Run letters together where possible (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

character_spacing

Additional spacing between characters (inherited from `TextStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0pt

hyphenate

Allow words to be broken over two lines (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

hyphen_chars

Minimum number of characters in a hyphenated part of a word (inherited from `TextStyle`)

Accepts Integer: a natural number (positive integer)
Default: 2

hyphen_lang

Language to use for hyphenation. Accepts locale codes such as 'en_US' (inherited from `TextStyle`)
Accepts Locale: locale identifier in the <language ID>_<region ID> format
Default: en_US

no_break_after

Prevent a line break after these words (inherited from `TextStyle`)
Accepts NoBreakAfter: language-default, or a space-separated list of words
Default: language-default

before

Item to insert before this one (inherited from `InlineStyle`)
Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

after

Item to insert after this one (inherited from `InlineStyle`)
Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

hide

Suppress rendering this element (inherited from `Style`)
Accepts Bool: true or false
Default: false

3.3.17 ListStyle

```
class rinoh.structure.ListStyle ( base=None, **attributes )  
    Style class for List
```

ordered

This list is ordered or unordered
Accepts Bool: true or false
Default: false

bullet

Bullet to use in unordered lists
Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: '•'

width

Width to render the flowable at (inherited from `GroupedFlowablesStyle`)
Accepts FlowableWidth: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: fill

title

Title to precede the flowables (inherited from `GroupedFlowablesStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

flowable_spacing

Spacing between flowables (inherited from `GroupedFlowablesStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

same_page

Keep all flowables on a single page, if possible. (inherited from `GroupedFlowablesStyle`)

Accepts `Bool`: true or false

Default: false

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts `HorizontalAlignment`: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts Bool: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts Color: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts Break: none, any, left, right, any restart, left restart, right

restart
Default: None

hide

Suppress rendering this element (inherited from `Style`)
Accepts `Bool`: true or false
Default: false

number_format

How numbers are formatted (inherited from `NumberStyle`)
Accepts `NumberFormat`: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman
Default: number

label_prefix

Text to prepend to the label (inherited from `LabelStyle`)
Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

label_suffix

Text to append to the label (inherited from `LabelStyle`)
Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

custom_label

Use a custom label if specified (inherited from `LabelStyle`)
Accepts `Bool`: true or false
Default: false

3.3.18 ListItemLabelStyle

```
class rinoh.structure.ListItemLabelStyle ( base=None, **attributes )  
    Style class for ListItemLabel
```

number_separator

Characters inserted between the number label of this element's parent and this element's own number label. If None, only show this item's number label. (inherited from `ParagraphStyle`)
Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value) (overrides `ParagraphStyle` default)

width

Width to render the flowable at (inherited from `ParagraphStyle`)
Accepts `FlowableWidth`: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: fill

indent_first

Indentation of the first line of text (inherited from `ParagraphStyle`)
Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0pt

line_spacing

Spacing between the baselines of two successive lines of text (inherited from ParagraphStyle)

Accepts LineSpacing: a predefined line spacing type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: <spacing type>(<arg1>, <arg2>, ...)

Default: default

text_align

Alignment of text to the margins (inherited from ParagraphStyle)

Accepts TextAlign: left, right, center, justify

Default: justify

tab_stops

List of tab positions (inherited from ParagraphStyle)

Accepts TabStopList: a comma-separated list of tab stops. A tab stop is specified as <position> [align] [fill string], where position (Dimension) is required and align (TabAlign) and fill string (string enclosed in quotes) are optional.

Default: (no value)

split_minimum_lines

Minimum number of lines to keep together when splitting a paragraph across pages (inherited from ParagraphStyle)

Accepts Integer: a natural number (positive integer)

Default: (no value)

number_format

How numbers are formatted (inherited from ParagraphStyle)

Accepts NumberFormat: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: None

numbering_level

At which section level to restart numbering (positive: absolute, negative: relative) (inherited from ParagraphStyle)

Accepts Integer: a natural number (positive integer)

Default: (no value)

horizontal_align

Horizontal alignment of the flowable (inherited from FlowableStyle)

Accepts HorizontalAlignment: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from FlowableStyle)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from FlowableStyle)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts Bool: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts Color: HEX string with optional alpha component (`#RRGGBB`, `#RRGGBBAA`, `#RGB` or `#RGBA`)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts Break: none, any, left, right, any restart, left restart, right restart

Default: None

label_prefix

Text to prepend to the label (inherited from `LabelStyle`)

Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

label_suffix

Text to append to the label (inherited from `LabelStyle`)

Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

custom_label

Use a custom label if specified (inherited from `LabelStyle`)

Accepts Bool: true or false

Default: false

typeface

Typeface to set the text in (inherited from `TextStyle`)

Accepts Typeface: the name of a typeface. See `rinoh --list-fonts` for a list of the available typefaces.

Default: Times

font_weight

Thickness of character outlines relative to their height (inherited from `TextStyle`)

Accepts FontWeight: hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black

Default: 500

font_slant

Slope style of the font (inherited from `TextStyle`)

Accepts `FontSlant`: upright, oblique, italic

Default: upright

font_width

Stretch of the characters (inherited from `TextStyle`)

Accepts `FontWidth`: ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded

Default: 5

font_size

Height of characters (inherited from `TextStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 10pt

font_color

Color of the font (inherited from `TextStyle`)

Accepts `Color`: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: #000

font_variant

Variant of the font (inherited from `TextStyle`)

Accepts `FontVariant`: normal, small capital, oldstyle figures

Default: normal

position

Vertical text position (inherited from `TextStyle`)

Accepts `TextPosition`: normal, superscript, subscript

Default: normal

kerning

Improve inter-letter spacing (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

ligatures

Run letters together where possible (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

character_spacing

Additional spacing between characters (inherited from `TextStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0pt

hyphenate

Allow words to be broken over two lines (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

hyphen_chars

Minimum number of characters in a hyphenated part of a word (inherited from

TextStyle)
Accepts Integer: a natural number (positive integer)
Default: 2

hyphen_lang

Language to use for hyphenation. Accepts locale codes such as 'en_US' (inherited from TextStyle)
Accepts Locale: locale identifier in the <language ID>_<region ID> format
Default: en_US

no_break_after

Prevent a line break after these words (inherited from TextStyle)
Accepts NoBreakAfter: language-default, or a space-separated list of words
Default: language-default

before

Item to insert before this one (inherited from InlineStyle)
Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

after

Item to insert after this one (inherited from InlineStyle)
Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

hide

Suppress rendering this element (inherited from Style)
Accepts Bool: true or false
Default: false

3.3.19 TableOfContentsStyle

```
class rinoh.structure.TableOfContentsStyle ( base=None, **attributes )  
    Style class for TableOfContents
```

depth

The number of section levels to include in the table of contents
Accepts Integer: a natural number (positive integer)
Default: 3

width

Width to render the flowable at (inherited from GroupedFlowablesStyle)
Accepts FlowableWidth: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: fill

title

Title to precede the flowables (inherited from GroupedFlowablesStyle)
Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

flowable_spacing

Spacing between flowables (inherited from `GroupedFlowablesStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

same_page

Keep all flowables on a single page, if possible. (inherited from `GroupedFlowablesStyle`)

Accepts Bool: true or false

Default: false

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts HorizontalAlignment: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts `Bool`: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts `Color`: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts `Break`: none, any, left, right, any restart, left restart, right restart

Default: None

hide

Suppress rendering this element (inherited from `Style`)

Accepts `Bool`: true or false

Default: false

indent_first

Indentation of the first line of text (inherited from `ParagraphStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0pt

line_spacing

Spacing between the baselines of two successive lines of text (inherited from `ParagraphStyle`)

Accepts `LineSpacing`: a predefined line spacing type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: <spacing type>(<arg1>, <arg2>, ...)

Default: default

text_align

Alignment of text to the margins (inherited from `ParagraphStyle`)

Accepts `TextAlign`: left, right, center, justify

Default: justify

tab_stops

List of tab positions (inherited from `ParagraphStyle`)

Accepts `TabStopList`: a comma-separated list of tab stops. A tab stop is specified as <position> [align] [fill string], where position (`Dimension`) is required and align (`TabAlign`) and fill string (string enclosed in quotes) are optional.

Default: (no value)

split_minimum_lines

Minimum number of lines to keep together when splitting a paragraph across pages (inherited from `ParagraphStyle`)

Accepts `Integer`: a natural number (positive integer)

Default: (no value)

number_format

How numbers are formatted (inherited from `ParagraphStyle`)

Accepts `NumberFormat`: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: None

number_separator

Characters inserted between the number label of this element's parent and this element's own number label. If None, only show this item's number label. (inherited from `ParagraphStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: ' . '

numbering_level

At which section level to restart numbering (positive: absolute, negative: relative) (inherited from `ParagraphStyle`)

Accepts `Integer`: a natural number (positive integer)

Default: (no value)

label_prefix

Text to prepend to the label (inherited from `LabelStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

label_suffix

Text to append to the label (inherited from `LabelStyle`)
Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

custom_label

Use a custom label if specified (inherited from `LabelStyle`)
Accepts `Bool`: true or false
Default: false

typeface

Typeface to set the text in (inherited from `TextStyle`)
Accepts `Typeface`: the name of a typeface. See `rinoh --list-fonts` for a list of the available typefaces.
Default: Times

font_weight

Thickness of character outlines relative to their height (inherited from `TextStyle`)
Accepts `FontWeight`: hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black
Default: 500

font_slant

Slope style of the font (inherited from `TextStyle`)
Accepts `FontSlant`: upright, oblique, italic
Default: upright

font_width

Stretch of the characters (inherited from `TextStyle`)
Accepts `FontWidth`: ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded
Default: 5

font_size

Height of characters (inherited from `TextStyle`)
Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 10pt

font_color

Color of the font (inherited from `TextStyle`)
Accepts `Color`: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
Default: #000

font_variant

Variant of the font (inherited from `TextStyle`)
Accepts `FontVariant`: normal, small capital, oldstyle figures
Default: normal

position

Vertical text position (inherited from `TextStyle`)

Accepts `TextPosition`: normal, superscript, subscript

Default: normal

kerning

Improve inter-letter spacing (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

ligatures

Run letters together where possible (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

character_spacing

Additional spacing between characters (inherited from `TextStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0pt

hyphenate

Allow words to be broken over two lines (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

hyphen_chars

Minimum number of characters in a hyphenated part of a word (inherited from `TextStyle`)

Accepts `Integer`: a natural number (positive integer)

Default: 2

hyphen_lang

Language to use for hyphenation. Accepts locale codes such as 'en_US' (inherited from `TextStyle`)

Accepts `Locale`: locale identifier in the <language ID>_<region ID> format

Default: en_US

no_break_after

Prevent a line break after these words (inherited from `TextStyle`)

Accepts `NoBreakAfter`: language-default, or a space-separated list of words

Default: language-default

before

Item to insert before this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

after

Item to insert after this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

3.3.20 TableOfContentsEntryStyle

```
class rinoh.structure.TableOfContentsEntryStyle ( base=None, **attributes )
```

Style class for TableOfContentsEntry

text

The text content of this paragraph (inherited from ReferencingParagraphStyle)

Accepts ReferenceText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: '{NUMBER}' '\t' '{TITLE}' '\t' '{PAGE}' (overrides ReferencingParagraphStyle default)

width

Width to render the flowable at (inherited from ParagraphStyle)

Accepts FlowableWidth: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: fill

indent_first

Indentation of the first line of text (inherited from ParagraphStyle)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0pt

line_spacing

Spacing between the baselines of two successive lines of text (inherited from ParagraphStyle)

Accepts LineSpacing: a predefined line spacing type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: <spacing type>(<arg1>, <arg2>, ...)

Default: default

text_align

Alignment of text to the margins (inherited from ParagraphStyle)

Accepts TextAlign: left, right, center, justify

Default: justify

tab_stops

List of tab positions (inherited from ParagraphStyle)

Accepts TabStopList: a comma-separated list of tab stops. A tab stop is specified as <position> [align] [fill string], where position (Dimension) is required and align (TabAlign) and fill string (string enclosed in quotes) are optional.

Default: (no value)

split_minimum_lines

Minimum number of lines to keep together when splitting a paragraph across pages (inherited from ParagraphStyle)

Accepts Integer: a natural number (positive integer)

Default: (no value)

number_format

How numbers are formatted (inherited from ParagraphStyle)

Accepts NumberFormat: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: None

number_separator

Characters inserted between the number label of this element's parent and this element's own number label. If None, only show this item's number label. (inherited from `ParagraphStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: ' . '

numbering_level

At which section level to restart numbering (positive: absolute, negative: relative) (inherited from `ParagraphStyle`)

Accepts `Integer`: a natural number (positive integer)

Default: (no value)

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts `HorizontalAlignment`: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts Bool: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts Color: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts Break: none, any, left, right, any restart, left restart, right restart

Default: None

label_prefix

Text to prepend to the label (inherited from `LabelStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

label_suffix

Text to append to the label (inherited from `LabelStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

custom_label

Use a custom label if specified (inherited from `LabelStyle`)

Accepts `Bool`: true or false

Default: false

typeface

Typeface to set the text in (inherited from `TextStyle`)

Accepts `Typeface`: the name of a typeface. See `rinoh --list-fonts` for a list of the available typefaces.

Default: Times

font_weight

Thickness of character outlines relative to their height (inherited from `TextStyle`)

Accepts `FontWeight`: hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black

Default: 500

font_slant

Slope style of the font (inherited from `TextStyle`)

Accepts `FontSlant`: upright, oblique, italic

Default: upright

font_width

Stretch of the characters (inherited from `TextStyle`)

Accepts `FontWidth`: ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded

Default: 5

font_size

Height of characters (inherited from `TextStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 10pt

font_color

Color of the font (inherited from `TextStyle`)

Accepts `Color`: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: #000

font_variant

Variant of the font (inherited from `TextStyle`)

Accepts `FontVariant`: normal, small capital, oldstyle figures

Default: normal

position

Vertical text position (inherited from `TextStyle`)

Accepts `TextPosition`: normal, superscript, subscript

Default: normal

kerning

Improve inter-letter spacing (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

ligatures

Run letters together where possible (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

character_spacing

Additional spacing between characters (inherited from `TextStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0pt

hyphenate

Allow words to be broken over two lines (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

hyphen_chars

Minimum number of characters in a hyphenated part of a word (inherited from `TextStyle`)

Accepts `Integer`: a natural number (positive integer)

Default: 2

hyphen_lang

Language to use for hyphenation. Accepts locale codes such as 'en_US' (inherited from `TextStyle`)

Accepts `Locale`: locale identifier in the <language ID>_<region ID> format

Default: en_US

no_break_after

Prevent a line break after these words (inherited from `TextStyle`)

Accepts `NoBreakAfter`: language-default, or a space-separated list of words

Default: language-default

before

Item to insert before this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

after

Item to insert after this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

hide

Suppress rendering this element (inherited from `Style`)
Accepts `Bool`: true or false
Default: false

3.3.21 `AdmonitionStyle`

```
class rinoh.structure.AdmonitionStyle ( base=None, **attributes )
```

Style class for `Admonition`

inline_title

Show the admonition's title inline with the body text, if possible
Accepts `Bool`: true or false
Default: true

label

Custom label to override the default (inherited from `LabeledFlowableStyle`)
Accepts `FlowablesList`: Python source code that represents a list of `Flowables`
Default: none

label_position

Where to place the label (inherited from `LabeledFlowableStyle`)
Accepts `LabelPosition`: left, right
Default: left

label_min_width

Minimum label width (inherited from `LabeledFlowableStyle`)
Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 12pt

label_max_width

Maximum label width (inherited from `LabeledFlowableStyle`)
Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 80pt

label_spacing

Spacing between a label and the labeled flowable (inherited from `LabeledFlowableStyle`)
Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 3pt

align_baselines

Line up the baselines of the label and the labeled flowable (inherited from `LabeledFlowableStyle`)
Accepts `Bool`: true or false
Default: true

wrap_label

Wrap the label at *label_max_width* (inherited from `LabeledFlowableStyle`)
Accepts `Bool`: true or false

Default: false

width

Width to render the flowable at (inherited from `FlowableStyle`)

Accepts `FlowableWidth`: `auto`, `fill` or a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)

Default: auto

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts `HorizontalAlignment`: `left`, `right`, `center`

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts `Bool`: `true` or `false`

Default: `false`

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: `none`

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: `none`

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: `none`

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: `none`

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: `none`

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts `Color`: HEX string with optional alpha component (`#RRGGBB`, `#RRGGBBAA`, `#RGB` or `#RGBA`)

Default: `none`

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts `Break`: `none`, `any`, `left`, `right`, `any restart`, `left restart`, `right restart`

Default: `None`

hide

Suppress rendering this element (inherited from `Style`)

Accepts `Bool`: `true` or `false`

Default: `false`

3.3.22 HorizontalRuleStyle

```
class rinoh.structure.HorizontalRuleStyle ( base=None, **attributes )
```

Style class for HorizontalRule

width

Width to render the flowable at (inherited from FlowableStyle)

Accepts FlowableWidth: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: auto

horizontal_align

Horizontal alignment of the flowable (inherited from FlowableStyle)

Accepts HorizontalAlignment: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from FlowableStyle)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from FlowableStyle)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from FlowableStyle)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from FlowableStyle)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from FlowableStyle)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from FlowableStyle)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from FlowableStyle)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from FlowableStyle)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts `Bool`: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts `Color`: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts `Break`: none, any, left, right, any restart, left restart, right restart

Default: None

hide

Suppress rendering this element (inherited from `Style`)

Accepts `Bool`: true or false

Default: false

stroke

Width and color used to draw the line (inherited from `LineStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: 1pt, #000

3.3.23 TableStyle

```
class rinoh.table.TableStyle ( base=None, **attributes )
```

Style class for Table

column_widths

Absolute or relative widths of each column

Accepts ColumnWidths: a whitespace-delimited list of column widths; `Dimensions` (absolute width), integers (relative width) and/or 'auto' (automatic width)

Default: none

split_minimum_rows

The minimum number of rows to display when the table is split across pages

Accepts Integer: a natural number (positive integer)

Default: (no value)

repeat_head

Repeat the head when the table is split across pages

Accepts Bool: true or false

Default: false

width

Width to render the flowable at (inherited from `FlowableStyle`)

Accepts FlowableWidth: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: auto

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts HorizontalAlignment: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts Bool: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by

a comma (,)
Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)
Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)
Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)
Accepts Color: HEX string with optional alpha component (`#RRGGBB`, `#RRGGBBAA`, `#RGB` or `#RGBA`)
Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)
Accepts Break: none, any, left, right, any restart, left restart, right restart
Default: None

hide

Suppress rendering this element (inherited from `Style`)
Accepts Bool: true or false
Default: false

3.3.24 TableCellStyle

```
class rinoh.table.TableCellStyle ( base=None, **attributes )  
    Style class for TableCell
```

vertical_align

Vertical alignment of the cell contents within the available space
Accepts VerticalAlign: top, middle, bottom
Default: middle

width

Width to render the flowable at (inherited from `GroupedFlowablesStyle`)
Accepts FlowableWidth: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: fill

title

Title to precede the flowables (inherited from `GroupedFlowablesStyle`)
Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

flowable_spacing

Spacing between flowables (inherited from `GroupedFlowablesStyle`)
Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

same_page

Keep all flowables on a single page, if possible. (inherited from `GroupedFlowablesStyle`)

Accepts `Bool`: `true` or `false`

Default: `false`

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts `HorizontalAlignment`: `left`, `right`, `center`

Default: `left`

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)

Default: `0`

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)

Default: `0`

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)

Default: `0`

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)

Default: `0`

padding

Padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)

Default: `0`

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)

Default: `0`

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)

Default: `0`

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)

Default: `0`

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)

Default: `0`

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts `Bool`: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts `Stroke`: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts `Color`: HEX string with optional alpha component (`#RRGGBB`, `#RRGGBBAA`, `#RGB` or `#RGBA`)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts `Break`: none, any, left, right, any restart, left restart, right restart

Default: None

hide

Suppress rendering this element (inherited from `Style`)

Accepts `Bool`: true or false

Default: false

3.3.25 TableCellBorderStyle

```
class rinoh.table.TableCellBorderStyle ( base=None, **attributes )
    Style class for TableCellBorder

    stroke
        Width and color used to draw the line (inherited from LineStyle)
        Accepts Stroke: the width (Dimension) and color (Color) of the stroke, separated by
        a comma (, )
        Default: none (overrides LineStyle default)

    hide
        Suppress rendering this element (inherited from Style)
        Accepts Bool: true or false
        Default: false
```

3.3.26 TableCellBackgroundStyle

```
class rinoh.table.TableCellBackgroundStyle ( base=None, **attributes )
    Style class for TableCellBackground

    fill_color
        Color to fill the shape (inherited from ShapeStyle)
        Accepts Color: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA,
        #RGB or #RGBA)
        Default: none (overrides ShapeStyle default)

    stroke
        Width and color used to draw the line (inherited from LineStyle)
        Accepts Stroke: the width (Dimension) and color (Color) of the stroke, separated by
        a comma (, )
        Default: none (overrides LineStyle default)

    hide
        Suppress rendering this element (inherited from Style)
        Accepts Bool: true or false
        Default: false
```

Rinohtype includes a number of document templates. These are configurable and therefore should cater for most documents.

4.1 Article

The article template consists of a title page, an optional table of contents and the body text. By default, it uses a single numbering style for all pages and the same template for even and odd pages.

```
class rinoh.templates.article.Article ( document_tree, configuration=None,  
backend=None )
```

stylesheet

The stylesheet to use for styling document elements (inherited from `DocumentTemplate`)

Accepts `StyleSheet`: the name of a Section 3.1 or the filename of a stylesheet file (with the `.rts` extension)

Default: `sphinx_article` (= `rinoh.stylesheets.sphinx_article`)
(overrides `:attr: `DocumentTemplate default`)

abstract_location

Where to place the abstract

Accepts `AbstractLocation`: title, body

Default: title

parts

The parts making up this document (inherited from `DocumentTemplate`)

Accepts `PartsList`: a space-separated list of document part template names

Default: contents (overrides `DocumentTemplate default`)

language

The main language of the document (inherited from `DocumentTemplate`)

Accepts `Language`: the code of one of the supported languages

Default: EN (English)

strings

Strings to override standard element names (inherited from `DocumentTemplate`)

Accepts `Strings`: strings need to be entered in INI in a section named 'STRINGS'

Default: none

Attributes

contents (`ArticleContentsPartTemplate`): base: None

Overrides these defaults:

- `page_number_format = number`

`page (ArticleBodyPageTemplate): base: None`

Overrides these defaults:

- `page_size = $ (paper_size)`
- `left_margin = 1.2cm`
- `right_margin = 1.2cm`
- `top_margin = 1.8cm`
- `bottom_margin = 1.6cm`
- `header_footer_distance = 2pt`

`contents_page (ArticleBodyPageTemplate): base: page`

Configuration

alias of `ArticleConfiguration`

ConfigurationFile

alias of `ArticleConfigurationFile`

class `rinoh.templates.article.AbstractLocation`

Where to place the article's abstract

Accepts: `title, body`

4.2 Book

The book template consists of a title page, the table of contents, the body text and an index. The front matter pages are numbered using lowercase roman numerals. The template uses different templates for even and odd pages.

class `rinoh.templates.book.Book ( document_tree, configuration=None, backend=None )`

stylesheet

The stylesheet to use for styling document elements (inherited from `DocumentTemplate`)

Accepts `StyleSheet`: the name of an Section 3.1 or the filename of a stylesheet file (with the `.rts` extension)

Default: `sphinx` (= `rinoh.stylesheets.sphinx`) (overrides `:attr: `DocumentTemplate default`)

parts

The parts making up this document (inherited from `DocumentTemplate`)

Accepts `PartsList`: a space-separated list of document part template names

Default: `title front_matter contents back_matter` (overrides `DocumentTemplate default`)

language

The main language of the document (inherited from `DocumentTemplate`)

Accepts `Language`: the code of one of the supported languages

Default: `EN` (English)

strings

Strings to override standard element names (inherited from `DocumentTemplate`)

Accepts `Strings`: strings need to be entered in INI in a section named `'STRINGS'`

Default: `none`

Attributes

`cover (FixedDocumentPartTemplate):` base: None

Overrides these defaults:

- `drop_if_empty` = False
- `page_number_format` = None
- `end_at_page` = left

`title (TitlePartTemplate):` base: None

Overrides these defaults:

- `page_number_format` = number
- `end_at_page` = left

`front_matter (FixedDocumentPartTemplate):` base: None

Overrides these defaults:

- `flowables` = [TableOfContentsSection(), ListOfFiguresSection(), ListOfTablesSection()]
- `page_number_format` = lowercase roman
- `end_at_page` = left

`contents (ContentsPartTemplate):` base: None

Overrides these defaults:

- `page_number_format` = number
- `end_at_page` = left

`back_matter (BackMatterTemplate):` base: None

Overrides these defaults:

- `page_number_format` = continue
- `end_at_page` = left

`page (BodyPageTemplate):` base: None

Overrides these defaults:

- `page_size` = \$ (paper_size)
- `left_margin` = 1in
- `right_margin` = 1in
- `top_margin` = 1in
- `bottom_margin` = 1in

`cover_page (BodyPageTemplate):` base: page `title_page (TitlePageTemplate):`

base: page `front_matter_page (BodyPageTemplate):` base: page

Overrides these defaults:

- `header_footer_distance` = 0
- `header_text` = None

`front_matter_right_page (BodyPageTemplate):` base: `front_matter_page`

Overrides these defaults:

- `footer_text` = '\t' '\t' '{PAGE_NUMBER}'
- `chapter_header_text` = None
- `chapter_footer_text` = '\t' '\t' '{PAGE_NUMBER}'
- `chapter_title_height` = 2.5in
- `chapter_title_flowables` = [<rinoh.paragraph.Paragraph object at 0x7fa39ef23a10>]
- `sideways` = right

`front_matter_left_page (BodyPageTemplate):` base: `front_matter_page`

Overrides these defaults:

- footer_text = '{PAGE_NUMBER}'
- sideways = left

contents_page (BodyPageTemplate): base: page

Overrides these defaults:

- header_footer_distance = 0

contents_right_page (BodyPageTemplate): base: contents_page

Overrides these defaults:

- header_text = '\t' '\t' '{DOCUMENT_TITLE}' ', ' '{DOCUMENT_SUBTITLE}'
- footer_text = '{SECTION_NUMBER(2)}' '\t' '{SECTION_TITLE(2)}' '\t' '{PAGE_NUMBER}'
- chapter_header_text = None
- chapter_footer_text = '\t' '\t' '{PAGE_NUMBER}'
- chapter_title_height = 2.4in
- chapter_title_flowables = [<rinoh.paragraph.Paragraph object at 0x7fa39f1156d0>, <rinoh.paragraph.Paragraph object at 0x7fa39f115950>]
- sideways = right

contents_left_page (BodyPageTemplate): base: contents_page

Overrides these defaults:

- header_text = '{DOCUMENT_TITLE}' ', ' '{DOCUMENT_SUBTITLE}'
- footer_text = '{PAGE_NUMBER}' '\t' '\t' '{@chapter}' '\t' '{SECTION_NUMBER(1)}' '\t' '{SECTION_TITLE(1)}'
- sideways = left

back_matter_page (BodyPageTemplate): base: page

Overrides these defaults:

- columns = 2
- header_footer_distance = 0

back_matter_right_page (BodyPageTemplate): base: back_matter_page

Overrides these defaults:

- header_text = '\t' '\t' '{DOCUMENT_TITLE}' ', ' '{DOCUMENT_SUBTITLE}'
- footer_text = '{SECTION_TITLE(1)}' '\t' '\t' '{PAGE_NUMBER}'
- chapter_header_text = None
- chapter_footer_text = '\t' '\t' '{PAGE_NUMBER}'
- chapter_title_height = 2.5in
- chapter_title_flowables = [<rinoh.paragraph.Paragraph object at 0x7fa39ef23a10>]
- sideways = right

back_matter_left_page (BodyPageTemplate): base: back_matter_page

Overrides these defaults:

- header_text = '{DOCUMENT_TITLE}' ', ' '{DOCUMENT_SUBTITLE}'
- footer_text = '{PAGE_NUMBER}' '\t' '\t' '{SECTION_TITLE(1)}'
- sideways = left

Configuration

alias of BookConfiguration

ConfigurationFile
alias of BookConfigurationFile

Note

The API documentation is still incomplete.

5.1 Attribute (`rinoh.attribute`)

class `rinoh.attribute.AcceptNoneAttributeType`

Accepts 'none' (besides other values)

class `rinoh.attribute.OptionSet`

Accepts the values listed in values

Accepts:

class `rinoh.attribute.Attribute` (*accepted_type*, *default_value*, *description*)

Descriptor used to describe a style attribute

class `rinoh.attribute.OverrideDefault` (*default_value*)

Overrides the default value of an attribute defined in a superclass

class `rinoh.attribute.AttributesDictionary` (*base=None*, ***attributes*)

class `rinoh.attribute.RuleSet` (*name*, *base=None*, *source=None*, ***kwargs*)

find_source (*name*)

Find top-most ruleset where configuration *name* is defined

class `rinoh.attribute.RuleSetFile` (*filename*, *base=None*, *source=None*, ***kwargs*)

property location

Textual representation of this source

property root

Directory path for resolving paths relative to this source

class `rinoh.attribute.Bool`

Expresses a binary choice

class `rinoh.attribute.Integer`

Accepts natural numbers

exception `rinoh.attribute.ParseError`

5.2 Color (`rinoh.color`)

class `rinoh.color.Color` (*red, green, blue, alpha=1*)

Color defined by component values

Parameters

red : float

red component (0 .. 1)

blue : float

blue component (0 .. 1)

green : float

green component (0 .. 1)

alpha : float

opacity (0 .. 1)

property **rgba**

classmethod **parse_string** (*string, source*)

classmethod **doc_format** ()

class `rinoh.color.HexColor` (*string*)

Color defined as a hexadecimal string

Parameters

string : str

#RGBA or #RRGGBBAA (# and A are optional)

class `rinoh.color.Gray` (*luminance, alpha=1*)

Shade of gray

Parameters

luminance : float

brightness (0 .. 1)

alpha : float

opacity (0 .. 1)

5.3 Dimension (`rinoh.dimension`)

Classes for expressing dimensions: lengths, widths, line thickness, etc.

Each dimension is expressed in terms of a unit. Several common units are defined here as constants. To create a new dimension, multiply number with a unit:

```
height = 100*PT
width = 50*PERCENT
```

Fractional dimensions are evaluated within the context they are defined in. For example, the width of a `Flowable` is evaluated with respect to the total width available to it.

class `rinoh.dimension.Dimension` (*value=0, unit=None*)

A simple dimension

Parameters

value : **int** or **float**

the magnitude of the dimension

unit : **DimensionUnit**

the unit this dimension is expressed in. Default: **PT**.

grow (*value*)

Grow this dimension (in-place)

The *value* is interpreted as a magnitude expressed in the same unit as this dimension.

Parameters

value : **int** or **float**

the amount to add to the magnitude of this dimension

Returns

Dimension – this (grewed) dimension itself

```
rinoh.dimension.PT = DimensionUnit(1.0, 'pt')
```

PostScript points

```
rinoh.dimension.PICA = DimensionUnit(12.0, 'pc')
```

computer pica

```
rinoh.dimension.INCH = DimensionUnit(72.0, 'in')
```

imperial/US inch

```
rinoh.dimension.MM = DimensionUnit(2.8346456692913384, 'mm')
```

millimeter

```
rinoh.dimension.CM = DimensionUnit(28.346456692913385, 'cm')
```

centimeter

```
rinoh.dimension.PERCENT = FractionUnit(100, '%')
```

fraction of 100

```
rinoh.dimension.HALVES = FractionUnit(2, '/2')
```

fraction of 2

```
rinoh.dimension.QUARTERS = FractionUnit(4, '/4')
```

fraction of 4

5.4 Document (**rinoh.document**)

```
class rinoh.document.DocumentTree ( flowables, options=None, style=None, source=None )
```

Holds the document's contents as a tree of flowables

Parameters

flowables : **list**[**Flowable**]

the list of top-level flowables

options : **Reader**

frontend-specific options

```
class rinoh.document.Document ( document_tree, stylesheet, language, strings=None, backend=None )
```

Renders a document tree to pages

Parameters

document_tree : DocumentTree

a tree of the document's contents

stylesheet : StyleSheet

style sheet used to style document elements

language : Language

the language to use for standard strings

strings : Strings

user-defined string variables and can override localized strings provided by *language*

backend=None

the backend used for rendering the document

render (*filename_root=None, file=None*)

Render the document repeatedly until the output no longer changes due to cross-references that need some iterations to converge.

5.4.1 Pages

```
class rinoh.document.Page ( document_part, number, paper, orientation='portrait',  
display_sideways=None )
```

A single page in a document.

A `Page` is a `Container`, so other containers can be added as children.

Parameters

document_part : DocumentPart

the document part this page is part of

number : int

the 1-based index of this page in the document part

paper : Paper

determines the dimensions of this page

orientation : PageOrientation

the orientation of this page

display_sideways : Sideways

display the page rotated

property page

Returns the page itself.

render ()

Render the contents of this container to its canvas.

Note that the rendered contents need to be `place()`d on the parent container's canvas before they become visible.

place ()

Place this container's canvas onto the parent container's canvas.

```
class rinoh.document.PageOrientation
```

Accepts: portrait, landscape

```
class rinoh.document.PageType
```

Accepts: left, right, any

class rinoh.document.**PageNumberFormat**

How (or if) page numbers are displayed

Accepts: none, number, symbol, lowercase character, uppercase character,
lowercase roman, uppercase roman, continue

5.5 Drawing Primitives (rinoh.draw)

class rinoh.draw.**Stroke** (*width, color*)

The display properties of a line

Parameters

width : **Dimension**

the width of the line

color : **Color**

the color of the line

class rinoh.draw.**Line** (*start, end, style=None, parent=None*)

Draws a line

Parameters

start : **2-tuple**

coordinates for the start point of the line

end : **2-tuple**

coordinates for the end point of the line

style_class

alias of `LineStyle`

class rinoh.draw.**Shape** (*style=None, parent=None*)

Base class for closed shapes

style_class

alias of `ShapeStyle`

class rinoh.draw.**Polygon** (*points, style=None, parent=None*)

class rinoh.draw.**Rectangle** (*bottom_left, width, height, style=None, parent=None*)

5.6 Flowable (rinoh.flowable)

class rinoh.flowable.**Flowable** (*align=None, width=None, id=None, style=None, parent=None, source=None*)

A document element that can be “flowed” into a container on the page.

A flowable can adapt to the width of the container, or it can horizontally align itself in the container.

Parameters

align : **HorizontalAlignment**

horizontal alignment of the flowable

width : **FlowableWidth** or **DimensionBase**

the width of the flowable.

```
class rinoh.flowable.FlowableState ( flowable, _initial=True )
```

Stores a flowable's rendering state, which can be copied.
This enables saving the rendering state at certain points in the rendering process, so rendering can later be resumed at those points, if needed.

5.6.1 No-Output Flowables

These flowables do not directly place anything on the page. All except `DummyFlowable` do have side-effects however. Some of these side-effects affect the rendering of the document in an indirect way.

```
class rinoh.flowable.DummyFlowable ( id=None, parent=None, source=None )
```

A flowable that does not directly place anything on the page.
Subclasses can produce side-effects to affect the output in another way.

```
class rinoh.flowable.AnchorFlowable ( id=None, parent=None, source=None )
```

A dummy flowable that registers a destination anchor.
Places a destination for the flowable's ID at the current cursor position.

```
class rinoh.flowable.SetMetadataFlowable ( parent=None, **metadata )
```

A dummy flowable that stores metadata in the document.
The metadata is passed as keyword arguments. It will be available to other flowables during the rendering stage.

```
class rinoh.flowable.WarnFlowable ( message, parent=None, source=None )
```

A dummy flowable that emits a warning during the rendering stage.

Parameters

message : `str`
the warning message to emit

```
class rinoh.flowable.PageBreak ( page_break= 'any' )
```

5.6.2 Labeled Flowables

```
class rinoh.flowable.LabeledFlowable ( label, flowable, id=None, style=None, parent=None )
```

A flowable with a label.

The flowable and the label are rendered side-by-side. If the label exceeds the `label_max_width` style attribute value, the flowable is rendered below the label.

Parameters

label : `Flowable`
the label for the flowable

flowable : `Flowable`
the flowable to label

style_class
alias of `LabeledFlowableStyle`

prepare (*flowable_target*)
Determine number labels and register references with the document

render (*container*, *last_descender*, *state*, *label_column_width=None*, *space_below=0*, ***kwargs*)
Renders the flowable's content to *container*, with the flowable's top edge lining up with

the container's cursor. *descender* is the descender height of the preceding line or *None*.

```
class rinoh.flowable.LabeledFlowableState ( flowable, content_flowable_state,
_initial=True )
```

5.6.3 Grouping Flowables

```
class rinoh.flowable.GroupedFlowables ( align=None, width=None, id=None,
style=None, parent=None, source=None )
```

Groups a list of flowables and renders them one below the other.

Makes sure that a flowable for which *keep_with_next* is enabled is not separated from the flowable that follows it.

Subclasses should implement `flowables()`.

style_class

alias of `GroupedFlowablesStyle`

flowables (*container*)

Generator yielding the `Flowables` to group

render (*container*, *descender*, *state*, *first_line_only=False*, ***kwargs*)

Renders the flowable's content to *container*, with the flowable's top edge lining up with the container's cursor. *descender* is the descender height of the preceding line or *None*.

```
class rinoh.flowable.GroupedFlowablesState ( groupedflowables, flowables,
first_flowable_state=None, _initial=True, _index=0 )
```

```
class rinoh.flowable.StaticGroupedFlowables ( flowables, align=None, width=None,
id=None, style=None, parent=None, source=None )
```

Groups a static list of flowables.

Parameters

flowables : `iterable[Flowable]`

the flowables to group

flowables (*container*)

Generator yielding the `Flowables` to group

build_document (*flowable_target*)

Set document metadata and populate front and back matter

prepare (*flowable_target*)

Determine number labels and register references with the document

```
class rinoh.flowable.GroupedLabeledFlowables ( align=None, width=None, id=None,
style=None, parent=None, source=None )
```

Groups a list of labeled flowables, lining them up.

render (*container*, *descender*, *state*, ***kwargs*)

Renders the flowable's content to *container*, with the flowable's top edge lining up with the container's cursor. *descender* is the descender height of the preceding line or *None*.

5.6.4 Floating Flowables

class rinoh.flowable.**Float** (*align=None, width=None, id=None, style=None, parent=None, source=None*)

A flowable that can optionally be placed elsewhere on the page.

If this flowable's *float* style attribute is set to `True`, it is not flowed in line with the surrounding flowables, but it is instead flowed into another container pointed to by the former's `Container.float_space` attribute.

This is typically used to place figures and tables at the top or bottom of a page, instead of in between paragraphs.

style_class

alias of `FloatStyle`

flow (*container, last_descender, state=None, **kwargs*)

Flow this flowable into *container* and return the vertical space consumed.

The flowable's contents are preceded by a vertical space with a height as specified in its style's *space_above* attribute. Similarly, the flowed content is followed by a vertical space with a height given by the *space_below* style attribute.

5.6.5 Styling Properties

class rinoh.flowable.**HorizontalAlignment**

Controls horizontal placement

Accepts: `left`, `right`, `center`

class rinoh.flowable.**FlowableWidth**

Controls the width of a flowable

Accepts: `auto`, `fill` or a numeric value followed by a unit (`pt`, `in`, `pc`, `mm`, `cm`, `%`, `/2`, `/4`)

5.7 Fonts and Typefaces (**rinoh.font**)

Classes for fonts and typefaces.

class rinoh.font.**Font** (*filename, weight, slant, width*)

A collection of glyphs in a particular style

This is a base class for classes that parse different font formats. See `rinoh.font.type1` and `rinoh.font.opentype`.

Parameters

filename : **str**

filename of the font file to load

weight : **FontWeight**

weight of the font

slant : **FontSlant**

slant of the font

width : **FontWidth**

width of the font

encoding

If no encoding is set for the `Font`, glyphs are addressed by glyph ID (and thus support more than 256 glyphs).

get_glyph_metrics (*char*, *variant*)

Return the glyph metrics for a particular character

If the glyph of requested font variant is not present in the font, the *normal* variant is returned instead. If that is not present either, an exception is raised.

Parameters

char : **str** of length 1

the character for which to find the glyph

variant : **FontVariant**

the variant of the glyph to return

Returns

GlyphMetrics – the requested glyph metrics

Raises

MissingGlyphException – when the requested glyph is not present in the font

get_ligature (*glyph*, *successor_glyph*)

Return the ligature to replace the given glyphs

If no ligature is defined in the font for the given glyphs, return *None*.

Parameters

glyph : **GlyphMetrics**

the first of the glyphs to combine

successor_glyph : **GlyphMetrics**

the second of the glyphs to combine

Returns

GlyphMetrics or *None* – the ligature to replace the given glyphs

get_kerning (*a*, *b*)

Look up the kerning for two glyphs

Parameters

a : **GlyphMetrics**

the first of the glyphs

b : **GlyphMetrics**

the second of the glyphs

Returns

float – the kerning value in font units

class `rinoh.font.Typeface` (*name*, **fonts*)

A set of fonts that share common design features

The fonts collected in a typeface differ in weight, width and/or slant.

Parameters

***fonts**

the fonts that make up this typeface

fonts ()

Generator yielding all fonts of this typeface

Yields

Font – the next font in this typeface

get_font (*weight=400, slant='upright', width=5*)

Return the font matching or closest to the given style

If a font with the given weight, slant and width is available, return it. Otherwise, return the font that is closest in style.

Parameters

weight : **FontWeight**
weight of the font

slant : **FontSlant**
slant of the font

width : **FontWidth**
width of the font

Returns

Font – the requested font

class rinoh.font.style.**FontWeight**

Accepts: hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black

class rinoh.font.style.**FontSlant**

Accepts: upright, oblique, italic

class rinoh.font.style.**FontWidth**

Accepts: ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded

class rinoh.font.style.**FontVariant**

Accepts: normal, small capital, oldstyle figures

class rinoh.font.style.**TextPosition**

Accepts: normal, superscript, subscript

5.8 Images and Figures (**rinoh.image**)

class rinoh.image.**Image** (*filename_or_file, scale=1.0, width=None, height=None, dpi=None, rotate=0, limit_width=<rinoh.dimension.Fraction object>, align=None, alt=None, id=None, style=None, parent=None, source=None*)

class rinoh.image.**InlineImage** (*filename_or_file, scale=1.0, width=None, height=None, dpi=None, rotate=0, alt=None, baseline=None, id=None, style=None, parent=None, source=None*)

arguments

alias of **InlineImageArgs**

class rinoh.image.**BackgroundImage** (*filename_or_file, scale=1.0, width=None, height=None, dpi=None, rotate=0, limit_width=<rinoh.dimension.Fraction object>, align=None, alt=None, id=None, style=None, parent=None, source=None*)

Image to place in the background of a page

Takes the same arguments as **Image**.

arguments

alias of **ImageArgs**

```
class rinoh.image.ImageArgs ( base=None, **attributes )
```

limit_width

Limit the image width when none of `scale`, `width` and `height` are given and the image would be wider than the container

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 100%

align

How to align the image within the page

Accepts HorizontalAlignment: left, right, center

Default: left

file_or_filename

Path to the image file (inherited from ImageArgsBase)

Accepts ImagePath: path to an image file enclosed in quotes

Default: none

scale

Scaling factor for the image (inherited from ImageArgsBase)

Accepts Scale: fit, fill or a float larger than 0

Default: fit

width

The width to scale the image to (inherited from ImageArgsBase)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: none

height

The height to scale the image to (inherited from ImageArgsBase)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: none

dpi

Overrides the DPI value set in the image (inherited from ImageArgsBase)

Accepts Integer: a natural number (positive integer)

Default: (no value)

rotate

Angle in degrees to rotate the image (inherited from ImageArgsBase)

Accepts Integer: a natural number (positive integer)

Default: (no value)

```
class rinoh.image.Scale
```

Scaling factor for images

Can be a numerical value where a value of 1 keeps the image's original size or one of values.

Accepts: fit, fill or a float larger than 0

```
class rinoh.image.Caption ( content, custom_label=None, align=None, width=None, id=None, style=None, parent=None, source=None )
```

style_class

alias of CaptionStyle

```

class rinoh.image.Figure ( flowables, align=None, width=None, id=None, style=None,
parent=None, source=None )

    style_class
        alias of FigureStyle

class rinoh.image.ListOfFiguresSection

    list_class
        alias of ListOfFigures

class rinoh.image.ListOfFigures ( local=False, id=None, style=None, parent=None )

```

5.9 Index (**rinoh.index**)

```

class rinoh.index.IndexSection ( title=None, flowables=None, style=None )

class rinoh.index.Index ( id=None, style=None, parent=None )

    style_class
        alias of IndexStyle

    flowables ( container )
        Generator yielding the Flowables to group

class rinoh.index.IndexLabel ( content, custom_label=None, align=None, width=None,
id=None, style=None, parent=None, source=None )

class rinoh.index.IndexTerm ( *levels )

class rinoh.index.InlineIndexTarget ( index_terms, *args, **kwargs )

    to_string ( flowable_target )
        Return the text content of this styled text.

class rinoh.index.IndexTarget ( index_terms, parent=None )

    flow ( container, last_descender, state=None, **kwargs )
        Flow this flowable into container and return the vertical space consumed.
        The flowable's contents are preceded by a vertical space with a height as specified in its
        style's space_above attribute. Similarly, the flowed content is followed by a vertical space
        with a height given by the space_below style attribute.

```

5.10 Language (**rinoh.language**)

```

class rinoh.language.Language ( code, name, **localized_strings )
    Collects localized strings for a particular language

    Parameters

        code : str
            short code identifying the language

        name : str
            native name of the language

```

paragraph
label for referencing paragraphs

section
label for referencing sections

chapter
label for top-level sections

figure
caption label for figures

table
caption label for tables

listing
caption label for (source code) listings

contents
title for the table of contents section

list_of_figures
title for the list of figures section

list_of_tables
title for the list of tables section

index
title for the index section

attention
title for attention admonitions

caution
title for caution admonitions

danger
title for danger admonitions

error
title for error admonitions

hint
title for hint admonitions

important
title for important admonitions

note
title for note admonitions

tip title for tip admonitions

warning
title for warning admonitions

seealso
title for see-also admonitions

```

languages = {'cs': <weakref at 0x7fa3a07d4bd0; to
'rinoh.language.cls.Language'>, 'de': <weakref at 0x7fa3a0a01df0;
to 'rinoh.language.cls.Language'>, 'en': <weakref at
0x7fa3a0a02160; to 'rinoh.language.cls.Language'>, 'es': <weakref
at 0x7fa3a05cd8f0; to 'rinoh.language.cls.Language'>, 'fr':
<weakref at 0x7fa3a0a022a0; to 'rinoh.language.cls.Language'>,
'hu': <weakref at 0x7fa3a05cdc10; to
'rinoh.language.cls.Language'>, 'it': <weakref at 0x7fa3a0a02340;
to 'rinoh.language.cls.Language'>, 'nl': <weakref at
0x7fa3a0a023e0; to 'rinoh.language.cls.Language'>, 'pl': <weakref
at 0x7fa3a0a02660; to 'rinoh.language.cls.Language'>}
    Dictionary mapping codes to Languages

```

The following languages are supported:

```

rinoh.language.CS = Language('cs', 'Česky')
    Localized strings for Česky :figure: Obrázek :table: Tabulka :contents: Obsah :list_of_fig-
ures: Seznam obrázků :list_of_tables: Seznam tabulek :chapter: Kapitola :index: Rejstřík
:attention: Pozor! :caution: Pozor! :danger: !NEBEZPEČÍ! :error: Chyba :hint: Poznámka
:important: Důležité :note: Poznámka :tip: Tip :warning: Varování :seealso: Viz také

```

```

rinoh.language.EN = Language('en', 'English')
    Localized strings for English :paragraph: Paragraph :section: Section :chapter: Chapter :fig-
ure: Figure :table: Table :listing: Listing :equation: Equation :contents: Table of Contents
:list_of_figures: List of Figures :list_of_tables: List of Tables :index: Index :attention: Atten-
tion! :caution: Caution! :danger: !DANGER! :error: Error :hint: Hint :important: Important
:note: Note :tip: Tip :warning: Warning :seealso: See also

```

```

rinoh.language.ES = Language('es', 'Spanish')
    Localized strings for Spanish :figure: Figura :table: Tabla :contents: Contenidos :list_of_fig-
ures: Índice de figuras :list_of_tables: Índice de tablas :chapter: Capítulo :index: Índice
:attention: ¡Atención! :caution: ¡Cuidado! :danger: ¡PELIGRO! :error: Error :hint: Pista
:important: Importante :note: Nota :tip: Consejo :warning: Precaución :seealso: Vea también

```

```

rinoh.language.FR = Language('fr', 'Français')
    Localized strings for Français :figure: Figure :table: Tableau :contents: Table des Matières
:list_of_figures: Liste des Figures :list_of_tables: Liste des Tableaux :chapter: Chapitre
:index: Index :attention: Attention! :caution: Prudence! :danger: !DANGER! :error: Erreur
:hint: Conseil :important: Important :note: Note :tip: Astuce :warning: Avertissement
:seealso: Voir aussi

```

```

rinoh.language.HU = Language('hu', 'Hungarian')
    Localized strings for Hungarian :contents: Tartalomjegyzék :list_of_figures: Ábrák Listája
:list_of_tables: Asztalok Listája :chapter: Fejezet :index: Index :attention: Figyelem! :caution:
Vigyázat!! :danger: !VESZÉLY! :error: Hiba :hint: Tanács :important: Fontos :note: Megje-
gyzés :tip: Tipp :warning: Figyelmeztetés :seealso: Lásd még

```

```

rinoh.language.IT = Language('it', 'Italiano')
    Localized strings for Italiano :figure: Figura :table: Tabelle :contents: Contenuti :list_of_fig-
ures: Elenco delle Figure :list_of_tables: Elenco delle Tabelle :chapter: Capitolo :index:
Indice :attention: Attenzione! :caution: Prudenza! :danger: !PERICOLO! :error: Errore :hint:
Consiglio :important: Importante :note: Nota :tip: Suggerimento :warning: Avvertimento
:seealso: Vedi anche

```

```

rinoh.language.NL = Language('nl', 'Nederlands')
    Localized strings for Nederlands :paragraph: Paragraaf :section: Sectie :chapter: Hoofdstuk
:figure: Figuur :table: Tabel :listing: Lijst :contents: Inhoudsopgave :list_of_figures: Lijst van
Figuren :list_of_tables: Lijst van Tabellen :index: Index :attention: Opgelet! :caution: Pas op!

```

:danger: !GEVAAR! :error: Fout :hint: Hint :important: Belangrijk :note: Noot :tip: Tip :warning: Waarschuwing :seealso: Zie ook

```
rinoh.language.PL = Language('pl', 'Polski')
```

Localized strings for Polski :figure: Ilustracja :table: Tabela :contents: Spis Treści :list_of_figures: Spis Ilustracji :list_of_tables: Spis Tabel :chapter: Rozdział :index: Skorowidz :attention: Uwaga! :caution: Ostrożnie! :danger: !NIEBEZPIECZEŃSTWO! :error: Błąd :hint: Wskazówka :important: Ważne :note: Notatka :tip: Porada :warning: Ostrzeżenie :seealso: Zobacz również

5.11 Number (rinoh.number)

class rinoh.number.NumberFormat

How (or if) numbers are displayed

Instead of a numbering format, it's possible to supply a custom label (`StyledText`) to show instead of the number.

Accepts: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

class rinoh.number.Label (custom_label=None)

Mixin class that formats a label

Parameters

custom_label : StyledText

a frontend can supply a custom label to use instead of an automatically determined label (typically a number)

class rinoh.number.LabelStyle (base=None, **attributes)

Style class for `Label`

label_prefix

Text to prepend to the label

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

label_suffix

Text to append to the label

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

custom_label

Use a custom label if specified

Accepts `Bool`: true or false

Default: false

hide

Suppress rendering this element (inherited from `Style`)

Accepts `Bool`: true or false

Default: false

class rinoh.number.NumberStyle (base=None, **attributes)

Style class for `Number`

number_format

How numbers are formatted

Accepts NumberFormat: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: number

label_prefix

Text to prepend to the label (inherited from LabelStyle)

Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

label_suffix

Text to append to the label (inherited from LabelStyle)

Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

custom_label

Use a custom label if specified (inherited from LabelStyle)

Accepts Bool: true or false

Default: false

hide

Suppress rendering this element (inherited from Style)

Accepts Bool: true or false

Default: false

`rinoh.number.format_number ( number, format )`

Format *number* according the given *format* (NumberFormat)

5.12 Paper sizes (rinoh.paper)

The Paper class and a number of predefined paper formats.

`class rinoh.paper.Paper ( name, width, height )`

Defines a paper size.

Parameters

name : str

the name of this paper type

width : Dimension

the (portrait) width of this paper type

height : Dimension

the (portrait) height of this paper type

`rinoh.paper.A0 = Paper('A0', width=841*MM, height=1189*MM)`

`rinoh.paper.A1 = Paper('A1', width=594*MM, height=841*MM)`

`rinoh.paper.A2 = Paper('A2', width=420*MM, height=594*MM)`

`rinoh.paper.A3 = Paper('A3', width=297*MM, height=420*MM)`

```

rinoh.paper.A4 = Paper('A4', width=210*MM, height=297*MM)
rinoh.paper.A5 = Paper('A5', width=148*MM, height=210*MM)
rinoh.paper.A6 = Paper('A6', width=105*MM, height=148*MM)
rinoh.paper.A7 = Paper('A7', width=74*MM, height=105*MM)
rinoh.paper.A8 = Paper('A8', width=52*MM, height=74*MM)
rinoh.paper.A9 = Paper('A9', width=37*MM, height=52*MM)
rinoh.paper.A10 = Paper('A10', width=26*MM, height=37*MM)
rinoh.paper.LETTER = Paper('letter', width=8.5*INCH, height=11*INCH)
rinoh.paper.LEGAL = Paper('legal', width=8.5*INCH, height=14*INCH)
rinoh.paper.JUNIOR_LEGAL = Paper('junior legal', width=8*INCH,
height=5*INCH)
rinoh.paper.LEDGER = Paper('ledger', width=17*INCH, height=11*INCH)
rinoh.paper.TABLOID = Paper('tabloid', width=11*INCH, height=17*INCH)

```

5.13 Paragraph (rinoh.paragraph)

class rinoh.paragraph.**ParagraphBase** (*custom_label=None, align=None, width=None, id=None, style=None, parent=None, source=None*)

Base class for paragraphs

A paragraph holds styled text and other line elements to be flowed into a container.

style_class

alias of ParagraphStyle

prepare (*flowable_target*)

Determine number labels and register references with the document

render (*container, descender, state, space_below=0, first_line_only=False*)

Typeset the paragraph

The paragraph is typeset in the given container starting below the current cursor position of the container. When the end of the container is reached, the rendering state is preserved to continue setting the rest of the paragraph when this method is called with a new container.

Parameters

container : Container

the container to render to

descender : float or None

descender height of the preceding line

state : ParagraphState

the state where rendering will continue

first_line_only : bool

typeset only the first line

```
class rinoh.paragraph.Paragraph ( content, custom_label=None, align=None, width=None,  
id=None, style=None, parent=None, source=None )
```

```
class rinoh.paragraph.ParagraphState ( paragraph, language, span_index=0,  
group_index=0, nested_flowable_state=None, _first_word=None, _initial=True )
```

5.13.1 Styled Text (`rinoh.text`)

```
class rinoh.text.StyledText ( id=None, style=None, parent=None, source=None )
```

Base class for text that has a `TextStyle` associated with it.

```
to_string ( flowable_target )
```

Return the text content of this styled text.

```
is_script ( container )
```

Returns `True` if this styled text is super/subscript.

```
script_level ( container )
```

Nesting level of super/subscript.

```
height ( container )
```

Font size after super/subscript size adjustment.

```
y_offset ( container )
```

Vertical baseline offset (up is positive).

property items

The list of items in this `StyledText`.

style_class

alias of `TextStyle`

```
class rinoh.text.SingleStyledText ( text, style=None, parent=None, source=None )
```

Text with a single style applied

```
class rinoh.text.MixedStyledText ( text_or_items, id=None, style=None, parent=None,  
source=None )
```

Concatenation of styled text

Parameters

text_or_items : `str`, `StyledText` or iterable of these
mixed styled text

style=None

see `Styled`

parent=None

see `DocumentElement`

```
prepare ( flowable_target )
```

Determine number labels and register references with the document

```
append ( item )
```

Append *item* (`StyledText` or `str`) to the end of this mixed-styled text.

The parent of *item* is set to this mixed-styled text.

property items

The list of items in this `StyledText`.

copy (*parent=None*)
Return a shallow copy of the list.

class rinoh.text.**Locale**
Selects a language

class rinoh.text.**NoBreakAfter** (*iterable=()*, */Positional-only parameter separator (PEP 570)*)
List of words after which no line break will be allowed

5.13.2 Inline Elements (**rinoh.inline**)

class rinoh.inline.**InlineFlowable** (*baseline=None, id=None, style=None, parent=None, source=None*)

style_class
alias of `InlineFlowableStyle`

5.13.3 Styling Properties

class rinoh.paragraph.**TextAlign**
Text justification
Accepts: left, right, center, justify

Line Spacing

class rinoh.paragraph.**LineSpacing**
Base class for line spacing types
Line spacing is defined as the distance between the baselines of two consecutive lines of text in a paragraph.

advance (*line, last_descender, container*)
Return the distance between the descender of the previous line and the baseline of the current line.

class rinoh.paragraph.**DefaultSpacing**
The default line spacing as specified by the font.

advance (*line, last_descender, container*)
Return the distance between the descender of the previous line and the baseline of the current line.

class rinoh.paragraph.**ProportionalSpacing** (*factor*)
Line spacing proportional to the line height
Parameters

factor : float
amount by which the line height is multiplied to obtain the line spacing

advance (*line, last_descender, container*)
Return the distance between the descender of the previous line and the baseline of the current line.

class rinoh.paragraph.**FixedSpacing** (*pitch, minimum=ProportionalSpacing(1.0)*)
Fixed line spacing, with optional minimum spacing

Parameters

pitch : Dimension

the distance between the baseline of two consecutive lines of text

minimum : LineSpacing

the minimum line spacing to prevents lines with large fonts (or inline elements) from overlapping; set to `None` if no minimum is required, set to *None*

advance (line, last_descender, container)

Return the distance between the descender of the previous line and the baseline of the current line.

class rinoh.paragraph.Leading (leading)

Line spacing determined by the space in between two lines

Parameters

leading : Dimension

the space between the bottom of a line and the top of the next line of text

advance (line, last_descender, container)

Return the distance between the descender of the previous line and the baseline of the current line.

The following standard line spacings have been predefined:

`rinoh.paragraph.DEFAULT = DefaultSpacing()`

The default line spacing as specified by the font.

`rinoh.paragraph.STANDARD = ProportionalSpacing(1.2)`

Line spacing of 1.2 times the line height.

`rinoh.paragraph.SINGLE = ProportionalSpacing(1.0)`

Line spacing equal to the line height (no leading).

`rinoh.paragraph.DOUBLE = ProportionalSpacing(2.0)`

Line spacing of double the line height.

Tabulation

class rinoh.paragraph.TabAlign

Alignment of text with respect to a tab stop

Accepts: left, right, center

class rinoh.paragraph.TabStop (position, align='left', fill=None)

Horizontal position for aligning text of successive lines

Parameters

position

tab stop position

align : TabAlign

the alignment of text with respect to the tab stop position

fill : str

string pattern to fill the empty tab space with

get_position (line_width)

Return the absolute position of this tab stop.

```
class rinoh.paragraph.TabStopList ( iterable= (), / )
    List of tab stop positions (with alignment and fill string)
```

5.13.4 Rendering Internals

```
class rinoh.paragraph.Glyph ( metrics, width, char )

class rinoh.paragraph.GlyphsSpan ( span, chars_to_glyphs, glyphs= [ ] )
```

5.13.5 Miscellaneous Internals

```
class rinoh.paragraph.HyphenatorStore
```

5.14 Cross-References and Fields (rinoh.reference)

```
class rinoh.reference.Reference ( target_id, *args, **kwargs )

class rinoh.reference.ReferenceStyle ( base=None, **attributes )
    Style class for Reference

type
    How the reference should be displayed
    Accepts ReferenceType: reference, number, title, page, custom
    Default: reference

link
    Create a hyperlink to the reference target
    Accepts Bool: true or false
    Default: true

quiet
    If the given reference type does not exist for the target, resolve to an empty string instead of making a fuss about it
    Accepts Bool: true or false
    Default: false

typeface
    Typeface to set the text in (inherited from TextStyle)
    Accepts Typeface: the name of a typeface. See rinoh --list-fonts for a list of the available typefaces.
    Default: Times

font_weight
    Thickness of character outlines relative to their height (inherited from TextStyle)
    Accepts FontWeight: hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black
    Default: 500

font_slant
    Slope style of the font (inherited from TextStyle)
    Accepts FontSlant: upright, oblique, italic
    Default: upright
```

font_width

Stretch of the characters (inherited from `TextStyle`)

Accepts `FontWidth`: ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded

Default: 5

font_size

Height of characters (inherited from `TextStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 10pt

font_color

Color of the font (inherited from `TextStyle`)

Accepts `Color`: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: #000

font_variant

Variant of the font (inherited from `TextStyle`)

Accepts `FontVariant`: normal, small capital, oldstyle figures

Default: normal

position

Vertical text position (inherited from `TextStyle`)

Accepts `TextPosition`: normal, superscript, subscript

Default: normal

kerning

Improve inter-letter spacing (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

ligatures

Run letters together where possible (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

character_spacing

Additional spacing between characters (inherited from `TextStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0pt

hyphenate

Allow words to be broken over two lines (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

hyphen_chars

Minimum number of characters in a hyphenated part of a word (inherited from `TextStyle`)

Accepts `Integer`: a natural number (positive integer)

Default: 2

hyphen_lang

Language to use for hyphenation. Accepts locale codes such as 'en_US' (inherited from

TextStyle)
Accepts `Locale`: locale identifier in the <language ID>_<region ID> format
Default: en_US

no_break_after

Prevent a line break after these words (inherited from `TextStyle`)
Accepts `NoBreakAfter`: language-default, or a space-separated list of words
Default: language-default

before

Item to insert before this one (inherited from `InlineStyle`)
Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

after

Item to insert after this one (inherited from `InlineStyle`)
Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

hide

Suppress rendering this element (inherited from `Style`)
Accepts `Bool`: true or false
Default: false

number_format

How numbers are formatted (inherited from `NumberStyle`)
Accepts `NumberFormat`: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman
Default: number

label_prefix

Text to prepend to the label (inherited from `LabelStyle`)
Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

label_suffix

Text to append to the label (inherited from `LabelStyle`)
Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

custom_label

Use a custom label if specified (inherited from `LabelStyle`)
Accepts `Bool`: true or false
Default: false

```
class rinoh.reference.ReferenceField ( type=None, custom_title=None, style=None,
parent=None, source=None )
```

```

class rinoh.reference.ReferenceText ( id=None, style=None, parent=None, source=None
)

class rinoh.reference.ReferenceType
    Accepts: reference, number, title, page, custom

class rinoh.reference.ReferenceParagraph ( target_id_or_flowable, id=None,
style=None, parent=None )

    style_class
        alias of ReferencingParagraphStyle

    target_style ( document )
        Filter selection on the style attribute of the target flowable

    target_has_class ( document )
        Filter selection on a class of the target flowable

    target_has_classes ( document )
        Filter selection on a set of classes of the target flowable

    target_is_of_type ( document )
        Filter selection on the type of the target flowable

class rinoh.reference.Note ( flowable, id=None, style=None, parent=None )

    style_class
        alias of NoteStyle

    flow ( container, last_descender, state=None, footnote=False, **kwargs )
        Flow this flowable into container and return the vertical space consumed.
        The flowable's contents are preceded by a vertical space with a height as specified in its
        style's space_above attribute. Similarly, the flowed content is followed by a vertical space
        with a height given by the space_below style attribute.

class rinoh.reference.NoteStyle ( base=None, **attributes )
    Style class for Note

    location
        Where to place the note
        Accepts NoteLocation: in-place, footer
        Default: footer

    label
        Custom label to override the default (inherited from LabeledFlowableStyle)
        Accepts FlowablesList: Python source code that represents a list of Flowables
        Default: none

    label_position
        Where to place the label (inherited from LabeledFlowableStyle)
        Accepts LabelPosition: left, right
        Default: left

    label_min_width
        Minimum label width (inherited from LabeledFlowableStyle)
        Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
        Default: 12pt

```

label_max_width

Maximum label width (inherited from `LabeledFlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 80pt

label_spacing

Spacing between a label and the labeled flowable (inherited from `LabeledFlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3pt

align_baselines

Line up the baselines of the label and the labeled flowable (inherited from `LabeledFlowableStyle`)

Accepts Bool: true or false

Default: true

wrap_label

Wrap the label at *label_max_width* (inherited from `LabeledFlowableStyle`)

Accepts Bool: true or false

Default: false

width

Width to render the flowable at (inherited from `FlowableStyle`)

Accepts FlowableWidth: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: auto

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts HorizontalAlignment: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts Bool: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (Dimension) and color (Color) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (Dimension) and color (Color) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (Dimension) and color (Color) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (Dimension) and color (Color) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (Dimension) and color (Color) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts Color: HEX string with optional alpha component (`#RRGGBB`, `#RRGGBBAA`, `#RGB` or `#RGBA`)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts Break: none, any, left, right, any restart, left restart, right restart

Default: None

hide

Suppress rendering this element (inherited from `Style`)

Accepts Bool: true or false

Default: false

```
class rinoh.reference.NoteMarkerBase ( custom_label=None, **kwargs )
```

style_class

alias of `NoteMarkerStyle`

prepare (flowable_target)

Determine number labels and register references with the document

```
class rinoh.reference.NoteMarkerByID ( target_id, *args, **kwargs )
```

```
class rinoh.reference.NoteMarkerWithNote ( referenceable, type= 'number' , **kwargs )
```

prepare (flowable_target)

Determine number labels and register references with the document

```
class rinoh.reference.Field ( type, id=None, style=None, parent=None, source=None )
```

5.15 Structure (`rinoh.structure`)

5.15.1 Sections

```
class rinoh.structure.Section ( flowables, align=None, width=None, id=None, style=None, parent=None, source=None )
```

A subdivision of a document

A section usually has a heading associated with it, which is optionally numbered.

```
class rinoh.structure.Heading ( content, custom_label=None, align=None, width=None, id=None, style=None, parent=None, source=None )
```

The title for a section

Parameters

content : `StyledText`

this heading's text

style_class

alias of `HeadingStyle`

prepare (*container*)

Determine number labels and register references with the document

flow (*container*, *last_descender*, *state=None*, ***kwargs*)

Flow this flowable into *container* and return the vertical space consumed.

The flowable's contents are preceded by a vertical space with a height as specified in its style's *space_above* attribute. Similarly, the flowed content is followed by a vertical space with a height given by the *space_below* style attribute.

5.15.2 Lists

```
class rinoh.structure.List ( list_items, start_index=1, id=None, style=None, parent=None )
```

style_class

alias of `ListStyle`

```
class rinoh.structure.ListStyle ( base=None, **attributes )
```

Style class for `List`

ordered

This list is ordered or unordered

Accepts Bool: true or false

Default: false

bullet

Bullet to use in unordered lists

Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: '•'

width

Width to render the flowable at (inherited from `GroupedFlowablesStyle`)

Accepts FlowableWidth: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: fill

title

Title to precede the flowables (inherited from `GroupedFlowablesStyle`)

Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

flowable_spacing

Spacing between flowables (inherited from `GroupedFlowablesStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

same_page

Keep all flowables on a single page, if possible. (inherited from `GroupedFlowablesStyle`)

Accepts Bool: true or false

Default: false

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts `HorizontalAlignment`: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts `Bool`: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts Color: HEX string with optional alpha component (`#RRGGBB`, `#RRGGBBAA`, `#RGB` or `#RGBA`)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts Break: none, any, left, right, any restart, left restart, right restart

Default: None

hide

Suppress rendering this element (inherited from `Style`)

Accepts Bool: true or false

Default: false

number_format

How numbers are formatted (inherited from `NumberStyle`)

Accepts NumberFormat: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: number

label_prefix

Text to prepend to the label (inherited from `LabelStyle`)

Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

label_suffix

Text to append to the label (inherited from `LabelStyle`)
Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

custom_label

Use a custom label if specified (inherited from `LabelStyle`)
Accepts Bool: true or false
Default: false

```
class rinoh.structure.ListItem ( flowable, id=None, style=None, parent=None )
```

```
class rinoh.structure.ListItemLabel ( custom_label=None, align=None, width=None, id=None, style=None, parent=None, source=None )
```

style_class

alias of `ListItemLabelStyle`

```
class rinoh.structure.ListItemLabelStyle ( base=None, **attributes )
```

Style class for `ListItemLabel`

number_separator

Characters inserted between the number label of this element's parent and this element's own number label. If `None`, only show this item's number label. (inherited from `ParagraphStyle`)
Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value) (overrides `ParagraphStyle` default)

width

Width to render the flowable at (inherited from `ParagraphStyle`)
Accepts FlowableWidth: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: fill

indent_first

Indentation of the first line of text (inherited from `ParagraphStyle`)
Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0pt

line_spacing

Spacing between the baselines of two successive lines of text (inherited from `ParagraphStyle`)
Accepts LineSpacing: a predefined line spacing type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: <spacing type>(<arg1>, <arg2>, ...)
Default: default

text_align

Alignment of text to the margins (inherited from `ParagraphStyle`)

Accepts TextAlign: left, right, center, justify
Default: justify

tab_stops

List of tab positions (inherited from ParagraphStyle)

Accepts TabStopList: a comma-separated list of tab stops. A tab stop is specified as <position> [align] [fill string], where position (Dimension) is required and align (TabAlign) and fill string (string enclosed in quotes) are optional.

Default: (no value)

split_minimum_lines

Minimum number of lines to keep together when splitting a paragraph across pages (inherited from ParagraphStyle)

Accepts Integer: a natural number (positive integer)

Default: (no value)

number_format

How numbers are formatted (inherited from ParagraphStyle)

Accepts NumberFormat: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: None

numbering_level

At which section level to restart numbering (positive: absolute, negative: relative) (inherited from ParagraphStyle)

Accepts Integer: a natural number (positive integer)

Default: (no value)

horizontal_align

Horizontal alignment of the flowable (inherited from FlowableStyle)

Accepts HorizontalAlignment: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from FlowableStyle)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from FlowableStyle)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from FlowableStyle)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from FlowableStyle)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from FlowableStyle)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts Bool: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (Dimension) and color (Color) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (Dimension) and color (Color) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (Dimension) and color (Color) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (Dimension) and color (Color) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (Dimension) and color (Color) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts Color: HEX string with optional alpha component (`#RRGGBB`, `#RRGGBBAA`, `#RGB` or `#RGBA`)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts Break: none, any, left, right, any restart, left restart, right restart

Default: None

label_prefix

Text to prepend to the label (inherited from `LabelStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or '), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

label_suffix

Text to append to the label (inherited from `LabelStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or '), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

custom_label

Use a custom label if specified (inherited from `LabelStyle`)

Accepts Bool: true or false

Default: false

typeface

Typeface to set the text in (inherited from `TextStyle`)

Accepts Typeface: the name of a typeface. See `rinoh --list-fonts` for a list of the available typefaces.

Default: Times

font_weight

Thickness of character outlines relative to their height (inherited from `TextStyle`)

Accepts `FontWeight`: hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black

Default: 500

font_slant

Slope style of the font (inherited from `TextStyle`)

Accepts `FontSlant`: upright, oblique, italic

Default: upright

font_width

Stretch of the characters (inherited from `TextStyle`)

Accepts `FontWidth`: ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded

Default: 5

font_size

Height of characters (inherited from `TextStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 10pt

font_color

Color of the font (inherited from `TextStyle`)

Accepts `Color`: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: #000

font_variant

Variant of the font (inherited from `TextStyle`)

Accepts `FontVariant`: normal, small capital, oldstyle figures

Default: normal

position

Vertical text position (inherited from `TextStyle`)

Accepts `TextPosition`: normal, superscript, subscript

Default: normal

kerning

Improve inter-letter spacing (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

ligatures

Run letters together where possible (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

character_spacing

Additional spacing between characters (inherited from `TextStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0pt

hyphenate

Allow words to be broken over two lines (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

hyphen_chars

Minimum number of characters in a hyphenated part of a word (inherited from `TextStyle`)

Accepts `Integer`: a natural number (positive integer)

Default: 2

hyphen_lang

Language to use for hyphenation. Accepts locale codes such as 'en_US' (inherited from `TextStyle`)

Accepts `Locale`: locale identifier in the <language ID>_<region ID> format

Default: en_US

no_break_after

Prevent a line break after these words (inherited from `TextStyle`)

Accepts `NoBreakAfter`: language-default, or a space-separated list of words

Default: language-default

before

Item to insert before this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

after

Item to insert after this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

hide

Suppress rendering this element (inherited from `Style`)

Accepts `Bool`: true or false

Default: false

```
class rinoh.structure.DefinitionList ( flowables, align=None, width=None, id=None,
style=None, parent=None, source=None )
```

5.15.3 Table of Contents

```
class rinoh.structure.TableOfContentsSection
```

```
class rinoh.structure.TableOfContents ( local=False, id=None, style=None,
parent=None )
```

style_class

alias of `TableOfContentsStyle`

flowables (*container*)

Generator yielding the Flowables to group

```
class rinoh.structure.TableOfContentsEntry ( flowable, id=None, style=None,
parent=None )
```

style_class

alias of `TableOfContentsEntryStyle`

5.15.4 List of ...

```
class rinoh.structure.ListOfStyle ( base=None, **attributes )
```

Style class for `ListOf`

width

Width to render the flowable at (inherited from `GroupedFlowablesStyle`)

Accepts `FlowableWidth`: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: fill

title

Title to precede the flowables (inherited from `GroupedFlowablesStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

flowable_spacing

Spacing between flowables (inherited from `GroupedFlowablesStyle`)
Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

same_page

Keep all flowables on a single page, if possible. (inherited from `GroupedFlowablesStyle`)
Accepts `Bool`: true or false
Default: false

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)
Accepts `HorizontalAlignment`: left, right, center
Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)
Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)
Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)
Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)
Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding

Padding (inherited from `FlowableStyle`)
Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)
Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)
Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts Bool: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts Color: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts Break: none, any, left, right, any restart, left restart, right restart

Default: None

hide

Suppress rendering this element (inherited from `Style`)

Accepts `Bool`: true or false

Default: false

indent_first

Indentation of the first line of text (inherited from `ParagraphStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0pt

line_spacing

Spacing between the baselines of two successive lines of text (inherited from `ParagraphStyle`)

Accepts `LineSpacing`: a predefined line spacing type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: <spacing type>(<arg1>, <arg2>, ...)

Default: default

text_align

Alignment of text to the margins (inherited from `ParagraphStyle`)

Accepts `TextAlign`: left, right, center, justify

Default: justify

tab_stops

List of tab positions (inherited from `ParagraphStyle`)

Accepts `TabStopList`: a comma-separated list of tab stops. A tab stop is specified as <position> [align] [fill string], where position (`Dimension`) is required and align (`TabAlign`) and fill string (string enclosed in quotes) are optional.

Default: (no value)

split_minimum_lines

Minimum number of lines to keep together when splitting a paragraph across pages (inherited from `ParagraphStyle`)

Accepts `Integer`: a natural number (positive integer)

Default: (no value)

number_format

How numbers are formatted (inherited from `ParagraphStyle`)

Accepts `NumberFormat`: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman

Default: None

number_separator

Characters inserted between the number label of this element's parent and this element's own number label. If None, only show this item's number label. (inherited from `ParagraphStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: ' . '

numbering_level

At which section level to restart numbering (positive: absolute, negative: relative) (inherited from `ParagraphStyle`)

Accepts Integer: a natural number (positive integer)
Default: (no value)

label_prefix

Text to prepend to the label (inherited from `LabelStyle`)
Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

label_suffix

Text to append to the label (inherited from `LabelStyle`)
Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

custom_label

Use a custom label if specified (inherited from `LabelStyle`)
Accepts Bool: true or false
Default: false

typeface

Typeface to set the text in (inherited from `TextStyle`)
Accepts Typeface: the name of a typeface. See `rinoh --list-fonts` for a list of the available typefaces.
Default: Times

font_weight

Thickness of character outlines relative to their height (inherited from `TextStyle`)
Accepts FontWeight: hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black
Default: 500

font_slant

Slope style of the font (inherited from `TextStyle`)
Accepts FontSlant: upright, oblique, italic
Default: upright

font_width

Stretch of the characters (inherited from `TextStyle`)
Accepts FontWidth: ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded
Default: 5

font_size

Height of characters (inherited from `TextStyle`)
Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 10pt

font_color

Color of the font (inherited from `TextStyle`)
Accepts Color: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)
Default: #000

font_variant

Variant of the font (inherited from `TextStyle`)

Accepts `FontVariant`: normal, small capital, oldstyle figures

Default: normal

position

Vertical text position (inherited from `TextStyle`)

Accepts `TextPosition`: normal, superscript, subscript

Default: normal

kerning

Improve inter-letter spacing (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

ligatures

Run letters together where possible (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

character_spacing

Additional spacing between characters (inherited from `TextStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0pt

hyphenate

Allow words to be broken over two lines (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

hyphen_chars

Minimum number of characters in a hyphenated part of a word (inherited from `TextStyle`)

Accepts `Integer`: a natural number (positive integer)

Default: 2

hyphen_lang

Language to use for hyphenation. Accepts locale codes such as 'en_US' (inherited from `TextStyle`)

Accepts `Locale`: locale identifier in the <language ID>_<region ID> format

Default: en_US

no_break_after

Prevent a line break after these words (inherited from `TextStyle`)

Accepts `NoBreakAfter`: language-default, or a space-separated list of words

Default: language-default

before

Item to insert before this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

after

Item to insert after this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

class `rinoh.structure.ListOfEntryStyle` (*base=None, **attributes*)

Style class for `ListOfEntry`

text

The text content of this paragraph (inherited from `ReferencingParagraphStyle`)
Accepts `ReferenceText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: '{REFERENCE}' : '{TITLE}' '\t' '{PAGE}' (overrides `ReferencingParagraphStyle` default)

width

Width to render the flowable at (inherited from `ParagraphStyle`)
Accepts `FlowableWidth`: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: fill

indent_first

Indentation of the first line of text (inherited from `ParagraphStyle`)
Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0pt

line_spacing

Spacing between the baselines of two successive lines of text (inherited from `ParagraphStyle`)
Accepts `LineSpacing`: a predefined line spacing type or the name of a line spacing type followed by comma-separated arguments enclosed in braces: <spacing type>(<arg1>, <arg2>, ...)
Default: default

text_align

Alignment of text to the margins (inherited from `ParagraphStyle`)
Accepts `TextAlign`: left, right, center, justify
Default: justify

tab_stops

List of tab positions (inherited from `ParagraphStyle`)
Accepts `TabStopList`: a comma-separated list of tab stops. A tab stop is specified as <position> [align] [fill string], where position (`Dimension`) is required and align (`TabAlign`) and fill string (string enclosed in quotes) are optional.
Default: (no value)

split_minimum_lines

Minimum number of lines to keep together when splitting a paragraph across pages (inherited from `ParagraphStyle`)
Accepts `Integer`: a natural number (positive integer)
Default: (no value)

number_format

How numbers are formatted (inherited from `ParagraphStyle`)
Accepts `NumberFormat`: none, number, symbol, lowercase character,

uppercase character, lowercase roman, uppercase roman
Default: None

number_separator

Characters inserted between the number label of this element's parent and this element's own number label. If None, only show this item's number label. (inherited from `ParagraphStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: ' . '

numbering_level

At which section level to restart numbering (positive: absolute, negative: relative) (inherited from `ParagraphStyle`)

Accepts `Integer`: a natural number (positive integer)

Default: (no value)

horizontal_align

Horizontal alignment of the flowable (inherited from `FlowableStyle`)

Accepts `HorizontalAlignment`: left, right, center

Default: left

space_above

Vertical space preceding the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

space_below

Vertical space following the flowable (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_left

Left margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

margin_right

Right margin (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding

Padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_left

Left padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_right

Right padding (inherited from `FlowableStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_top

Top padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

padding_bottom

Bottom padding (inherited from `FlowableStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from `FlowableStyle`)

Accepts Bool: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts Color: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts Break: none, any, left, right, any restart, left restart, right restart

Default: None

label_prefix

Text to prepend to the label (inherited from `LabelStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

label_suffix

Text to append to the label (inherited from `LabelStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

custom_label

Use a custom label if specified (inherited from `LabelStyle`)

Accepts `Bool`: true or false

Default: false

typeface

Typeface to set the text in (inherited from `TextStyle`)

Accepts `Typeface`: the name of a typeface. See `rinoh --list-fonts` for a list of the available typefaces.

Default: Times

font_weight

Thickness of character outlines relative to their height (inherited from `TextStyle`)

Accepts `FontWeight`: hairline, thin, ultra-light, extra-light, light, regular, normal, book, roman, medium, semi-bold, demi-bold, bold, extra-bold, ultra-bold, black, heavy, extra-black, ultra-black

Default: 500

font_slant

Slope style of the font (inherited from `TextStyle`)

Accepts `FontSlant`: upright, oblique, italic

Default: upright

font_width

Stretch of the characters (inherited from `TextStyle`)

Accepts `FontWidth`: ultra-condensed, extra-condensed, condensed, semi-condensed, normal, medium, semi-expanded, expanded, extra-expanded, ultra-expanded

Default: 5

font_size

Height of characters (inherited from `TextStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 10pt

font_color

Color of the font (inherited from `TextStyle`)

Accepts `Color`: HEX string with optional alpha component (#RRGGBB, #RRGGBBAA, #RGB or #RGBA)

Default: #000

font_variant

Variant of the font (inherited from `TextStyle`)

Accepts `FontVariant`: normal, small capital, oldstyle figures

Default: normal

position

Vertical text position (inherited from `TextStyle`)

Accepts `TextPosition`: normal, superscript, subscript

Default: normal

kerning

Improve inter-letter spacing (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

ligatures

Run letters together where possible (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

character_spacing

Additional spacing between characters (inherited from `TextStyle`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0pt

hyphenate

Allow words to be broken over two lines (inherited from `TextStyle`)

Accepts `Bool`: true or false

Default: true

hyphen_chars

Minimum number of characters in a hyphenated part of a word (inherited from `TextStyle`)

Accepts `Integer`: a natural number (positive integer)

Default: 2

hyphen_lang

Language to use for hyphenation. Accepts locale codes such as 'en_US' (inherited from `TextStyle`)

Accepts `Locale`: locale identifier in the <language ID>_<region ID> format

Default: en_US

no_break_after

Prevent a line break after these words (inherited from `TextStyle`)

Accepts `NoBreakAfter`: language-default, or a space-separated list of words

Default: language-default

before

Item to insert before this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

after

Item to insert after this one (inherited from `InlineStyle`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

hide

Suppress rendering this element (inherited from `Style`)
Accepts `Bool`: true or false
Default: false

5.15.5 Admonitions

```
class rinoh.structure.Admonition ( label, flowable, title=None, type=None, id=None,
style=None, parent=None )
```

style_class

alias of `AdmonitionStyle`

5.15.6 Horizontal Rule

```
class rinoh.structure.HorizontalRule ( align=None, width=None, id=None, style=None,
parent=None, source=None )
```

style_class

alias of `HorizontalRuleStyle`

render (*container*, *descender*, *state*, ***kwargs*)

Renders the flowable's content to *container*, with the flowable's top edge lining up with the container's cursor. *descender* is the descender height of the preceding line or *None*.

5.16 Strings (`rinoh.strings`)

```
class rinoh.strings.Strings
```

Stores several `StringCollections`

```
class rinoh.strings.StringField ( key, style=None, parent=None, source=None,
user=False )
```

Styled text that will be substituted with a configured string

The displayed string is either the localized string as determined by the language set for the document or the user-supplied string passed to the `TemplateConfiguration`.

5.17 Style (`rinoh.style`)

```
class rinoh.style.Styled ( id=None, style=None, parent=None, source=None )
```

A document element who's style can be configured.

Parameters

style: `str`, `Style`

the style to associate with this element. If *style* is a string, the corresponding style is lookup up in the document's style sheet by means of selectors.

style_class = None

The `Style` subclass that corresponds to this `Styled` subclass.

property has_id

Filter selection on an ID of this `Styled`

property has_class

Filter selection on a class of this `Styled`

property has_classes

Filter selection on a set of classes of this `Styled`

class `rinoh.style.Style` (*base=None, **attributes*)

Dictionary storing style attributes.

The style attributes associated with this `Style` are specified as class attributes of type `Attribute`.

Style attributes can also be accessed as object attributes.

hide

Suppress rendering this element

Accepts Bool: true or false

Default: false

5.17.1 Style Sheet

class `rinoh.style.StyleSheet` (*name, matcher=None, base=None, source=None, description=None, pygments_style=None, **user_options*)

Dictionary storing a collection of related styles by name.

Styles stored in a `StyleSheet` can refer to their base style by name.

Parameters

name : str

a label for this style sheet

matcher : StyledMatcher

the matcher providing the selectors the styles contained in this style sheet map to.
If no matcher is given and *base* is specified, the *base*'s matcher is used. If *base* is not set, the default matcher is used.

base : StyleSheet or str

the style sheet to extend

description : str

a short string describing this style sheet

pygments_style : str

the Pygments style to use for styling code blocks

get_selector (*name*)

Find a selector mapped to a style in this or a base style sheet.

Parameters

name : str

a style name

Returns

`Selector` – the selector mapped to the style *name*

Raises

KeyError – if the style *name* was not found in this or a base style sheet

class `rinoh.style.StyleSheetFile` (*filename*, *base=None*, *source=None*, ****kwargs**)

Loads styles defined in a *.rts* file (INI format).

Parameters

filename : **str**

the path to the style sheet file

`StyleSheetFile` takes the same optional arguments as `StyleSheet`. These can also be specified in the [STYLESHEET] section of the style sheet file. If an argument is specified in both places, the one passed as an argument overrides the one specified in the style sheet file.

class `rinoh.style.StyledMatcher` (*mapping_or_iterable=None*, ****kwargs**)

Dictionary mapping labels to selectors.

This matcher can be initialized in the same way as a `dict` by passing a mapping, an iterable and/or keyword arguments.

update (****F** [, *E*]) → None. Update *D* from mapping/iterable *E* and *F*.

If *E* is present and has a `.keys()` method, then does: for *k* in *E*.keys(): *D*[*k*] = *E*[*k*] If *E* is present and lacks a `.keys()` method, then does: for *k*, *v* in *E*: *D*[*k*] = *v* In either case, this is followed by: for *k* in *F*: *D*[*k*] = *F*[*k*]

5.18 Tables (`rinoh.table`)

class `rinoh.table.Table` (*body*, *head=None*, *align=None*, *width=None*, *column_widths=None*, *id=None*, *style=None*, *parent=None*)

style_class

alias of `TableStyle`

prepare (*flowable_target*)

Determine number labels and register references with the document

render (*container*, *last_descender*, *state*, *space_below=0*, ****kwargs**)

Renders the flowable's content to *container*, with the flowable's top edge lining up with the container's cursor. *descender* is the descender height of the preceding line or *None*.

class `rinoh.table.TableWithCaption` (*flowables*, *align=None*, *width=None*, *id=None*, *style=None*, *parent=None*, *source=None*)

style_class

alias of `TableWithCaptionStyle`

class `rinoh.table.TableWithCaptionStyle` (*base=None*, ****attributes**)

Style class for `TableWithCaption`

float

Float the flowable to the top or bottom of the current page, to a dedicated page, or sideways to a dedicated page (inherited from `FloatStyle`)

Accepts `FloatLocation`: none, here, sideways

Default: None

width

Width to render the flowable at (inherited from `FlowableStyle`)

Accepts FlowableWidth: auto, fill or a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: auto

horizontal_align

Horizontal alignment of the flowable (inherited from FlowableStyle)
Accepts HorizontalAlignment: left, right, center
Default: left

space_above

Vertical space preceding the flowable (inherited from FlowableStyle)
Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

space_below

Vertical space following the flowable (inherited from FlowableStyle)
Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

margin_left

Left margin (inherited from FlowableStyle)
Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

margin_right

Right margin (inherited from FlowableStyle)
Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding

Padding (inherited from FlowableStyle)
Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_left

Left padding (inherited from FlowableStyle)
Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_right

Right padding (inherited from FlowableStyle)
Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_top

Top padding (inherited from FlowableStyle)
Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

padding_bottom

Bottom padding (inherited from FlowableStyle)
Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 0

keep_with_next

Keep this flowable and the next on the same page (inherited from FlowableStyle)
Accepts Bool: true or false

Default: false

border

Border surrounding the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_left

Border left of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_right

Border right of the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_top

Border above the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

border_bottom

Border below the flowable (inherited from `FlowableStyle`)

Accepts Stroke: the width (`Dimension`) and color (`Color`) of the stroke, separated by a comma (,)

Default: none

background_color

Color of the area within the flowable's borders (inherited from `FlowableStyle`)

Accepts Color: HEX string with optional alpha component (`#RRGGBB`, `#RRGGBBAA`, `#RGB` or `#RGBA`)

Default: none

page_break

Type of page break to insert before rendering this flowable (inherited from `FlowableStyle`)

Accepts Break: none, any, left, right, any restart, left restart, right restart

Default: None

hide

Suppress rendering this element (inherited from `Style`)

Accepts Bool: true or false

Default: false

title

Title to precede the flowables (inherited from `GroupedFlowablesStyle`)

Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

flowable_spacing

Spacing between flowables (inherited from `GroupedFlowablesStyle`)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 0

same_page

Keep all flowables on a single page, if possible. (inherited from `GroupedFlowablesStyle`)

Accepts Bool: true or false

Default: false

```
class rinoh.table.TableSection ( rows, style=None, parent=None )
```

```
    prepare ( flowable_target )
```

Determine number labels and register references with the document

```
class rinoh.table.TableHead ( rows, style=None, parent=None )
```

```
class rinoh.table.TableBody ( rows, style=None, parent=None )
```

```
class rinoh.table.TableRow ( cells, style=None, parent=None )
```

```
    prepare ( flowable_target )
```

Determine number labels and register references with the document

```
    get_rowspanned_columns ( )
```

Return a dictionary mapping column indices to the number of columns spanned.

```
class rinoh.table.TableCell ( flowables, rowspan=1, colspan=1, id=None, style=None,
parent=None )
```

```
    style_class
```

alias of `TableCellStyle`

```
class rinoh.table.TableCellBorder ( rendered_cell, cell_height, position, style=None )
```

```
    style_class
```

alias of `TableCellBorderStyle`

```
class rinoh.table.TableCellBackground ( bottom_left, width, height, style=None,
parent=None )
```

```
    style_class
```

alias of `TableCellBackgroundStyle`

```
class rinoh.table.VerticalAlign
```

Accepts: top, middle, bottom

```
class rinoh.table.ListOfTables ( local=False, id=None, style=None, parent=None )
```

```
class rinoh.table.ListOfTablesSection
```

```
    list_class
```

alias of `ListOfTables`

5.19 Templates (`rinoh.template`)

5.19.1 Documents

Document templates are created by subclassing `DocumentTemplate`, just like the Chapter 4 shipped with `rinoh`.

```
class rinoh.template.DocumentTemplate ( document_tree, configuration=None,
backend=None )
```

Template for documents

Parameters

document_tree : `DocumentTree`

a tree of the document's contents

configuration : `TemplateConfiguration`

configuration for this template

backend=None

the backend used for rendering the document

language

The main language of the document

Accepts `Language`: the code of one of the supported languages

Default: EN (English)

strings

Strings to override standard element names

Accepts `Strings`: strings need to be entered in INI in a section named 'STRINGS'

Default: none

stylesheet

The stylesheet to use for styling document elements

Accepts `StyleSheet`: the name of an Section 3.1 or the filename of a stylesheet file (with the `.rts` extension)

Default: sphinx (= `:data:rinoh.stylesheets.sphinx`)

parts

The parts making up this document

Accepts `PartsList`: a space-separated list of document part template names

Default: (empty list)

Configuration

alias of `DocumentTemplateConfiguration`

ConfigurationFile

alias of `DocumentTemplateConfigurationFile`

Document templates can be customized by setting values for the configuration attributes defined in a `DocumentTemplate` subclass in a `TemplateConfiguration`. An template configuration can be passed as *configuration* on template instantiation. However, it is better to make use of the `document` method, however.

```
class rinoh.template.TemplateConfiguration ( name, base=None, source=None,
template=None, description=None, **options )
```

Stores a configuration for a `DocumentTemplate`

Parameters

name : str
a label for this template configuration

base : TemplateConfiguration
the template configuration to extend

source : str
the source of this configuration (e.g. a file path)

template : DocumentTemplateMeta or str
the document template to configure

description : str
a short string describing this style sheet

****options**
configuration values for the configuration attributes defined by the document template

template = None

The `DocumentTemplate` subclass to configure

document (document_tree, backend=None)

Create a `DocumentTemplate` object based on the given document tree and this template configuration

Parameters

document_tree : DocumentTree
tree of the document's contents

backend=None
the backend to use when rendering the document

class rinoh.template.PartsList (*parts)

Stores the names of the document part templates making up a document

Parameters

parts : list[str]
the names of the document parts

5.19.2 Document Parts

class rinoh.template.DocumentPart (template, document, flowables, last_number_format)

Part of a document.

Parameters

template : DocumentPartTemplate
the template that determines the contents and style of this document part

document : Document
the document this part belongs to

flowables : list[Flowable]
the flowables to render in this document part

configuration_class

alias of `DocumentPartTemplate`

add_page (page)

Append *page* (`Page`) to this `DocumentPart`.

new_page (*page_number*, *chain*, *new_chapter*, *sideways=False*)

Called by `render()` with the Chain's that need more :class:`Container`s. This method should create a new :class:`Page` which contains a container associated with *chain*.

The document part templates which are listed by name in `DocumentTemplate.parts` are looked up as attributes of the `DocumentTemplate` subclass. They are instances of `DocumentPartTemplate` subclasses:

class `rinoh.template.DocumentPartTemplate` (*base=None*, ***attributes*)

A template that produces a document part

The document part is created given a set of flowables, and page templates. The latter are looked up in the `TemplateConfiguration` where this part template was.

page_number_prefix

Text to place in front of the page number.

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

page_number_format

The format for page numbers in this document part.

Accepts `PageNumberFormat`: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman, continue

Default: number

end_at_page

The type of page to end this document part on

Accepts `PageType`: left, right, any

Default: any

drop_if_empty

Exclude this part from the document if it is empty (no flowables)

Accepts `Bool`: true or false

Default: true

The following document part templates are used in the standard document templates:

class `rinoh.template.TitlePartTemplate` (*base=None*, ***attributes*)

The title page of a document.

drop_if_empty

Exclude this part from the document if it is empty (no flowables) (inherited from `DocumentPartTemplate`)

Accepts `Bool`: true or false

Default: false (overrides `DocumentPartTemplate` default)

page_number_prefix

Text to place in front of the page number. (inherited from `DocumentPartTemplate`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

page_number_format

The format for page numbers in this document part. (inherited from `DocumentPartTemplate`)

Accepts PageNumberFormat: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman, continue
Default: number

end_at_page

The type of page to end this document part on (inherited from DocumentPartTemplate)

Accepts PageType: left, right, any

Default: any

class rinoh.template.**ContentsPartTemplate** (*base=None, **attributes*)

The body of a document.

Renders all of the content present in the DocumentTree passed to the DocumentTemplate.

page_number_prefix

Text to place in front of the page number. (inherited from DocumentPartTemplate)

Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

page_number_format

The format for page numbers in this document part. (inherited from DocumentPartTemplate)

Accepts PageNumberFormat: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman, continue

Default: number

end_at_page

The type of page to end this document part on (inherited from DocumentPartTemplate)

Accepts PageType: left, right, any

Default: any

drop_if_empty

Exclude this part from the document if it is empty (no flowables) (inherited from DocumentPartTemplate)

Accepts Bool: true or false

Default: true

class rinoh.template.**FixedDocumentPartTemplate** (*base=None, **attributes*)

A document part template that renders a fixed list of flowables

flowables

The list of flowables to include in this document part

Accepts FlowablesList: Python source code that represents a list of Flowables

Default: []

page_number_prefix

Text to place in front of the page number. (inherited from DocumentPartTemplate)

Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

page_number_format

The format for page numbers in this document part. (inherited from DocumentPartTemplate)

Accepts PageNumberFormat: none, number, symbol, lowercase character, uppercase character, lowercase roman, uppercase roman, continue

Default: number

end_at_page

The type of page to end this document part on (inherited from DocumentPartTemplate)

Accepts PageType: left, right, any

Default: any

drop_if_empty

Exclude this part from the document if it is empty (no flowables) (inherited from DocumentPartTemplate)

Accepts Bool: true or false

Default: true

5.19.3 Page Templates

The document templates make use of page templates:

```
class rinoh.template.BodyPageTemplateBase ( base=None, **attributes )
```

header_footer_distance

Distance of the header and footer to the content area

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 14pt

columns

The number of columns for the body text

Accepts Integer: a natural number (positive integer)

Default: 1

column_spacing

The spacing between columns

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 1cm

header_text

The text to place in the page header

Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: '{SECTION_NUMBER(1)}' ' ' ' '{SECTION_TITLE(1)}'

footer_text

The text to place in the page footer

Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: '\t' '{PAGE_NUMBER}' ' / ' '{NUMBER_OF_PAGES}'

page_size

The format of the pages in the document (inherited from PageTemplateBase)

Accepts Paper: the name of a Section 5.12 or <width> * <height> where width and height are Dimensions

Default: A4

page_orientation

The orientation of pages in the document (inherited from PageTemplateBase)

Accepts PageOrientation: portrait, landscape

Default: portrait

left_margin

The margin size on the left of the page (inherited from PageTemplateBase)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

right_margin

The margin size on the right of the page (inherited from PageTemplateBase)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

top_margin

The margin size at the top of the page (inherited from PageTemplateBase)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

bottom_margin

The margin size at the bottom of the page (inherited from PageTemplateBase)

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

background

An image to place in the background of the page (inherited from PageTemplateBase)

Accepts BackgroundImage: filename of an image file enclosed in quotes, optionally followed by space-delimited keyword arguments (<keyword>=<value>) that determine how the image is displayed

Default: none

after_break_background

An image to place in the background after a page break (inherited from PageTemplateBase)

Accepts BackgroundImage: filename of an image file enclosed in quotes, optionally followed by space-delimited keyword arguments (<keyword>=<value>) that determine how the image is displayed

Default: none

sideways

Rotate sideways pages to the left or right (inherited from PageTemplateBase)

Accepts Sideways: left, right

Default: right

class rinoh.template.BodyPageTemplate (base=None, **attributes)

chapter_header_text

The text to place in the header on a page that starts a new chapter

Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

chapter_footer_text

The text to place in the footer on a page that starts a new chapter

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: (no value)

chapter_title_flowables

Generator that yields the flowables to represent the chapter title

Accepts `FlowablesList`: Python source code that represents a list of `Flowables`

Default: none

chapter_title_height

The height of the container holding the chapter title

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: none

header_footer_distance

Distance of the header and footer to the content area (inherited from `BodyPageTemplateBase`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 14pt

columns

The number of columns for the body text (inherited from `BodyPageTemplateBase`)

Accepts `Integer`: a natural number (positive integer)

Default: 1

column_spacing

The spacing between columns (inherited from `BodyPageTemplateBase`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 1cm

header_text

The text to place in the page header (inherited from `BodyPageTemplateBase`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: '{SECTION_NUMBER(1)}' ' ' ' '{SECTION_TITLE(1)}'

footer_text

The text to place in the page footer (inherited from `BodyPageTemplateBase`)

Accepts `StyledText`: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)

Default: '\t' '{PAGE_NUMBER}' ' / ' '{NUMBER_OF_PAGES}'

page_size

The format of the pages in the document (inherited from `PageTemplateBase`)

Accepts `Paper`: the name of a Section 5.12 or <width> * <height> where width and height are `Dimensions`

Default: A4

page_orientation

The orientation of pages in the document (inherited from `PageTemplateBase`)

Accepts PageOrientation: portrait, landscape
Default: portrait

left_margin

The margin size on the left of the page (inherited from PageTemplateBase)
Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 3cm

right_margin

The margin size on the right of the page (inherited from PageTemplateBase)
Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 3cm

top_margin

The margin size at the top of the page (inherited from PageTemplateBase)
Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 3cm

bottom_margin

The margin size at the bottom of the page (inherited from PageTemplateBase)
Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)
Default: 3cm

background

An image to place in the background of the page (inherited from PageTemplateBase)
Accepts BackgroundImage: filename of an image file enclosed in quotes, optionally followed by space-delimited keyword arguments (<keyword>=<value>) that determine how the image is displayed
Default: none

after_break_background

An image to place in the background after a page break (inherited from PageTemplateBase)
Accepts BackgroundImage: filename of an image file enclosed in quotes, optionally followed by space-delimited keyword arguments (<keyword>=<value>) that determine how the image is displayed
Default: none

sideways

Rotate sideways pages to the left or right (inherited from PageTemplateBase)
Accepts Sideways: left, right
Default: right

class rinoh.template.TitlePageTemplate (base=None, **attributes)

extra

Extra text to include on the title page below the title
Accepts StyledText: a list of styled text strings, separated by spaces. A styled text string is a quoted string (' or "), optionally followed by a style name enclosed in braces: 'text string' (style name)
Default: (no value)

page_size

The format of the pages in the document (inherited from PageTemplateBase)
Accepts Paper: the name of a Section 5.12 or <width> * <height> where width and height are Dimensions

Default: A4

page_orientation

The orientation of pages in the document (inherited from `PageTemplateBase`)

Accepts `PageOrientation`: portrait, landscape

Default: portrait

left_margin

The margin size on the left of the page (inherited from `PageTemplateBase`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

right_margin

The margin size on the right of the page (inherited from `PageTemplateBase`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

top_margin

The margin size at the top of the page (inherited from `PageTemplateBase`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

bottom_margin

The margin size at the bottom of the page (inherited from `PageTemplateBase`)

Accepts `Dimension`: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

background

An image to place in the background of the page (inherited from `PageTemplateBase`)

Accepts `BackgroundImage`: filename of an image file enclosed in quotes, optionally followed by space-delimited keyword arguments (<keyword>=<value>) that determine how the image is displayed

Default: none

after_break_background

An image to place in the background after a page break (inherited from `PageTemplateBase`)

Accepts `BackgroundImage`: filename of an image file enclosed in quotes, optionally followed by space-delimited keyword arguments (<keyword>=<value>) that determine how the image is displayed

Default: none

sideways

Rotate sideways pages to the left or right (inherited from `PageTemplateBase`)

Accepts `Sideways`: left, right

Default: right

The base class for these collects the common options:

```
class rinoh.template.PageTemplateBase ( base=None, **attributes )
```

page_size

The format of the pages in the document

Accepts `Paper`: the name of a Section 5.12 or <width> * <height> where width and height are `Dimensions`

Default: A4

page_orientation

The orientation of pages in the document

Accepts PageOrientation: portrait, landscape

Default: portrait

left_margin

The margin size on the left of the page

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

right_margin

The margin size on the right of the page

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

top_margin

The margin size at the top of the page

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

bottom_margin

The margin size at the bottom of the page

Accepts Dimension: a numeric value followed by a unit (pt, in, pc, mm, cm, %, /2, /4)

Default: 3cm

background

An image to place in the background of the page

Accepts BackgroundImage: filename of an image file enclosed in quotes, optionally followed by space-delimited keyword arguments (<keyword>=<value>) that determine how the image is displayed

Default: none

after_break_background

An image to place in the background after a page break

Accepts BackgroundImage: filename of an image file enclosed in quotes, optionally followed by space-delimited keyword arguments (<keyword>=<value>) that determine how the image is displayed

Default: none

sideways

Rotate sideways pages to the left or right

Accepts Sideways: left, right

Default: right

Python Module Index

r

rinoh

- rinoh.attribute, 99
- rinoh.color, 100
- rinoh.dimension, 100
- rinoh.document, 101
- rinoh.draw, 103
- rinoh.flowable, 103
- rinoh.font, 106
- rinoh.font.style, 108
- rinoh.image, 108
- rinoh.index, 110
- rinoh.inline, 117
- rinoh.language, 110
- rinoh.number, 113
- rinoh.paper, 114
- rinoh.paragraph, 115
- rinoh.reference, 119
- rinoh.strings, 145
- rinoh.structure, 125
- rinoh.style, 145
- rinoh.stylesheets, 11
- rinoh.table, 147
- rinoh.template, 151
- rinoh.templates.article, 93
- rinoh.templates.book, 94
- rinoh.text, 116

Index

Symbols

- docs
 - rinoh command line option, 6
- format
 - rinoh command line option, 5
- help
 - rinoh command line option, 5
- install-resources
 - rinoh command line option, 5
- list-fonts
 - rinoh command line option, 6
- list-formats
 - rinoh command line option, 6
- list-options
 - rinoh command line option, 6
- list-stylesheets
 - rinoh command line option, 5
- list-templates
 - rinoh command line option, 5
- option
 - rinoh command line option, 5
- output
 - rinoh command line option, 5
- paper
 - rinoh command line option, 5
- stylesheet
 - rinoh command line option, 5
- template
 - rinoh command line option, 5
- version
 - rinoh command line option, 6
- versions
 - rinoh command line option, 6
- f
 - rinoh command line option, 5
- h
 - rinoh command line option, 5
- i
 - rinoh command line option, 5
- O
 - rinoh command line option, 5
- o

- rinoh command line option, 5
- P
 - rinoh command line option, 5
- s
 - rinoh command line option, 5
- t
 - rinoh command line option, 5

A

- A0 (in module rinoh.paper), 114
- A1 (in module rinoh.paper), 114
- A10 (in module rinoh.paper), 115
- A2 (in module rinoh.paper), 114
- A3 (in module rinoh.paper), 114
- A4 (in module rinoh.paper), 115
- A5 (in module rinoh.paper), 115
- A6 (in module rinoh.paper), 115
- A7 (in module rinoh.paper), 115
- A8 (in module rinoh.paper), 115
- A9 (in module rinoh.paper), 115
- abstract_location (rinoh.templates.article.Article attribute), 93
- AbstractLocation (class in rinoh.templates.article), 94
- AcceptNoneAttributeType (class in rinoh.attribute), 99
- add_page() (rinoh.template.DocumentPart method), 152
- Admonition (class in rinoh.structure), 145
- AdmonitionStyle (class in rinoh.structure), 82
- advance() (rinoh.paragraph.DefaultSpacing method), 117
- advance() (rinoh.paragraph.FixedSpacing method), 118
- advance() (rinoh.paragraph.Leading method), 118
- advance() (rinoh.paragraph.LineSpacing method), 117
- advance() (rinoh.paragraph.ProportionalSpacing method), 117
- after (rinoh.image.CaptionStyle attribute), 33
- after (rinoh.inline.InlineFlowableStyle attribute), 48
- after (rinoh.paragraph.ParagraphStyle attribute), 43
- after (rinoh.reference.NoteMarkerStyle attribute), 55
- after (rinoh.reference.ReferenceStyle attribute), 121
- after (rinoh.reference.ReferencingParagraphStyle attribute), 53
- after (rinoh.structure.HeadingStyle attribute), 63
- after (rinoh.structure.ListItemLabelStyle attribute), 71, 134
- after (rinoh.structure.ListOfEntryStyle attribute), 144
- after (rinoh.structure.ListOfStyle attribute), 139
- after (rinoh.structure.TableOfContentsEntryStyle attribute), 81
- after (rinoh.structure.TableOfContentsStyle attribute), 76
- after (rinoh.text.TextStyle attribute), 45
- after_break_background (rinoh.template.BodyPageTemplate attribute), 158
- after_break_background (rinoh.template.BodyPageTemplateBase attribute), 156
- after_break_background (rinoh.template.PageTemplateBase attribute), 160
- after_break_background (rinoh.template.TitlePageTemplate attribute), 159
- align (rinoh.image.ImageArgs attribute), 109
- align_baselines (rinoh.flowable.LabeledFlowableStyle attribute), 22
- align_baselines (rinoh.reference.NoteStyle attribute), 123
- align_baselines (rinoh.structure.AdmonitionStyle attribute), 82
- AnchorFlowable (class in rinoh.flowable), 104
- append() (rinoh.text.MixedStyledText method), 116
- arguments (rinoh.image.BackgroundImage attribute), 108
- arguments (rinoh.image.InlineImage attribute), 108
- Article (class in rinoh.templates.article), 93

Attribute (class in rinoh.attribute), 99
Attributes (rinoh.templates.article.Article attribute), 93
Attributes (rinoh.templates.book.Book attribute), 95
AttributesDictionary (class in rinoh.attribute), 99

B

background (rinoh.template.BodyPageTemplate attribute), 158
background (rinoh.template.BodyPageTemplateBase attribute), 156
background (rinoh.template.PageTemplateBase attribute), 160
background (rinoh.template.TitlePageTemplate attribute), 159
background_color (rinoh.flowable.FloatStyle attribute), 28
background_color (rinoh.flowable.FlowableStyle attribute), 21
background_color (rinoh.flowable.GroupedFlowablesStyle attribute), 26
background_color (rinoh.flowable.LabeledFlowableStyle attribute), 24
background_color (rinoh.image.CaptionStyle attribute), 31
background_color (rinoh.image.FigureStyle attribute), 35
background_color (rinoh.index.IndexStyle attribute), 38
background_color (rinoh.inline.InlineFlowableStyle attribute), 47
background_color (rinoh.paragraph.ParagraphStyle attribute), 41
background_color (rinoh.reference.NoteStyle attribute), 125
background_color (rinoh.reference.ReferencingParagraphStyle attribute), 51
background_color (rinoh.structure.AdmonitionStyle attribute), 84
background_color (rinoh.structure.HeadingStyle attribute), 61
background_color (rinoh.structure.HorizontalRuleStyle attribute), 86
background_color (rinoh.structure.ListItemLabelStyle attribute), 69, 132
background_color (rinoh.structure.ListOfEntryStyle attribute), 142
background_color (rinoh.structure.ListOfStyle attribute), 136
background_color (rinoh.structure.ListStyle attribute), 65, 128
background_color (rinoh.structure.SectionStyle attribute), 58
background_color (rinoh.structure.TableOfContentsEntryStyle attribute), 79
background_color (rinoh.structure.TableOfContentsStyle attribute), 73
background_color (rinoh.table.TableCellStyle attribute), 91
background_color (rinoh.table.TableStyle attribute), 89
background_color (rinoh.table.TableWithCaptionStyle attribute), 149
BackgroundImage (class in rinoh.image), 108
baseline (rinoh.inline.InlineFlowableStyle attribute), 46
before (rinoh.image.CaptionStyle attribute), 33
before (rinoh.inline.InlineFlowableStyle attribute), 48
before (rinoh.paragraph.ParagraphStyle attribute), 43
before (rinoh.reference.NoteMarkerStyle attribute), 55
before (rinoh.reference.ReferenceStyle attribute), 121
before (rinoh.reference.ReferencingParagraphStyle attribute), 53
before (rinoh.structure.HeadingStyle attribute), 63
before (rinoh.structure.ListItemLabelStyle attribute), 71, 134
before (rinoh.structure.ListOfEntryStyle attribute), 144
before (rinoh.structure.ListOfStyle attribute), 139
before (rinoh.structure.TableOfContentsEntryStyle attribute), 81
before (rinoh.structure.TableOfContentsStyle attribute), 76
before (rinoh.text.TextStyle attribute), 45
BodyPageTemplate (class in rinoh.template), 156
BodyPageTemplateBase (class in rinoh.template), 155
Book (class in rinoh.templates.book), 94
Bool (class in rinoh.attribute), 99
border (rinoh.flowable.FloatStyle attribute), 28
border (rinoh.flowable.FlowableStyle attribute), 21
border (rinoh.flowable.GroupedFlowablesStyle attribute), 26
border (rinoh.flowable.LabeledFlowableStyle attribute), 23

border (rinoh.image.CaptionStyle attribute), 31
border (rinoh.image.FigureStyle attribute), 35
border (rinoh.index.IndexStyle attribute), 38
border (rinoh.inline.InlineFlowableStyle attribute), 47
border (rinoh.paragraph.ParagraphStyle attribute), 41
border (rinoh.reference.NoteStyle attribute), 124
border (rinoh.reference.ReferencingParagraphStyle attribute), 50
border (rinoh.structure.AdmonitionStyle attribute), 84
border (rinoh.structure.HeadingStyle attribute), 60
border (rinoh.structure.HorizontalRuleStyle attribute), 86
border (rinoh.structure.ListItemLabelStyle attribute), 68, 131
border (rinoh.structure.ListOfEntryStyle attribute), 142
border (rinoh.structure.ListOfStyle attribute), 136
border (rinoh.structure.ListStyle attribute), 65, 128
border (rinoh.structure.SectionStyle attribute), 57
border (rinoh.structure.TableOfContentsEntryStyle attribute), 79
border (rinoh.structure.TableOfContentsStyle attribute), 73
border (rinoh.table.TableCellStyle attribute), 91
border (rinoh.table.TableStyle attribute), 88
border (rinoh.table.TableWithCaptionStyle attribute), 149
border_bottom (rinoh.flowable.FloatStyle attribute), 28
border_bottom (rinoh.flowable.FlowableStyle attribute), 21
border_bottom (rinoh.flowable.GroupedFlowablesStyle attribute), 26
border_bottom (rinoh.flowable.LabeledFlowableStyle attribute), 24
border_bottom (rinoh.image.CaptionStyle attribute), 31
border_bottom (rinoh.image.FigureStyle attribute), 35
border_bottom (rinoh.index.IndexStyle attribute), 38
border_bottom (rinoh.inline.InlineFlowableStyle attribute), 47
border_bottom (rinoh.paragraph.ParagraphStyle attribute), 41
border_bottom (rinoh.reference.NoteStyle attribute), 124
border_bottom (rinoh.reference.ReferencingParagraphStyle attribute), 50
border_bottom (rinoh.structure.AdmonitionStyle attribute), 84
border_bottom (rinoh.structure.HeadingStyle attribute), 61
border_bottom (rinoh.structure.HorizontalRuleStyle attribute), 86
border_bottom (rinoh.structure.ListItemLabelStyle attribute), 69, 131
border_bottom (rinoh.structure.ListOfEntryStyle attribute), 142
border_bottom (rinoh.structure.ListOfStyle attribute), 136
border_bottom (rinoh.structure.ListStyle attribute), 65, 128
border_bottom (rinoh.structure.SectionStyle attribute), 58
border_bottom (rinoh.structure.TableOfContentsEntryStyle attribute), 79
border_bottom (rinoh.structure.TableOfContentsStyle attribute), 73
border_bottom (rinoh.table.TableCellStyle attribute), 91
border_bottom (rinoh.table.TableStyle attribute), 89
border_bottom (rinoh.table.TableWithCaptionStyle attribute), 149
border_left (rinoh.flowable.FloatStyle attribute), 28
border_left (rinoh.flowable.FlowableStyle attribute), 21
border_left (rinoh.flowable.GroupedFlowablesStyle attribute), 26
border_left (rinoh.flowable.LabeledFlowableStyle attribute), 23
border_left (rinoh.image.CaptionStyle attribute), 31
border_left (rinoh.image.FigureStyle attribute), 35
border_left (rinoh.index.IndexStyle attribute), 38
border_left (rinoh.inline.InlineFlowableStyle attribute), 47
border_left (rinoh.paragraph.ParagraphStyle attribute), 41
border_left (rinoh.reference.NoteStyle attribute), 124
border_left (rinoh.reference.ReferencingParagraphStyle attribute), 50
border_left (rinoh.structure.AdmonitionStyle attribute), 84
border_left (rinoh.structure.HeadingStyle attribute), 60
border_left (rinoh.structure.HorizontalRuleStyle attribute), 86

border_left (rinoh.structure.ListItemLabelStyle attribute), 68, 131
border_left (rinoh.structure.ListOfEntryStyle attribute), 142
border_left (rinoh.structure.ListOfStyle attribute), 136
border_left (rinoh.structure.ListStyle attribute), 65, 128
border_left (rinoh.structure.SectionStyle attribute), 57
border_left (rinoh.structure.TableOfContentsEntryStyle attribute), 79
border_left (rinoh.structure.TableOfContentsStyle attribute), 73
border_left (rinoh.table.TableCellStyle attribute), 91
border_left (rinoh.table.TableStyle attribute), 88
border_left (rinoh.table.TableWithCaptionStyle attribute), 149
border_right (rinoh.flowable.FloatStyle attribute), 28
border_right (rinoh.flowable.FlowableStyle attribute), 21
border_right (rinoh.flowable.GroupedFlowablesStyle attribute), 26
border_right (rinoh.flowable.LabeledFlowableStyle attribute), 23
border_right (rinoh.image.CaptionStyle attribute), 31
border_right (rinoh.image.FigureStyle attribute), 35
border_right (rinoh.index.IndexStyle attribute), 38
border_right (rinoh.inline.InlineFlowableStyle attribute), 47
border_right (rinoh.paragraph.ParagraphStyle attribute), 41
border_right (rinoh.reference.NoteStyle attribute), 124
border_right (rinoh.reference.ReferencingParagraphStyle attribute), 50
border_right (rinoh.structure.AdmonitionStyle attribute), 84
border_right (rinoh.structure.HeadingStyle attribute), 60
border_right (rinoh.structure.HorizontalRuleStyle attribute), 86
border_right (rinoh.structure.ListItemLabelStyle attribute), 68, 131
border_right (rinoh.structure.ListOfEntryStyle attribute), 142
border_right (rinoh.structure.ListOfStyle attribute), 136
border_right (rinoh.structure.ListStyle attribute), 65, 128
border_right (rinoh.structure.SectionStyle attribute), 57
border_right (rinoh.structure.TableOfContentsEntryStyle attribute), 79
border_right (rinoh.structure.TableOfContentsStyle attribute), 73
border_right (rinoh.table.TableCellStyle attribute), 91
border_right (rinoh.table.TableStyle attribute), 88
border_right (rinoh.table.TableWithCaptionStyle attribute), 149
border_top (rinoh.flowable.FloatStyle attribute), 28
border_top (rinoh.flowable.FlowableStyle attribute), 21
border_top (rinoh.flowable.GroupedFlowablesStyle attribute), 26
border_top (rinoh.flowable.LabeledFlowableStyle attribute), 23
border_top (rinoh.image.CaptionStyle attribute), 31
border_top (rinoh.image.FigureStyle attribute), 35
border_top (rinoh.index.IndexStyle attribute), 38
border_top (rinoh.inline.InlineFlowableStyle attribute), 47
border_top (rinoh.paragraph.ParagraphStyle attribute), 41
border_top (rinoh.reference.NoteStyle attribute), 124
border_top (rinoh.reference.ReferencingParagraphStyle attribute), 50
border_top (rinoh.structure.AdmonitionStyle attribute), 84
border_top (rinoh.structure.HeadingStyle attribute), 61
border_top (rinoh.structure.HorizontalRuleStyle attribute), 86
border_top (rinoh.structure.ListItemLabelStyle attribute), 69, 131
border_top (rinoh.structure.ListOfEntryStyle attribute), 142
border_top (rinoh.structure.ListOfStyle attribute), 136
border_top (rinoh.structure.ListStyle attribute), 65, 128
border_top (rinoh.structure.SectionStyle attribute), 58
border_top (rinoh.structure.TableOfContentsEntryStyle attribute), 79
border_top (rinoh.structure.TableOfContentsStyle attribute), 73
border_top (rinoh.table.TableCellStyle attribute), 91
border_top (rinoh.table.TableStyle attribute), 88
border_top (rinoh.table.TableWithCaptionStyle attribute), 149

bottom_margin (rinoh.template.BodyPageTemplate attribute), 158
 bottom_margin (rinoh.template.BodyPageTemplateBase attribute), 156
 bottom_margin (rinoh.template.PageTemplateBase attribute), 160
 bottom_margin (rinoh.template.TitlePageTemplate attribute), 159
 build_document() (rinoh.flowable.StaticGroupedFlowables method), 105
 bullet (rinoh.structure.ListStyle attribute), 63, 126

C

Caption (class in rinoh.image), 109
 CaptionStyle (class in rinoh.image), 29
 chapter_footer_text (rinoh.template.BodyPageTemplate attribute), 157
 chapter_header_text (rinoh.template.BodyPageTemplate attribute), 156
 chapter_title_flowables (rinoh.template.BodyPageTemplate attribute), 157
 chapter_title_height (rinoh.template.BodyPageTemplate attribute), 157
 character_spacing (rinoh.image.CaptionStyle attribute), 33
 character_spacing (rinoh.paragraph.ParagraphStyle attribute), 43
 character_spacing (rinoh.reference.NoteMarkerStyle attribute), 54
 character_spacing (rinoh.reference.ReferenceStyle attribute), 120
 character_spacing (rinoh.reference.ReferencingParagraphStyle attribute), 52
 character_spacing (rinoh.structure.HeadingStyle attribute), 62
 character_spacing (rinoh.structure.ListItemLabelStyle attribute), 70, 133
 character_spacing (rinoh.structure.ListOfEntryStyle attribute), 144
 character_spacing (rinoh.structure.ListOfStyle attribute), 139
 character_spacing (rinoh.structure.TableOfContentsEntryStyle attribute), 81
 character_spacing (rinoh.structure.TableOfContentsStyle attribute), 76
 character_spacing (rinoh.text.TextStyle attribute), 45
 CM (in module rinoh.dimension), 101
 Color (class in rinoh.color), 100
 column_spacing (rinoh.template.BodyPageTemplate attribute), 157
 column_spacing (rinoh.template.BodyPageTemplateBase attribute), 155
 column_widths (rinoh.table.TableStyle attribute), 87
 columns (rinoh.template.BodyPageTemplate attribute), 157
 columns (rinoh.template.BodyPageTemplateBase attribute), 155
 Configuration (rinoh.template.DocumentTemplate attribute), 151
 Configuration (rinoh.templates.article.Article attribute), 94
 Configuration (rinoh.templates.book.Book attribute), 96
 configuration_class (rinoh.template.DocumentPart attribute), 152
 ConfigurationFile (rinoh.template.DocumentTemplate attribute), 151
 ConfigurationFile (rinoh.templates.article.Article attribute), 94
 ConfigurationFile (rinoh.templates.book.Book attribute), 97
 ContentsPartTemplate (class in rinoh.template), 154
 copy() (rinoh.text.MixedStyledText method), 117
 CS (in module rinoh.language), 112
 custom_label (rinoh.image.CaptionStyle attribute), 32
 custom_label (rinoh.number.LabelStyle attribute), 113
 custom_label (rinoh.number.NumberStyle attribute), 114
 custom_label (rinoh.paragraph.ParagraphStyle attribute), 42
 custom_label (rinoh.reference.NoteMarkerStyle attribute), 55
 custom_label (rinoh.reference.ReferenceStyle attribute), 121
 custom_label (rinoh.reference.ReferencingParagraphStyle attribute), 51
 custom_label (rinoh.structure.HeadingStyle attribute), 61
 custom_label (rinoh.structure.ListItemLabelStyle attribute), 69, 132
 custom_label (rinoh.structure.ListOfEntryStyle attribute), 143
 custom_label (rinoh.structure.ListOfStyle attribute), 138
 custom_label (rinoh.structure.ListStyle attribute), 66, 129
 custom_label (rinoh.structure.TableOfContentsEntryStyle attribute), 80
 custom_label (rinoh.structure.TableOfContentsStyle attribute), 75

D

DEFAULT (in module rinoh.paragraph), 118
DefaultSpacing (class in rinoh.paragraph), 117
DefinitionList (class in rinoh.structure), 134
depth (rinoh.structure.TableOfContentsStyle attribute), 71
Dimension (class in rinoh.dimension), 100
doc_format() (rinoh.color.Color class method), 100
Document (class in rinoh.document), 101
document() (rinoh.template.TemplateConfiguration method), 152
DocumentPart (class in rinoh.template), 152
DocumentPartTemplate (class in rinoh.template), 153
DocumentTemplate (class in rinoh.template), 151
DocumentTree (class in rinoh.document), 101
DOUBLE (in module rinoh.paragraph), 118
dpi (rinoh.image.ImageArgs attribute), 109
drop_if_empty (rinoh.template.ContentsPartTemplate attribute), 154
drop_if_empty (rinoh.template.DocumentPartTemplate attribute), 153
drop_if_empty (rinoh.template.FixedDocumentPartTemplate attribute), 155
drop_if_empty (rinoh.template.TitlePartTemplate attribute), 153
DummyFlowable (class in rinoh.flowable), 104

E

EN (in module rinoh.language), 112
encoding (rinoh.font.Font attribute), 106
end_at_page (rinoh.template.ContentsPartTemplate attribute), 154
end_at_page (rinoh.template.DocumentPartTemplate attribute), 153
end_at_page (rinoh.template.FixedDocumentPartTemplate attribute), 155
end_at_page (rinoh.template.TitlePartTemplate attribute), 154
ES (in module rinoh.language), 112
extra (rinoh.template.TitlePageTemplate attribute), 158

F

Field (class in rinoh.reference), 125
Figure (class in rinoh.image), 110
FigureStyle (class in rinoh.image), 34
file_or_filename (rinoh.image.ImageArgs attribute), 109
fill_color (rinoh.draw.ShapeStyle attribute), 19
fill_color (rinoh.table.TableCellBackgroundStyle attribute), 92
find_source() (rinoh.attribute.RuleSet method), 99
FixedDocumentPartTemplate (class in rinoh.template), 154
FixedSpacing (class in rinoh.paragraph), 117
Float (class in rinoh.flowable), 106
float (rinoh.flowable.FloatStyle attribute), 26
float (rinoh.image.FigureStyle attribute), 34
float (rinoh.table.TableWithCaptionStyle attribute), 147
FloatStyle (class in rinoh.flowable), 26
flow() (rinoh.flowable.Float method), 106
flow() (rinoh.index.IndexTarget method), 110
flow() (rinoh.reference.Note method), 122
flow() (rinoh.structure.Heading method), 126
Flowable (class in rinoh.flowable), 103
flowable_spacing (rinoh.flowable.GroupedFlowablesStyle attribute), 24
flowable_spacing (rinoh.image.FigureStyle attribute), 36
flowable_spacing (rinoh.index.IndexStyle attribute), 36
flowable_spacing (rinoh.structure.ListOfStyle attribute), 135
flowable_spacing (rinoh.structure.ListStyle attribute), 64, 126

flowable_spacing (rinoh.structure.SectionStyle attribute), 56
 flowable_spacing (rinoh.structure.TableOfContentsStyle attribute), 72
 flowable_spacing (rinoh.table.TableCellStyle attribute), 89
 flowable_spacing (rinoh.table.TableWithCaptionStyle attribute), 150
 flowables (rinoh.template.FixedDocumentPartTemplate attribute), 154
 flowables() (rinoh.flowable.GroupedFlowables method), 105
 flowables() (rinoh.flowable.StaticGroupedFlowables method), 105
 flowables() (rinoh.index.Index method), 110
 flowables() (rinoh.structure.TableOfContents method), 134
 FlowableState (class in rinoh.flowable), 104
 FlowableStyle (class in rinoh.flowable), 19
 FlowableWidth (class in rinoh.flowable), 106
 Font (class in rinoh.font), 106
 font_color (rinoh.image.CaptionStyle attribute), 32
 font_color (rinoh.paragraph.ParagraphStyle attribute), 42
 font_color (rinoh.reference.NoteMarkerStyle attribute), 54
 font_color (rinoh.reference.ReferenceStyle attribute), 120
 font_color (rinoh.reference.ReferencingParagraphStyle attribute), 52
 font_color (rinoh.structure.HeadingStyle attribute), 62
 font_color (rinoh.structure.ListItemLabelStyle attribute), 70, 133
 font_color (rinoh.structure.ListOfEntryStyle attribute), 143
 font_color (rinoh.structure.ListOfStyle attribute), 138
 font_color (rinoh.structure.TableOfContentsEntryStyle attribute), 80
 font_color (rinoh.structure.TableOfContentsStyle attribute), 75
 font_color (rinoh.text.TextStyle attribute), 44
 font_size (rinoh.image.CaptionStyle attribute), 32
 font_size (rinoh.paragraph.ParagraphStyle attribute), 42
 font_size (rinoh.reference.NoteMarkerStyle attribute), 54
 font_size (rinoh.reference.ReferenceStyle attribute), 120
 font_size (rinoh.reference.ReferencingParagraphStyle attribute), 52
 font_size (rinoh.structure.HeadingStyle attribute), 62
 font_size (rinoh.structure.ListItemLabelStyle attribute), 70, 133
 font_size (rinoh.structure.ListOfEntryStyle attribute), 143
 font_size (rinoh.structure.ListOfStyle attribute), 138
 font_size (rinoh.structure.TableOfContentsEntryStyle attribute), 80
 font_size (rinoh.structure.TableOfContentsStyle attribute), 75
 font_size (rinoh.text.TextStyle attribute), 44
 font_slant (rinoh.image.CaptionStyle attribute), 32
 font_slant (rinoh.paragraph.ParagraphStyle attribute), 42
 font_slant (rinoh.reference.NoteMarkerStyle attribute), 54
 font_slant (rinoh.reference.ReferenceStyle attribute), 119
 font_slant (rinoh.reference.ReferencingParagraphStyle attribute), 51
 font_slant (rinoh.structure.HeadingStyle attribute), 62
 font_slant (rinoh.structure.ListItemLabelStyle attribute), 70, 132
 font_slant (rinoh.structure.ListOfEntryStyle attribute), 143
 font_slant (rinoh.structure.ListOfStyle attribute), 138
 font_slant (rinoh.structure.TableOfContentsEntryStyle attribute), 80
 font_slant (rinoh.structure.TableOfContentsStyle attribute), 75
 font_slant (rinoh.text.TextStyle attribute), 44
 font_variant (rinoh.image.CaptionStyle attribute), 32
 font_variant (rinoh.paragraph.ParagraphStyle attribute), 42
 font_variant (rinoh.reference.NoteMarkerStyle attribute), 54
 font_variant (rinoh.reference.ReferenceStyle attribute), 120
 font_variant (rinoh.reference.ReferencingParagraphStyle attribute), 52
 font_variant (rinoh.structure.HeadingStyle attribute), 62
 font_variant (rinoh.structure.ListItemLabelStyle attribute), 70, 133
 font_variant (rinoh.structure.ListOfEntryStyle attribute), 144
 font_variant (rinoh.structure.ListOfStyle attribute), 139

font_variant (rinoh.structure.TableOfContentsEntryStyle attribute), 81
 font_variant (rinoh.structure.TableOfContentsStyle attribute), 75
 font_variant (rinoh.text.TextStyle attribute), 44
 font_weight (rinoh.image.CaptionStyle attribute), 32
 font_weight (rinoh.paragraph.ParagraphStyle attribute), 42
 font_weight (rinoh.reference.NoteMarkerStyle attribute), 53
 font_weight (rinoh.reference.ReferenceStyle attribute), 119
 font_weight (rinoh.reference.ReferencingParagraphStyle attribute), 51
 font_weight (rinoh.structure.HeadingStyle attribute), 61
 font_weight (rinoh.structure.ListItemLabelStyle attribute), 69, 132
 font_weight (rinoh.structure.ListOfEntryStyle attribute), 143
 font_weight (rinoh.structure.ListOfStyle attribute), 138
 font_weight (rinoh.structure.TableOfContentsEntryStyle attribute), 80
 font_weight (rinoh.structure.TableOfContentsStyle attribute), 75
 font_weight (rinoh.text.TextStyle attribute), 44
 font_width (rinoh.image.CaptionStyle attribute), 32
 font_width (rinoh.paragraph.ParagraphStyle attribute), 42
 font_width (rinoh.reference.NoteMarkerStyle attribute), 54
 font_width (rinoh.reference.ReferenceStyle attribute), 120
 font_width (rinoh.reference.ReferencingParagraphStyle attribute), 51
 font_width (rinoh.structure.HeadingStyle attribute), 62
 font_width (rinoh.structure.ListItemLabelStyle attribute), 70, 132
 font_width (rinoh.structure.ListOfEntryStyle attribute), 143
 font_width (rinoh.structure.ListOfStyle attribute), 138
 font_width (rinoh.structure.TableOfContentsEntryStyle attribute), 80
 font_width (rinoh.structure.TableOfContentsStyle attribute), 75
 font_width (rinoh.text.TextStyle attribute), 44
 fonts() (rinoh.font.Typeface method), 107
 FontSlant (class in rinoh.font.style), 108
 FontVariant (class in rinoh.font.style), 108
 FontWeight (class in rinoh.font.style), 108
 FontWidth (class in rinoh.font.style), 108
 footer_text (rinoh.template.BodyPageTemplate attribute), 157
 footer_text (rinoh.template.BodyPageTemplateBase attribute), 155
 format_number() (in module rinoh.number), 114
 FR (in module rinoh.language), 112

G

get_font() (rinoh.font.Typeface method), 108
 get_glyph_metrics() (rinoh.font.Font method), 107
 get_kerning() (rinoh.font.Font method), 107
 get_ligature() (rinoh.font.Font method), 107
 get_position() (rinoh.paragraph.TabStop method), 118
 get_rowspanned_columns() (rinoh.table.TableRow method), 150
 get_selector() (rinoh.style.StyleSheet method), 146
 Glyph (class in rinoh.paragraph), 119
 GlyphsSpan (class in rinoh.paragraph), 119
 Gray (class in rinoh.color), 100
 GroupedFlowables (class in rinoh.flowable), 105
 GroupedFlowablesState (class in rinoh.flowable), 105
 GroupedFlowablesStyle (class in rinoh.flowable), 24
 GroupedLabeledFlowables (class in rinoh.flowable), 105
 grow() (rinoh.dimension.Dimension method), 101

H

HALVES (in module rinoh.dimension), 101
 has_class (rinoh.style.Styled property), 146

- has_classes (rinoh.style.Styled property), 146
- has_id (rinoh.style.Styled property), 146
- header_footer_distance (rinoh.template.BodyPageTemplate attribute), 157
- header_footer_distance (rinoh.template.BodyPageTemplateBase attribute), 155
- header_text (rinoh.template.BodyPageTemplate attribute), 157
- header_text (rinoh.template.BodyPageTemplateBase attribute), 155
- Heading (class in rinoh.structure), 125
- HeadingStyle (class in rinoh.structure), 58
- height (rinoh.image.ImageArgs attribute), 109
- height() (rinoh.text.StyledText method), 116
- HexColor (class in rinoh.color), 100
- hide (rinoh.draw.LineStyle attribute), 19
- hide (rinoh.draw.ShapeStyle attribute), 19
- hide (rinoh.flowable.FloatStyle attribute), 28
- hide (rinoh.flowable.FlowableStyle attribute), 21
- hide (rinoh.flowable.GroupedFlowablesStyle attribute), 26
- hide (rinoh.flowable.LabeledFlowableStyle attribute), 24
- hide (rinoh.image.CaptionStyle attribute), 33
- hide (rinoh.image.FigureStyle attribute), 36
- hide (rinoh.index.IndexStyle attribute), 38
- hide (rinoh.inline.InlineFlowableStyle attribute), 47
- hide (rinoh.number.LabelStyle attribute), 113
- hide (rinoh.number.NumberStyle attribute), 114
- hide (rinoh.paragraph.ParagraphStyle attribute), 41
- hide (rinoh.reference.NoteMarkerStyle attribute), 56
- hide (rinoh.reference.NoteStyle attribute), 125
- hide (rinoh.reference.ReferenceStyle attribute), 121
- hide (rinoh.reference.ReferencingParagraphStyle attribute), 53
- hide (rinoh.structure.AdmonitionStyle attribute), 84
- hide (rinoh.structure.HeadingStyle attribute), 63
- hide (rinoh.structure.HorizontalRuleStyle attribute), 86
- hide (rinoh.structure.ListItemLabelStyle attribute), 71, 134
- hide (rinoh.structure.ListOfEntryStyle attribute), 145
- hide (rinoh.structure.ListOfStyle attribute), 137
- hide (rinoh.structure.ListStyle attribute), 66, 128
- hide (rinoh.structure.SectionStyle attribute), 58
- hide (rinoh.structure.TableOfContentsEntryStyle attribute), 82
- hide (rinoh.structure.TableOfContentsStyle attribute), 73
- hide (rinoh.style.Style attribute), 146
- hide (rinoh.table.TableCellBackgroundStyle attribute), 92
- hide (rinoh.table.TableCellBorderStyle attribute), 92
- hide (rinoh.table.TableCellStyle attribute), 91
- hide (rinoh.table.TableStyle attribute), 89
- hide (rinoh.table.TableWithCaptionStyle attribute), 149
- hide (rinoh.text.TextStyle attribute), 45
- horizontal_align (rinoh.flowable.FloatStyle attribute), 27
- horizontal_align (rinoh.flowable.FlowableStyle attribute), 20
- horizontal_align (rinoh.flowable.GroupedFlowablesStyle attribute), 25
- horizontal_align (rinoh.flowable.LabeledFlowableStyle attribute), 22
- horizontal_align (rinoh.image.CaptionStyle attribute), 30
- horizontal_align (rinoh.image.FigureStyle attribute), 34
- horizontal_align (rinoh.index.IndexStyle attribute), 37
- horizontal_align (rinoh.inline.InlineFlowableStyle attribute), 46
- horizontal_align (rinoh.paragraph.ParagraphStyle attribute), 40
- horizontal_align (rinoh.reference.NoteStyle attribute), 123
- horizontal_align (rinoh.reference.ReferencingParagraphStyle attribute), 49
- horizontal_align (rinoh.structure.AdmonitionStyle attribute), 83
- horizontal_align (rinoh.structure.HeadingStyle attribute), 59

horizontal_align (rinoh.structure.HorizontalRuleStyle attribute), 85
 horizontal_align (rinoh.structure.ListItemLabelStyle attribute), 67, 130
 horizontal_align (rinoh.structure.ListOfEntryStyle attribute), 141
 horizontal_align (rinoh.structure.ListOfStyle attribute), 135
 horizontal_align (rinoh.structure.ListStyle attribute), 64, 127
 horizontal_align (rinoh.structure.SectionStyle attribute), 56
 horizontal_align (rinoh.structure.TableOfContentsEntryStyle attribute), 78
 horizontal_align (rinoh.structure.TableOfContentsStyle attribute), 72
 horizontal_align (rinoh.table.TableCellStyle attribute), 90
 horizontal_align (rinoh.table.TableStyle attribute), 87
 horizontal_align (rinoh.table.TableWithCaptionStyle attribute), 148
 HorizontalAlignment (class in rinoh.flowable), 106
 HorizontalRule (class in rinoh.structure), 145
 HorizontalRuleStyle (class in rinoh.structure), 85
 HU (in module rinoh.language), 112
 hyphen_chars (rinoh.image.CaptionStyle attribute), 33
 hyphen_chars (rinoh.paragraph.ParagraphStyle attribute), 43
 hyphen_chars (rinoh.reference.NoteMarkerStyle attribute), 55
 hyphen_chars (rinoh.reference.ReferenceStyle attribute), 120
 hyphen_chars (rinoh.reference.ReferencingParagraphStyle attribute), 52
 hyphen_chars (rinoh.structure.HeadingStyle attribute), 62
 hyphen_chars (rinoh.structure.ListItemLabelStyle attribute), 70, 133
 hyphen_chars (rinoh.structure.ListOfEntryStyle attribute), 144
 hyphen_chars (rinoh.structure.ListOfStyle attribute), 139
 hyphen_chars (rinoh.structure.TableOfContentsEntryStyle attribute), 81
 hyphen_chars (rinoh.structure.TableOfContentsStyle attribute), 76
 hyphen_chars (rinoh.text.TextStyle attribute), 45
 hyphen_lang (rinoh.image.CaptionStyle attribute), 33
 hyphen_lang (rinoh.paragraph.ParagraphStyle attribute), 43
 hyphen_lang (rinoh.reference.NoteMarkerStyle attribute), 55
 hyphen_lang (rinoh.reference.ReferenceStyle attribute), 120
 hyphen_lang (rinoh.reference.ReferencingParagraphStyle attribute), 52
 hyphen_lang (rinoh.structure.HeadingStyle attribute), 63
 hyphen_lang (rinoh.structure.ListItemLabelStyle attribute), 71, 133
 hyphen_lang (rinoh.structure.ListOfEntryStyle attribute), 144
 hyphen_lang (rinoh.structure.ListOfStyle attribute), 139
 hyphen_lang (rinoh.structure.TableOfContentsEntryStyle attribute), 81
 hyphen_lang (rinoh.structure.TableOfContentsStyle attribute), 76
 hyphen_lang (rinoh.text.TextStyle attribute), 45
 hyphenate (rinoh.image.CaptionStyle attribute), 33
 hyphenate (rinoh.paragraph.ParagraphStyle attribute), 43
 hyphenate (rinoh.reference.NoteMarkerStyle attribute), 54
 hyphenate (rinoh.reference.ReferenceStyle attribute), 120
 hyphenate (rinoh.reference.ReferencingParagraphStyle attribute), 52
 hyphenate (rinoh.structure.HeadingStyle attribute), 62
 hyphenate (rinoh.structure.ListItemLabelStyle attribute), 70, 133
 hyphenate (rinoh.structure.ListOfEntryStyle attribute), 144
 hyphenate (rinoh.structure.ListOfStyle attribute), 139
 hyphenate (rinoh.structure.TableOfContentsEntryStyle attribute), 81
 hyphenate (rinoh.structure.TableOfContentsStyle attribute), 76
 hyphenate (rinoh.text.TextStyle attribute), 45
 HyphenatorStore (class in rinoh.paragraph), 119

I

Image (class in rinoh.image), 108
 ImageArgs (class in rinoh.image), 109
 INCH (in module rinoh.dimension), 101

- indent_first (rinoh.image.CaptionStyle attribute), 29
- indent_first (rinoh.paragraph.ParagraphStyle attribute), 39
- indent_first (rinoh.reference.ReferencingParagraphStyle attribute), 48
- indent_first (rinoh.structure.HeadingStyle attribute), 58
- indent_first (rinoh.structure.ListItemLabelStyle attribute), 66, 129
- indent_first (rinoh.structure.ListOfEntryStyle attribute), 140
- indent_first (rinoh.structure.ListOfStyle attribute), 137
- indent_first (rinoh.structure.TableOfContentsEntryStyle attribute), 77
- indent_first (rinoh.structure.TableOfContentsStyle attribute), 74
- Index (class in rinoh.index), 110
- IndexLabel (class in rinoh.index), 110
- IndexSection (class in rinoh.index), 110
- IndexStyle (class in rinoh.index), 36
- IndexTarget (class in rinoh.index), 110
- IndexTerm (class in rinoh.index), 110
- initials (rinoh.index.IndexStyle attribute), 36
- inline_title (rinoh.structure.AdmonitionStyle attribute), 82
- InlineFlowable (class in rinoh.inline), 117
- InlineFlowableStyle (class in rinoh.inline), 45
- InlineImage (class in rinoh.image), 108
- InlineIndexTarget (class in rinoh.index), 110
- input
 - rinoh command line option, 5
- Integer (class in rinoh.attribute), 99
- is_script() (rinoh.text.StyledText method), 116
- IT (in module rinoh.language), 112
- items (rinoh.text.MixedStyledText property), 116
- items (rinoh.text.StyledText property), 116

J

- JUNIOR_LEGAL (in module rinoh.paper), 115

K

- keep_with_next (rinoh.flowable.FloatStyle attribute), 28
- keep_with_next (rinoh.flowable.FlowableStyle attribute), 20
- keep_with_next (rinoh.flowable.GroupedFlowablesStyle attribute), 25
- keep_with_next (rinoh.flowable.LabeledFlowableStyle attribute), 23
- keep_with_next (rinoh.image.CaptionStyle attribute), 31
- keep_with_next (rinoh.image.FigureStyle attribute), 35
- keep_with_next (rinoh.index.IndexStyle attribute), 38
- keep_with_next (rinoh.inline.InlineFlowableStyle attribute), 47
- keep_with_next (rinoh.paragraph.ParagraphStyle attribute), 41
- keep_with_next (rinoh.reference.NoteStyle attribute), 124
- keep_with_next (rinoh.reference.ReferencingParagraphStyle attribute), 50
- keep_with_next (rinoh.structure.AdmonitionStyle attribute), 84
- keep_with_next (rinoh.structure.HeadingStyle attribute), 58
- keep_with_next (rinoh.structure.HorizontalRuleStyle attribute), 86
- keep_with_next (rinoh.structure.ListItemLabelStyle attribute), 68, 131
- keep_with_next (rinoh.structure.ListOfEntryStyle attribute), 142
- keep_with_next (rinoh.structure.ListOfStyle attribute), 136
- keep_with_next (rinoh.structure.ListStyle attribute), 65, 127
- keep_with_next (rinoh.structure.SectionStyle attribute), 57
- keep_with_next (rinoh.structure.TableOfContentsEntryStyle attribute), 79
- keep_with_next (rinoh.structure.TableOfContentsStyle attribute), 73
- keep_with_next (rinoh.table.TableCellStyle attribute), 91
- keep_with_next (rinoh.table.TableStyle attribute), 88
- keep_with_next (rinoh.table.TableWithCaptionStyle attribute), 148

- Kerning (rinoh.image.CaptionStyle attribute), 33
- Kerning (rinoh.paragraph.ParagraphStyle attribute), 43
- Kerning (rinoh.reference.NoteMarkerStyle attribute), 54
- Kerning (rinoh.reference.ReferenceStyle attribute), 120
- Kerning (rinoh.reference.ReferencingParagraphStyle attribute), 52
- Kerning (rinoh.structure.HeadingStyle attribute), 62
- Kerning (rinoh.structure.ListItemLabelStyle attribute), 70, 133
- Kerning (rinoh.structure.ListOfEntryStyle attribute), 144
- Kerning (rinoh.structure.ListOfStyle attribute), 139
- Kerning (rinoh.structure.TableOfContentsEntryStyle attribute), 81
- Kerning (rinoh.structure.TableOfContentsStyle attribute), 76
- Kerning (rinoh.text.TextStyle attribute), 44

L

- Label (class in rinoh.number), 113
- label (rinoh.flowable.LabeledFlowableStyle attribute), 21
- label (rinoh.reference.NoteStyle attribute), 122
- label (rinoh.structure.AdmonitionStyle attribute), 82
- label_max_width (rinoh.flowable.LabeledFlowableStyle attribute), 22
- label_max_width (rinoh.reference.NoteStyle attribute), 123
- label_max_width (rinoh.structure.AdmonitionStyle attribute), 82
- label_min_width (rinoh.flowable.LabeledFlowableStyle attribute), 22
- label_min_width (rinoh.reference.NoteStyle attribute), 122
- label_min_width (rinoh.structure.AdmonitionStyle attribute), 82
- label_position (rinoh.flowable.LabeledFlowableStyle attribute), 22
- label_position (rinoh.reference.NoteStyle attribute), 122
- label_position (rinoh.structure.AdmonitionStyle attribute), 82
- label_prefix (rinoh.image.CaptionStyle attribute), 31
- label_prefix (rinoh.number.LabelStyle attribute), 113
- label_prefix (rinoh.number.NumberStyle attribute), 114
- label_prefix (rinoh.paragraph.ParagraphStyle attribute), 41
- label_prefix (rinoh.reference.NoteMarkerStyle attribute), 55
- label_prefix (rinoh.reference.ReferenceStyle attribute), 121
- label_prefix (rinoh.reference.ReferencingParagraphStyle attribute), 51
- label_prefix (rinoh.structure.HeadingStyle attribute), 61
- label_prefix (rinoh.structure.ListItemLabelStyle attribute), 69, 132
- label_prefix (rinoh.structure.ListOfEntryStyle attribute), 143
- label_prefix (rinoh.structure.ListOfStyle attribute), 138
- label_prefix (rinoh.structure.ListStyle attribute), 66, 128
- label_prefix (rinoh.structure.TableOfContentsEntryStyle attribute), 80
- label_prefix (rinoh.structure.TableOfContentsStyle attribute), 74
- label_spacing (rinoh.flowable.LabeledFlowableStyle attribute), 22
- label_spacing (rinoh.reference.NoteStyle attribute), 123
- label_spacing (rinoh.structure.AdmonitionStyle attribute), 82
- label_suffix (rinoh.image.CaptionStyle attribute), 32
- label_suffix (rinoh.number.LabelStyle attribute), 113
- label_suffix (rinoh.number.NumberStyle attribute), 114
- label_suffix (rinoh.paragraph.ParagraphStyle attribute), 42
- label_suffix (rinoh.reference.NoteMarkerStyle attribute), 55
- label_suffix (rinoh.reference.ReferenceStyle attribute), 121
- label_suffix (rinoh.reference.ReferencingParagraphStyle attribute), 51
- label_suffix (rinoh.structure.HeadingStyle attribute), 61
- label_suffix (rinoh.structure.ListItemLabelStyle attribute), 69, 132
- label_suffix (rinoh.structure.ListOfEntryStyle attribute), 143
- label_suffix (rinoh.structure.ListOfStyle attribute), 138
- label_suffix (rinoh.structure.ListStyle attribute), 66, 129
- label_suffix (rinoh.structure.TableOfContentsEntryStyle attribute), 80

label_suffix (rinoh.structure.TableOfContentsStyle attribute), 75
 LabeledFlowable (class in rinoh.flowable), 104
 LabeledFlowableState (class in rinoh.flowable), 105
 LabeledFlowableStyle (class in rinoh.flowable), 21
 LabelStyle (class in rinoh.number), 113
 Language (class in rinoh.language), 110
 language (rinoh.template.DocumentTemplate attribute), 151
 language (rinoh.templates.article.Article attribute), 93
 language (rinoh.templates.book.Book attribute), 94
 languages (rinoh.language.Language attribute), 112
 Leading (class in rinoh.paragraph), 118
 LEDGER (in module rinoh.paper), 115
 left_margin (rinoh.template.BodyPageTemplate attribute), 158
 left_margin (rinoh.template.BodyPageTemplateBase attribute), 156
 left_margin (rinoh.template.PageTemplateBase attribute), 160
 left_margin (rinoh.template.TitlePageTemplate attribute), 159
 LEGAL (in module rinoh.paper), 115
 LETTER (in module rinoh.paper), 115
 ligatures (rinoh.image.CaptionStyle attribute), 33
 ligatures (rinoh.paragraph.ParagraphStyle attribute), 43
 ligatures (rinoh.reference.NoteMarkerStyle attribute), 54
 ligatures (rinoh.reference.ReferenceStyle attribute), 120
 ligatures (rinoh.reference.ReferencingParagraphStyle attribute), 52
 ligatures (rinoh.structure.HeadingStyle attribute), 62
 ligatures (rinoh.structure.ListItemLabelStyle attribute), 70, 133
 ligatures (rinoh.structure.ListOfEntryStyle attribute), 144
 ligatures (rinoh.structure.ListOfStyle attribute), 139
 ligatures (rinoh.structure.TableOfContentsEntryStyle attribute), 81
 ligatures (rinoh.structure.TableOfContentsStyle attribute), 76
 ligatures (rinoh.text.TextStyle attribute), 45
 limit_width (rinoh.image.ImageArgs attribute), 109
 Line (class in rinoh.draw), 103
 line_spacing (rinoh.image.CaptionStyle attribute), 29
 line_spacing (rinoh.paragraph.ParagraphStyle attribute), 39
 line_spacing (rinoh.reference.ReferencingParagraphStyle attribute), 48
 line_spacing (rinoh.structure.HeadingStyle attribute), 59
 line_spacing (rinoh.structure.ListItemLabelStyle attribute), 67, 129
 line_spacing (rinoh.structure.ListOfEntryStyle attribute), 140
 line_spacing (rinoh.structure.ListOfStyle attribute), 137
 line_spacing (rinoh.structure.TableOfContentsEntryStyle attribute), 77
 line_spacing (rinoh.structure.TableOfContentsStyle attribute), 74
 LineSpacing (class in rinoh.paragraph), 117
 LineStyle (class in rinoh.draw), 19
 link (rinoh.reference.NoteMarkerStyle attribute), 53
 link (rinoh.reference.ReferenceStyle attribute), 119
 List (class in rinoh.structure), 126
 list_class (rinoh.image.ListOfFiguresSection attribute), 110
 list_class (rinoh.table.ListOfTablesSection attribute), 150
 ListItem (class in rinoh.structure), 129
 ListItemLabel (class in rinoh.structure), 129
 ListItemLabelStyle (class in rinoh.structure), 66, 129
 ListOfEntryStyle (class in rinoh.structure), 140
 ListOfFigures (class in rinoh.image), 110
 ListOfFiguresSection (class in rinoh.image), 110
 ListOfStyle (class in rinoh.structure), 134
 ListOfTables (class in rinoh.table), 150
 ListOfTablesSection (class in rinoh.table), 150
 ListStyle (class in rinoh.structure), 63, 126

Locale (class in rinoh.text), 117
location (rinoh.attribute.RuleSetFile property), 99
location (rinoh.reference.NoteStyle attribute), 122

M

margin_left (rinoh.flowable.FloatStyle attribute), 27
margin_left (rinoh.flowable.FlowableStyle attribute), 20
margin_left (rinoh.flowable.GroupedFlowablesStyle attribute), 25
margin_left (rinoh.flowable.LabeledFlowableStyle attribute), 22
margin_left (rinoh.image.CaptionStyle attribute), 30
margin_left (rinoh.image.FigureStyle attribute), 34
margin_left (rinoh.index.IndexStyle attribute), 37
margin_left (rinoh.inline.InlineFlowableStyle attribute), 46
margin_left (rinoh.paragraph.ParagraphStyle attribute), 40
margin_left (rinoh.reference.NoteStyle attribute), 123
margin_left (rinoh.reference.ReferencingParagraphStyle attribute), 49
margin_left (rinoh.structure.AdmonitionStyle attribute), 83
margin_left (rinoh.structure.HeadingStyle attribute), 60
margin_left (rinoh.structure.HorizontalRuleStyle attribute), 85
margin_left (rinoh.structure.ListItemLabelStyle attribute), 68, 130
margin_left (rinoh.structure.ListOfEntryStyle attribute), 141
margin_left (rinoh.structure.ListOfStyle attribute), 135
margin_left (rinoh.structure.ListStyle attribute), 64, 127
margin_left (rinoh.structure.SectionStyle attribute), 57
margin_left (rinoh.structure.TableOfContentsEntryStyle attribute), 78
margin_left (rinoh.structure.TableOfContentsStyle attribute), 72
margin_left (rinoh.table.TableCellStyle attribute), 90
margin_left (rinoh.table.TableStyle attribute), 87
margin_left (rinoh.table.TableWithCaptionStyle attribute), 148
margin_right (rinoh.flowable.FloatStyle attribute), 27
margin_right (rinoh.flowable.FlowableStyle attribute), 20
margin_right (rinoh.flowable.GroupedFlowablesStyle attribute), 25
margin_right (rinoh.flowable.LabeledFlowableStyle attribute), 23
margin_right (rinoh.image.CaptionStyle attribute), 30
margin_right (rinoh.image.FigureStyle attribute), 34
margin_right (rinoh.index.IndexStyle attribute), 37
margin_right (rinoh.inline.InlineFlowableStyle attribute), 46
margin_right (rinoh.paragraph.ParagraphStyle attribute), 40
margin_right (rinoh.reference.NoteStyle attribute), 123
margin_right (rinoh.reference.ReferencingParagraphStyle attribute), 49
margin_right (rinoh.structure.AdmonitionStyle attribute), 83
margin_right (rinoh.structure.HeadingStyle attribute), 60
margin_right (rinoh.structure.HorizontalRuleStyle attribute), 85
margin_right (rinoh.structure.ListItemLabelStyle attribute), 68, 130
margin_right (rinoh.structure.ListOfEntryStyle attribute), 141
margin_right (rinoh.structure.ListOfStyle attribute), 135
margin_right (rinoh.structure.ListStyle attribute), 64, 127
margin_right (rinoh.structure.SectionStyle attribute), 57
margin_right (rinoh.structure.TableOfContentsEntryStyle attribute), 78
margin_right (rinoh.structure.TableOfContentsStyle attribute), 72
margin_right (rinoh.table.TableCellStyle attribute), 90
margin_right (rinoh.table.TableStyle attribute), 88
margin_right (rinoh.table.TableWithCaptionStyle attribute), 148
matcher (in module rinoh.stylesheets), 11
MixedStyledText (class in rinoh.text), 116
MM (in module rinoh.dimension), 101
module

- rinoh.attribute, 99
- rinoh.color, 100
- rinoh.dimension, 100
- rinoh.document, 101
- rinoh.draw, 103
- rinoh.flowable, 103
- rinoh.font, 106
- rinoh.font.style, 108
- rinoh.image, 108
- rinoh.index, 110
- rinoh.inline, 117
- rinoh.language, 110
- rinoh.number, 113
- rinoh.paper, 114
- rinoh.paragraph, 115
- rinoh.reference, 119
- rinoh.strings, 145
- rinoh.structure, 125
- rinoh.style, 145
- rinoh.stylesheets, 11
- rinoh.table, 147
- rinoh.template, 151
- rinoh.templates.article, 93
- rinoh.templates.book, 94
- rinoh.text, 116

N

- new_page() (rinoh.template.DocumentPart method), 153
- NL (in module rinoh.language), 112
- no_break_after (rinoh.image.CaptionStyle attribute), 33
- no_break_after (rinoh.paragraph.ParagraphStyle attribute), 43
- no_break_after (rinoh.reference.NoteMarkerStyle attribute), 55
- no_break_after (rinoh.reference.ReferenceStyle attribute), 121
- no_break_after (rinoh.reference.ReferencingParagraphStyle attribute), 53
- no_break_after (rinoh.structure.HeadingStyle attribute), 63
- no_break_after (rinoh.structure.ListItemLabelStyle attribute), 71, 133
- no_break_after (rinoh.structure.ListOfEntryStyle attribute), 144
- no_break_after (rinoh.structure.ListOfStyle attribute), 139
- no_break_after (rinoh.structure.TableOfContentsEntryStyle attribute), 81
- no_break_after (rinoh.structure.TableOfContentsStyle attribute), 76
- no_break_after (rinoh.text.TextStyle attribute), 45
- NoBreakAfter (class in rinoh.text), 117
- Note (class in rinoh.reference), 122
- NoteMarkerBase (class in rinoh.reference), 125
- NoteMarkerByID (class in rinoh.reference), 125
- NoteMarkerStyle (class in rinoh.reference), 53
- NoteMarkerWithNote (class in rinoh.reference), 125
- NoteStyle (class in rinoh.reference), 122
- number_format (rinoh.image.CaptionStyle attribute), 29
- number_format (rinoh.number.NumberStyle attribute), 114
- number_format (rinoh.paragraph.ParagraphStyle attribute), 39
- number_format (rinoh.reference.NoteMarkerStyle attribute), 55
- number_format (rinoh.reference.ReferenceStyle attribute), 121
- number_format (rinoh.reference.ReferencingParagraphStyle attribute), 49
- number_format (rinoh.structure.HeadingStyle attribute), 59
- number_format (rinoh.structure.ListItemLabelStyle attribute), 67, 130
- number_format (rinoh.structure.ListOfEntryStyle attribute), 140

- number_format (rinoh.structure.ListOfStyle attribute), 137
- number_format (rinoh.structure.ListStyle attribute), 66, 128
- number_format (rinoh.structure.TableOfContentsEntryStyle attribute), 77
- number_format (rinoh.structure.TableOfContentsStyle attribute), 74
- number_separator (rinoh.image.CaptionStyle attribute), 30
- number_separator (rinoh.paragraph.ParagraphStyle attribute), 39
- number_separator (rinoh.reference.ReferencingParagraphStyle attribute), 49
- number_separator (rinoh.structure.HeadingStyle attribute), 59
- number_separator (rinoh.structure.ListItemLabelStyle attribute), 66, 129
- number_separator (rinoh.structure.ListOfEntryStyle attribute), 141
- number_separator (rinoh.structure.ListOfStyle attribute), 137
- number_separator (rinoh.structure.TableOfContentsEntryStyle attribute), 78
- number_separator (rinoh.structure.TableOfContentsStyle attribute), 74
- NumberFormat (class in rinoh.number), 113
- numbering_level (rinoh.image.CaptionStyle attribute), 29
- numbering_level (rinoh.paragraph.ParagraphStyle attribute), 40
- numbering_level (rinoh.reference.ReferencingParagraphStyle attribute), 49
- numbering_level (rinoh.structure.HeadingStyle attribute), 58
- numbering_level (rinoh.structure.ListItemLabelStyle attribute), 67, 130
- numbering_level (rinoh.structure.ListOfEntryStyle attribute), 141
- numbering_level (rinoh.structure.ListOfStyle attribute), 137
- numbering_level (rinoh.structure.TableOfContentsEntryStyle attribute), 78
- numbering_level (rinoh.structure.TableOfContentsStyle attribute), 74
- NumberStyle (class in rinoh.number), 113

O

- OptionSet (class in rinoh.attribute), 99
- ordered (rinoh.structure.ListStyle attribute), 63, 126
- OverrideDefault (class in rinoh.attribute), 99

P

- padding (rinoh.flowable.FloatStyle attribute), 27
- padding (rinoh.flowable.FlowableStyle attribute), 20
- padding (rinoh.flowable.GroupedFlowablesStyle attribute), 25
- padding (rinoh.flowable.LabeledFlowableStyle attribute), 23
- padding (rinoh.image.CaptionStyle attribute), 30
- padding (rinoh.image.FigureStyle attribute), 34
- padding (rinoh.index.IndexStyle attribute), 37
- padding (rinoh.inline.InlineFlowableStyle attribute), 46
- padding (rinoh.paragraph.ParagraphStyle attribute), 40
- padding (rinoh.reference.NoteStyle attribute), 123
- padding (rinoh.reference.ReferencingParagraphStyle attribute), 50
- padding (rinoh.structure.AdmonitionStyle attribute), 83
- padding (rinoh.structure.HeadingStyle attribute), 60
- padding (rinoh.structure.HorizontalRuleStyle attribute), 85
- padding (rinoh.structure.ListItemLabelStyle attribute), 68, 130
- padding (rinoh.structure.ListOfEntryStyle attribute), 141
- padding (rinoh.structure.ListOfStyle attribute), 135
- padding (rinoh.structure.ListStyle attribute), 64, 127
- padding (rinoh.structure.SectionStyle attribute), 57
- padding (rinoh.structure.TableOfContentsEntryStyle attribute), 78
- padding (rinoh.structure.TableOfContentsStyle attribute), 72
- padding (rinoh.table.TableCellStyle attribute), 90
- padding (rinoh.table.TableStyle attribute), 88
- padding (rinoh.table.TableWithCaptionStyle attribute), 148
- padding_bottom (rinoh.flowable.FloatStyle attribute), 27
- padding_bottom (rinoh.flowable.FlowableStyle attribute), 20

padding_bottom (rinoh.flowable.GroupedFlowablesStyle attribute), 25

padding_bottom (rinoh.flowable.LabeledFlowableStyle attribute), 23

padding_bottom (rinoh.image.CaptionStyle attribute), 30

padding_bottom (rinoh.image.FigureStyle attribute), 35

padding_bottom (rinoh.index.IndexStyle attribute), 37

padding_bottom (rinoh.inline.InlineFlowableStyle attribute), 47

padding_bottom (rinoh.paragraph.ParagraphStyle attribute), 40

padding_bottom (rinoh.reference.NoteStyle attribute), 124

padding_bottom (rinoh.reference.ReferencingParagraphStyle attribute), 50

padding_bottom (rinoh.structure.AdmonitionStyle attribute), 83

padding_bottom (rinoh.structure.HeadingStyle attribute), 60

padding_bottom (rinoh.structure.HorizontalRuleStyle attribute), 86

padding_bottom (rinoh.structure.ListItemLabelStyle attribute), 68, 131

padding_bottom (rinoh.structure.ListOfEntryStyle attribute), 142

padding_bottom (rinoh.structure.ListOfStyle attribute), 136

padding_bottom (rinoh.structure.ListStyle attribute), 65, 127

padding_bottom (rinoh.structure.SectionStyle attribute), 57

padding_bottom (rinoh.structure.TableOfContentsEntryStyle attribute), 79

padding_bottom (rinoh.structure.TableOfContentsStyle attribute), 73

padding_bottom (rinoh.table.TableCellStyle attribute), 90

padding_bottom (rinoh.table.TableStyle attribute), 88

padding_bottom (rinoh.table.TableWithCaptionStyle attribute), 148

padding_left (rinoh.flowable.FloatStyle attribute), 27

padding_left (rinoh.flowable.FlowableStyle attribute), 20

padding_left (rinoh.flowable.GroupedFlowablesStyle attribute), 25

padding_left (rinoh.flowable.LabeledFlowableStyle attribute), 23

padding_left (rinoh.image.CaptionStyle attribute), 30

padding_left (rinoh.image.FigureStyle attribute), 34

padding_left (rinoh.index.IndexStyle attribute), 37

padding_left (rinoh.inline.InlineFlowableStyle attribute), 46

padding_left (rinoh.paragraph.ParagraphStyle attribute), 40

padding_left (rinoh.reference.NoteStyle attribute), 124

padding_left (rinoh.reference.ReferencingParagraphStyle attribute), 50

padding_left (rinoh.structure.AdmonitionStyle attribute), 83

padding_left (rinoh.structure.HeadingStyle attribute), 60

padding_left (rinoh.structure.HorizontalRuleStyle attribute), 85

padding_left (rinoh.structure.ListItemLabelStyle attribute), 68, 131

padding_left (rinoh.structure.ListOfEntryStyle attribute), 141

padding_left (rinoh.structure.ListOfStyle attribute), 135

padding_left (rinoh.structure.ListStyle attribute), 64, 127

padding_left (rinoh.structure.SectionStyle attribute), 57

padding_left (rinoh.structure.TableOfContentsEntryStyle attribute), 78

padding_left (rinoh.structure.TableOfContentsStyle attribute), 72

padding_left (rinoh.table.TableCellStyle attribute), 90

padding_left (rinoh.table.TableStyle attribute), 88

padding_left (rinoh.table.TableWithCaptionStyle attribute), 148

padding_right (rinoh.flowable.FloatStyle attribute), 27

padding_right (rinoh.flowable.FlowableStyle attribute), 20

padding_right (rinoh.flowable.GroupedFlowablesStyle attribute), 25

padding_right (rinoh.flowable.LabeledFlowableStyle attribute), 23

padding_right (rinoh.image.CaptionStyle attribute), 30

padding_right (rinoh.image.FigureStyle attribute), 34

padding_right (rinoh.index.IndexStyle attribute), 37

padding_right (rinoh.inline.InlineFlowableStyle attribute), 46

padding_right (rinoh.paragraph.ParagraphStyle attribute), 40

padding_right (rinoh.reference.NoteStyle attribute), 124

padding_right (rinoh.reference.ReferencingParagraphStyle attribute), 50

padding_right (rinoh.structure.AdmonitionStyle attribute), 83

padding_right (rinoh.structure.HeadingStyle attribute), 60

padding_right (rinoh.structure.HorizontalRuleStyle attribute), 85

padding_right (rinoh.structure.ListItemLabelStyle attribute), 68, 131

padding_right (rinoh.structure.ListOfEntryStyle attribute), 141

padding_right (rinoh.structure.ListOfStyle attribute), 135

padding_right (rinoh.structure.ListStyle attribute), 64, 127

padding_right (rinoh.structure.SectionStyle attribute), 57

padding_right (rinoh.structure.TableOfContentsEntryStyle attribute), 78

padding_right (rinoh.structure.TableOfContentsStyle attribute), 72

padding_right (rinoh.table.TableCellStyle attribute), 90

padding_right (rinoh.table.TableStyle attribute), 88

padding_right (rinoh.table.TableWithCaptionStyle attribute), 148

padding_top (rinoh.flowable.FloatStyle attribute), 27

padding_top (rinoh.flowable.FlowableStyle attribute), 20

padding_top (rinoh.flowable.GroupedFlowablesStyle attribute), 25

padding_top (rinoh.flowable.LabeledFlowableStyle attribute), 23

padding_top (rinoh.image.CaptionStyle attribute), 30

padding_top (rinoh.image.FigureStyle attribute), 35

padding_top (rinoh.index.IndexStyle attribute), 37

padding_top (rinoh.inline.InlineFlowableStyle attribute), 46

padding_top (rinoh.paragraph.ParagraphStyle attribute), 40

padding_top (rinoh.reference.NoteStyle attribute), 124

padding_top (rinoh.reference.ReferencingParagraphStyle attribute), 50

padding_top (rinoh.structure.AdmonitionStyle attribute), 83

padding_top (rinoh.structure.HeadingStyle attribute), 60

padding_top (rinoh.structure.HorizontalRuleStyle attribute), 85

padding_top (rinoh.structure.ListItemLabelStyle attribute), 68, 131

padding_top (rinoh.structure.ListOfEntryStyle attribute), 142

padding_top (rinoh.structure.ListOfStyle attribute), 136

padding_top (rinoh.structure.ListStyle attribute), 65, 127

padding_top (rinoh.structure.SectionStyle attribute), 57

padding_top (rinoh.structure.TableOfContentsEntryStyle attribute), 79

padding_top (rinoh.structure.TableOfContentsStyle attribute), 72

padding_top (rinoh.table.TableCellStyle attribute), 90

padding_top (rinoh.table.TableStyle attribute), 88

padding_top (rinoh.table.TableWithCaptionStyle attribute), 148

Page (class in rinoh.document), 102

page (rinoh.document.Page property), 102

page_break (rinoh.flowable.FloatStyle attribute), 28

page_break (rinoh.flowable.FlowableStyle attribute), 21

page_break (rinoh.flowable.GroupedFlowablesStyle attribute), 26

page_break (rinoh.flowable.LabeledFlowableStyle attribute), 24

page_break (rinoh.image.CaptionStyle attribute), 31

page_break (rinoh.image.FigureStyle attribute), 35

page_break (rinoh.index.IndexStyle attribute), 38

page_break (rinoh.inline.InlineFlowableStyle attribute), 47

page_break (rinoh.paragraph.ParagraphStyle attribute), 41

page_break (rinoh.reference.NoteStyle attribute), 125

page_break (rinoh.reference.ReferencingParagraphStyle attribute), 51

page_break (rinoh.structure.AdmonitionStyle attribute), 84

page_break (rinoh.structure.HeadingStyle attribute), 61

page_break (rinoh.structure.HorizontalRuleStyle attribute), 86

page_break (rinoh.structure.ListItemLabelStyle attribute), 69, 132

page_break (rinoh.structure.ListOfEntryStyle attribute), 142

page_break (rinoh.structure.ListOfStyle attribute), 136

page_break (rinoh.structure.ListStyle attribute), 65, 128

page_break (rinoh.structure.SectionStyle attribute), 58

page_break (rinoh.structure.TableOfContentsEntryStyle attribute), 79

page_break (rinoh.structure.TableOfContentsStyle attribute), 73
 page_break (rinoh.table.TableCellStyle attribute), 91
 page_break (rinoh.table.TableStyle attribute), 89
 page_break (rinoh.table.TableWithCaptionStyle attribute), 149
 page_number_format (rinoh.template.ContentsPartTemplate attribute), 154
 page_number_format (rinoh.template.DocumentPartTemplate attribute), 153
 page_number_format (rinoh.template.FixedDocumentPartTemplate attribute), 155
 page_number_format (rinoh.template.TitlePartTemplate attribute), 153
 page_number_prefix (rinoh.template.ContentsPartTemplate attribute), 154
 page_number_prefix (rinoh.template.DocumentPartTemplate attribute), 153
 page_number_prefix (rinoh.template.FixedDocumentPartTemplate attribute), 154
 page_number_prefix (rinoh.template.TitlePartTemplate attribute), 153
 page_orientation (rinoh.template.BodyPageTemplate attribute), 157
 page_orientation (rinoh.template.BodyPageTemplateBase attribute), 156
 page_orientation (rinoh.template.PageTemplateBase attribute), 160
 page_orientation (rinoh.template.TitlePageTemplate attribute), 159
 page_size (rinoh.template.BodyPageTemplate attribute), 157
 page_size (rinoh.template.BodyPageTemplateBase attribute), 155
 page_size (rinoh.template.PageTemplateBase attribute), 159
 page_size (rinoh.template.TitlePageTemplate attribute), 158
 PageBreak (class in rinoh.flowable), 104
 PageNumberFormat (class in rinoh.document), 103
 PageOrientation (class in rinoh.document), 102
 PageTemplateBase (class in rinoh.template), 159
 PageType (class in rinoh.document), 102
 Paper (class in rinoh.paper), 114
 Paragraph (class in rinoh.paragraph), 116
 ParagraphBase (class in rinoh.paragraph), 115
 ParagraphState (class in rinoh.paragraph), 116
 ParagraphStyle (class in rinoh.paragraph), 39
 parse_string() (rinoh.color.Color class method), 100
 ParseError, 99
 parts (rinoh.template.DocumentTemplate attribute), 151
 parts (rinoh.templates.article.Article attribute), 93
 parts (rinoh.templates.book.Book attribute), 94
 PartsList (class in rinoh.template), 152
 PERCENT (in module rinoh.dimension), 101
 PICA (in module rinoh.dimension), 101
 PL (in module rinoh.language), 113
 place() (rinoh.document.Page method), 102
 Polygon (class in rinoh.draw), 103
 position (rinoh.image.CaptionStyle attribute), 32
 position (rinoh.paragraph.ParagraphStyle attribute), 43
 position (rinoh.reference.NoteMarkerStyle attribute), 54
 position (rinoh.reference.ReferenceStyle attribute), 120
 position (rinoh.reference.ReferencingParagraphStyle attribute), 52
 position (rinoh.structure.HeadingStyle attribute), 62
 position (rinoh.structure.ListItemLabelStyle attribute), 70, 133
 position (rinoh.structure.ListOfEntryStyle attribute), 144
 position (rinoh.structure.ListOfStyle attribute), 139
 position (rinoh.structure.TableOfContentsEntryStyle attribute), 81
 position (rinoh.structure.TableOfContentsStyle attribute), 76
 position (rinoh.text.TextStyle attribute), 44
 prepare() (rinoh.flowable.LabeledFlowable method), 104
 prepare() (rinoh.flowable.StaticGroupedFlowables method), 105
 prepare() (rinoh.paragraph.ParagraphBase method), 115
 prepare() (rinoh.reference.NoteMarkerBase method), 125
 prepare() (rinoh.reference.NoteMarkerWithNote method), 125

prepare() (rinoh.structure.Heading method), 126
prepare() (rinoh.table.Table method), 147
prepare() (rinoh.table.TableRow method), 150
prepare() (rinoh.table.TableSection method), 150
prepare() (rinoh.text.MixedStyledText method), 116
ProportionalSpacing (class in rinoh.paragraph), 117
PT (in module rinoh.dimension), 101

Q

QUARTERS (in module rinoh.dimension), 101
quiet (rinoh.reference.NoteMarkerStyle attribute), 53
quiet (rinoh.reference.ReferenceStyle attribute), 119

R

Rectangle (class in rinoh.draw), 103
Reference (class in rinoh.reference), 119
ReferenceField (class in rinoh.reference), 121
ReferenceStyle (class in rinoh.reference), 119
ReferenceText (class in rinoh.reference), 122
ReferenceType (class in rinoh.reference), 122
ReferencingParagraph (class in rinoh.reference), 122
ReferencingParagraphStyle (class in rinoh.reference), 48
render() (rinoh.document.Document method), 102
render() (rinoh.document.Page method), 102
render() (rinoh.flowable.GroupedFlowables method), 105
render() (rinoh.flowable.GroupedLabeledFlowables method), 105
render() (rinoh.flowable.LabeledFlowable method), 104
render() (rinoh.paragraph.ParagraphBase method), 115
render() (rinoh.structure.HorizontalRule method), 145
render() (rinoh.table.Table method), 147
repeat_head (rinoh.table.TableStyle attribute), 87
rgba (rinoh.color.Color property), 100
right_margin (rinoh.template.BodyPageTemplate attribute), 158
right_margin (rinoh.template.BodyPageTemplateBase attribute), 156
right_margin (rinoh.template.PageTemplateBase attribute), 160
right_margin (rinoh.template.TitlePageTemplate attribute), 159
rinoh command line option
 --docs, 6
 --format, 5
 --help, 5
 --install-resources, 5
 --list-fonts, 6
 --list-formats, 6
 --list-options, 6
 --list-stylesheets, 5
 --list-templates, 5
 --option, 5
 --output, 5
 --paper, 5
 --stylesheet, 5
 --template, 5
 --version, 6
 --versions, 6
 -f, 5
 -h, 5
 -i, 5
 -O, 5

- o, 5
- p, 5
- s, 5
- t, 5
- input, 5
- rinoh.attribute
 - module, 99
- rinoh.color
 - module, 100
- rinoh.dimension
 - module, 100
- rinoh.document
 - module, 101
- rinoh.draw
 - module, 103
- rinoh.flowable
 - module, 103
- rinoh.font
 - module, 106
- rinoh.font.style
 - module, 108
- rinoh.image
 - module, 108
- rinoh.index
 - module, 110
- rinoh.inline
 - module, 117
- rinoh.language
 - module, 110
- rinoh.number
 - module, 113
- rinoh.paper
 - module, 114
- rinoh.paragraph
 - module, 115
- rinoh.reference
 - module, 119
- rinoh.strings
 - module, 145
- rinoh.structure
 - module, 125
- rinoh.style
 - module, 145
- rinoh.stylesheets
 - module, 11
- rinoh.table
 - module, 147
- rinoh.template
 - module, 151
- rinoh.templates.article
 - module, 93
- rinoh.templates.book
 - module, 94
- rinoh.text
 - module, 116
- rinoh_documents
 - Sphinx builder configuration value, 7
- rinoh_domain_indices

- Sphinx builder configuration value, 9
- rinoh_logo
 - Sphinx builder configuration value, 9
- rinoh_metadata
 - Sphinx builder configuration value, 9
- rinoh_paper_size
 - Sphinx builder configuration value, 8
- rinoh_stylesheet
 - Sphinx builder configuration value, 8
- rinoh_targets
 - Sphinx builder configuration value, 8
- rinoh_template
 - Sphinx builder configuration value, 8
- root (rinoh.attribute.RuleSetFile property), 99
- rotate (rinoh.image.ImageArgs attribute), 109
- RuleSet (class in rinoh.attribute), 99
- RuleSetFile (class in rinoh.attribute), 99

S

- same_page (rinoh.flowable.GroupedFlowablesStyle attribute), 24
- same_page (rinoh.image.FigureStyle attribute), 36
- same_page (rinoh.index.IndexStyle attribute), 37
- same_page (rinoh.structure.ListOfStyle attribute), 135
- same_page (rinoh.structure.ListStyle attribute), 64, 126
- same_page (rinoh.structure.SectionStyle attribute), 56
- same_page (rinoh.structure.TableOfContentsStyle attribute), 72
- same_page (rinoh.table.TableCellStyle attribute), 90
- same_page (rinoh.table.TableWithCaptionStyle attribute), 150
- Scale (class in rinoh.image), 109
- scale (rinoh.image.ImageArgs attribute), 109
- script_level() (rinoh.text.StyledText method), 116
- Section (class in rinoh.structure), 125
- SectionStyle (class in rinoh.structure), 56
- SetMetadataFlowable (class in rinoh.flowable), 104
- Shape (class in rinoh.draw), 103
- ShapeStyle (class in rinoh.draw), 19
- show_in_toc (rinoh.structure.SectionStyle attribute), 56
- sideways (rinoh.template.BodyPageTemplate attribute), 158
- sideways (rinoh.template.BodyPageTemplateBase attribute), 156
- sideways (rinoh.template.PageTemplateBase attribute), 160
- sideways (rinoh.template.TitlePageTemplate attribute), 159
- SINGLE (in module rinoh.paragraph), 118
- SingleStyledText (class in rinoh.text), 116
- space_above (rinoh.flowable.FloatStyle attribute), 27
- space_above (rinoh.flowable.FlowableStyle attribute), 20
- space_above (rinoh.flowable.GroupedFlowablesStyle attribute), 25
- space_above (rinoh.flowable.LabeledFlowableStyle attribute), 22
- space_above (rinoh.image.CaptionStyle attribute), 30
- space_above (rinoh.image.FigureStyle attribute), 34
- space_above (rinoh.index.IndexStyle attribute), 37
- space_above (rinoh.inline.InlineFlowableStyle attribute), 46
- space_above (rinoh.paragraph.ParagraphStyle attribute), 40
- space_above (rinoh.reference.NoteStyle attribute), 123
- space_above (rinoh.reference.ReferencingParagraphStyle attribute), 49
- space_above (rinoh.structure.AdmonitionStyle attribute), 83
- space_above (rinoh.structure.HeadingStyle attribute), 59
- space_above (rinoh.structure.HorizontalRuleStyle attribute), 85

- space_above (rinoh.structure.ListItemLabelStyle attribute), 67, 130
- space_above (rinoh.structure.ListOfEntryStyle attribute), 141
- space_above (rinoh.structure.ListOfStyle attribute), 135
- space_above (rinoh.structure.ListStyle attribute), 64, 127
- space_above (rinoh.structure.SectionStyle attribute), 56
- space_above (rinoh.structure.TableOfContentsEntryStyle attribute), 78
- space_above (rinoh.structure.TableOfContentsStyle attribute), 72
- space_above (rinoh.table.TableCellStyle attribute), 90
- space_above (rinoh.table.TableStyle attribute), 87
- space_above (rinoh.table.TableWithCaptionStyle attribute), 148
- space_below (rinoh.flowable.FloatStyle attribute), 27
- space_below (rinoh.flowable.FlowableStyle attribute), 20
- space_below (rinoh.flowable.GroupedFlowablesStyle attribute), 25
- space_below (rinoh.flowable.LabeledFlowableStyle attribute), 22
- space_below (rinoh.image.CaptionStyle attribute), 30
- space_below (rinoh.image.FigureStyle attribute), 34
- space_below (rinoh.index.IndexStyle attribute), 37
- space_below (rinoh.inline.InlineFlowableStyle attribute), 46
- space_below (rinoh.paragraph.ParagraphStyle attribute), 40
- space_below (rinoh.reference.NoteStyle attribute), 123
- space_below (rinoh.reference.ReferencingParagraphStyle attribute), 49
- space_below (rinoh.structure.AdmonitionStyle attribute), 83
- space_below (rinoh.structure.HeadingStyle attribute), 59
- space_below (rinoh.structure.HorizontalRuleStyle attribute), 85
- space_below (rinoh.structure.ListItemLabelStyle attribute), 67, 130
- space_below (rinoh.structure.ListOfEntryStyle attribute), 141
- space_below (rinoh.structure.ListOfStyle attribute), 135
- space_below (rinoh.structure.ListStyle attribute), 64, 127
- space_below (rinoh.structure.SectionStyle attribute), 56
- space_below (rinoh.structure.TableOfContentsEntryStyle attribute), 78
- space_below (rinoh.structure.TableOfContentsStyle attribute), 72
- space_below (rinoh.table.TableCellStyle attribute), 90
- space_below (rinoh.table.TableStyle attribute), 87
- space_below (rinoh.table.TableWithCaptionStyle attribute), 148
- sphinx (in module rinoh.stylesheets), 11
- Sphinx builder configuration value
 - rinoh_documents, 7
 - rinoh_domain_indices, 9
 - rinoh_logo, 9
 - rinoh_metadata, 9
 - rinoh_paper_size, 8
 - rinoh_stylesheet, 8
 - rinoh_targets, 8
 - rinoh_template, 8
- sphinx_article (in module rinoh.stylesheets), 11
- sphinx_base14 (in module rinoh.stylesheets), 11
- split_minimum_lines (rinoh.image.CaptionStyle attribute), 29
- split_minimum_lines (rinoh.paragraph.ParagraphStyle attribute), 39
- split_minimum_lines (rinoh.reference.ReferencingParagraphStyle attribute), 49
- split_minimum_lines (rinoh.structure.HeadingStyle attribute), 59
- split_minimum_lines (rinoh.structure.ListItemLabelStyle attribute), 67, 130
- split_minimum_lines (rinoh.structure.ListOfEntryStyle attribute), 140
- split_minimum_lines (rinoh.structure.ListOfStyle attribute), 137
- split_minimum_lines (rinoh.structure.TableOfContentsEntryStyle attribute), 77
- split_minimum_lines (rinoh.structure.TableOfContentsStyle attribute), 74
- split_minimum_rows (rinoh.table.TableStyle attribute), 87
- STANDARD (in module rinoh.paragraph), 118
- StaticGroupedFlowables (class in rinoh.flowable), 105

StringField (class in rinoh.strings), 145
 Strings (class in rinoh.strings), 145
 strings (rinoh.template.DocumentTemplate attribute), 151
 strings (rinoh.templates.article.Article attribute), 93
 strings (rinoh.templates.book.Book attribute), 94
 Stroke (class in rinoh.draw), 103
 stroke (rinoh.draw.LineStyle attribute), 19
 stroke (rinoh.draw.ShapeStyle attribute), 19
 stroke (rinoh.structure.HorizontalRuleStyle attribute), 87
 stroke (rinoh.table.TableCellBackgroundStyle attribute), 92
 stroke (rinoh.table.TableCellBorderStyle attribute), 92
 Style (class in rinoh.style), 146
 style_class (rinoh.draw.Line attribute), 103
 style_class (rinoh.draw.Shape attribute), 103
 style_class (rinoh.flowable.Float attribute), 106
 style_class (rinoh.flowable.GroupedFlowables attribute), 105
 style_class (rinoh.flowable.LabeledFlowable attribute), 104
 style_class (rinoh.image.Caption attribute), 109
 style_class (rinoh.image.Figure attribute), 110
 style_class (rinoh.index.Index attribute), 110
 style_class (rinoh.inline.InlineFlowable attribute), 117
 style_class (rinoh.paragraph.ParagraphBase attribute), 115
 style_class (rinoh.reference.Note attribute), 122
 style_class (rinoh.reference.NoteMarkerBase attribute), 125
 style_class (rinoh.reference.ReferencingParagraph attribute), 122
 style_class (rinoh.structure.Admonition attribute), 145
 style_class (rinoh.structure.Heading attribute), 125
 style_class (rinoh.structure.HorizontalRule attribute), 145
 style_class (rinoh.structure.List attribute), 126
 style_class (rinoh.structure.ListItemLabel attribute), 129
 style_class (rinoh.structure.TableOfContents attribute), 134
 style_class (rinoh.structure.TableOfContentsEntry attribute), 134
 style_class (rinoh.style.Styled attribute), 146
 style_class (rinoh.table.Table attribute), 147
 style_class (rinoh.table.TableCell attribute), 150
 style_class (rinoh.table.TableCellBackground attribute), 150
 style_class (rinoh.table.TableCellBorder attribute), 150
 style_class (rinoh.table.TableWithCaption attribute), 147
 style_class (rinoh.text.StyledText attribute), 116
 Styled (class in rinoh.style), 145
 StyledMatcher (class in rinoh.style), 147
 StyledText (class in rinoh.text), 116
 StyleSheet (class in rinoh.style), 146
 stylesheet (rinoh.template.DocumentTemplate attribute), 151
 stylesheet (rinoh.templates.article.Article attribute), 93
 stylesheet (rinoh.templates.book.Book attribute), 94
 StyleSheetFile (class in rinoh.style), 147

T

tab_stops (rinoh.image.CaptionStyle attribute), 29
 tab_stops (rinoh.paragraph.ParagraphStyle attribute), 39
 tab_stops (rinoh.reference.ReferencingParagraphStyle attribute), 48
 tab_stops (rinoh.structure.HeadingStyle attribute), 59
 tab_stops (rinoh.structure.ListItemLabelStyle attribute), 67, 130
 tab_stops (rinoh.structure.ListOfEntryStyle attribute), 140
 tab_stops (rinoh.structure.ListOfStyle attribute), 137
 tab_stops (rinoh.structure.TableOfContentsEntryStyle attribute), 77

tab_stops (rinoh.structure.TableOfContentsStyle attribute), 74
 TabAlign (class in rinoh.paragraph), 118
 Table (class in rinoh.table), 147
 TableBody (class in rinoh.table), 150
 TableCell (class in rinoh.table), 150
 TableCellBackground (class in rinoh.table), 150
 TableCellBackgroundStyle (class in rinoh.table), 92
 TableCellBorder (class in rinoh.table), 150
 TableCellBorderStyle (class in rinoh.table), 92
 TableCellStyle (class in rinoh.table), 89
 TableHead (class in rinoh.table), 150
 TableOfContents (class in rinoh.structure), 134
 TableOfContentsEntry (class in rinoh.structure), 134
 TableOfContentsEntryStyle (class in rinoh.structure), 77
 TableOfContentsSection (class in rinoh.structure), 134
 TableOfContentsStyle (class in rinoh.structure), 71
 TableRow (class in rinoh.table), 150
 TableSection (class in rinoh.table), 150
 TableStyle (class in rinoh.table), 87
 TableWithCaption (class in rinoh.table), 147
 TableWithCaptionStyle (class in rinoh.table), 147
 TABLOID (in module rinoh.paper), 115
 TabStop (class in rinoh.paragraph), 118
 TabStopList (class in rinoh.paragraph), 119
 target_has_class() (rinoh.reference.ReferencingParagraph method), 122
 target_has_classes() (rinoh.reference.ReferencingParagraph method), 122
 target_is_of_type() (rinoh.reference.ReferencingParagraph method), 122
 target_style() (rinoh.reference.ReferencingParagraph method), 122
 template (rinoh.template.TemplateConfiguration attribute), 152
 TemplateConfiguration (class in rinoh.template), 151
 text (rinoh.reference.ReferencingParagraphStyle attribute), 48
 text (rinoh.structure.ListOfEntryStyle attribute), 140
 text (rinoh.structure.TableOfContentsEntryStyle attribute), 77
 text_align (rinoh.image.CaptionStyle attribute), 29
 text_align (rinoh.paragraph.ParagraphStyle attribute), 39
 text_align (rinoh.reference.ReferencingParagraphStyle attribute), 48
 text_align (rinoh.structure.HeadingStyle attribute), 59
 text_align (rinoh.structure.ListItemLabelStyle attribute), 67, 129
 text_align (rinoh.structure.ListOfEntryStyle attribute), 140
 text_align (rinoh.structure.ListOfStyle attribute), 137
 text_align (rinoh.structure.TableOfContentsEntryStyle attribute), 77
 text_align (rinoh.structure.TableOfContentsStyle attribute), 74
 TextAlign (class in rinoh.paragraph), 117
 TextPosition (class in rinoh.font.style), 108
 TextStyle (class in rinoh.text), 44
 title (rinoh.flowable.GroupedFlowablesStyle attribute), 24
 title (rinoh.image.FigureStyle attribute), 36
 title (rinoh.index.IndexStyle attribute), 36
 title (rinoh.structure.ListOfStyle attribute), 134
 title (rinoh.structure.ListStyle attribute), 64, 126
 title (rinoh.structure.SectionStyle attribute), 56
 title (rinoh.structure.TableOfContentsStyle attribute), 71
 title (rinoh.table.TableCellStyle attribute), 89
 title (rinoh.table.TableWithCaptionStyle attribute), 149
 TitlePageTemplate (class in rinoh.template), 158
 TitlePartTemplate (class in rinoh.template), 153
 to_string() (rinoh.index.InlineIndexTarget method), 110
 to_string() (rinoh.text.StyledText method), 116

top_margin (rinoh.template.BodyPageTemplate attribute), 158
 top_margin (rinoh.template.BodyPageTemplateBase attribute), 156
 top_margin (rinoh.template.PageTemplateBase attribute), 160
 top_margin (rinoh.template.TitlePageTemplate attribute), 159
 type (rinoh.reference.NoteMarkerStyle attribute), 53
 type (rinoh.reference.ReferenceStyle attribute), 119
 Typeface (class in rinoh.font), 107
 typeface (rinoh.image.CaptionStyle attribute), 32
 typeface (rinoh.paragraph.ParagraphStyle attribute), 42
 typeface (rinoh.reference.NoteMarkerStyle attribute), 53
 typeface (rinoh.reference.ReferenceStyle attribute), 119
 typeface (rinoh.reference.ReferencingParagraphStyle attribute), 51
 typeface (rinoh.structure.HeadingStyle attribute), 61
 typeface (rinoh.structure.ListItemLabelStyle attribute), 69, 132
 typeface (rinoh.structure.ListOfEntryStyle attribute), 143
 typeface (rinoh.structure.ListOfStyle attribute), 138
 typeface (rinoh.structure.TableOfContentsEntryStyle attribute), 80
 typeface (rinoh.structure.TableOfContentsStyle attribute), 75
 typeface (rinoh.text.TextStyle attribute), 44

U

update() (rinoh.style.StyledMatcher method), 147

V

vertical_align (rinoh.table.TableCellStyle attribute), 89
 VerticalAlign (class in rinoh.table), 150

W

WarnFlowable (class in rinoh.flowable), 104
 width (rinoh.flowable.FloatStyle attribute), 27
 width (rinoh.flowable.FlowableStyle attribute), 19
 width (rinoh.flowable.GroupedFlowablesStyle attribute), 24
 width (rinoh.flowable.LabeledFlowableStyle attribute), 22
 width (rinoh.image.CaptionStyle attribute), 29
 width (rinoh.image.FigureStyle attribute), 34
 width (rinoh.image.ImageArgs attribute), 109
 width (rinoh.index.IndexStyle attribute), 36
 width (rinoh.inline.InlineFlowableStyle attribute), 46
 width (rinoh.paragraph.ParagraphStyle attribute), 39
 width (rinoh.reference.NoteStyle attribute), 123
 width (rinoh.reference.ReferencingParagraphStyle attribute), 48
 width (rinoh.structure.AdmonitionStyle attribute), 83
 width (rinoh.structure.HeadingStyle attribute), 58
 width (rinoh.structure.HorizontalRuleStyle attribute), 85
 width (rinoh.structure.ListItemLabelStyle attribute), 66, 129
 width (rinoh.structure.ListOfEntryStyle attribute), 140
 width (rinoh.structure.ListOfStyle attribute), 134
 width (rinoh.structure.ListStyle attribute), 63, 126
 width (rinoh.structure.SectionStyle attribute), 56
 width (rinoh.structure.TableOfContentsEntryStyle attribute), 77
 width (rinoh.structure.TableOfContentsStyle attribute), 71
 width (rinoh.table.TableCellStyle attribute), 89
 width (rinoh.table.TableStyle attribute), 87
 width (rinoh.table.TableWithCaptionStyle attribute), 147
 wrap_label (rinoh.flowable.LabeledFlowableStyle attribute), 22
 wrap_label (rinoh.reference.NoteStyle attribute), 123
 wrap_label (rinoh.structure.AdmonitionStyle attribute), 82

Y

`y_offset()` (`rinoh.text.StyledText` method), 116