

Workshop 3: Functions and modules

FIE463: Numerical Methods in Macroeconomics and Finance using Python

Richard Foltyn

Norwegian School of Economics (NHH)

January 30, 2025

See GitHub repository for notebooks and data:

<https://github.com/richardfoltyn/FIE463-V25>

1 Standard deviation of a sequence of numbers

The standard deviation σ characterizes the dispersion of a sequence of data (x_1, x_2, \dots, x_N) around its mean \bar{x} . It is computed as the square root of the variance σ^2 , defined as

$$\sigma^2 = \frac{1}{N} \sum_{i=1}^N (x_i - \bar{x})^2$$

where N is the number of elements (we ignore the degrees-of-freedom correction), and the mean \bar{x} is defined as

$$\bar{x} = \frac{1}{N} \sum_{i=1}^N x_i$$

The above formula for the variance can be rewritten as

$$\sigma^2 = \left(\frac{1}{N} \sum_{i=1}^N x_i^2 \right) - \bar{x}^2$$

This suggests the following algorithm to compute the standard deviation:

1. Compute the mean $\bar{x} = \frac{1}{N} \sum_{i=1}^N x_i$
2. Compute the mean of squares $S = \frac{1}{N} \sum_{i=1}^N x_i^2$
3. Compute the variance $\sigma^2 = S - \bar{x}^2$
4. Compute the standard deviation $\sigma = \sqrt{\sigma^2}$

In this exercise, you are asked to implement the above algorithm and compare your function with NumPy's implementation `np.std()`.

1. Create a module `my_stats.py` and add the function

```
def my_std(x):  
    """  
    Compute and return the standard deviation of the sequence x.  
    """
```

which implements the above algorithm to compute the standard deviation of a given sequence x (this could be a tuple, list, array, etc.). Your implementation should only use built-in functions such as `len()`, `sum()`, and `sqrt()` from the `math` module.

2. Import this function into the Jupyter notebook. Using an array of 11 elements which are uniformly spaced on the interval $[0, 10]$, confirm that your function returns the same value as `np.std()`.
3. Benchmark your implementation against `np.std()` for three different arrays with 11, 101, and 10001 elements which are uniformly spaced on the interval $[0, 10]$.

Hint: Use the cell magic `%timeit` to time the execution of a statement.

2 Locating maximum values

In this exercise, you are asked to write a function that returns the position of the largest element from a given sequence (list, tuple, array, etc.).

1. Write a function `my_argmax()` that takes as argument a sequence and returns the (first) index where the maximum value is located. Only use built-in functionality in your implementation (no NumPy).
2. Create an array with 101 values constructed using the sine function,

```
arr = np.sin(np.linspace(0.0, np.pi, 101))
```

and use it to test your function.

3. Compare the result returned by your function to NumPy's implementation `np.argmax()`.

3 Two-period consumption-savings problem

This exercise asks you to find the utility-maximizing consumption levels using grid search, an algorithm that evaluates all possible alternatives from a given set (the "grid") to locate the maximum.

Consider the following standard consumption-savings problem over two periods with lifetime utility $U(c_1, c_2)$ given by

$$\begin{aligned} \max_{c_1, c_2} \quad & U(c_1, c_2) = u(c_1) + \beta u(c_2) \\ \text{s.t.} \quad & c_1 + \frac{c_2}{1+r} = w \\ & c_1 \geq 0, c_2 \geq 0 \end{aligned}$$

where γ is the RRA coefficient, β is the discount factor, r is the interest rate, w is initial wealth, (c_1, c_2) is the optimal consumption allocation to be determined, and $u(c)$ is the per-period CRRA utility function given by

$$u(c) = \begin{cases} \frac{c^{1-\gamma}}{1-\gamma} & \text{if } \gamma \neq 1 \\ \ln(c) & \text{if } \gamma = 1 \end{cases}$$

The second line is the budget constraint which ensures that the chosen consumption bundle (c_1, c_2) is feasible.

1. Write a function `util(x, gamma)` which evaluates the per-period utility $u(c)$ for a given consumption level c and the parameter γ . Make sure to take into account the log case!

Hint: You can use the `np.log()` function from NumPy to compute the natural logarithm.

2. Write a function `util_life(c_1, c_2, beta, gamma)` which uses `util()` from above to compute the lifetime utility $U(c_1, c_2)$ for given consumption levels (c_1, c_2) and parameters.
3. Assume that $r = 0.04$, $\beta = 0.96$, $\gamma = 1$, and $w = 1$.

- Create a candidate array (grid) of period-1 consumption levels with 100 grid points which are uniformly spaced on the interval $[10^{-5}, w]$.
- Compute the implied array of period-2 consumption levels from the budget constraint.

- Given these candidate consumption levels, use the function `util_life()` you wrote earlier to evaluate lifetime utility for each bundle of consumption levels (c_1, c_2) .
4. Use the function `np.argmax()` to locate the index at which lifetime utility is maximized. Print the maximizing consumption levels (c_1, c_2) as well as the associated maximized utility level.