

Threat Modeling Report

Created on 10/05/2026 12:15:59 am

Threat Model Name:

Owner:

Reviewer:

Contributors:

Description:


Assumptions:

External Dependencies:

Threat Model Summary:

Not Started	21
Not Applicable	0
Needs Investigation	0
Mitigation Implemented	0
Total	21
Total Migrated	0

Diagram: Diagram 1




Validation Messages:

1. **Error:** The connector should be attached to two elements.

Diagram 1 Diagram Summary:

Not Started	21
Not Applicable	0
Needs Investigation	0
Mitigation Implemented	0
Total	21
Total Migrated	0

Interaction: Approval Status Update



1. An adversary can gain unauthorized access to Azure Postgres DB instances due to weak network security configuration [State: Not Started] [Priority: High]

Category: Elevation of Privileges

Description: An adversary can gain unauthorized access to Supabase (PostgreSQL) instances due to weak network security configuration.

Justification: <no mitigation provided>

Possible Mitigation(s): Restrict access to Azure Postgres DB instances by configuring server-level firewall rules to only permit connections from selected IP addresses where possible. Refer: https://aka.ms/tmt-th153

SDL Phase: Implementation

2. An adversary may read and/or tamper with the data transmitted to Azure Postgres DB due to weak configuration [State: Not Started] [Priority: High]

Category: Tampering

Description: An adversary may read and/or tamper with the data transmitted to Supabase (PostgreSQL) due to weak configuration.

Justification: <no mitigation provided>

Possible Mitigation(s): Enforce communication between clients and Azure Postgres DB to be over SSL/TLS by enabling the Enforce SSL connection feature on the server. Check that the connection strings used to connect to MySQL databases have the right configuration (e.g. ssl = true or sslmode=require or sslmode=true are set). Refer: https://aka.ms/tmt-th154a Configure MySQL server to use a verifiable SSL certificate (needed for SSL/TLS communication). Refer: https://aka.ms/tmt-th154b

SDL Phase: Implementation

3. An adversary can gain long term, persistent access to an Azure Postgres DB instance through the compromise of local user account password(s) [State: Not Started] [Priority: High]

Category: Elevation of Privileges


Description: An adversary can gain long term, persistent access to Supabase (PostgreSQL) instance through the compromise of local user account password(s).

Justification: <no mitigation provided>

Possible Mitigation(s): It is recommended to rotate user account passwords (e.g. those used in connection strings) regularly, in accordance with your organization's policies. Store secrets in a secret storage solution (e.g. Azure Key Vault).

SDL Phase: Implementation

Interaction: Pending Request Query



4. An adversary can gain long term, persistent access to an Azure Postgres DB instance through the compromise of local user account password(s) [State: Not Started] [Priority: High]

Category: Elevation of Privileges

Description: An adversary can gain long term, persistent access to Supabase (PostgreSQL) instance through the compromise of local user account password(s).

Justification: <no mitigation provided>

Possible Mitigation(s): It is recommended to rotate user account passwords (e.g. those used in connection strings) regularly, in accordance with your organization's policies. Store secrets in a secret storage solution (e.g. Azure Key Vault).

SDL Phase: Implementation

5. An adversary may read and/or tamper with the data transmitted to Azure Postgres DB due to weak configuration [State: Not Started] [Priority: High]

Category: Tampering

Description: An adversary may read and/or tamper with the data transmitted to Supabase (PostgreSQL) due to weak configuration.

Justification: <no mitigation provided>

Possible Mitigation(s): Enforce communication between clients and Azure Postgres DB to be over SSL/TLS by enabling the Enforce SSL connection feature on the server. Check that the connection strings used to connect to MySQL databases have the right configuration (e.g. ssl = true or sslmode=require or sslmode=true are set). Refer: https://aka.ms/tmt-th154a Configure MySQL server to use a verifiable SSL certificate (needed for SSL/TLS communication). Refer: https://aka.ms/tmt-th154b

SDL Phase: Implementation

6. An adversary can gain unauthorized access to Azure Postgres DB instances due to weak network security configuration [State: Not Started] [Priority: High]

Category: Elevation of Privileges


Description: An adversary can gain unauthorized access to Supabase (PostgreSQL) instances due to weak network security configuration.

Justification: <no mitigation provided>

Possible Mitigation(s): Restrict access to Azure Postgres DB instances by configuring server-level firewall rules to only permit connections from selected IP addresses where possible. Refer: https://aka.ms/tmt-th153

SDL Phase: Implementation

Interaction: Program Data Query



7. An adversary can gain long term, persistent access to an Azure Postgres DB instance through the compromise of local user account password(s) [State: Not Started] [Priority: High]

Category: Elevation of Privileges

Description: An adversary can gain long term, persistent access to Supabase (PostgreSQL) instance through the compromise of local user account password(s).

Justification: <no mitigation provided>

Possible Mitigation(s): It is recommended to rotate user account passwords (e.g. those used in connection strings) regularly, in accordance with your organization's policies. Store secrets in a secret storage solution (e.g. Azure Key Vault).

SDL Phase: Implementation

8. An adversary may read and/or tamper with the data transmitted to Azure Postgres DB due to weak configuration [State: Not Started] [Priority: High]

Category: Tampering

Description: An adversary may read and/or tamper with the data transmitted to Supabase (PostgreSQL) due to weak configuration.

Justification: <no mitigation provided>

Possible Mitigation(s): Enforce communication between clients and Azure Postgres DB to be over SSL/TLS by enabling the Enforce SSL connection feature on the server. Check that the connection strings used to connect to MySQL databases have the right configuration (e.g. ssl = true or sslmode=require or sslmode=true are set). Refer: https://aka.ms/tmt-th154a Configure MySQL server to use a verifiable SSL certificate (needed for SSL/TLS communication). Refer: https://aka.ms/tmt-th154b

SDL Phase: Implementation

9. An adversary can gain unauthorized access to Azure Postgres DB instances due to weak network security configuration [State: Not Started] [Priority: High]

Category: Elevation of Privileges


Description: An adversary can gain unauthorized access to Supabase (PostgreSQL) instances due to weak network security configuration.

Justification: <no mitigation provided>

Possible Mitigation(s): Restrict access to Azure Postgres DB instances by configuring server-level firewall rules to only permit connections from selected IP addresses where possible. Refer: https://aka.ms/tmt-th153

SDL Phase: Implementation

Interaction: Program Data Update Request



10. An adversary can gain long term, persistent access to an Azure Postgres DB instance through the compromise of local user account password(s) [State: Not Started] [Priority: High]

Category: Elevation of Privileges
 Description: An adversary can gain long term, persistent access to Supabase (PostgreSQL) instance through the compromise of local user account password(s).
 Justification: <no mitigation provided>
 Possible Mitigation(s): It is recommended to rotate user account passwords (e.g. those used in connection strings) regularly, in accordance with your organization's policies. Store secrets in a secret storage solution (e.g. Azure Key Vault).
 SDL Phase: Implementation


11. An adversary may read and/or tamper with the data transmitted to Azure Postgres DB due to weak configuration [State: Not Started] [Priority: High]

Category: Tampering
 Description: An adversary may read and/or tamper with the data transmitted to Supabase (PostgreSQL) due to weak configuration.
 Justification: <no mitigation provided>
 Possible Mitigation(s): Enforce communication between clients and Azure Postgres DB to be over SSL/TLS by enabling the Enforce SSL connection feature on the server. Check that the connection strings used to connect to MySQL databases have the right configuration (e.g. ssl = true or sslmode=require or sslmode=true are set). Refer: https://aka.ms/tmt-th154a Configure MySQL server to use a verifiable SSL certificate (needed for SSL/TLS communication). Refer: https://aka.ms/tmt-th154b
 SDL Phase: Implementation

12. An adversary can gain unauthorized access to Azure Postgres DB instances due to weak network security configuration [State: Not Started] [Priority: High]

Category: Elevation of Privileges
 Description: An adversary can gain unauthorized access to Supabase (PostgreSQL) instances due to weak network security configuration.
 Justification: <no mitigation provided>
 Possible Mitigation(s): Restrict access to Azure Postgres DB instances by configuring server-level firewall rules to only permit connections from selected IP addresses where possible. Refer: https://aka.ms/tmt-th153
 SDL Phase: Implementation

Interaction: Program Information Query



13. An adversary can gain long term, persistent access to an Azure Postgres DB instance through the compromise of local user account password(s) [State: Not Started] [Priority: High]

Category: Elevation of Privileges
 Description: An adversary can gain long term, persistent access to Supabase (PostgreSQL) instance through the compromise of local user account password(s).
 Justification: <no mitigation provided>
 Possible Mitigation(s): It is recommended to rotate user account passwords (e.g. those used in connection strings) regularly, in accordance with your organization's policies. Store secrets in a secret storage solution (e.g. Azure Key Vault).
 SDL Phase: Implementation


14. An adversary may read and/or tamper with the data transmitted to Azure Postgres DB due to weak configuration [State: Not Started] [Priority: High]

Category: Tampering
 Description: An adversary may read and/or tamper with the data transmitted to Supabase (PostgreSQL) due to weak configuration.
 Justification: <no mitigation provided>
 Possible Mitigation(s): Enforce communication between clients and Azure Postgres DB to be over SSL/TLS by enabling the Enforce SSL connection feature on the server. Check that the connection strings used to connect to MySQL databases have the right configuration (e.g. ssl = true or sslmode=require or sslmode=true are set). Refer: https://aka.ms/tmt-th154a Configure MySQL server to use a verifiable SSL certificate (needed for SSL/TLS communication). Refer: https://aka.ms/tmt-th154b
 SDL Phase: Implementation

15. An adversary can gain unauthorized access to Azure Postgres DB instances due to weak network security configuration [State: Not Started] [Priority: High]

Category: Elevation of Privileges
 Description: An adversary can gain unauthorized access to Supabase (PostgreSQL) instances due to weak network security configuration.
 Justification: <no mitigation provided>
 Possible Mitigation(s): Restrict access to Azure Postgres DB instances by configuring server-level firewall rules to only permit connections from selected IP addresses where possible. Refer: https://aka.ms/tmt-th153
 SDL Phase: Implementation

Interaction: Session Validation Query



16. An adversary can gain unauthorized access to Azure Postgres DB instances due to weak network security configuration [State: Not Started] [Priority: High]

Category: Elevation of Privileges
 Description: An adversary can gain unauthorized access to Supabase (PostgreSQL) instances due to weak network security configuration.
 Justification: <no mitigation provided>
 Possible Mitigation(s): Restrict access to Azure Postgres DB instances by configuring server-level firewall rules to only permit connections from selected IP addresses where possible. Refer: https://aka.ms/tmt-th153
 SDL Phase: Implementation

17. An adversary may read and/or tamper with the data transmitted to Azure Postgres DB due to weak configuration [State: Not Started] [Priority: High]

Category: Tampering
 Description: An adversary may read and/or tamper with the data transmitted to Supabase (PostgreSQL) due to weak configuration.
 Justification: <no mitigation provided>
 Possible Mitigation(s): Enforce communication between clients and Azure Postgres DB to be over SSL/TLS by enabling the Enforce SSL connection feature on the server. Check that the connection strings used to connect to MySQL databases have the right configuration (e.g. ssl = true or sslmode=require or sslmode=true are set). Refer: https://aka.ms/tmt-th154a Configure MySQL server to use a verifiable SSL certificate (needed for SSL/TLS communication). Refer: https://aka.ms/tmt-th154b

or sslmode=true are set). Refer: https://aka.ms/tmt-th154a Configure MySQL server to use a verifiable SSL certificate (needed for SSL/TLS communication). Refer: https://aka.ms/tmt-th154b

SDL Phase: Implementation

18. An adversary can gain long term, persistent access to an Azure Postgres DB instance through the compromise of local user account password(s) [State: Not Started] [Priority: High]

Category: Elevation of Privileges


Description: An adversary can gain long term, persistent access to Supabase (PostgreSQL) instance through the compromise of local user account password(s).

Justification: <no mitigation provided>

Possible Mitigation(s): It is recommended to rotate user account passwords (e.g. those used in connection strings) regularly, in accordance with your organization's policies. Store secrets in a secret storage solution (e.g. Azure Key Vault).

SDL Phase: Implementation

Interaction: User Credential Query



19. An adversary can gain unauthorized access to Azure Postgres DB instances due to weak network security configuration [State: Not Started] [Priority: High]

Category: Elevation of Privileges

Description: An adversary can gain unauthorized access to Supabase (PostgreSQL) instances due to weak network security configuration.

Justification: <no mitigation provided>

Possible Mitigation(s): Restrict access to Azure Postgres DB instances by configuring server-level firewall rules to only permit connections from selected IP addresses where possible. Refer: https://aka.ms/tmt-th153

SDL Phase: Implementation

20. An adversary may read and/or tamper with the data transmitted to Azure Postgres DB due to weak configuration [State: Not Started] [Priority: High]

Category: Tampering

Description: An adversary may read and/or tamper with the data transmitted to Supabase (PostgreSQL) due to weak configuration.

Justification: <no mitigation provided>

Possible Mitigation(s): Enforce communication between clients and Azure Postgres DB to be over SSL/TLS by enabling the Enforce SSL connection feature on the server. Check that the connection strings used to connect to MySQL databases have the right configuration (e.g. ssl = true or sslmode=require or sslmode=true are set). Refer: https://aka.ms/tmt-th154a Configure MySQL server to use a verifiable SSL certificate (needed for SSL/TLS communication). Refer: https://aka.ms/tmt-th154b

SDL Phase: Implementation

21. An adversary can gain long term, persistent access to an Azure Postgres DB instance through the compromise of local user account password(s) [State: Not Started] [Priority: High]

Category:	Elevation of Privileges
Description:	An adversary can gain long term, persistent access to Supabase (PostgreSQL) instance through the compromise of local user account password(s).
Justification:	<no mitigation provided>
Possible Mitigation(s):	It is recommended to rotate user account passwords (e.g. those used in connection strings) regularly, in accordance with your organization's policies. Store secrets in a secret storage solution (e.g. Azure Key Vault).
SDL Phase:	Implementation