Bluetooth SIG Shop | Bluetooth.com



Select Language w

Step 4 - Project: BT + LE PSS

Welcome, Carsten Poulsen Home | My Bluetooth.org | Logout

About Us

Membership

Marketing Resources

Technical Resources

Assigned Numbers

Roadmap Specifications

Errata

ATLAS

Product Development

Software Licensing

Test Tools

Overview

Test Plan Generator

Listing Process

Build Your Test Plan

Overview

My Projects Create Project

Import Project

Create Test Plan

»[1] Select a Project

»[2] Declaration

»[3] Core PICS

»[4] Profile PICS

»[5] Consistency Check

»[6] Generate Plan Qualify Your Design Update Your PRD 1.0 Product

Find Design/Product Listings

Online References

Profile Tuning Suite

Device Library

Test Vector Licensing

Qualification

Security Regulatory

The SIG Community

Training & Events

Groups

1 of 3 16-02-2011 13:54

» Project Details »

Product Type Verification Status Product Type Selection in PROD Table: Profile Subsystem Valid

Product Type Selection from Dropdown: Profile Subsystem

• Product Type Conformance Check: Profile Subsystem

-- All mandatory profiles are being claimed. --

PROFILE: [A2DP AVRCP BIP BPP 1.2 DUN DID FAX FTP GAVDP HFP 1.5 HDP HID HSP IOP MAP MCAP OPP PBAP SAP SPP SYNC]

SIM Access Profile External to Core

Update PICS Information

TOOLS: [Consistency Check]

TABLE OF CONTENTS

Role Declaration
Application Features Application Features

Role Declaration [top]

Table 0: Versions

Item	Capability	System Spec Reference	Status	Support [Yes] or [No]	
1	SIM Access Profile v1.0 ①	2.2	0.1	0 0	
2	SIM Access Profile v1.1	2.2	0.1	• •	

O.1: It is mandatory to support only one of these versions.

Table 1: Roles

Item	Capability	System Spec Reference	Status	Support [Yes] or [N	
1	SIM Access Client (Client)	2.2	0.1	⊙ C	>
2	SIM Access Server (Server) 💿	2.2	O.1	⊙ ○)

O.1: Mandatory to support at least One of the defined roles.

Update PICS Information

TOOLS: [Consistency Check]

Application Features

[top]

Table 2: Client Application Features

Prerequisite: 1/1

Item	Capability	System Spec Reference	Status	Support [Yes] or [No]	
1	Connection Management	4.1, 4.2, 4.3	M.1	•	0
1a	Passkey length - Devices are bonded	4.1	C.1	•	0
1b	Security mode 4 support	GAP 2/7	C.4, C.5	•	0
2	Transfer APDU	4.4	M.1	•	0
3	Transfer ATR	4.5	M.1	•	0
4	Power SIM off	4.6	0	•	0
5a	Power SIM on (SAP Connection CAN be established and or maintained WITHOUT a SIM card in the Server)	4.7	C.2	•	0
5b	Power SIM on (SAP Connection can NOT be established and or maintained WITHOUT a SIM card in the Server)	4.7	C.2	•	0
6	Reset SIM	4.8	0	•	0
7a	Report status (SAP Connection CAN be established and or maintained WITHOUT a SIM card in the Server)	4.9	C.3	•	0
7b	Report status (SAP Connection can NOT be established and or maintained WITHOUT a SIM card in the Server)	4.9	C.3	•	0
8	Transfer card reader status	4.10	0	•	0
9	Set Transport Protocol	4.12	0	•	0
10	Perform Bonding outside SIM Access Profile connection	2.5	0	•	0

- M.1: Mandatory to support IF (1/1) supported.
 C.1: Mandatory to support IF (2/10) is supported, otherwise optional.
 C.2: Mandatory to support at least One of these two features.

- C.3: Mandatory to support at least One of these two features.

 C.5: Prerequisite Table 0/2.

 C.4: Mandatory if GAP 2/7 is supported, otherwise excluded.

Update PICS Information

TOOLS: [Consistency Check]

[<u>top</u>]

Application Features

Table 3: Server Application Features

Pre	real	ii.si	te:	1/

Item	Capability	System Spec Reference	Status	Support [Yes] or [No]	
1	Connection Management	4.1, 4.2, 4.3	M.1	•	0
1a	Passkey length - Devices are bonded	4.1	C.1	•	0
1b	Security mode 4 support	4.1, GAP 2/7	C.4, C.5	•	0
2	Transfer APDU	4.4	M.1	•	0
3	Transfer ATR	4.5	M.1	•	0
4	Power SIM off	4.6	M.1	•	0
5	Power SIM on (SIM CAN be inserted into the Server WITHOUT terminating the SIM Access Profile connection.)	4.7	C.2	•	0
6	Power SIM on (SIM can NOT be inserted into the Server WITHOUT terminating the SIM Access Profile connection.)	4.7	C.2	•	0
7	Reset SIM	4.8	M.1	•	0
8	Report status (SIM CAN be inserted into or removed from the Server WITHOUT terminating the SIM Access Profile connection.)	4.9	C.3	•	0
9	Report status (SIM can NOT be inserted into or removed from the Server WITHOUT terminating the SIM Access Profile connection.)	4.9	C.3	•	0
10	Transfer card reader status	4.10	M.1	•	0
11	Set Transport Protocol	4.12	0	•	0
12	Perform bonding outside SIM Access Profile connection	2.5	0	•	0

- M.1: Mandatory to support IF (1/2) supported
 C.2: Mandatory to support at least One of the two features.
 C.3: Mandatory to support at least One of the two features.
 C.1: Mandatory to support IF (3/12) supported, otherwise optional.
 C.4: Mandatory if GAP 2/7 is supported, otherwise excluded.
 C.5: Prerequisite Table 0/2.

Update PICS Information

TOOLS: [Consistency Check]

ericeson 🖇















© 2011 Bluetooth SIG all rights reserved

print | site map | legal | privacy policy