

DBMS Practical Implementation, Lab 10.

1. Task1: Perform following task.

SELECT “Task1: Perform following task”

create table student(id int PRIMARY KEY, name varchar(20));

start transaction;

insert into student values(1,'Amita'),(2,'Sheena'),(3,'Lavina'),(4,'Rex'),(5, 'Rahul');

UPDATE student SET name = 'Abhijit' WHERE id = '5';

SAVEPOINT A;

INSERT INTO student VALUES(6, 'Chris');


SAVEPOINT B;

INSERT INTO student VALUES (7, 'Bravo');

SAVEPOINT C;

SELECT “After task 1”

SELECT * FROM student;



phpMyAdmin

Recent Favorites

- New
- assignment
- assignments
- credendo_webgeeks
- dbmspracs
 - Functions
 - Procedures
 - Tables
 - New
 - borrower
 - client_master
 - dept
 - emp
 - employee
 - fine
 - product_master
 - sales_order
 - sales_order_details
- hospital
- information_schema
- mysql
- performance_schema
- phpmyadmin
- python_pracs
- students
- test
- todolist

Server: 127.0.0.1 Database: dbmspracs Table: student

Browse Structure SQL Search Insert Export Import Privileges Operations Tracking Triggers

MySQL returned an empty result set (i.e. zero rows). (Query took 0.0106 seconds.)

```
create table student(id int, name varchar(20))
```

[Edit inline] [Edit] [Create PHP code]

MySQL returned an empty result set (i.e. zero rows). (Query took 0.0001 seconds.)

```
start transaction
```

[Edit inline] [Edit] [Create PHP code]

5 rows inserted. (Query took 0.0020 seconds.)

```
insert into student values(1,'Amita'),(2,'Sheena'),(3,'Lavina'),(4,'Rex'),(5,'Rahul')
```

[Edit inline] [Edit] [Create PHP code]

1 row affected. (Query took 0.0005 seconds.)

```
UPDATE student SET name = 'Abhijit' WHERE id = '5'
```

[Edit inline] [Edit] [Create PHP code]

MySQL returned an empty result set (i.e. zero rows). (Query took 0.0002 seconds.)

```
SAVEPOINT A
```

[Edit inline] [Edit] [Create PHP code]

1 row inserted. (Query took 0.0004 seconds.)

phpMyAdmin

Recent Favorites

- New
- assignment
- assignments
- credendo_webgeeks
- dbmspracs
 - Functions
 - Procedures
 - Tables
 - New
 - borrower
 - client_master
 - dept
 - emp
 - employee
 - fine
 - product_master
 - sales_order
 - sales_order_details
- hospital
- information_schema
- mysql
- performance_schema
- phpmyadmin
- python_pracs
- students
- test
- todolist
- university

Server: 127.0.0.1 Database: dbmspracs Table: student

Browse Structure SQL Search Insert Export Import Privileges Operations Tracking Triggers

Current selection does not contain a unique column. Grid edit, checkbox, Edit, Copy and Delete features are not available.

Showing rows 0 - 6 (7 total, Query took 0.0004 seconds.)

```
SELECT * FROM student
```

☐ Profiling [Edit inline] [Edit] [Explain SQL] [Create PHP code] [Refresh]

☐ Show all | Number of rows: 25 | Filter rows: Search this table

+ Options

id	name
1	Amita
2	Sheena
3	Lavina
4	Rex
5	Abhijit
6	Chris
7	Bravo

☐ Show all | Number of rows: 25 | Filter rows: Search this table

Query results operations

☐ Let every user access this bookmark

Console

2. Rollback to save point B and observe the output:

rollback to B;

SELECT * FROM student;

Explanation:

Note that transaction is rolled back to savepoint B, so whatever operations performed after save point B will be rolled back.

So record of 'Bravo' that was inserted after save point B will be rolled back.

Output:

The screenshot shows the phpMyAdmin interface with the 'student' table selected. The SQL query entered is `SELECT "task 2: Rollback to save point B and observe the output "`. The output shows 'Showing rows 0 - 0 (1 total, Query took 0.0002 seconds.)'. Below the query, there are options to show all rows (25) and a filter row. The 'Query results operations' section includes buttons for Print, Copy to clipboard, Export, Display chart, and Create view. The 'Bookmark this SQL query' section has a label field and a checkbox 'Let every user access this bookmark'. The console shows the message 'MySQL returned an empty result set (i.e. zero rows). (Query took 0.0002 seconds.)' and the SQL command `rollback to B`.

The screenshot shows the phpMyAdmin interface with the 'student' table selected. The SQL query entered is `SELECT * FROM student`. The output shows 'Showing rows 0 - 5 (6 total, Query took 0.0004 seconds.)'. Below the query, there are options to show all rows (25) and a filter row. The 'Query results operations' section includes buttons for Print, Copy to clipboard, Export, Display chart, and Create view. The console shows the message 'MySQL returned an empty result set (i.e. zero rows). (Query took 0.0002 seconds.)' and the SQL command `rollback to B`. The table data is displayed as follows:

ID	name
1	Amita
2	Sheena
3	Lavina
4	Rex
5	Abhijit
6	Chris

3. Rollback to save point A and observe the output

Rollback to A;

```
SELECT * FROM student;
```

Explanation:

Note that transaction is rolled back to savepoint A, so whatever operations performed after save point A will be rolled back.

So After save point A we inserted record of 'chris' and 'Bravo' so this insert statements will be rolled back and hence table contains only 5 records.

Output:

The screenshot shows the phpMyAdmin interface with the 'student' table selected. The SQL query entered is `SELECT * FROM student;`. The output message states: "MySQL returned an empty result set (i.e. zero rows). (Query took 0.0002 seconds.)". Below the message, the text "Rollback to A" is visible. The interface includes a sidebar with a database structure tree, a top navigation bar, and a main content area with various toolbars and options.

The screenshot shows the phpMyAdmin interface with the 'student' table selected. The SQL query entered is `SELECT * FROM student;`. The output message states: "Showing rows 0 - 4 (5 total, Query took 0.0004 seconds.)". Below the message, the text "Rollback to A" is visible. The table data is displayed as follows:

id	name
1	Amita
2	Sheena
3	Lavina
4	Rex
5	Abhijit

The interface includes a sidebar with a database structure tree, a top navigation bar, and a main content area with various toolbars and options.

4. Now delete record of 'Rex', before delete create a save point, and rollback to this save point to undo this delete operation

savepoint DD;

delete from student where id =4;

select * from student;

// Now we want to undo this delete operation, so perform rollback to check point DD


rollback to DD;

select * from student;

Explanation:

Note a new savepoint is created in the transaction DD and Rex with id = 4 is deleted from the database. But now to reverse the effect of delete we rollback to savepoint DD

Output:



phpMyAdmin

Recent Favorites

- New
- assignment
- assignments
- crecendo_webgeeks
- dbmspracs
 - Functions
 - Procedures
 - Tables
 - New
 - borrower
 - client_master
 - dept
 - emp
 - employee
 - fine
 - product_master
 - sales_order
 - sales_order_details
- hospital
- information_schema
- mysql
- performance_schema
- phpmyadmin
- python_pracs
- students
- test
- todoist
- university

Server: 127.0.0.1 » Database: dbmspracs » Table: student

Browse Structure SQL Search Insert Export Import Privileges Operations Tracking Triggers

MySQL returned an empty result set (i.e. zero rows). (Query took 0.0002 seconds.)

savepoint DD

[Edit inline] [Edit] [Create PHP code]

1 row affected. (Query took 0.0005 seconds.)

delete FROM student WHERE student.id='4'

[Edit inline] [Edit] [Create PHP code]

Current selection does not contain a unique column. Grid edit, checkbox, Edit, Copy and Delete features are not available.

Showing rows 0 - 3 (4 total, Query took 0.0004 seconds.)

select * from student

Profiling [Edit inline] [Edit] [Explain SQL] [Create PHP code] [Refresh]

Show all | Number of rows: 25 | Filter rows: Search this table

+ Options

id	name
1	Amita
2	Sheena
3	Lavina
5	Abhijit

Show all | Number of rows: 25 | Filter rows: Search this table

Console

phpMyAdmin

Recent Favorites

- New
- assignment
- assignments
- crecendo_webgeeks
- dbmspracs
 - Functions
 - Procedures
 - Tables
 - New
 - borrower
 - client_master
 - dept
 - emp
 - employee
 - fine
 - product_master
 - sales_order
 - sales_order_details
- hospital
- information_schema
- mysql
- performance_schema
- phpmyadmin
- python_pracs
- students
- test
- todoist
- university

Server: 127.0.0.1 » Database: dbmspracs » Table: student

Browse Structure SQL Search Insert Export Import Privileges Operations Tracking Triggers

MySQL returned an empty result set (i.e. zero rows). (Query took 0.0002 seconds.)

rollback to DD

[Edit inline] [Edit] [Create PHP code]

Current selection does not contain a unique column. Grid edit, checkbox, Edit, Copy and Delete features are not available.

Showing rows 0 - 4 (5 total, Query took 0.0005 seconds.)

SELECT * FROM student

Profiling [Edit inline] [Edit] [Explain SQL] [Create PHP code] [Refresh]

Show all | Number of rows: 25 | Filter rows: Search this table

+ Options

id	name
1	Amita
2	Sheena
3	Lavina
4	Rex
5	Abhijit

Show all | Number of rows: 25 | Filter rows: Search this table

Query results operations

Print Copy to clipboard Export Display chart Create view

Console

5. Task 5: Now Perform commit:

Commit;

`SELECT * FROM student;`

Explanation:

Now as the transaction is complete i.e. all operations are done we commit the changes to the database. Here after the changes will be reflected in the database.

Output:

The screenshot shows the phpMyAdmin interface with the 'task 5: Now Perform commit' query executed. The query is `SELECT "task 5: Now Perform commit"`. The result shows 0 rows, indicating an empty result set. The interface includes a sidebar with a database tree, a top navigation bar, and a main content area with query execution details and options.

Server: 127.0.0.1 » Database: dbmspracs » Table: student

Showing rows 0 - 0 (1 total, Query took 0.0002 seconds)

`SELECT "task 5: Now Perform commit"`

Options: `task 5: Now Perform commit`

MySQL returned an empty result set (i.e. zero rows). (Query took 0.0011 seconds.)

Commit

The screenshot shows the phpMyAdmin interface with the `SELECT * FROM student` query executed. The query result shows 5 rows of data. The interface includes a sidebar with a database tree, a top navigation bar, and a main content area with query execution details and options.

Server: 127.0.0.1 » Database: dbmspracs » Table: student


Showing rows 0 - 4 (5 total, Query took 0.0004 seconds)

`SELECT * FROM student`

Options: `id name`

id	name
1	Amita
2	Sheena
3	Lavina
4	Rex
5	Abhijit

6. The Complete SQL Query:



The screenshot shows the phpMyAdmin interface with the 'SQL' tab selected. The left sidebar displays a tree view of databases, with 'dbmspracs' expanded. The main area shows a SQL query editor with the following code:

```
1 SELECT "task 1:Perform the following task";
2 create table student(id int, name varchar(20));
3 start transaction;
4 insert into student values(1,'Amita'),(2,'Sheena'),(3,'Lavina'),(4,'Rex'),(5, 'Rahul');
5 UPDATE student SET name = 'Abhijit' WHERE id = '5';
6 SAVEPOINT A;
7 INSERT INTO student VALUES(6, 'Chris');
8 SAVEPOINT B;
9 INSERT INTO student VALUES (7, 'Bravo');
10 SAVEPOINT C;
11 SELECT "After task 1";
12 SELECT * FROM student;
13 SELECT "task 2: Rollback to save point B and observe the output ";
14 rollback to B;
15 SELECT * FROM student;
16 SELECT "task 3: Rollback to save point A and observe the output";
17 Rollback to A;
18 SELECT * FROM student;
19 SELECT "task 4: Now delete record of 'Rex' , before delete create a check point";
20 savepoint D;
21 delete FROM student WHERE student.id='4';
22 select * from student;
23 rollback to D;
24 SELECT * FROM student;
25 SELECT "task 5: Now Perform commit";
26 Commit;
27 SELECT * FROM student;
```

Below the query editor, there are buttons for 'Clear', 'Format', and 'Get auto-saved query'. A checkbox for 'Bind parameters' is also present. At the bottom, a 'Console' tab is visible with the text 'his SQL query:'.

Postlab:

1. Explain Set Transaction command in SQL

Ans.

The SET TRANSACTION command can be used to initiate a database transaction. This command is used to specify characteristics for the transaction that follows. For example, you can specify a transaction to be read only or read write.

Transactions group a set of tasks into a single execution unit. Each transaction begins with a specific task and ends when all the tasks in the group successfully complete. If any of the tasks fail, the transaction fails. Therefore, a transaction has only two results: success or failure.

Use the SET TRANSACTION statement to establish the current transaction as read-only or read/write, establish its isolation level, or assign it to a specified rollback segment. The operations performed by a SET TRANSACTION statement affect only your current transaction, not other users or other transactions. Your transaction ends whenever you issue a COMMIT or ROLLBACK statement.

2. Explain how do you remove a save point (checkpoint) that you have created?

Ans.

RELEASE SAVEPOINT destroys a savepoint previously defined in the current transaction. Destroying a savepoint makes it unavailable as a rollback point, but it has no other user visible behaviour. It does not undo the effects of commands executed after the savepoint was established. (To do that, see ROLLBACK TO SAVEPOINT.) Destroying a savepoint when it is no longer needed allows the system to reclaim some resources earlier than transaction end. RELEASE SAVEPOINT also destroys all savepoints that were established after the named savepoint was established.

Specifying a savepoint name that was not previously defined is an error. It is not possible to release a savepoint when the transaction is in an aborted state. If multiple savepoints have the same name, only the one that was most recently defined is released.